

## 5 FCC §2.1091, §15.247(i) & ISEDC RSS-102 - RF Exposure

### 5.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

#### Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

Before equipment certification is granted, the procedure of IC RSS-102 must be followed concerning the exposure of humans to RF field

According to ISED RSS-102 Issue 5:

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f <sup>0.5</sup>	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ f <sup>0.25</sup>	0.1540/ f <sup>0.25</sup>	8.944/ f <sup>0.5</sup>	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f <sup>0.3417</sup>	0.008335 f <sup>0.3417</sup>	0.02619 f <sup>0.8834</sup>	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f <sup>1.2</sup>
150000-300000	0.158 f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/f <sup>1.2</sup>

**Note:** f is frequency in MHz.  
 \* Based on nerve stimulation (NS).  
 \*\* Based on specific absorption rate (SAR).

## 5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

## 5.3 MPE Results

### Host SPS986

#### Single Transmitter MPE Evaluation

900 MHz Radio:

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>29.95</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>988.55</u>
<u>Prediction distance (cm):</u>	<u>25</u>
<u>Prediction frequency (MHz):</u>	<u>902.6</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>2.5</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>1.778</u>
<u>Power density of prediction frequency at 25 cm (mW/cm<sup>2</sup>):</u>	<u>0.2239</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm<sup>2</sup>):</u>	<u>0.602</u>

2.4 GHz Bluetooth:

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>11.64</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>14.588</u>
<u>Prediction distance (cm):</u>	<u>25</u>
<u>Prediction frequency (MHz):</u>	<u>2402</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>2</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>1.585</u>
<u>Power density of prediction frequency at 25 cm (mW/cm<sup>2</sup>):</u>	<u>0.0029</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm<sup>2</sup>):</u>	<u>1.0</u>

2.4GHz Wi-Fi:

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>23.86</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>243.2204</u>
<u>Prediction distance (cm):</u>	<u>25</u>
<u>Prediction frequency (MHz):</u>	<u>2437</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>2</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>1.585</u>
<u>Power density of prediction frequency at 25 cm (mW/cm<sup>2</sup>):</u>	<u>0.0491</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm<sup>2</sup>):</u>	<u>1.0</u>

Note: Bluetooth Module: JUP-WL18DBMOD, IC: 1756A-WL18DBMOD.  
 2.4 GHz Wi-Fi Module: JUP-WL18DBMOD, IC: 1756A-WL18DBMOD.

### Multi Transmitter MPE Evaluation

Wi-Fi+Bluetooth+900 MHz Radio =  $0.0491/1+0.0029/1+0.2239/0.602 = 0.4239 < 1.0$

### Conclusion

In order to meet the multi-transmitter RF Exposure requirement, all transceiver modules must be installed with a separation distance of no less than **25** cm from all persons.

## 5.4 RF exposure evaluation for IC

### Host SPS986

#### Single Transmitter MPE Evaluation

900 MHz Radio:

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>29.95</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>988.55</u>
<u>Prediction distance (cm):</u>	<u>25</u>
<u>Prediction frequency (MHz):</u>	<u>902.6</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>2.5</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>1.778</u>
<u>Power density of prediction frequency at 25 cm (W/m<sup>2</sup>):</u>	<u>2.2394</u>
<u>ISED MPE limit for uncontrolled exposure at prediction frequency (W/m<sup>2</sup>):</u>	<u>2.741</u>

2.4 GHz Bluetooth:

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>11.64</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>14.588</u>
<u>Prediction distance (cm):</u>	<u>25</u>
<u>Prediction frequency (MHz):</u>	<u>2402</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>2</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>1.585</u>
<u>Power density of prediction frequency at 25 cm (W/m<sup>2</sup>):</u>	<u>0.02945</u>
<u>ISED MPE limit for uncontrolled exposure at prediction frequency (W/m<sup>2</sup>):</u>	<u>5.35</u>