

MEASUREMENT REPORT

of

Wireless LAN Mini PCI

Applicant : BenQ Corporation
Model No. : AWL200
EUT : Wireless LAN Mini PCI
FCC ID : JVPAWL200
Report No. : B2215853 (Version 2)

Tested by :

Training Research Co., Ltd.

TEL : 886-2-26935155 FAX : 886-2-26934440

No. 255, Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C.

CERTIFICATION

We here by verify that:

The test data, data evaluation, test procedures and equipment configurations shown in this report were made mainly in accordance with the procedures given in ANSI C63.4 (1992) as a reference. All test were conducted by **Training Research Co., Ltd.**, 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Also, we attest to the accuracy of each.

We further submit that the energy emitted by the sample EUT tested as described in the report is **in compliance with** the technical requirements set forth in the FCC Rules Part 15 Subpart C Section 15.247.

Applicant : BenQ Corporation
Applicant address : 18, Jihu Rd., Neihu Dist., Taipei 114, Taiwan, R.O.C.
EUT : Wireless LAN Mini PCI
Model No. : AWL200
FCC ID : JVPAWL200
Report No. : B2215853
Test Date : February 28, 2003

Prepared by: _____
Eric Wong

Approved by: _____
Frank Tsai

Tested by :

Training Research Co., Ltd.

TEL: 886-2-26935155 FAX: 886-2-26934440
255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C.

Tables of Contents

I. GENERAL	5
1.1 Introduction	5
1.2 Description of EUT	5
1.3 Description of Support Equipment	6
1.4 Test method	7
1.5 Configuration of System Under Test	8
1.6 Verify the Frequency and Channel	10
1.7 Test Procedure	11
1.8 Location of the Test Site	11
1.9 General Test Condition	11
 II. Section 15.101(a) : Equipment Authorization of Unintentional Radiators	 12
 III. Section 15.203 : Antenna Requirement.....	 13
 IV. Section 15.207 : Power Line Conducted Emissions for AC Powered Units	 14
4.1 Test Condition & Setup	14
4.2 List of Test Instruments	14
4.3 Test Result of Conducted Emissions	15
 V. Section 15.247(a) : Technical Description of the EUT	 16
 VI. Section 15.247(a)(2) : Bandwidth for Direct Sequence System	 17
6.1 Test Condition & Setup	17
6.2 Test Instruments Configuration	17
6.3 List of Test Instruments	17
6.4 Test Result of Bandwidth	18
Channel 01	19
Channel 06	20
Channel 11	21

VII. Section 15.247(b) : Power Output	22
7.1 Test Condition & Setup	22
7.2 List of Test Instruments	22
7.3 Test Result	22
VIII. Section 15.247(c) : Spurious Emissions (Radiated)	23
8.1 Test Condition & Setup	23
8.2 List of Test Instruments	24
8.3 Test Result of Spurious Radiated Emissions	25
Table 1 Radiated emissions of Horizontal for 30MHz to 1GHz	25
Table 2 Radiated emissions of Vertical for 30MHz to 1GHz	25
Table 3 Above 1GHz Radiated emissions of Horizontal of CH1	26
Table 4 Above 1GHz Radiated emissions of Vertical of CH1	26
Table 5 Above 1GHz Radiated emissions of Horizontal of CH6	27
Table 6 Above 1GHz Radiated emissions of Vertical of CH6	27
Table 7 Above 1GHz Radiated emissions of Horizontal of CH11	28
Table 8 Above 1GHz Radiated emissions of Vertical of CH11	28
8.4 Test Result of Bandedge.....	29
Channel 01	30
Channel 11	31
IX. Section 15.247(d) : Power Spectral Density	32
9.1 Test Condition & Setup	32
9.2 Test Instruments Configuration	32
9.3 List of Test Instruments	32
9.4 Test Result of Power Spectral Density	32
Channel 01	33
Channel 06	34
Channel 11	35

. GENERAL

1.1 Introduction

The following measurement report is submitted on behalf of applicant in support that the Wireless LAN Mini PCI card certification in accordance with Part 2 Subpart J and Part 15 Subpart A and C of the Commission's Rules and Regulations.

1.2 Description of EUT

EUT : Wireless LAN Mini PCI
Model No. : AWL200
Granted FCC ID : JVPWL200
Frequency Range : 2.412 GHz ~ 2.462GHz
Support Channel : 11 Channel
Modulation Skill : DBPSK, DQPSK, CCK
Power Type : Powered by Mini-PCI slot of the client' s device
Style Interface : Mini-PCI interface

1.3 Description of Support Equipment

In order to construct the minimum testing, following equipment were used as the support units.

PC : **HEWLETT-PACKARD**
Model No. : M-BA47
Serial No. : LZE92250027
FCC ID : DoC Approved
檢磁 : 4872A220
Power type : Powered by Computer
Power Cable : Shielded, 1.5m long, Plastic hoods, No ferrite bead

Monitor : HP 15' Color Monitor

Model No. : D2827A
Serial No. : KR91161717
FCC ID : C5F7NFCMC1518X
檢磁 : 3872B039
Power type : 100 ~ 240 VAC / 50 ~ 60 Hz, Switching
Power cord : Shielded, 1.83m long, No ferrite core
Data cable : Shielded, 1.46m long, with two ferrite cores

Int. simulator : SPEEDBUS TECHNOLOGIES, INC.

Model No. : PCI PARSSER PX-II (PX2000)
Serial No. : A200457
Power Core : Shielded, 1.5m long, Plastic hoods, No ferrite bead
Int. Cable : Shielded, 1.8m long, No ferrite bead
Console Cable : Non-shielded, 0.65m long, No ferrite bead

Int. PCI card : SPEEDBUS TECHNOLOGIES, INC.

Model No. : PCI HOST CARD (V.200.01)
Serial No. : 2H00525

Keyboard : HEWLETT-PACKARD

Model No. : SK-2502C
Serial No. : M000519803
FCC ID : DoC Approved
Power type : Powered by Computer (PS2)
Power Cable : Shielded, 1.5m long, Plastic hoods, No ferrite bead

Mouse : HEWLETT-PACKARD

Model No. : C3751B
Serial No. : LZ81625049
FCC ID : DoC Approved
檢磁 : 4862A011
Power type : Powered by Computer (PS2)
Power Cable : Shielded, 1.5m long, Plastic hoods, No ferrite bead

Printer : HP
Model No. : C6464A
Serial No. : TH16LEB5PK
FCC ID : N/A, DoC Approved
檢磁 : 3892H381
Power type : Switching adaptor
Power cord : Non-shielded, 173cm long, No ferrite core
(between adaptor and AC source)
Non-shielded, 180cm long, with ferrite core
(between printer and adaptor)
Data cable : Shielded, 1.70m long, No ferrite core


USB Mouse : Logitech Inc.
Model No. : M-BE58
Serial No. : LZE14370953
FCC ID : DoC Approved
檢磁 : 3892B471
Power type : By Computer
Data Cable : Shielded, 1.90m long, Plastic, No ferrite core

1.4 Test method

1. Insert the EUT into the Mini PCI slot of the interface simulator, which is connected with the PC via the PCI host card.
2. Using the PC and software provided by the manufacturer to control and link wireless access point, then making access to the mode of continuous transmission. The software is operated under the Windows to control the EUT in the continuous transmission mode.
3. Then making access to the mode of continuous transmission and set testing channel.
4. *The testing configuration of test setup is showing in the next page.*

1.5 Configuration of System Under Test

(Conducted and Radiated for Unintentional)



Connections of Equipment


HP Personal computer:

- *Parallel Port --- a Printer
- *Monitor Port --- a monitor
- *PS2 Keyboard Port --- a PS2 keyboard
- *PS2 Mouse Port --- a PS2 mouse
- *USB Port --- a USB mouse
- *PCI BUS --- a PCI card

EUT:

- *Mini-PCI --- Plug the EUT in the mini-PIC interface of simulator

(Radiated for Intentional)



Connections of Equipment

EUT:

*Mini-PCI --- Plug the EUT in the mini-PIC interface of simulator

Simulator:

*Power Cable --- Shielded, 1.5m long, Plastic hoods, No ferrite bead

*Interface Cable --- Shielded, 1.8m long, No ferrite bead

*Console Cable --- Non-shielded, 0.65m long, No ferrite bead

1.6 Verify the Frequency and Channel

Channel	Frequency (GHz)
1	2.412
2	2.417
3	2.422
4	2.427
5	2.432
6	2.437
7	2.442
8	2.447
9	2.452
10	2.457
11	2.462

Note:

- 1.This is for confirming that all frequencies are in 2.412GHz to 2.462GHz.
- 2.Section 15.31(m): Measurements on intentional radiators or receivers shall be performed at three frequencies for operating frequency range over 10 MHz.
(The locations of these frequencies one near the top, one near the middle and one near the bottom.)
- 3.After test, the EUT operating frequencies are in 2.412GHz to 2.462GHz. So all the items as followed in testing report are need to test these three frequencies:
Top: Channel – 1; Middle: Channel – 6; Bottom: Channel – 11.

1.7 Test Procedure

All measurements contained in this report were performed mainly according to the techniques described in ANSI C63.4 (1992) and the pre-setup was written on Appendix A, the detail setup was written on each test item.

1.8 Location of the Test Site

The radiated emissions measurements required by the rules were performed on the **three-meter, Anechoic Chamber (Registration Number: 93906)** maintained by *Training Research Co., Ltd.* 1F, No. 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. Complete description and measurement data have been placed on file with the commission. The conducted power line emissions tests and other test items were performed in a anechoic chamber also located at Training Research Co., Ltd.

No. 255 Nanyang Street, Shijr, Taipei Hsien 221, Taiwan, R.O.C. *Training Research Co., Ltd.* is listed by the FCC as a facility available to do measurement work for others on a contract basis.

1.9 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests were chosen as that which produced the highest emission levels. However, only those conditions, which the EUT was considered likely to encounter in normal use were investigated.

In test, they were set in high power and continuously transmitting mode that controlled by computer. The ch01, ch06 and ch11 of EUT were all tested. The setting up procedure is recorded on Appendix A.

II. Section 15.101(a): Equipment authorization of unintentional radiators

The EUT equipped with a USB bus interface and should be operated with the computer. It was categorized to *Class B personal computers and peripherals* as cannot be operated stand-alone. The authorization requires Certification and the items required such as Sect.15.107 (Conducted limits) and Sect.15.109 (Radiated emission limits) is same as Sect.15.207 and 15.247(C) we'd performed respectively. We dropped this part, as the result will be repeated as the part we mentioned above.

III. Section 15.203: Antenna requirement

The EUT has no external antenna or connector employed for any other antenna than the one bundled with. The antenna requirement stated in Sect.15.203 is satisfied to this EUT.

IV. Section 15.207: Power Line Conducted Emissions for AC Powered Units

4.1 Test Condition & Setup

The power line conducted emission measurements were performed in an anechoic chamber. The EUT was assembled on a wooden table, which is 80 centimeters high, was placed 40 centimeters from the backwall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and Line Impedance Stabilization Networks (LISNs). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer (or EMI receiver) was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPER quasi-peak detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 450 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 2.4.

There is a test condition apply in this test item, the test procedure description as the following:

EUT transmit only:

Plug the EUT in the USB port of notebook computer and software to control the EUT. Then making access to the mode of continuous transmission and setting the testing channel. Three channels were tested, one in the top (CH01), one in the middle (CH06) and the other in bottom (CH11).

4.2 List of Test Instruments

<u>Instrument Name</u>	<u>Model No.</u>	<u>Brand</u>	<u>Serial No.</u>	<u>Last time</u>	<u>Next time</u>
EMI Receiver	8546A	H P	3520A00242	06/28/02	06/28/03
RF Filter Section	85460A	H P	3448A00217	06/28/02	06/28/03
LISN (EUT)	LISN-01	TRC	9912-03,04	12/09/02	12/09/03
LISN (Support E.)	LISN-01	TRC	9912-05	07/15/02	07/15/03
Switch/Control Unit (< 30MHz)	3488A	HP	N/A	11/20/02	11/20/03
Auto Switch Box (< 30MHz)	ASB-01	TRC	9904-01	11/20/02	11/20/03

The level of confidence of 95%, the uncertainty of measurement of conducted emission is $\pm 2.02\text{dB}$.

4.3 Test Result of Power Line Conducted Emissions

EUT station transmit only

The following table shows a summary of the highest emissions of power line conducted emissions on the LIVE and NETURAL conductors of the EUT power cord. The worst case to show as follows.

Test Conditions: Testing room : Temperature : 26.2 °C Humidity : 55.8 % RH

<i>Power Connected Emissions</i>				<i>FCC Class B</i>	
<i>Conductor</i>	<i>Frequency (KHz)</i>	<i>Peak Amplitude (dBmV)</i>	<i>QP Amplitude (dBmV)</i>	<i>Limit (dBmV)</i>	<i>Margin (dB)</i>
Line 1	593.000	39.43	---	48.00	-8.57
	672.000	41.87	---	48.00	-6.13
	747.000	39.33	---	48.00	-8.67
	895.000	38.51	---	48.00	-9.49
	966.000	36.74	---	48.00	-11.26
	1194.000	37.36	---	48.00	-10.64
	1263.000	37.69	---	48.00	-10.31
	1414.000	36.07	---	48.00	-11.93
	1793.000	37.23	---	48.00	-10.77
	2084.000	36.58	---	48.00	-11.42
Line 2	597.000	35.28	---	48.00	-12.72
	668.000	35.78	---	48.00	-12.22
	895.000	35.88	---	48.00	-12.12
	966.000	31.83	---	48.00	-16.17
	1116.000	32.71	---	48.00	-15.29
	1194.000	35.56	---	48.00	-12.44
	1414.000	32.02	---	48.00	-15.98
	1491.000	32.69	---	48.00	-15.31
	1563.000	31.59	---	48.00	-16.41
	1793.000	34.37	---	48.00	-13.63

NOTE:

(1)Margin = Peak Amplitude – Limit, **The reading amplitudes are all under limit.**

(2)A "+" sign in the margin column means the emission is OVER the Class B Limit
and "-" sign of means UNDER the Class B limit

V. Section 15.247 (a): Technical description of the EUT


Based on the Section 2.1, *Direct Sequence System* is a spread spectrum system in which the carrier has been modulated by a high speed spreading code and an information data stream. The high speed code sequence dominates the “modulating function” and is the direct cause of the wide spreading of the transmitted signal. In the Exhibit H, operational description demonstrates the operation principles of the Baseband processor employed by the EUT, shows that which is a complete DSSS baseband processor and meets the definition of the Direct sequence spread spectrum system.

VI. Section 15.247(a)(2): Bandwidth for Direct Sequence System.

6.1 Test Condition & Setup

The transmitter bandwidth measurements were performed by the contact manner. The EUT was set to transmit continuously, also various channels were investigated to find the maximum occupied bandwidth.. The output of the EUT was connected to the spectrum analyzer. The bandwidth of the fundamental frequency is observed by the spectrum analyzer with 100kHz RBW and 100kHz VBW.

6.2 Test Instruments Configuration



Test Configuration of Bandwidth for Direct Sequence System

P.S.: Notebook computer to control the EUT at maximal power output and channel Number and set antenna kit

6.3 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
Spectrum Analyzer	8592A	H P	3003AD1401	01/02/03	01/01/04

6.4 Test Result of Bandwidth

Bandwidth of Channel 1

Bandwidth : 11.05 MHz
The min. 6 dB BW at least : 500 KHz

Bandwidth of Channel 6

Bandwidth : 11.00 MHz
The min. 6 dB BW at least : 500 KHz


Bandwidth of Channel 11

Bandwidth : 11.25 MHz
The min. 6 dB BW at least : 500 KHz


Note:

1. The data in the above table are summarizing the following attachment spectrum analyzer hard copy. According to the guidance, we'd made the measurement with the spectrum analyzer's resolution bandwidth (RBW)= $100kHz$ and set the $span \gg RBW$. The results show the measured 6dB bandwidth comply with the minimum 500kHz requirement.
2. The attachments show these on the following pages.


Bandwidth of Channel 1: 11.05 MHz



Bandwidth of Channel 6: 11.00 MHz



Bandwidth of Channel 11: 11.25 MHz



VII. Section 15.247(b): Power Output

7.1 Test Condition & Setup



1. The output of the transmitter is connected to the BOONTON RF Power Meter.
2. The calibration is performed before every test. The values of the output power of the EUT will shown in the dBm directly are the transmitter output peak power. Recording as follows.

7.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.
RF Power Meter	4532	BOONTON	117501

7.3 Test Result

Formula:					
Signal generator + Cable loss = Output peak power					
Channel	Signal Generator	Cable Loss	Limit	Output peak power	
	dBm	dBm	(DTS)	dBm	mW
CH 1	11.32	0.70	100mW	12.02	15.92
CH 6	11.13	0.70	100mW	11.83	15.24
CH 11	11.05	0.70	100mW	11.75	14.96

Note:

The limit is varied according to the equipment class, listed below:

1. Digital Transmission System (DTS): 100mW
2. Spread Spectrum Transmitter (DSS): 1W

VIII. Section 15.247 (C): Spurious Emissions (Radiated)

8.1 Test Condition & Setup

We'd performed the test by the *radiated emission skill*: The EUT was placed in an anechoic chamber, and set the EUT transmitting continuously and scanned at 3-meter distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration, which produced the highest emissions was noted so it could be reproduced later during the final tests. For the measurement above 1GHz, according to the guidance we'd set the spectrum analyzer's 6dB bandwidth RBW to 1MHz.

This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

Final radiation measurements were made on a three-meter, anechoic chamber. The EUT system was placed on a nonconductive turntable, which is 0.8 meters height, top surface 1.0 x 1.5 meter.

The spectrum was examined from 30 MHz to 1000 MHz using an Hewlett Packard 85460A EMI Receiver, Schaffner whole range Bi-Log antenna (Model No.: CBL6141A) is used to measure frequency from 30 MHz to 1GHz. The final test is used the spectrum HP 85460A and spectrum was examined from 1GHz to 18GHz using an Hewlett Packard 8564E Spectrum Analyzer, EMCO Horn Antenna (Model 3115) for 1G ~ 18GHz.

At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. There are two spectrum analyzers use on this testing, HP 85460A for frequency 30MHz to 1000MHz, and 8564E for frequency 1GHz to 18GHz. No post-detector video filters were used in the test. The spectrum analyzer's 6dB bandwidth was set to 120KHz (spectrum was examined from 30 MHz to 1000 MHz), the spectrum analyzer's 6 dB bandwidth was set to 1 MHz (spectrum was examined from 1GHz to 18GHz) and the analyzer was operated in the maximum hold mode. There is a test condition apply in this test item, the test procedure description as the following:

Making access to the mode of continuous transmission by the software in the computer via the PCI interface. Three channels were tested, one in the top (CH01), one in the middle (CH06) and the other in bottom (CH11).

With the transmitter operating from a AC source and using the internal of EUT, radiates spurious emissions falling within the restricted bands of 15.209 were measured at operating frequencies corresponding to upper, middle and bottom channels in the 2400 ~ 2483.5 MHz band.

The actual field intensity in decibels referenced to 1 microvolt per meter (dB μ V/m) is determined by algebraically adding the measured reading in dB μ V, the antenna factor (dB), and cable loss (dB) at the appropriate frequency. Since the EUT was set to transmit continuously, no *duty cycle* is present.

For frequency between 30MHz to 1000MHz

$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factors}$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

Correction Factors = Antenna Factor + Cable Loss – Amplifier Gain

For frequency between 1 GHz to 18 GHz

$F_{Ia} \text{ (dB}\mu\text{V/m)} = F_{Ir} \text{ (dB}\mu\text{V)} + \text{Correction Factor}$

F_{Ia} : Actual Field Intensity

F_{Ir} : Reading of the Field Intensity

Correction Factors = Antenna Factor + Cable Loss – Amplifier Gain

The setting up procedure is recorded on Appendix A.

8.2 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
Spectrum analyzer	8591EM	H P	3710A01203	05/29/02	05/29/03
Pre-selector (>30MHz)	AMP-01	TRC	REP-001	10/02/02	10/02/03
Spectrum analyzer	8568B	H P	3004A18617	06/19/02	06/19/03
Quasi-peak Adapter	85650A	H P	2521A00984	06/20/02	06/20/03
RF Pre-selector	85685A	H P	2947A01011	06/20/02	06/20/03
RF Pre-selector	AMP-01	TRC	REP-002	10/02/02	10/02/03
Bi-log Antenna	VULB9160	M. E.	3064	07/09/02	07/09/03
Antenna (30M-2GHz)	3142	EMCO	9610-1094	10/02/02	10/02/03
Open test side (Antenna, Amplify, cable calibrated together)				05/20/02	05/20/03
Spectrum Analyzer	8564E	HP	US36433002	08/01/02	08/01/03
Microwave Preamplifier	83051A	HP	3232A00347	08/01/02	08/01/03
Horn Antenna	3115	EMCO	9704 – 5178	08/01/02	08/01/03

The level of confidence of 95% , the uncertainty of measurement of radiated emission is $\pm 3.44\text{dB}$.

8.3 Test Result of Spurious Radiated Emissions

EUT's transmit only: The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarizations, EUT orientation, etc. are recorded on the following.

Testing room : Temperature : 26 ° C Humidity : 55 % RH

Table 1 Radiated Emissions for 30MHz 1GHz [Horizontal]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
166.41	33.37	1.00	144	1.80	35.17	43.50	-8.33
232.90	37.97	1.00	266	1.55	39.52	46.00	-6.48
267.65	36.18	1.00	292	1.69	37.87	46.00	-8.13
298.77	37.24	1.00	198	2.04	39.28	46.00	-6.72
332.82	33.60	1.00	22	2.76	36.36	46.00	-9.64
367.68	36.13	1.00	71	3.82	39.95	46.00	-6.05

Table 2 Radiated Emissions For 30MHz 1GHz [Vertical]

Radiated Emission				Correction Factors	Corrected Amplitude	FCC Class B (3 m)	
Frequency (MHz)	Amplitude (dBmV)	Ant. H. (m)	Table (°)			Limit (dBmV/m)	Margin (dB)
232.90	34.28	1.00	152	1.55	35.83	46.00	-10.17
298.57	36.53	1.00	118	2.04	38.57	46.00	-7.43
331.31	34.91	1.00	117	2.72	37.63	46.00	-8.37
365.45	24.20	1.00	120	3.73	27.93	46.00	-18.07
497.42	28.52	1.00	122	8.73	37.25	46.00	-8.75
599.98	23.01	1.00	213	13.71	36.72	46.00	-9.28

- Note:
1. Margin = Amplitude – limit, if margin is minus means under limit.
 2. Corrected Amplitude = Reading Amplitude + Correction Factors
 3. Correction factor = Antenna factor + (Cable Loss – Amplitude gain)

Table 3 Open Field Radiated Emissions For 1GHz 18GHz [Horizontal] [CH 1]

Radiated Emission				Corrected Amplitude		FCC Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
4075.97	1.00	268	1.48	41.08	---	74.00	54.00	-12.92
7237.78	1.00	337	10.10	46.70	---	74.00	54.00	-7.30

Table 4 Open Field Radiated Emissions For 1GHz 18GHz [Vertical] [CH 1]

Radiated Emission				Corrected Amplitude		FCC Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
7237.78	1.00	21	10.10	46.54	---	74.00	54.00	-7.46

Note:

1. Margin = Corrected - Limit.
2. The spurious RF conducted emissions levels do comply with the 20dBc limit both at its bandedges and other spurious emissions.
3. As stated in Section 15.35(b), for any frequencies above 1000MHz, radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. As the results of our test, the peak amplitudes are already below the FCC limit. Thus the average amplitudes of the rest are omitted.

Table 5 Open Field Radiated Emissions For 1GHz 18GHz [Horizontal] [CH 6]

Radiated Emission				Corrected Amplitude		FCC Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
4124.31	1.00	92	1.55	43.32	---	74.00	54.00	-10.68

Table 6 Open Field Radiated Emissions For 1GHz 18GHz [Vertical] [CH 6]

Radiated Emission				Corrected Amplitude		FCC Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBμV/m)		Limit (dBμV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
4124.31	1.00	86	1.55	40.99	---	74.00	54.00	-13.01
6186.53	1.00	169	7.48	42.09	---	74.00	54.00	-11.91

Note:

1. Margin = Corrected - Limit.
2. The spurious RF conducted emissions levels do comply with the *20dBc limit* both at its bandedges and other spurious emissions.
3. As stated in Section 15.35(b), for any frequencies above 1000MHz, radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. As the results of our test, the peak amplitudes are already below the FCC limit. Thus the average amplitudes of the rest are omitted.

Table 7 Open Field Radiated Emissions For 1GHz 18GHz [Horizontal] [CH 11]

Radiated Emission				Corrected Amplitude		FCC Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
4176.67	1.00	223	1.86	43.47	---	74.00	54.00	-10.53

Table 8 Open Field Radiated Emissions For 1GHz 18GHz [Vertical] [CH 11]

Radiated Emission				Corrected Amplitude		FCC Class B (3m)		
Frequency (MHz)	Ant. H. (m)	Table (°)	Correction Factors (dB)	(dBµV/m)		Limit (dBµV/m)		Margin (dB)
				Peak	Average	Peak	Ave.	
4176.67	1.00	76	1.86	40.13	---	74.00	54.00	-13.87
6263.06	1.00	249	7.65	42.59	---	74.00	54.00	-11.41

Note:

1. Margin = Corrected - Limit.
2. The spurious RF conducted emissions levels do comply with the 20dBc limit both at its bandedges and other spurious emissions.
3. As stated in Section 15.35(b), for any frequencies above 1000MHz, radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. As the results of our test, the peak amplitudes are already below the FCC limit. Thus the average amplitudes of the rest are omitted.

8.4 Test Result of the Bandedge


If any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either *at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in § 15.209(a)*,

We perform this section by the *conducted* manner, the RBW is set to 100kHz and VBW>RBW. We'd made the observation *up to 10th harmonics and the criterion is all the harmonic/spurious emissions must be 20dB below the highest emission level measured*. If the emissions fall in the restricted bands stated in the Part15.205(a) must also *comply with the radiated emission limits specified in Part15.209(a)*.

The following pages show our observations referring to the channel 1 and 11 respectively.

Test Condition & Setup: same as 3.1

Channel 1



This is the hard copy of our bandedge measurement generated by our bandedge testing program. The picture shown above is the bandedge of channel 1.

1. The lobe right by the fundamental side is already 20dB below the highest emission level.
2. The emissions recorded in the restricted band (<2400MHz) is do comply with the Part 15.209(a) – under the limited line marked in red color.

Channel 11

This is the hard copy of our bandedge measurement generated by our bandedge testing program. The picture shown above is the bandedge of channel 11.

1. The lobe right by the fundamental side is already 20dB below the highest emission level.
2. The emissions recorded in the restricted band ($>2483.5\text{MHz}$) is do comply with the Part 15.209(a) – under the limited line marked in red color.

IX. Section 15.247(d): Power Spectral Density

9.1 Test Condition & Setup

The tests below are running with the EUT transmitter set at high power in TDD mode . The EUT is needed to force selection of output power level and channel number. While testing, the EUT was set to transmit continuously and to be tested by the contact manner with the spectrum analyzer.

The attachments below show our observation.

9.2 Test Instruments Configuration



P.S.: Notebook computer to control the EUT at maximal power output and channel Number and set antenna kit

9.3 List of Test Instruments

Instrument Name	Model No.	Brand	Serial No.	Last time	Next time
Spectrum Analyzer	8592A	H P	3003AD1401	01/02/03	01/01/04

9.4 Test Result of Power spectral density


The following table shows a summary of the test results of the Power Spectral Density.

Channel	Frequency (GHz)	Ppr (dBm)	Cable Loss (dB)	Ppq (dBm)	Limit (dB)	Margin (dB)
CH 01	2.412	-12.17	1.80	-10.37	8.00	-18.37
CH 06	2.437	-11.70	1.85	-9.85	8.00	-17.85
CH 11	2.462	-12.45	1.93	-10.52	8.00	-18.52


Note:

- The following pages show the results of spectrum reading.
- Ppr: spectrum read power density (using peak search mode),
Ppq: actual peak power density in the spread spectrum band. $Ppq = Ppr + |\text{Cable Loss}|$

Channel 01



Channel 06



Channel 11

