

FCC TEST REPORT

for

47 CFR Part 15 Subpart C

Equipment : Mobile Phone
Trade Name : BenQ-Siemens
Model No. : EF51
Marketing Name : PANB3A
FCC ID : JVPEF51A
Filing Type : Certification
Applicant : BenQ Corporation
157 Shan-Ying Road, Gueishan Taoyuan 333, Taiwan
BenQ Ref. No. : NL-6823

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**
- The data shown in this test report were carried out on Jan. 6, 2006 at **Sporton International Inc. LAB.**
- Report No.: FR5D2711-02, Report Version: Rev. 01.



Dr. Daniel Lee
EMC/SAR Director

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255



Table of Contents

History of this test report.....ii

1. General Description of Equipment under Test.....1

 1.1.Applicant.....1

 1.2.Manufacturer1

 1.3.Basic Description of Equipment under Test.....1

 1.4.Feature of Equipment under Test2

2. Test Configuration of Equipment under Test3

 2.1.Test Manner3

 2.2.Test Mode3

 2.3.Connection Diagram of Test System3

 2.4.Ancillary Equipment List.....3

3. RF Utility4

4. General Information of Test.....5

 4.1.Test Voltage5

 4.2.Standard for Methods of Measurement.....5

 4.3.Test in Compliance with5

 4.4.Frequency Range Investigated5

 4.5.Test Distance5

5. Report of Measurements and Examinations6

 5.1.List of Measurements and Examinations6

 5.2.Hopping Channel Separation7

 5.3.Number of Hopping Frequency11

 5.5 Dwell Time of Each Frequency within a 30 Seconds Period17

 5.6 Output Power37

 5.7 100kHz Bandwidth of Frequency Band Edges37

 5.8 Conducted Emission37

 5.9 Radiated Emission Measurement37

 5.10 Antenna Requirements.....37

6. List of Measuring Equipments Used37

7. Uncertainty Evaluation.....37

Appendix A. External Product Photograph

Appendix B. Internal Photograph

Appendix C. Setup Photograph



History of this test report

Report Issue Date: Jun. 06, 2006

Report No.	Description



1. General Description of Equipment under Test

1.1. Applicant

BenQ Corporation

157 Shan-Ying Road, Gueishan Taoyuan 333, Taiwan

1.2. Manufacturer

1. BneQ Corporation

157 Shan-Ying Road, Gueishan Taoyuan 333, Taiwan

2. BenQ (IT) Co., Ltd.

No.169, Zhujiang Road, New District, Suzhou, Jiangsu, P.R., China

1.3. Basic Description of Equipment under Test

Equipment	: Mobile Phone
Trade Name	: BenQ-Siemens
Model No.	: EF51
Marketing Name	: PANB3A
FCC ID	: JVPEF51A
Power Supply Type	: Switching, From Battery 3.7V
AC Power Cord	: AC 120V, Weave-Shielded, Wall-mount, 1.7 meter, 2 pin
Earphone	: HES-104
Date Cable	: 5K.G6501.001
Battery	: BenQ, 2C.2G0M0.101
Adapter	: BenQ, JSP054070UU

**1.4. Feature of Equipment under Test**

Product Feature & Specification			
1. Support Band	GSM850/1800/1900 with Bluetooth		
2. Modulation Type/Data Rate	GFSK		
3. Frequency Range.	2400 MHz ~ 2483.5 MHz		
4. Number of Channels	79		
5. Carrier Frequency of each channel	2402+ n*1 MHz, n= 0~78		
6. Channel Spacing	1 MHz		
7. Maximum Output Power to Antenna (Normal condition)	-0.01 dBm		
8. Antenna Type	PIFA		
9. Antenna Gain	5 dBi		
10. HW Version	LPR4		
11. SW Version	V0.01		
12. Function Type	Transmitter		Transceiver V
13. Power Rating (DC/AC , Voltage)	3.8V / 250mA		
14. DUT Stage	Identical Prototype		

2. Test Configuration of Equipment under Test


2.1. Test Manner

- a. The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.
- b. For spurious emission below 1GHz, only one channel of each application was tested because it is not related to channel selection.
- c. The EUT is programmed to transmit signal continuously for all testings.
- d. Frequency range investigated: conduction 150 kHz to 30 MHz, radiation 30 MHz to 25000MHz.

2.2. Test Mode

Application	Bluetooth
Radiated Emission and conducted test items	Mode 1: Tx_CH00_2402 MHz Mode 2: Tx_CH39_2441 MHz Mode 3: Tx_CH78_2480 MHz
Conducted Emission	Mode 1: PCS 1900 Idle Mode + USB Link Mode 2: PCS1900 Idle Mode + Camera + Earphone Mode 3: PCS1900 Idle Mode + MP3 Player + Earphone + BT Link

2.3. Connection Diagram of Test System



2.4. Ancillary Equipment List

Item	Equipment	Model No.	Serial No.
1.	Base Station (R&S)	CMU200	105934



3. RF Utility

The EUT is in BT link mode with BT earphone for conducted emission or in BT continuous Tx Mode controlled by RF utility and base station simulator for radiated emission and other conducted tests.



4. General Information of Test

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park,
Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
TEL : 886-3-327-3456
FAX : 886-3-318-0055
Test Site No : CO01-HY, 03CH06-HY

4.1. Test Voltage

AC 120V

4.2. Standard for Methods of Measurement

ANSI C63.4-2003

4.3. Test in Compliance with

47 CFR Part 15 Subpart C

4.4. Frequency Range Investigated

Conduction: from 150 kHz to 30 MHz
Radiation: from 30 MHz to 25000MHz

4.5. Test Distance

The test distance of radiated emission from antenna to EUT is 3 m.



5. Report of Measurements and Examinations

5.1. List of Measurements and Examinations

FCC Rule	Description of Test	Result	Section
15.247(a)(1)	Hopping Channel Separation	Pass	5.2
15.247(a)(1)(iii)	Number of Hopping Frequency Used	Pass	5.3
15.247(a)(1)	Hopping Channel Bandwidth	Pass	5.4
15.247(a)(1)(iii)	Dwell Time of Each Frequency	Pass	5.5
15.247(b)(1)	Output Power	Pass	5.6
15.247(c)	100kHz Bandwidth of Frequency Band Edges	Pass	5.7
15.207	Conducted Emission	Pass	5.8
15.209	Radiated Emission	Pass	5.9
15.203	Antenna Requirement	Pass	5.10

5.2. Hopping Channel Separation


5.2.1. Measuring Instruments :

As described in chapter 6 of this test report.

5.2.2. Test Procedure :

1. The transmitter output was connected to the spectrum analyzer directly.
2. Set RBW of spectrum analyzer to 30kHz and VBW to 100kHz.
3. The Hopping Channel Separation is defined as the channel is separated with the next channel.

5.2.3. Test Setup Layout :



5.2.4. Test Result : The spectrum analyzer plots are attached as below

- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay

Channel	Frequency (MHz)	Hopping Channel Separation (MHz)	Limits (MHz)	Plot Ref. No.
00	2402	1.000	0.880	Mode 1
39	2441	1.003	0.877	Mode 2
78	2480	1.003	0.877	Mode 3

Remark: Limit is the greater one of 25kHz or the 20dB bandwidth of the hopping channel.




5.2.5 Hopping Channel Separation

Mode 1: CH00 (2402MHz)



* RBW 30 kHz Delta 2 [T1]
 * VBW 100 kHz -0.25 dB
 * SWT 500 ms 1.000000000 MHz
 Ref 10 dBm * Att 20 dB



Date: 5.JAN.2006 21:10:50



Mode 2: CH39 (2441MHz)




* RBW 30 kHz Delta 2 [T1]
 * VBW 100 kHz -0.01 dB
 * SWT 500 ms 1.003205128 MHz

Ref 10 dBm

* Att 20 dB

1 PK
MAXH



Center 2.4415 GHz

200 kHz/

Span 2 MHz

Date: 5.JAN.2006 21:11:54



Mode 3: CH78 (2480MHz)




*RBW 30 kHz Delta 2 [T1]
 *VBW 100 kHz -0.22 dB
 *SWT 500 ms 1.003205128 MHz

Ref 10 dBm

* Att 20 dB

1 PK
MAXH



Center 2.4795 GHz

200 kHz/

Span 2 MHz

Date: 5.JAN.2006 21:14:05

5.3. Number of Hopping Frequency


5.3.1. Measuring Instruments :

As described in chapter 6 of this test report.

5.3.2. Test Procedure :

1. The transmitter output was connected to the spectrum analyzer directly.
2. Set RBW of spectrum analyzer to 100kHz and VBW to 100kHz.
3. The number of hopping frequency used is defined as the device has the numbers of total channel.

5.3.3. Test Setup Layout :




5.3.4. Test Result : See spectrum analyzer plots below

- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay

Number of Hopping Frequency (Channel)	Limits (Channel)
79	15



5.3.5 Number of Hopping Frequency



Date: 5.JAN.2006 23:20:52

5.4 Hopping Channel Bandwidth


5.4.1 Measuring Instruments :

As described in chapter 6 of this test report.

5.4.2 Test Procedure :

1. The transmitter output was connected to the spectrum analyzer directly.
2. Set RBW of spectrum analyzer to 30kHz and VBW to 300kHz.
3. The Hopping Channel bandwidth is defined as the frequency range where the power is higher than peak power minus 20dB.

5.4.3 Test Setup Layout :



5.4.4 Test Result : See spectrum analyzer plots below


- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay

Channel	Frequency (MHz)	Hopping Channel Bandwidth (MHz)	Limits (MHz)	Plot Ref. No.
00	2402	0.880	1.0	Mode 1
39	2441	0.877	1.0	Mode 2
78	2480	0.877	1.0	Mode 3



5.4.5 Hopping Channel Bandwidth

Mode 1: CH00 (2402MHz)



Date: 5.JAN.2006 19:33:59




Mode 2: CH39 (2441MHz)



* RBW 30 kHz Delta 2 [T1]
 * VBW 300 kHz 0.16 dB
 * SWT 500 ms 876.602564100 kHz

Ref 10 dBm * Att 20 dB



Center 2.441 GHz 100 kHz/ Span 1 MHz

Date: 5.JAN.2006 19:29:02




Mode 3: CH78 (2480MHz)



* RBW 30 kHz Delta 2 [T1]
 * VBW 300 kHz -0.15 dB
 * SWT 500 ms 876.602564100 kHz

Ref 10 dBm * Att 20 dB



Center 2.48 GHz 100 kHz/ Span 1 MHz

Date: 5.JAN.2006 19:26:19

5.5 Dwell Time of Each Frequency within a 30 Seconds Period


5.5.1 Measuring Instruments :

As described in chapter 6 of this test report.

5.5.2 Test Procedure :

1. The transmitter output was connected to the spectrum analyzer directly.
2. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
3. Set the center frequency on any frequency would be measured and set the frequency span to zero span.
4. The equation = $30 \cdot (1600/79) \cdot t$ (t = the time duration of one single pulse)

5.5.3 Test Setup Layout :



5.5.4 Test Result : See spectrum analyzer plots below

- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay

Ch00

Package Mode	Average Hopping Channel	Package Transfer Time (us)	Dwell Time (s)	Limit (s)
DH1	9.2	548.07	0.159	0.4
DH3	4.3	1834.93	0.249	0.4
DH5	3.5	3044.87	0.337	0.4



CH39

Package Mode	Average Hopping Channel	Package Transfer Time (us)	Dwell Time (s)	Limit (s)
DH1	9.5	544.87	0.164	0.4
DH3	5.4	1802.88	0.308	0.4
DH5	2.7	3092.94	0.264	0.4

CH78

Package Mode	Average Hopping Channel	Package Transfer Time (us)	Dwell Time (s)	Limit (s)
DH1	9.8	544.87	0.169	0.4
DH3	4.8	1802.88	0.273	0.4
DH5	3.3	3108.97	0.324	0.4

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)




5.5.5 Dwell Time


DH1 (CH00)



Ref 10 dBm * Att 20 dB RBW 1 MHz Marker 1 [T1] -51.91 dBm
 * VBW 1 MHz SWT 2 ms 89.743590 μ s



Date: 5.JAN.2006 21:22:27




Date: 5.JAN.2006 21:47:22




DH1 (CH39)



Ref 10 dBm * Att 20 dB RBW 1 MHz Delta 3 [T1] -0.35 dB
 * VBW 1 MHz SWT 2 ms 1.259615 ms



Date: 5.JAN.2006 21:31:03




Date: 5.JAN.2006 21:48:14



DH1 (CH78)




Ref 10 dBm * Att 20 dB RBW 1 MHz Delta 3 [T1] 2.84 dB
 * VBW 1 MHz SWT 2 ms 1.259615 ms



Date: 5.JAN.2006 21:34:36



Ref 10 dBm * Att 20 dB RBW 1 MHz
* VBW 1 MHz SWT 10 s




Date: 5.JAN.2006 21:50:04




DH3 (CH00)



RBW 1 MHz Delta 3 [T1] 4.79 dB
 * VBW 1 MHz 2.516026 ms
 Ref 10 dBm * Att 20 dB SWT 5 ms



Date: 5.JAN.2006 23:41:50



Date: 5.JAN.2006 21:52:17




DH3 (CH39)



Ref 10 dBm * Att 20 dB RBW 1 MHz Delta 3 [T1] -0.15 dB


* VBW 1 MHz SWT 5 ms 2.500000 ms



Date: 5.JAN.2006 21:29:32



Ref 10 dBm * Att 20 dB RBW 1 MHz
* VBW 1 MHz SWT 10 s




Date: 5.JAN.2006 21:53:04



DH3 (CH78)




Ref 10 dBm * Att 20 dB RBW 1 MHz Delta 3 [T1] 0.16 dB
 * VBW 1 MHz SWT 5 ms 2.500000 ms



Date: 5.JAN.2006 21:35:52



Ref 10 dBm * Att 20 dB RBW 1 MHz
* VBW 1 MHz SWT 10 s




Date: 5.JAN.2006 21:53:43



DH5 (CH00)




Ref 10 dBm * Att 20 dB RBW 1 MHz Delta 3 [T1] -0.04 dB
 * VBW 1 MHz SWT 10 ms 3.750000 ms



Center 2.402 GHz 1 ms/

Date: 5.JAN.2006 21:26:20



Date: 5.JAN.2006 21:54:45




DH5 (CH39)




Ref 10 dBm * Att 20 dB RBW 1 MHz Delta 3 [T1] -0.42 dB

* VBW 1 MHz SWT 10 ms 3.750000 ms



Date: 5.JAN.2006 21:27:55




Date: 5.JAN.2006 22:44:26




DH5 (CH78)



Ref 10 dBm * Att 20 dB RBW 1 MHz Delta 3 [T1] 3.94 dB
 * VBW 1 MHz SWT 10 ms 3.766026 ms



Date: 5.JAN.2006 21:37:02



Date: 5.JAN.2006 22:44:58

5.6 Output Power


5.6.1 Measuring Instruments :

As described in chapter 6 of this test report.

5.6.2 Test Procedure :

1. The transmitter output was connected to the spectrum analyzer directly.
2. The center frequency of the spectrum analyzer was set to the fundamental frequency and set RBW to 3MHz and VBW to 3MHz.

5.6.3 Test Setup Layout :



5.6.4 Test Result : See spectrum analyzer plots below

- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay

Channel	Frequency (MHz)	Measured Output Power (dBm)	Limits (Watt/dBm)	Plot Ref. No.
00	2402	-0.01	1W/30 dBm	Mode 1
39	2441	-0.04	1W/30 dBm	Mode 2
78	2480	-0.06	1W/30 dBm	Mode 3




5.6.5 Output Power

Mode 1: CH00 (2402MHz)



Ref 9 dBm * Att 20 dB * RBW 3 MHz Marker 1 [T1]
 * VBW 3 MHz -0.01 dBm
 * SWT 500 ms 2.401863782 GHz



Date: 5.JAN.2006 19:04:07



Mode 2: CH39 (2441MHz)




* RBW 3 MHz Marker 1 [T1]
 * VBW 3 MHz -0.04 dBm
 * SWT 500 ms 2.440887821 GHz

Ref 9 dBm

* Att 20 dB

1 PK
MAXH



Center 2.441 GHz 500 kHz/ Span 5 MHz

Date: 5.JAN.2006 19:06:08



Mode 3: CH78 (2480MHz)




* RBW 3 MHz Marker 1 [T1]
 * VBW 3 MHz -0.06 dBm
 * SWT 500 ms 2.479847756 GHz

Ref 9 dBm

* Att 20 dB

1 PK
MAXH



Center 2.48 GHz

500 kHz/

Span 5 MHz

Date: 5.JAN.2006 19:06:44



5.7 100kHz Bandwidth of Frequency Band Edges

5.7.1 Measuring Instruments :

As described in chapter 6 of this test report.

5.7.2 Test Procedure :

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span for the conducted measurement, and RBW/VBW=1MHz/1MHz for peak measurement and RBW/VBW=1MHz/300Hz for average measurement in the radiated measurement.
3. The band edges was measured and recorded.

5.7.3 Test Result :

- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay

Test Result in lower band (Channel 00) : PASS

Test Result in higher band(Channel 78) : PASS

5.7.4 Note on Band edge Emission

CH00 (Horizontal)

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Detect Mode
2390.00	49.51	-24.49	74.00	50.22	30.48	4.26	35.46	200	0	Peak
2390.00	38.38	-15.62	54.00	39.09	30.48	4.26	35.46	100	126	Average

CH00 (Vertical)

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Detect Mode
2390.00	49.40	-24.60	74.00	50.11	30.48	4.26	35.46	200	360	Peak
2390.00	38.36	-15.64	54.00	39.07	30.48	4.26	35.46	104	255	Average



CH78 (Horizontal)

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Detect Mode
2483.50	61.04	-12.96	74.00	61.78	30.41	4.36	35.51	200	0	Peak
2483.50	45.21	-8.79	54.00	45.95	30.41	4.36	35.51	100	12	Average

CH78 (Vertical)

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Detect Mode
2483.50	64.05	-9.94	74.00	64.80	30.41	4.36	35.51	102	0	Peak
2483.50	47.78	-6.22	54.00	48.52	30.41	4.36	35.51	100	255	Average




5.7.5 Frequency Band Edge

Mode 1: CH00 (2402 MHz)



*RBW 100 kHz Marker 1 [T1]
 *VBW 100 kHz -38.01 dBm
 *SWT 500 ms 2.400115385 GHz




Date: 5.JAN.2006 22:57:42



Mode 3: CH78 (2480 MHz)



* RBW 100 kHz Marker 1 [T1]
* VBW 100 kHz -47.52 dBm
* SWT 500 ms 2.483891031 GHz



Date: 5.JAN.2006 19:47:45



5.8 Conducted Emission

5.8.1 Measuring Instruments

As described in chapter 6 of this test Report.

5.8.2 Test Procedures :


- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power port of a line impedance stabilization network (LISN).
- c. All the support units are connected to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.



5.8.3 Test Data Test Mode 1


- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay
- Test Mode : Mode 1

The test that passed at minimum margin was marked by the frame in the following table.



Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B 2001/004 200505 LINE
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120V/60Hz
 Model : FD 5D2711
 Memo : PCS1900 Idle Mode+USB Link

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.173	49.68	-15.14	64.82	49.59	0.06	0.03	QP
2	0.173	39.87	-14.95	54.82	39.78	0.06	0.03	Average
3	0.230	44.17	-18.28	62.45	44.09	0.06	0.02	QP
4	0.230	34.42	-18.03	52.45	34.34	0.06	0.02	Average
5	0.350	37.12	-21.84	58.96	37.02	0.06	0.04	QP
6	0.350	37.61	-11.35	48.96	37.51	0.06	0.04	Average
7	2.140	39.25	-16.75	56.00	39.01	0.12	0.12	QP
8	2.140	36.94	-9.06	46.00	36.70	0.12	0.12	Average
9	3.470	43.01	-12.99	56.00	42.67	0.19	0.15	QP
10	3.470	36.65	-9.35	46.00	36.31	0.19	0.15	Average
11	5.510	40.23	-19.77	60.00	39.83	0.21	0.19	QP
12	5.510	31.99	-18.01	50.00	31.59	0.21	0.19	Average



Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B 2001/004 200505 NEUTRAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120V/60Hz
 Model : FD 5D2711
 Memo : PCS1900 Idle Mode+USB Link


	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.233	53.48	-8.86	62.34	53.35	0.11	0.02	QP
2	0.233	35.88	-16.46	52.34	35.75	0.11	0.02	Average
3	0.291	50.98	-9.52	60.50	50.84	0.11	0.03	QP
4	0.291	40.05	-10.45	50.50	39.91	0.11	0.03	Average
5	0.348	44.41	-14.60	59.01	44.26	0.11	0.04	QP
6	0.348	38.23	-10.78	49.01	38.08	0.11	0.04	Average
7	0.464	48.89	-7.73	56.62	48.71	0.13	0.05	QP
8	0.464	42.64	-3.98	46.62	42.46	0.13	0.05	Average
9	1.580	35.55	-20.45	56.00	35.21	0.23	0.11	QP
10	1.580	25.30	-20.70	46.00	24.96	0.23	0.11	Average
11	3.620	33.34	-22.66	56.00	32.96	0.23	0.15	QP
12	3.620	27.96	-18.04	46.00	27.58	0.23	0.15	Average



5.8.4 Test Data Test Mode 2


- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay
- Test Mode : Mode 1

The test that passed at minimum margin was marked by the frame in the following table.



Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B 2001/004 200505 LINE
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120V/60Hz
 Model : FD 5D2711
 Memo : PCS1900 Idle Mode+Camera+Earphone
 : +BT Link

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.173	49.32	-15.50	64.82	49.23	0.06	0.03	QP
2	0.173	38.96	-15.86	54.82	38.87	0.06	0.03	Average
3	0.232	43.75	-18.63	62.38	43.67	0.06	0.02	QP
4	0.232	24.18	-28.20	52.38	24.10	0.06	0.02	Average
5	0.350	45.49	-13.47	58.96	45.39	0.06	0.04	QP
6	0.350	29.68	-19.28	48.96	29.58	0.06	0.04	Average
7	0.755	38.61	-17.39	56.00	38.44	0.09	0.08	QP
8	0.755	31.07	-14.93	46.00	30.90	0.09	0.08	Average
9	1.040	39.22	-16.78	56.00	39.01	0.11	0.10	QP
10	1.040	20.24	-25.76	46.00	20.03	0.11	0.10	Average
11	2.380	34.35	-21.65	56.00	34.08	0.14	0.13	QP
12	2.380	24.49	-21.51	46.00	24.22	0.14	0.13	Average



Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B 2001/004 200505 NEUTRAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120V/60Hz
 Model : FD 5D2711
 Memo : PCS1900 Idle Mode+Camera+Earphone
 :+BT Link


	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.172	49.53	-15.33	64.86	49.39	0.11	0.03	QP
2	0.172	38.11	-16.75	54.86	37.97	0.11	0.03	Average
3	0.230	43.42	-19.03	62.45	43.29	0.11	0.02	QP
4	0.230	29.57	-22.88	52.45	29.44	0.11	0.02	Average
5	0.289	34.81	-25.74	60.55	34.67	0.11	0.03	QP
6	0.289	29.95	-20.60	50.55	29.81	0.11	0.03	Average
7	0.346	36.29	-22.77	59.06	36.14	0.11	0.04	QP
8	0.346	26.69	-22.37	49.06	26.54	0.11	0.04	Average
9	0.464	36.94	-19.68	56.62	36.76	0.13	0.05	QP
10	0.464	30.55	-16.07	46.62	30.37	0.13	0.05	Average
11	5.330	31.21	-28.79	60.00	30.76	0.26	0.19	QP
12	5.330	26.28	-23.72	50.00	25.83	0.26	0.19	Average



5.8.5 Test Data Test Mode 3


- Temperature: 25°C
- Relative Humidity: 60%
- Test Engineer : Jay
- Test Mode : Mode 1

The test that passed at minimum margin was marked by the frame in the following table.



Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B 2001/004 200505 LINE
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120V/60Hz
 Model : FD 5D2711
 Memo : PCS1900 Idle Mode+MP3 Player+Earphone
 :+BT Link

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.176	48.68	-15.99	64.67	48.59	0.06	0.03	QP
2	0.176	38.60	-16.07	54.67	38.51	0.06	0.03	Average
3	0.232	44.25	-18.13	62.38	44.17	0.06	0.02	QP
4	0.232	29.60	-22.78	52.38	29.52	0.06	0.02	Average
5	0.292	41.07	-19.40	60.47	40.98	0.06	0.03	QP
6	0.292	22.64	-27.83	50.47	22.55	0.06	0.03	Average
7	0.410	38.64	-19.01	57.65	38.54	0.06	0.04	QP
8	0.410	23.97	-23.68	47.65	23.87	0.06	0.04	Average
9	3.550	36.42	-19.58	56.00	36.08	0.19	0.15	QP
10	3.550	32.96	-13.04	46.00	32.62	0.19	0.15	Average
11	6.950	38.16	-21.84	60.00	37.73	0.21	0.22	QP
12	6.950	24.70	-25.30	50.00	24.27	0.21	0.22	Average



Site : CO01-HY
 Condition : CNS/VCCI/CISPR-B 2001/004 200505 NEUTRAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120V/60Hz
 Model : FD 5D2711
 Memo : PCS1900 Idle Mode+MP3 Player+Earphone
 :+BT Link

	Freq	Level	Over	Limit	Read	Probe	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.176	49.23	-15.44	64.67	49.09	0.11	0.03	QP
2	0.176	37.47	-17.20	54.67	37.33	0.11	0.03	Average
3	0.232	44.66	-17.72	62.38	44.53	0.11	0.02	QP
4	0.232	34.39	-17.99	52.38	34.26	0.11	0.02	Average
5	0.291	41.47	-19.03	60.50	41.33	0.11	0.03	QP
6	0.291	30.24	-20.26	50.50	30.10	0.11	0.03	Average
7	0.408	36.02	-21.67	57.69	35.87	0.11	0.04	QP
8	0.408	29.35	-18.34	47.69	29.20	0.11	0.04	Average
9	0.466	32.08	-24.50	56.58	31.90	0.13	0.05	QP
10	0.466	27.03	-19.55	46.58	26.85	0.13	0.05	Average
11	8.110	33.56	-26.44	60.00	33.01	0.31	0.24	QP
12	8.110	25.36	-24.64	50.00	24.81	0.31	0.24	Average



5.9 Radiated Emission Measurement


5.9.1 Measuring Instruments

As described in chapter 6 of this Report.

5.9.2 Test Procedures

1. The EUT was placed on a rotatable table top 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. For testing below 1GHz, If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

5.9.3 Typical Test Setup Layout of Radiated Emission






5.9.4 Test Data

- Temperature : 24 °C
- Relating Humidity : 52 %
- Test Engineer : Jay
- Test Mode : Mode 1
- Polarization : Horizontal


The test that passed at the minimum margin was marked by the frame in the following test record



Site : 03CH06-HY
 Condition : HF-ANT-071025-940201 HORIZONTAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch00,2402MHz
 Plane : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 @	2390.00	49.51	-24.49	74.00	50.22	30.48	4.26	35.46	200	0 Peak
2 @	2390.00	38.38	-15.62	54.00	39.09	30.48	4.26	35.46	100	126 Average
3 @	2402.00	94.25			94.96	30.48	4.26	35.46	200	0 Peak
4 @	2402.00	67.84			68.55	30.48	4.26	35.46	100	126 Average
5 @	2498.00	49.83	-24.17	74.00	50.57	30.40	4.39	35.53	200	0 Peak
6 @	2498.00	38.19	-15.81	54.00	38.93	30.40	4.39	35.53	100	126 Average


Remark: #3 and #4 Fundamental Signal





- Test Mode : Mode 1
- Polarization : Vertical


The test that passed at minimum margin was marked by the frame in the following table.



Site : 03CH06-HY
 Condition : HF-ANT-071025-940201 VERTICAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch00,2402MHz
 Plane : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table		
	MHz	dBuV/m	dB	dBuV/m	Level	Loss	Factor	Pos	Pos	Remark	
					dBuV	dB	dB	cm	deg		
1 @	2390.00	49.40	-24.60	74.00	50.11	30.48	4.26	35.46	200	360	Peak
2 @	2390.00	38.36	-15.64	54.00	39.07	30.48	4.26	35.46	104	255	Average
3 @	2402.00	97.07			97.78	30.48	4.26	35.46	200	360	Peak
4 @	2402.00	71.85			72.56	30.48	4.26	35.46	104	255	Average
5 @	2498.00	49.94	-24.06	74.00	50.68	30.40	4.39	35.53	200	360	Peak
6 @	2498.00	38.19	-15.81	54.00	38.93	30.40	4.39	35.53	104	255	Average


Remark: #3 and #4 Fundamental Signal






- Temperature : 24 °C
- Relating Humidity : 52 %
- Test Enginner : Jay
- Test Mode : Mode 2
- Polarization : Horizontal

The test that passed at minimum margin was marked by the frame in the following table.




Site : 03CH06-HY
 Condition : BI-LOG-2004-1122 HORIZONTAL
 EUT : GSM Tri Band Mobile Phone(Bhuetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch39,2441MHz
 Plane : E1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	30.00	16.99	-23.01	40.00	28.40	18.73	1.35	31.49	147	346	QP
2	107.49	19.24	-24.26	43.50	36.35	11.36	2.51	30.98	400	0	QP
3	121.53	17.03	-26.47	43.50	33.30	12.66	2.63	31.56	400	0	QP



Site : 03CH06-HY
 Condition : BI-LOG-2004-1122 HORIZONTAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch39,2441MHz
 Plane : E1


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	700.40	27.20	-18.80	46.00	31.84	19.04	6.93	30.61	100	0	QP
2 @	799.80	28.36	-17.64	46.00	29.13	21.90	7.45	30.12	152	348	QP
3	1000.00	28.31	-25.69	54.00	27.55	22.97	8.42	30.63	100	0	QP



Site : 03CH06-HY
 Condition : HF-ANT-071025-940201 HORIZONTAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch39,2441MHz
 Plane : E1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2344.00	50.14	-23.86	74.00	50.83	30.52	4.20	35.42	0	0	Peak
2 @	2344.00	38.38	-15.62	54.00	39.08	30.52	4.20	35.42	100	12	Average
3 @	2441.00	96.01			96.75	30.44	4.29	35.47	0	0	Peak
4 @	2441.00	69.90			70.63	30.44	4.33	35.49	100	12	Average
5	2498.00	49.84	-24.16	74.00	50.58	30.40	4.39	35.53	0	0	Peak
6 @	2498.00	38.19	-15.81	54.00	38.93	30.40	4.39	35.53	100	12	Average


Remark: #3 and #4 Fundamental Signal






- Test Mode : Mode 2
- Polarization : Vertical

The test that passed at minimum margin was marked by the frame in the following table.




Site : 03CH06-HY
 Condition : BI-LOG-2004-1122 VERTICAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch39,2441MHz
 Plane : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	30.00	21.65	-18.35	40.00	33.06	18.73	1.35	31.49	100	360 QP
2 @	40.54	34.10	-5.90	40.00	50.00	14.28	1.53	31.72	100	273 QP
3 @	46.08	31.80	-8.20	40.00	50.00	11.74	1.65	31.59	100	360 QP



Site : 03CH06-HY
 Condition : BI-LOG-2004-1122 VERTICAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch39,2441MHz
 Plane : E1


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1 @	600.30	26.93	-19.07	46.00	33.28	17.94	6.35	30.64	100	0 QP
2 @	700.40	32.47	-13.53	46.00	37.11	19.04	6.93	30.61	100	264 QP
3 @	799.80	30.33	-15.67	46.00	31.10	21.90	7.45	30.12	100	0 QP



Site : 03CH06-HY
 Condition : HF-ANT-071025-940201 VERTICAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch39,2441MHz
 Plane : E1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	2328.00	50.54	-23.46	74.00	51.23	30.54	4.17	35.40	200	0	Peak
2 @	2328.00	38.25	-15.75	54.00	38.95	30.54	4.17	35.40	103	255	Average
3 @	2441.00	97.28			98.02	30.44	4.29	35.47	200	0	Peak
4 @	2441.00	71.63			72.36	30.44	4.33	35.49	103	255	Average
5	2494.00	49.73	-24.27	74.00	50.47	30.40	4.39	35.53	200	0	Peak
6 @	2494.00	38.23	-15.77	54.00	38.97	30.40	4.39	35.53	103	255	Average


Remark: #3 and #4 Fundamental Signal





- Temperature : 24 °C
- Relating Humidity : 52 %
- Test Enginner : Jay
- Test Mode : Mode 3
- Polarization : Horizontal


The test that passed at minimum margin was marked by the frame in the following table.



Site : 03CH06-HY
 Condition : HF-ANT-071025-940201 HORIZONTAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch78,2480MHz
 Plane : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	
1	2354.00	50.06	-23.94	74.00	50.77	30.51	4.20	35.42	200	0 Peak
2	2354.00	38.42	-15.58	54.00	39.13	30.51	4.20	35.42	100	12 Average
3 X	2480.00	94.93			95.67	30.41	4.36	35.51	200	0 Peak
4 X	2480.00	69.95			70.69	30.41	4.36	35.51	100	12 Average
5	2483.50	61.04	-12.96	74.00	61.78	30.41	4.36	35.51	200	0 Peak
6	2483.50	45.21	-8.79	54.00	45.95	30.41	4.36	35.51	100	12 Average


Remark: #3 and #4 Fundamental Signal.





- Test Mode : Mode 3
- Polarization : Vertical


The test that passed at minimum margin was marked by the frame in the following table.



Site : 03CH06-HY
 Condition : HF-ANT-071025-940201 VERTICAL
 EUT : GSM Tri Band Mobile Phone(Bluetooth)
 Power : 120Vac/60Hz
 Model : FR5D2711
 Memo : BT TX Ch78,2480MHz
 Plane : E1

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Loss	Pos	Pos	
			dB	dBuV/m	dBuV	dB	dB	cm	deg	
1	2334.00	49.99	-24.01	74.00	50.68	30.54	4.17	35.40	102	0 Peak
2	2334.00	38.46	-35.54	74.00	39.16	30.54	4.17	35.40	100	255 QP
3 @	2480.00	97.72			98.45	30.41	4.36	35.51	102	0 Peak
4 !	2480.00	71.94			72.68	30.41	4.36	35.51	100	255 Average
5	2483.50	64.06	-9.94	74.00	64.80	30.41	4.36	35.51	102	0 Peak
6	2483.50	47.78	-6.22	54.00	48.52	30.41	4.36	35.51	100	255 Average

Remark: #3 and #4 Fundamental Signal



Remark: There is no more obvious spurious emission except the listings above.



5.10 Antenna Requirements

5.10.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no other antenna except assembled by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi.

5.10.2 Antenna Connected Construction

The antenna used in this product is a PIFA without connector and it is considered to meet antenna requirement of FCC.

5.10.3 Antenna Gain

The antenna gain of EUT is less than 6dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



6. List of Measuring Equipments Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Feb. 19, 2005	Feb. 19, 2006	Conduction (CO01-HY)
LISN	MessTec	NNB-2/16Z	2001/009	9kHz – 30MHz	Apr. 26, 2005	Apr. 26, 2006	Conduction (CO01-HY)
LISN (Support Unit)	MessTec	NNB-2/16Z	2001/004	9kHz – 30MHz	Apr. 20, 2005	Apr. 20, 2006	Conduction (CO01-HY)
EMI Filter	LINDGREN	LRE-2060	1004	< 450Hz	N/A	N/A	Conduction (CO01-HY)
EMI Filter	LINDGREN	N6006	201052	0 – 60Hz	N/A	N/A	Conduction (CO01-HY)
RF Cable-CON	Suhner Switzerland	RG223/U	CB029	9kHz – 30MHz	Dec. 22, 2005	Dec. 22, 2006	Conduction (CO01-HY)
Spectrum analyzer	Agilent	E4408B	MY44211030	9KHz-26.5GHz	Jul. 27, 2004	Jul. 27, 2006	Radiation (03CH06-HY)
Receiver	R&S	ESCS30	100356	9KHz-2.75GHz	Jul. 09,2004	Jul. 09,2006	Radiation (03CH06-HY)
Controller	CT	SC100	N/A	N/A	N/A	N/A	Radiation (03CH06-HY)
Bilog Antenna	SCHAFFNER	CBL6112B	2885	30MHz -2GHz	Nov. 22, 2005	Nov. 22, 2006	Radiation (03CH06-HY)
Horn Antenna	Com-Power	AH118	071025	1G-18G	Feb. 22, 2005	Feb. 22, 2006	Radiation (03CH06-HY)
SHF-EHF Horn	SCHWARZBECK	BBHA 9170	9170-249	14G - 40G	Jul. 21, 2005	Jul. 20, 2006	Radiation (03CH06-HY)
HF Amplifier	MITEQ	AFS44	973248	0.1G - 26.5G	Dec. 17, 2005	Dec. 17, 2006	Radiation (03CH06-HY)
Amplifier	MITEQ	AMF-6F	997165	26G - 40G	Jul. 21, 2005	Jul. 20, 2006	Radiation (03CH06-HY)
Turn Table	HD	DS 420	420/650/00	0 ~ 360 degree	N/A	N/A	Radiation (03CH06-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	N/A	Radiation (03CH06-HY)



7. Uncertainty Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.10	Normal(k=2)	0.05
Cable loss	0.10	Normal(k=2)	0.05
AMN insertion loss	2.50	Rectangular	0.63
Receiver Spec	1.50	Rectangular	0.43
Site imperfection	1.39	Rectangular	0.80
Mismatch	+0.34/-0.35	U-shape	0.24
combined standard uncertainty Uc(y)	1.13		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	2.26		

Uncertainty of Radiated Emission Evaluation (30MHz ~ 1000MHz)

Contribution	Uncertainty of x_i		$u(x_i)$
	dB	Probability Distribution	
Receiver reading	0.15	Normal(k=2)	0.08
Antenna factor calibration	1.12	Normal(k=2)	0.56
Cable loss calibration	0.12	Normal(k=2)	0.06
Pre Amplifier Gain calibration	0.13	Normal(k=2)	0.07
RCV/SPA specification	2.5	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1	Rectangular	0.29
Site imperfection	2.1	Rectangular	1.21
Mismatch	+0.39/-0.41	U-shaped	0.28
combined standard uncertainty Uc(y)	1.58		
Measuring uncertainty for a level of confidence of 95% U=2Uc(y)	3.16		



Uncertainty of Radiated Emission Measurement (1GHz ~ 40GHz)

Contribution	Uncertainty of x_i		$u(x_i)$	C_i	$C_i * u(x_i)$
	dB	Probability Distribution			
Receiver reading	±0.10	Normal(k=1)	0.10	1	0.10
Antenna factor calibration	±1.70	Normal(k=2)	0.85	1	0.85
Cable loss calibration	±0.50	Normal(k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20 \log(1 - \Gamma_1 * \Gamma_2 * \Gamma_3)$	+0.34/-0.35	U-shaped	0.244	1	0.244
Combined standard uncertainty $U_c(y)$	2.36				
Measuring uncertainty for a level of confidence of 95% $U = 2U_c(y)$	4.72				