

SAR Test Report

Product Name : GSM900/DCS1800/PCS1900
GSM/GPRS Mobile Phone
Model No. : M305(56E14)

Applicant : BenQ Corporation
Address : 157 Shan-Ying Road, Gueishan Taoyuan 333,
Taiwan, R.O.C.

Date of Receipt : 2004/09/22
Issued Date : 2004/09/29
Report No. : 049L155SF

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date: 2004/09/29

Report No.:049L155SF



Product Name : GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
 Applicant : BenQ Corporation
 Address : 157 Shan-Ying Road, Gueishan Taoyuan 333, Taiwan,
 R.O.C.
 Manufacturer : BenQ Corporation
 Model No. : M305(56E14)
 Trade Name : BenQ
 Measurement : FCC Oet65 Supplement C June 2001
 Standard : IEEE Std. 1528-2003
 Measurement : FCC Oet65 Supplement C June 2001
 Procedure : IEEE Std. 1528-2003
 Test Result : Max. SAR Measurement (1g)
 Head: 1.26 W/kg
 Body : 0.75 W/kg
 Application Type : Certification

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

Documented By : Grace Lin
 (Grace Lin)

Tested By : Shine Hsu
 (Shine Hsu)

Approved By : Gene Chang
 (Gene Chang)

TABLE OF CONTENTS

Description	Page
1. General Information.....	5
1.1 EUT Description	5
1.2 Test Environment	5
2. SAR Measurement System	6
2.1 ALSAS-10U System Description	6
2.1.1 Applications	6
2.1.2 Area Scans.....	6
2.1.3 Zoom Scan (Cube Scan Averaging).....	7
2.1.4 ALSAS-10U Interpolation and Extrapolation Uncertainty.....	7
2.2 Isotropic E-Field Probe	7
2.2.1 Isotropic E-Field Probe Specification	9
2.3 Boundary Detection Unit and Probe Mounting Device	9
2.4 Daq-Paq (Analog to Digital Electronics).....	10
2.5 Axis Articulated Robot	10
2.6 ALSAS Universal Workstation.....	11
2.7 Universal Device Positioner.....	11
2.8 Phantom Types.....	11
2.8.1 APREL SAM Phantoms	12
2.8.2 APREL Laboratories Universal Phantom	12
3. Tissue Simulating Liquid	13
3.1 The composition of the tissue simulating liquid	13
3.2 Tissue Calibration Result	13
3.3 Tissue Dielectric Parameters for Head and Body Phantoms	14
4. SAR Measurement Procedure	15
4.1 SAR System Validation.....	15
4.1.1 Validation Dipoles.....	15
4.1.2 Validation Result	15
4.2 Arrangement Assessment Setup	16
4.2.1 Test Positions of Device Relative to Head.....	16
4.2.1.1 Definition of the “Cheek” Position	16
4.2.1.2 Definition of the “Tilted” Position.....	17
4.2.2 Test Positions for body-worn.....	18
4.3 SAR Measurement Procedure	18
5. SAR Exposure Limits	20

6. Test Equipment List..... 21
7. Measurement Uncertainty 22
8. Test Results 23
8.1 SAR Test Results Summary 23
8.2 SAR System Validation Data 25
Test Setup Photographs 58
EUT Photographs 61
Probe Calibration 62
Dipole Calibration..... 63

1. General Information

1.1 EUT Description

Product Name	GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone
Trade Name	BenQ
Model No.	M305(56E14)
IMEI No.	355092000000024
TX Frequency	1850MHz ~ 1910MHz
RX Frequency	1930MHz ~ 1990MHz
Antenna Type	Internal
Device Category	Portable
RF Exposure Environment	Uncontrolled
Hardware version	101A2
Software version	1.02
Max. Output Power (Conducted)	PCS: 30.0dBm

1.2 Test Environment

Ambient conditions in the laboratory:

Items	Required	Actual
Temperature (°C)	18-25	24
Humidity (%RH)	30-70	55

2. SAR Measurement System

2.1 ALSAS-10U System Description

ALSAS-10-U is fully compliant with the technical and scientific requirements of IEEE 1528, IEC 62209, CENELEC, ARIB, ACA, and the Federal Communications Commission. The system comprises of a six axes articulated robot which utilizes a dedicated controller.

ALSAS-10U uses the latest methodologies and FDTD modeling to provide a platform which is repeatable with minimum uncertainty.

2.1.1 Applications


Predefined measurement procedures compliant with the guidelines of CENELEC, IEEE, IEC, FCC, etc are utilized during the assessment for the device. Automatic detection for all SAR

maxima are embedded within the core architecture for the system, ensuring that peak locations used for centering the zoom scan are within a 1mm resolution and a 0.05mm repeatable position. System operation range currently available up-to 6 GHz in simulated tissue.

2.1.2 Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm² step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.



2.1.3 Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the ALSAS-10U software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m³ is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21,5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 5x5x8 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 35mm in the Z axis.

2.1.4 ALSAS-10U Interpolation and Extrapolation Uncertainty

The overall uncertainty for the methodology and algorithms the used during the SAR calculation was evaluated using the data from IEEE 1528 based on the example f3 algorithm:


$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \cdot \left(e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$

2.2 Isotropic E-Field Probe

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change. A number of methods is used for calibrating probes, and these are outlined in the table below:

Calibration Frequency	Air Calibration	Tissue Calibration
1900MHz	TEM Cell	Temperature

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



SAR is assessed with a calibrated probe which moves at a default height of 5mm from the center of the diode, which is mounted to the sensor, to the phantom surface (in the Z Axis). The 5mm offset height has been selected so as to minimize any resultant boundary effect due to the probe being in close proximity to the phantom surface.

The following algorithm is an example of the function used by the system for linearization of the output from the probe when measuring complex modulation schemes.

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

2.2.1 Isotropic E-Field Probe Specification

Calibration in Air	Frequency Dependent Below 2GHz Calibration in air performed in a TEM Cell Above 2GHz Calibration in air performed in waveguide
Sensitivity	0.70 $\mu\text{V}/(\text{V}/\text{m})^2$ to 0.85 $\mu\text{V}/(\text{V}/\text{m})^2$
Dynamic Range	0.0005 W/kg to 100W/kg
Isotropic Response	Better than 0.2dB
Diode Compression point (DCP)	Calibration for Specific Frequency
Probe Tip Radius	< 5mm
Sensor Offset	1.56 (+/- 0.02mm)
Probe Length	290mm
Video Bandwidth	@ 500 Hz: 1dB @1.02 KHz: 3dB
Boundary Effect	Less than 2% for distance greater than 2.4mm
Spatial Resolution	Diameter less than 5mm Compliant with Standards

2.3 Boundary Detection Unit and Probe Mounting Device

ALSAS-10U incorporates a boundary detection unit with a sensitivity of 0.05mm for detecting all types of surfaces. The robust design allows for detection during probe tilt (probe normalize) exercises, and utilizes a second stage emergency stop. The signal electronics are fed directly into the robot controller for high accuracy surface detection in lateral and axial detection modes (X, Y, & Z).

The probe is mounted directly onto the Boundary Detection unit for accurate tooling and displacement calculations controlled by the robot kinematics. The probe is connect to an isolated probe interconnect where the output stage of the probe is fed directly into the amplifier stage of the Daq-Paq

2.4 Daq-Paq (Analog to Digital Electronics)

ALSAS-10U incorporates a fully calibrated Daq-Paq (analog to digital conversion system) which has a 4 channel input stage, sent via a 2 stage auto-set amplifier module. The input signal is amplified accordingly so as to offer a dynamic range from 5µV to 800mV. Integration of the fields measured is carried out at board level utilizing a Co-Processor which then sends the measured fields down into the main computational module in digitized form via an RS232 communications port. Probe linearity and duty cycle compensation is carried out within the main Daq-Paq module.

ADC	12 Bit
Amplifier Range	20mV to 200mV and 150mV to 800mV
Field Integration	Local Co-Processor utilizing proprietary integration algorithms
Number of Input Channels	4 in total 3 dedicated and 1 spare
Communication	Packet data via RS232

2.5 Axis Articulated Robot



ALSAS-10U utilizes a six axis articulated robot, which is controlled using a Pentium based real-time movement controller. The movement kinematics engine utilizes proprietary (Thermo CRS) interpolation and extrapolation algorithms, which allow full freedom of movement for each of the six joints within the working envelope. Utilization of joint 6 allows for full probe rotation with a tolerance better than 0.05mm around the central axis.

Robot/Controller Manufacturer	Thermo CRS
Number of Axis	Six independently controlled axis
Positioning Repeatability	0.05mm
Controller Type	Single phase Pentium based C500C
Robot Reach	710mm
Communication	RS232 and LAN compatible

2.6 ALSAS Universal Workstation

ALSAS Universal workstation allows for repeatability and fast adaptability. It allows users to do calibration, testing and measurements using different types of phantoms with one set up, which significantly speeds up the measurement process.

2.7 Universal Device Positioner

The universal device positioner allow complete freedom of movement of the EUT. Developed to hold a EUT in a free-space scenario any additional loading attributable to the material used in the construction of the positioner has been eliminated. Repeatability has been enhanced through the linear scales which form the design used to indicate positioning for any given test scenario in all major axes. A 15° tilt indicator is included for the of aid cheek to tilt movements for head SAR analysis. Overall uncertainty for measurements have been reduced due to the design of the Universal device positioner, which allows positioning of a device in as near to a free-space scenario as possible, and by providing the means for complete repeatability.




2.8 Phantom Types

The ALSAS-10U allows the integration of multiple phantom types. SAM Phantoms fully compliant with IEEE 1528, Universal Phantom, and Universal Flat.

2.8.1 APREL SAM Phantoms

The SAM phantoms developed using the IEEE SAM CAD file. They are fully compliant with the requirements for both IEEE 1528 and FCC Supplement C. Both the left and right SAM phantoms are interchangeable, transparent and include the IEEE 1528 grid with visible NF and MB lines.



2.8.2 APREL Laboratories Universal Phantom

The Universal Phantom is used on the ALSAS-10U as a system validation phantom. The Universal Phantom has been fully validated both experimentally from 800MHz to 6GHz and numerically using XFDTD numerical software. The shell thickness is 2mm overall, with a 4mm spacer located at the NF/MB intersection providing an overall thickness of 6mm in line with the requirements of IEEE-1528.



The design allows for fast and accurate measurements, of handsets, by allowing the conservative SAR to be evaluated at on frequency for both left and right head experiments in one measurement.

3. Tissue Simulating Liquid

3.1 The composition of the tissue simulating liquid

INGREDIENT (% Weight)	900MHz Head	1800MHz Head	1900MHz Head	1900MHz Body
Water	--	--	54.90	40.5
Salt	--	--	0.18	0.50
Sugar	--	--	0.00	58.0
HEC	--	--	0.00	0.50
Preventol	--	--	0.00	0.50
DGBE	--	--	44.92	0.00

3.2 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using APREL Dielectric Probe Kit and Anritsu MS4623B Vector Network Analyzer

Liquid	Frequency	Parameters	Target Value	Measured Value	Deviation [%]	Limit [%]
Head	1900 MHz	ϵ_r	40.0	39.6	-1.0	± 5
		σ	1.40	1.42	+1.4	± 5
Body	1900 MHz	ϵ_r	53.3	52.5	-1.5	± 5
		σ	1.52	1.54	+1.3	± 5

3.3 Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.


Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

4. SAR Measurement Procedure

4.1 SAR System Validation

4.1.1 Validation Dipoles



The dipoles used is based on the IEEE-1528 standard, and is complied with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical specifications for the dipoles.

Frequency	L (mm)	h (mm)	d (mm)
1900MHz	68.0	39.5	3.6

4.1.2 Validation Result

Validation Kit: ASL-D-900-S-2		Dipole Separation Distance:10mm						
Frequency	Power	Measured Value [mW/g]		Target Value [mW/g]		Deviation [%]		Limit [%]
		1g	10g	1g	10g	1g	10g	
1900 MHz Head	1W	38.90	21.25	39.7	20.5	-2.01	+3.66	± 5

4.2 Arrangement Assessment Setup

4.2.1 Test Positions of Device Relative to Head

This specifies exactly two test positions for the handset against the head phantom, the “cheek” position and the “tilted” position. The handset should be tested in both positions on the left and right sides of the SAM phantom. If the handset construction is such that it cannot be positioned using the handset positioning procedures described in 4.2.2.1 and 4.2.2.2 to represent normal use conditions (e.g., asymmetric handset), alternative alignment procedures should be considered with details provided in the test report.




Figure 4.1a Fixed Case




Figure 4.1b Clam Shell

4.2.1.1 Definition of the “Cheek” Position

The “cheek” position is defined as follows:

- a. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece, open the cover. (If the handset can also be used with the cover closed both configurations must be tested.)
- b. Define two imaginary lines on the handset: the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A on Figures 4.1a and 4.1b), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 4.1a). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 4.1b), especially for clamshell handsets, handsets with flip pieces,

- and other irregularly-shaped handsets.
- c. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 4.2), such that the plane defined by the vertical center line and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
 - d. Translate the handset towards the phantom along the line passing through RE and LE until the handset touches the pinna.
 - e. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).
 - f. Rotate the handset around the vertical centerline until the handset (horizontal line) is symmetrical with respect to the line NF.
 - g. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the handset contact with the pinna, rotate the handset about the line NF until any point on the handset is in contact with a phantom point below the pinna (cheek). See Figure 4.2 the physical angles of rotation should be noted.




Figure 4.2 – Phone position 1, “cheek” or “touch” position.

4.2.1.2 Definition of the “Tilted” Position

The “tilted” position is defined as follows:

- a. Repeat steps (a) – (g) of 4.2.1.1 to place the device in the “cheek position.”
- b. While maintaining the orientation of the handset move the handset away from the pinna along the line passing through RE and LE in order to enable a rotation of the handset by 15 degrees.
- c. Rotate the handset around the horizontal line by 15 degrees.

d. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna (e.g., the antenna with the back of the phantom head), the angle of the handset should be reduced. In this case, the tilted position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is contact with the phantom (e.g., the antenna with the back of the head).




Figure 4.3 – Phone position 2, “tilted” position.

4.2.2 Test Positions for body-worn

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distance may be use, but not exceed 2.5 cm.

4.3 SAR Measurement Procedure

The ALSAS-10U calculates SAR using the following equation,

$$SAR = \frac{\sigma |E|^2}{\rho}$$

σ : represents the simulated tissue conductivity

ρ : represents the tissue density

The EUT is set to transmit at the required power in line with product specification, at each frequency relating to the LOW, MID, and HIGH channel settings.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The EUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR location (interpolated resolution set at 1mm^2) which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm^3).

5. SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 “Uncontrolled Environments” limits. These limits apply to a location which is deemed as “Uncontrolled Environment” which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Limits for General Population/Uncontrolled Exposure (W/kg)

Type Exposure	Uncontrolled Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	1.60 W/kg
Spatial Average SAR (whole body)	0.08 W/kg
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	4.00 W/kg

6. Test Equipment List

Instrument	Manufacturer	Model No.	Serial No.	Last Calibration
Data Acquisition Package	Aprél	ALS-DAQ-PAQ-1	QTK-313	Jun. 2004
Aprél Laboratories Probe	Aprél	ALS-E020	225	Jun. 2004
Aprél Laboratories Probe	Aprél	ALS-E020	226	Jun. 2004
Aprél Reference Dipole 1900Mhz	Aprél	ALS-D-1900-S-2	QTK-318	Jun. 2004
Boundary Detection Sensor System	Aprél	ALS-PMDPS-1	QTK-314	N/A
Dielectric Probe Kit	Aprél	ALS-PR-DIEL	QTK-296	N/A
Universal Work Station	Aprél	ALS-UWS	QTK-326	N/A
Device Holder 2.0	Aprél	ALS-H-E-SET-2	QTK-294	N/A
Left Ear SAM Phantom	Aprél	ALS-P-SAM-L	QTK-292	N/A
Right Ear SAM Phantom	Aprél	ALS-P-SAM-R	QTK-288	N/A
Universal Phantom	Aprél	ALS-P-UP-1	QTK-246	N/A
Aprél Dipole Spacer	Aprél	ALS-DS-U	QTK-295	N/A
SAR Software	Aprél	ALSAS-10	Ver. 1.1.14	N/A
CRS C500C Controller	Thermo	ALS-C500	RCF0404433	N/A
CRF F3 Robot	Thermo	ALS-F3	RAF0412222	N/A
Power Amplifier	Mini-Circuit	ZHL-42	D051404-20	N/A
Directional Coupler	Agilent	778D-012	50550	N/A
Universal Radio Communication Tester	Rohde & Schwarz	CMU 200	104846	Mar. 2004
Radio Communication Analyzer	Anritsu	MT8820A	6200323183	Jun. 2004
Vector Network	Anritsu	MS4623B	992801	Mar 2004
Signal Generator	Anritsu	MG3692A	042319	Jun. 2004
Power Meter	Anritsu	ML2487A	6K00001447	Jan. 2004
Wide Bandwidth Sensor	Anritsu	MA2491	030677	Nov. 2003

Note: All equipment upon which need to be calibrated are with calibration period of 1 year.

7. Measurement Uncertainty

Exposure Assessment Measurement Uncertainty

Source of Uncertainty	Tolerance Value	Probability Distribution	Divisor	c_1^1 (1-g)	c_1^1 (10-g)	Standard Uncertainty (1-g)	Standard Uncertainty (10-g)
Measurement System							
Probe Calibration	3.5	normal	1	1	1	3.5	3.5
Axial Isotropy	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5
Hemispherical Isotropy	10.9	rectangular	$\sqrt{3}$	\sqrt{cp}	\sqrt{cp}	4.4	4.4
Boundary Effect	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6
Linearity	4.7	rectangular	$\sqrt{3}$	1	1	2.7	2.7
Detection Limit	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6
Readout Electronics	1.0	normal	1	1	1	1.0	1.0
Response Time	0.8	rectangular	$\sqrt{3}$	1	1	0.5	0.5
Integration Time	1.7	rectangular	$\sqrt{3}$	1	1	1.0	1.0
RF Ambient Condition	3.0	rectangular	$\sqrt{3}$	1	1	1.7	1.7
Probe Positioner Mech.	0.4	rectangular	$\sqrt{3}$	1	1	0.2	0.2
Restriction							
Probe Positioning with respect to Phantom Shell	2.9	rectangular	$\sqrt{3}$	1	1	2.1	2.1
Extrapolation and Integration	3.7	rectangular	$\sqrt{3}$	1	1	2.1	2.1
Test Sample Positioning	4.0	normal	1	1	1	4.0	4.0
Device Holder Uncertainty	2.0	normal	1	1	1	2.0	2.0
Drift of Output Power	0.0	rectangular	$\sqrt{3}$	1	1	0.0	0.0
Phantom and Setup							
Phantom Uncertainty(shape & thickness tolerance)	3.4	rectangular	$\sqrt{3}$	1	1	2.0	2.0
Liquid Conductivity(target)	13.0	rectangular	$\sqrt{3}$	0.7	0.5	5.3	3.8
Liquid Conductivity(meas.)	0.1	rectangular	$\sqrt{3}$	0.7	0.5	0.0	0.0
Liquid Permittivity(target)	2.0	rectangular	$\sqrt{3}$	0.6	0.5	0.8	0.6
Liquid Permittivity(meas.)	4.2	rectangular	$\sqrt{3}$	0.6	0.5	1.4	1.2
Combined Uncertainty		RSS				10.3	9.5
Combined Uncertainty (coverage factor=2)		Normal (k=2)				20.6	19.1

8. Test Results

8.1 SAR Test Results Summary


SAR MEASUREMENT						
Ambient Temperature (°C) : 24 ±2				Relative Humidity (%): 55		
Liquid Temperature (°C) : 23.5 ±2				Depth of Liquid (cm):>15		
Product: GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone						
Test Mode: PCS1900						
Test Position Head	Antenna Position	Frequency		Conducted Power (dBm)	SAR 1g (W/kg)	Limit (W/kg)
		Channel	MHz			
Right-Cheek	Internal	512	1850.2	30.0	0.97	1.6
Right-Cheek	Internal	661	1880.0	29.7	0.86	1.6
Right-Cheek	Internal	810	1909.8	29.3	0.75	1.6
Left-Cheek	Internal	512	1850.2	30.0	1.26	1.6
Left-Cheek	Internal	661	1880.0	29.7	1.17	1.6
Left-Cheek	Internal	810	1909.8	29.3	1.05	1.6
Right-Tilted	Internal	512	1850.2	30.0	1.08	1.6
Right-Tilted	Internal	661	1880.0	29.7	0.91	1.6
Right-Tilted	Internal	810	1909.8	29.3	0.77	1.6
Left-Tilted	Internal	512	1850.2	30.0	1.11	1.6
Left-Tilted	Internal	661	1880.0	29.7	1.01	1.6
Left-Tilted	Internal	810	1909.8	29.3	0.99	1.6

SAR MEASUREMENT						
Ambient Temperature (°C) :24 ±2				Relative Humidity (%): 55		
Liquid Temperature (°C) : 23.5 ±2				Depth of Liquid (cm):>15		
Product: GSM900/DCS1800/PCS1900 GSM/GPRS Mobile Phone						
Test Mode: PCS1900(GSM)						
Test Position Body	Antenna Position	Frequency		Conducted Power (dBm)	SAR 1g (W/kg)	Limit (W/kg)
		Channel	MHz			
Body-wore	Internal	512	1850.2	30.0	0.58	1.6
Body-wore	Internal	661	1880.0	29.7	0.75	1.6
Body-wore	Internal	810	1909.8	29.3	0.64	1.6
Test Mode: PCS1900(GPRS)						
Body-wore	Internal	512	1850.2	30.0	0.69	1.6
Body-wore	Internal	661	1880.0	29.7	0.71	1.6
Body-wore	Internal	810	1909.8	29.3	0.64	1.6

8.2 SAR System Validation Data

SAR Test Report

Name : APREL-Uni
Channel : dipole – 1900
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 1.00
Conversion Factor : 3.30



1 gram SAR value : 38.90 W/kg
10 gram SAR value : 21.25 W/kg
Area Scan Peak SAR : 42.29
Zoom Scan Peak SAR : 69.90

8.3 SAR Measurement Data

APREL-SAM Right Ear**SAR Data Report**

Operator : Quietek
Validation Date : 22-Sep-2004
Measurement Date : 22-Sep-2004
Starting Time : 22-Sep-2004 02:06:45 PM
End Time : 22-Sep-2004 02:18:53 PM
Scanning Time : 728 secs

Product Data

Device Name : Benq
Serial No. : Benq
Type : Std Form Cell Phone
Model : Standard
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 102.8
Width : 44.2
Depth : 18.3
Antenna Type : Internal
Power Drift-Start : 0.86
Power Drift-Finish: 0.82
Power Drift : 0.04

Phantom Data

Name : APREL-SAM Right Ear
Type : SAM-Right
Size : 280 x 280 x 280
Serial No. : System Default
Location : Right
Description : Q_Right

Tissue Data

Type : Head
Serial No. : 324-H
Frequency : 1900 MHz
Calibration Date : 22-Sep-2004
Temperature : 23.5 °C
Ambient Temp. : 24 °C
Humidity : 55 RH%
Epsilon : 39.6 F/m
Sigma : 1.42 S/m
Density : 1000 kg/cu. m


Probe Data

Name : Probe 225
Model : E020
Type : E-Field Triangle
Serial No. : 225
Calibration Date : 28-Jun-2004
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.3
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{sq. m})$
Compression Point: 95
Offset : 1.56

Measurement Data

Crest Factor : 8
Scan Type : Complete
Set-up Date : 22-Sep-2004
Set-up Time : 1:14:57 PM

Name : APREL-SAM Right Ear
DUT Position : Touch
Channel : Low – 512
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 0.97 W/kg

10 gram SAR value : 0.69 W/kg

Area Scan Peak SAR : 1.01

Zoom Scan Peak SAR : 1.60

Name : APREL-SAM Right Ear
DUT Position : Touch
Channel : Mid – 661
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 0.86 W/kg

10 gram SAR value : 0.64 W/kg

Area Scan Peak SAR : 0.94


Zoom Scan Peak SAR : 1.37

Name : APREL-SAM Right Ear
DUT Position : Touch
Channel : High – 810
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30



1 gram SAR value : 0.75 W/kg
10 gram SAR value : 0.56 W/kg
Area Scan Peak SAR : 0.72
Zoom Scan Peak SAR : 1.19

Name : APREL-SAM Right Ear
DUT Position : 15° Tilt
Channel : Low – 512
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 1.08 W/kg

10 gram SAR value : 0.76 W/kg

Area Scan Peak SAR : 1.19

Zoom Scan Peak SAR : 1.81

Name : APREL-SAM Right Ear
DUT Position : 15° Tilt
Channel : Mid – 661
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 0.91 W/kg

10 gram SAR value : 0.66 W/kg

Area Scan Peak SAR : 1.01

Zoom Scan Peak SAR : 1.53

Name : APREL-SAM Right Ear
DUT Position : 15° Tilt
Channel : High – 810
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 0.77 W/kg

10 gram SAR value : 0.59 W/kg

Area Scan Peak SAR : 0.83

Zoom Scan Peak SAR : 1.23



APREL-SAM Left Ear**SAR Data Report**

Operator : Quietek
Validation Date : 22-Sep-2004
Measurement Date : 22-Sep-2004
Starting Time : 22-Sep-2004 03:11:52 PM
End Time : 22-Sep-2004 03:23:59 PM
Scanning Time : 727 secs

Product Data

Device Name : Benq
Serial No. : Benq
Type : Std Form Cell Phone
Model : Standard
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 102.8
Width : 44.2
Depth : 18.3
Antenna Type : Internal
Power Drift-Start : 0.95
Power Drift-Finish: 0.90
Power Drift : 0.05

Phantom Data

Name : APREL-SAM Left Ear
Type : SAM-Left
Size : 280 x 280 x 280
Serial No. : System Default
Location : Left
Description : Q_Left

Tissue Data

Type : Head
Serial No. : 324-H
Frequency : 1900 MHz
Calibration Date : 22-Sep-2004
Temperature : 23.5 °C
Ambient Temp. : 24 °C
Humidity : 55 RH%
Epsilon : 39.6 F/m
Sigma : 1.42 S/m
Density : 1000 kg/cu. m


Probe Data

Name : Probe 225
Model : E020
Type : E-Field Triangle
Serial No. : 225
Calibration Date : 28-Jun-2004
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.3
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{sq. m})$
Compression Point: 95
Offset : 1.56

Measurement Data

Crest Factor : 8
Scan Type : Complete
Set-up Date : 22-Sep-2004
Set-up Time : 1:14:57 PM

Name : APREL-SAM Left Ear
DUT Position : Touch
Channel : Low – 512
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 1.26 W/kg

10 gram SAR value : 0.92 W/kg

Area Scan Peak SAR : 1.25

Zoom Scan Peak SAR : 1.92

Name : APREL-SAM Left Ear
DUT Position : Touch
Channel : Mid – 661
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 1.17 W/kg

10 gram SAR value : 0.86 W/kg

Area Scan Peak SAR : 1.21

Zoom Scan Peak SAR : 1.83

Name : APREL-SAM Left Ear
DUT Position : Touch
Channel : High – 810
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 1.05 W/kg

10 gram SAR value : 0.79 W/kg

Area Scan Peak SAR : 1.02


Zoom Scan Peak SAR : 1.57

Name : APREL-SAM Left Ear
DUT Position : 15° Tilt
Channel : Low – 512
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 1.11 W/kg
10 gram SAR value : 0.80 W/kg
Area Scan Peak SAR : 1.10
Zoom Scan Peak SAR : 1.79

Name : APREL-SAM Left Ear
DUT Position : 15° Tilt
Channel : Mid – 661
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 1.01 W/kg
10 gram SAR value : 0.71 W/kg
Area Scan Peak SAR : 1.00
Zoom Scan Peak SAR : 1.76

Name : APREL-SAM Left Ear
DUT Position : 15° Tilt
Channel : High – 810
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30



1 gram SAR value : 0.99 W/kg
10 gram SAR value : 0.74 W/kg
Area Scan Peak SAR : 0.95
Zoom Scan Peak SAR : 1.57



APREL-Uni (GSM)

Operator : Quietek
Validation Date : 22-Sep-2004
Measurement Date : 22-Sep-2004
Starting Time : 22-Sep-2004 08:25:39 PM
End Time : 22-Sep-2004 08:37:34 PM
Scanning Time : 715 secs

Product Data

Device Name : Benq
Serial No. : Benq
Type : Std Form Cell Phone
Model : Standard
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 102.8
Width : 44.2
Depth : 18.3
Antenna Type : Internal
Power Drift-Start : 0.46
Power Drift-Finish: 0.49
Power Drift : 0.03

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Q_Center

Tissue Data

Type : Body
Serial No. : 324-B
Frequency : 1900 MHz
Calibration Date : 22-Sep-2004
Temperature : 23.5 °C
Ambient Temp. : 24 °C
Humidity : 55 RH%
Epsilon : 53.3 F/m
Sigma : 1.52 S/m
Density : 1000 kg/cu. m


Probe Data

Name : Probe 225
Model : E020
Type : E-Field Triangle
Serial No. : 225
Calibration Date : 28-Jun-2004
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.7
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{sq. m})$
Compression Point: 95
Offset : 1.56

Measurement Data


Crest Factor : 8
Scan Type : Complete
Set-up Date : 22-Sep-2004
Set-up Time : 1:14:57 PM

Name : APREL-Uni
DUT Position : Rotated Left 90°(distance 15mm)
Channel : Low – 512
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 0.58 W/kg
10 gram SAR value : 0.48 W/kg
Area Scan Peak SAR : 0.75
Zoom Scan Peak SAR : 1.11

Name : APREL-Uni
DUT Position : Rotated Left 90°(distance 15mm)
Channel : Mid – 661
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30




1 gram SAR value : 0.75 W/kg
10 gram SAR value : 0.60 W/kg
Area Scan Peak SAR : 0.80
Zoom Scan Peak SAR : 1.11

Name : APREL-Uni
DUT Position : Rotated Left 90°(distance 15mm)
Channel : High – 810
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 8.00
Conversion Factor : 3.30



1 gram SAR value : 0.64 W/kg
10 gram SAR value : 0.52 W/kg
Area Scan Peak SAR : 0.66
Zoom Scan Peak SAR : 0.92



APREL-Uni (GPRS)

Operator : Quietek
Validation Date : 22-Sep-2004
Measurement Date : 22-Sep-2004
Starting Time : 22-Sep-2004 07:35:49 PM
End Time : 22-Sep-2004 07:47:45 PM
Scanning Time : 716 secs

Product Data

Device Name : Benq
Serial No. : Benq
Type : Std Form Cell Phone
Model : Standard
Frequency : 1900.00 MHz
Max. Transmit Pwr : 1 W
Drift Time : 0 min(s)
Length : 102.8
Width : 44.2
Depth : 18.3
Antenna Type : Internal
Power Drift-Start : 0.55
Power Drift-Finish: 0.52
Power Drift : 0.03

Phantom Data

Name : APREL-Uni
Type : Uni-Phantom
Size : 280 x 280 x 200
Serial No. : System Default
Location : Center
Description : Q_Center

Tissue Data

Type : Body
Serial No. : 324-B
Frequency : 1900 MHz
Calibration Date : 22-Sep-2004
Temperature : 23.5 °C
Ambient Temp. : 24 °C
Humidity : 55 RH%
Epsilon : 53.3 F/m
Sigma : 1.52 S/m
Density : 1000 kg/cu. m


Probe Data

Name : Probe 225
Model : E020
Type : E-Field Triangle
Serial No. : 225
Calibration Date : 28-Jun-2004
Frequency : 1900 MHz
Duty Cycle Factor: 1
Conversion Factor: 3.7
Probe Sensitivity: 1.20 1.20 1.20 $\mu\text{V}/(\text{V}/\text{sq. m})$
Compression Point: 95
Offset : 1.56

Measurement Data


Crest Factor : 4
Scan Type : Complete
Set-up Date : 22-Sep-2004
Set-up Time : 1:14:57 PM

Name : APREL-Uni
 DUT Position : Rotated Left 90°(distance 15mm)
 Channel : Low – 512
 Tissue Temperature : 23.50 °C ±2
 Tissue Ambient Temp. : 24.00 °C ±2
 Duty Cycle Factor : 4.00
 Conversion Factor : 3.30



1 gram SAR value : 0.69 W/kg
 10 gram SAR value : 0.57 W/kg
 Area Scan Peak SAR : 0.77
 Zoom Scan Peak SAR : 0.98

Name : APREL-Uni
DUT Position : Rotated Left 90°(distance 15mm)
Channel : Mid – 661
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 4.00
Conversion Factor : 3.30




1 gram SAR value : 0.71 W/kg

10 gram SAR value : 0.60 W/kg

Area Scan Peak SAR : 0.78

Zoom Scan Peak SAR : 1.06

Name : APREL-Uni
DUT Position : Rotated Left 90°(distance 15mm)
Channel : High – 810
Tissue Temperature : 23.50 °C ±2
Tissue Ambient Temp. : 24.00 °C ±2
Duty Cycle Factor : 4.00
Conversion Factor : 3.30




1 gram SAR value : 0.64 W/kg

10 gram SAR value : 0.53 W/kg


Area Scan Peak SAR : 0.68

Zoom Scan Peak SAR : 0.95



Test Setup Photographs


Right Head (Cheek)




Right Head (Tilted)




Left Head (Cheek)



Left Head (Tilted)



Body worn bottom (distance 15mm)



EUT Photographs



Probe Calibration

NCL CALIBRATION LABORATORIES

Calibration File No.: CP-425

Client.: Quietek

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 1900 MHz

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 225

Calibration Procedure: SSI/DRB-TP-D01-032-E020-V2

Project No: QTKB-ALSAS10U-505

Calibrated: 23rd June 2004
Released on: 23rd June 2004

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: _____

NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4161

Introduction

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 225.

References

SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"
SSI-TP-011 Tissue Calibration Procedure

Conditions

Probe 225 was a new probe taken from stock prior to calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 21 °C +/- 0.5°C

Calibration Results Summary

Probe Type:	E-Field Probe E-020
Serial Number:	225
Frequency:	1900 MHz
Sensor Offset:	1.56 mm
Sensor Length:	2.5 mm
Tip Enclosure:	Ertalyte*
Tip Diameter:	<5 mm
Tip Length:	60 mm
Total Length:	290 mm

*Resistive to recommended tissue recipes per IEEE-1528

Sensitivity in Air

Channel X:	$1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Channel Y:	$1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Channel Z:	$1.2 \mu\text{V}/(\text{V}/\text{m})^2$
Diode Compression Point:	95 mV

Sensitivity in Head Tissue

Frequency: 1900 MHz

Epsilon: 40.0 (+/-5%) **Sigma:** 1.40 S/m (+/-10%)

ConvF

Channel X: 3.65

Channel Y: 3.65

Channel Z: 3.65

Tissue sensitivity values were calculated using the load impedance of the APREL Laboratories Daq-Paq.


Boundary Effect:

Uncertainty resulting from the boundary effect is less than 2% for the distance between the tip of the probe and the tissue boundary, when less than 2.44mm.



Spatial Resolution:

The measured probe tip diameter is 5 mm (+/- 0.01 mm) and therefore meets the requirements of SSI/DRB-TP-D01-032 for spatial resolution.

Receiving Pattern 1900 MHz (Air)




Isotropy Error 1900 MHz (Air)




Isotropy: 0.10 dB

Dynamic Range



Video Bandwidth

Probe Frequency Characteristics



Video Bandwidth at 500 Hz 1 dB
Video Bandwidth at 1.02 KHz: 3 dB

Conversion Factor Uncertainty Assessment

Frequency:		1900MHz	
Epsilon:	40.0 (+/-5%)	Sigma:	1.40 S/m (+/-10%)
ConvF			
Channel X:	3.65		7%(K=2)
Channel Y:	3.65		7%(K=2)
Channel Z:	3.65		7%(K=2)

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 M Ω .

Boundary Effect:

For a distance of 2.4mm the evaluated uncertainty (increase in the probe sensitivity) is less than 2%.

Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2004.

NCL CALIBRATION LABORATORIES

Calibration File No.: CP-431

Client.: Quietek

CERTIFICATE OF CALIBRATION

It is certified that the equipment identified below has been calibrated in the
NCL CALIBRATION LABORATORIES by qualified personnel following recognized
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 1900 MHz

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 225

Body Calibration

Calibration Procedure: SSI/DRB-TP-D01-032-E020-V2

Project No: QTKB-ALSAS10U-505

Calibrated: 23rd June 2004

Released on: 23rd June 2004

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration Results Summary

Released By: _____

NCL CALIBRATION LABORATORIES

51 SPECTRUM WAY
NEPEAN, ONTARIO
CANADA K2R 1E6

Division of APREL Lab.
TEL: (613) 820-4988
FAX: (613) 820-4161

Introduction

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 225.

References

SSI/DRB-TP-D01-032-E020-V2 E-Field Probe Calibration Procedure
IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"
SSI-TP-011 Tissue Calibration Procedure

Conditions

Probe 225 was a new probe taken from stock prior to calibration.

Ambient Temperature of the Laboratory: 22 °C +/- 0.5°C
Temperature of the Tissue: 21 °C +/- 0.5°C