

RF Exposure Evaluation Report

Product Name : QCast Mirror

Model No. : QP30

FCC ID : JVPQP30

Applicant : BenQ Corporation

Address : 16, Jihu Road, Taipei Neihu 114 Taiwan

Date of Receipt : 2022/09/14

Date of Declaration : 2022/11/18

Report No. : 2290395R-RFUSMPEV02-A

Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.


Issued Date: 2022/11/18

Report No.: 2290395R-RFUSMPEV02-A



Product Name	QCast Mirror	
Applicant	BenQ Corporation	
Address	16, Jihu Road, Taipei Neihu 114 Taiwan	
Manufacturer	BenQ Corporation	
Model No.	QP30	
FCC ID	JVPQP30	
Trade Name	BenQ	
Applicable Standard	KDB 447498 D01 v06	<input checked="" type="checkbox"/> Minimum test separation distance ≥ 20 cm <input type="checkbox"/> For low power devices
Test Result	Complied	

Documented By :



(Project Specialist / Ida Tung)

Tested By :



(Senior Engineer / Jack Hsu)

Approved By :



(Manager / Tim Sung)

Revision History

Report No.	Version	Description	Issued Date
2290395R-RFUSMPEV02-A	V1.0	Initial issue of report.	2022/11/18

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	QCast Mirror
Trade Name	BenQ
Model No.	QP30
Contains FCC ID	JVPQP30

Note: For more detailed information please refer to report No.: 2290395R-RFUSWL2V01-A and 2290395R-RFUSWL5V01-A.

2. Test Facility

USA : FCC Registration Number: TW0033

Canada : CAB Identifier Number: TW3023 / Company Number: 26930

Site Description : Accredited by TAF
Accredited Number: 3023

Test Laboratory : DEKRA Testing and Certification Co., Ltd
Address : No. 5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan
Performed Location : No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number : +886-3-275-7255
Fax Number : +886-3-327-8031
Email Address : info.tw@dekra.com
Website : <http://www.dekra.com.tw>

3. RF Exposure Evaluation

3.1. Standard Applicable

According to KDB 447498 D01 (7.1), A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits.

3.2. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0

3.3. Test Result of RF Exposure Evaluation

Product : QCast Mirror
Test Item : RF Exposure Evaluation

Band	Frequency (MHz)	E.I.R.P (dBm)	E.I.R.P (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
2.4GHz	2462	27.710	590.201	0.1174	1
5GHz	5220	17.010	50.234	0.0100	1

Note: The conducted output power is refer to report No.: 2290395R-RFUSWL2V01-A and 2290395R-RFUSWL5V01-A from the DEKRA.

Results	PASS
---------	------