

# HCT CO., LTD.

## CERTIFICATE OF COMPLIANCE

### FCC Certification

<b>Applicant Name:</b> Pantech Co., Ltd.  <b>Address:</b> Pantech Bldg, I-2, DMC, Sangam-dong, Mapo-gu, Seoul, 121-792, Korea	<b>Date of Issue:</b> December 14, 2011 <b>Location:</b> HCT CO., LTD., 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, Korea <b>Test Report No.:</b> HCTR1109FR08-1 <b>HCT FRN:</b> 0005866421
--	--

**FCC ID** :JYCP6020

**APPLICANT** :Pantech Co., Ltd.

<b>FCC Model(s):</b>	P6020
<b>EUT Type:</b>	GSM/WCDMA Phone with Bluetooth
<b>Max. RF Output Power:</b>	4.31 dBm(2.70 mW)
<b>Frequency Range:</b>	2402 MHz - 2480 MHz (Bluetooth)
<b>Modulation type</b>	GFSK(Normal), PSK(EDR)
<b>FCC Classification:</b>	FCC Part 15 Spread Spectrum Transmitter
<b>FCC Rule Part(s):</b>	Part 15 subpart C 15.247

#### Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

*Jong Seok Lee*

**Report prepared by**  
: Jong Seok Lee

**Test Engineer of RF Team**

*Chang Seok Choi*

**Approved by**  
: Chang Seok Choi

**Manager of RF Team**

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1109FR08-1	Date of Issue: December 14, 2011	EUT Type: GSM/WCDMA Phone with Bluetooth	FCC ID : JYCP6020

## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1109FR08	September 09, 2011	First Approval Report
HCTR1109FR08-1	December 14, 2011	Insert a information about hopping on and off

# Table of Contents

1.	GENERAL INFORMATION .....	4
2.	EUT DESCRIPTION .....	4
3.	TEST METHODOLOGY .....	5
3.1	EUT CONFIGURATION .....	5
3.2	EUT EXERCISE .....	5
3.3	GENERAL TEST PROCEDURES .....	5
3.4	DESCRIPTION OF TEST MODES .....	5
4.	INSTRUMENT CALIBRATION .....	6
5.	FACILITIES AND ACCREDITATIONS .....	6
5.1	FACILITIES .....	6
5.2	EQUIPMENT .....	6
6.	ANTENNA REQUIREMENTS.....	6
7.	SUMMARY OF TEST RESULTS.....	7
8.	FCC PART 15.247 REQUIREMENTS .....	8
8.1	PEAK POWER .....	8
8.2	BAND EDGES MEASUREMENT .....	12
8.3	FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW) .....	17
8.4	NUMBER OF HOPPING FREQUENCY .....	22
8.5	TIME OF OCCUPANCY (DWELL TIME).....	25
8.6	SPURIOUS EMISSIONS.....	29
8.6.1	CONDUCTED SPURIOUS MEASUREMENT .....	29
8.6.2	RADIATED SPURIOUS EMISSIONS .....	36
8.6.3	RADIATED RESTRICTED BAND EDGE MEASUREMENTS.....	44
8.7	POWERLINE CONDUCTED EMISSIONS.....	45
9.	LIST OF TEST EQUIPMENT.....	50

## 1. GENERAL INFORMATION

**Applicant Name:** Pantech Co., Ltd.  
**Address:** Pantech Bldg, I-2, DMC, Sangam-dong, Mapo-gu, Seoul, 121-792, Korea  
**FCC ID:** JYCP6020  
**EUT:** GSM/WCDMA Phone with Bluetooth  
**Model name(s):** P6020  
**Date(s) of Tests:** August 23, 2011 ~ September 07, 2011  
**Contact Person:** Name: Jong Chul Yoon  
Phone #: +82-2-2030-1311  
**Place of Tests:** HCT Co., Ltd.  
105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, KOREA.  
(IC Recognition No. : 5944A-3)

## 2. EUT DESCRIPTION

<b>EUT Type</b>	GSM/WCDMA Phone with Bluetooth
<b>FCC Model Name</b>	P6020
<b>Power Supply</b>	DC 3.7 V
<b>Battery Type</b>	Li-ion Battery(Standard)
<b>Frequency Range</b>	2402 MHz - 2480 MHz (Bluetooth)
<b>Transmit Power</b>	4.31 dBm(2.70 mW)
<b>Modulation Type</b>	GFSK(Normal), PSK(EDR)
<b>Modulation Technique</b>	FHSS
<b>Number of Channels</b>	79Channels
<b>Antenna Specification</b>	Antenna type: Internal Antenna Peak Gain : -1.51 dBi

### ※ 15.247 Requirements for Bluetooth transmitter

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  - 1) This system is hopping pseudorandomly.
  - 2) Each frequency is used equally on the average by each transmitter.
  - 3) The receiver input bandwidths that match the hopping channel bandwidths of their corresponding transmitters
  - 4) The receiver shifts frequencies in synchronization with the transmitted signals.
- 15.247(g): The system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this Section 15.247 should the transmitter be presented with a continuous data (or information) stream.
- 15.247(h): The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 3. TEST METHODOLOGY

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40 GHz(ANSI C63.4-2003) and FCC Public Notice DA 00-705 dated March 30, 2000 entitled "Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems" were used in the measurement of the **Pantech Co., Ltd.**

**GSM/WCDMA Phone with Bluetooth FCC ID: JYCP6020**

#### 3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### 3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

#### 3.3 GENERAL TEST PROCEDURES

##### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

#### 3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

<b>FCC PT.15.247 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1109FR08-1	<b>Date of Issue:</b> December 14, 2011	<b>EUT Type:</b> GSM/WCDMA Phone with Bluetooth	<b>FCC ID :</b> JYCP6020

## 4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 105-1, Jangam-ri, Majang-Myeon, Icheon-si, Kyunggi-Do, 467-811, Korea. The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated March 02, 2011 (Registration Number: 90661)

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 6. ANTENNA REQUIREMENTS

### According to FCC 47 CFR §15.203:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

\* The antennas of this E.U.T are permanently attached.

\*The E.U.T Complies with the requirement of §15.203

<b>FCC PT.15.247 TEST REPORT</b>	<b>FCC CERTIFICATION REPORT</b>		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
<b>Test Report No.</b> HCTR1109FR08-1	<b>Date of Issue:</b> December 14, 2011	<b>EUT Type:</b> GSM/WCDMA Phone with Bluetooth	<b>FCC ID :</b> JYCP6020

## 7. SUMMARY OF TEST RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
20 dB Bandwidth	§15.247(a)(1)(ii) or (iii)	NA	CONDUCTED	PASS
Occupied Bandwidth		NA		PASS
Conducted Maximum Peak Output Power	§15.247(b)(1)	< 1 Watts		PASS
Carrier Frequency Separation	§15.247(a)(1)	>25 kHz or >2/3 of the 20dB BW		PASS
Number of Hopping Frequencies	§15.247(a)(1)(iii)	>15		PASS
Time of Occupancy	§15.247(a)(1)(iii)	<400 ms		PASS
Conducted Spurious Emissions	§15.247(d)	< 20 dB for all out-of band emissions		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	< 20 dB for all out-of band emissions		PASS
AC Power line Conducted Emissions	§15.207(a)	cf. Section 8.7		PASS
Radiated Spurious Emissions	§15.247(d), 15.205, 15.209	cf. Section 8.1.1	RADIATED	PASS
Radiated Restricted Band Edge	§15.247(d), 15.205, 15.209	cf. Section 8.1.2		PASS

## 8. FCC PART 15.247 REQUIREMENTS


### 8.1 PEAK POWER

#### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902 ~ 928 MHz, 2400 ~ 2483.5 MHz, and 5725 ~ 5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Test Configuration



#### TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the peak detector mode. **This test is performed with hopping off.**

1. Span = 2 MHz (GFSK) / 5 MHz (8DPSK)
2. RBW = 1 MHz (GFSK) / 3 MHz (8DPSK)
3. VBW = 1 MHz (GFSK) / 3 MHz (8DPSK)
4. Sweep = auto
5. Packet type= DH5 (GFSK) / 3-DH5 (8DPSK)

#### TEST RESULTS


No non-compliance noted

#### Test Data


Channel	Frequency (MHz)	Output Power(GFSK)		Output Power(8DPSK)		Limit (W)	Result
		(dBm)	(mW)	(dBm)	(mW)		
Low	2402	1.76	1.50	4.31	2.70	1	PASS
Mid	2441	1.53	1.42	4.12	2.58		PASS
High	2480	1.18	1.31	3.71	2.35		PASS




Test Plots (GFSK)  
Peak Power (Low-CH)




Test Plots (GFSK)  
Peak Power (Mid-CH)




Test Plots (GFSK)  
Peak Power (High-CH)




Test Plots (8DPSK)  
Peak Power (Low-CH)



Test Plots (8DPSK)  
Peak Power (Mid-CH)



Test Plots (8DPSK)  
Peak Power (High-CH)




## 8.2 BAND EDGES MEASUREMENT

### LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

### Test Configuration



### TEST PROCEDURE

**This test is performed with hopping off and hopping on.**


The spectrum analyzer is set to :

1. Span = 8 MHz
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Sweep = auto
5. Detector Mode = Peak


### TEST RESULTS

See attached.


Test Plots without hopping (GFSK)  
Band Edges (Low-CH)




Test Plots without hopping (GFSK)  
Band Edges (High-CH)




Test Plots without hopping (8DPSK)  
Band Edges (Low-CH)




Test Plots without hopping (8DPSK)  
Band Edges (High-CH)




Test Plots with hopping (GFSK)  
Band Edges (Low-CH)




Test Plots with hopping (GFSK)  
Band Edges (High-CH)



Test Plots with hopping (8DPSK)  
Band Edges (Low-CH)



Test Plots with hopping (8DPSK)  
Band Edges (High-CH)






### 8.3 FREQUENCY SEPARATION / OCCUPIED BANDWIDTH (99% BW)

#### LIMIT

According to §15.247(a)(1), Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

#### Test Configuration



#### TEST PROCEDURE

The Channel Separation test is performed with hopping on. And the 20 dB Bandwidth test is performed with hopping off.

The spectrum analyzer is set to :

1. Span = 3 MHz
2. RBW = 30 kHz
3. VBW = 100 kHz
4. Sweep = auto

The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.

#### TEST RESULTS

No non-compliance noted

#### Test Data


Channel Separation (kHz)		20dB Bandwidth (kHz)			Limit (kHz)	Result
GFSK	8DPSK	Channel	GFSK	8DPSK		
1000	995	Low CH	949.2	1295.0	>25 or >2/3 of the 20dB BW	Pass
		Middle CH	949.9	1282.0		
		High CH	949.0	1294.0		

#### Occupied Bandwidth (99% BW )


99% BW (kHz)			Result
Channel	GFSK	8DPSK	
Low CH	907.6	1179.8	Pass
Middle CH	909.4	1167.9	
High CH	910.3	1181.0	

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1109FR08-1	Date of Issue: December 14, 2011	EUT Type: GSM/WCDMA Phone with Bluetooth	FCC ID : JYCP6020

## Test Plots (GFSK) Channel Separation



## Test Plots (8DPSK) Channel Separation




### Test Plots (GFSK)

#### 20 dB Bandwidth & Occupied Bandwidth (Low-CH)




### Test Plots (GFSK)

#### 20 dB Bandwidth & Occupied Bandwidth (Mid-CH)




## Test Plots (GFSK)

### 20 dB Bandwidth & Occupied Bandwidth (High-CH)




## Test Plots (8DPSK)

### 20 dB Bandwidth & Occupied Bandwidth (Low-CH)




### Test Plots (8DPSK)

#### 20 dB Bandwidth & Occupied Bandwidth (Mid-CH)



### Test Plots (8DPSK)

#### 20 dB Bandwidth & Occupied Bandwidth (High-CH)




## 8.4 NUMBER OF HOPPING FREQUENCY

### LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands shall use at least 15 hopping frequencies.

### Test Configuration



### TEST PROCEDURE

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer was set to :

1. Span = the frequency band of operation ( Start = 2400 MHz, Stop = 2483.5 MHz )
2. RBW = 300 kHz
3. VBW = 300 kHz
4. Sweep = auto

The trace was allowed to stabilize.

### TEST RESULTS


No non-compliance noted

### Test Data

Result (No. of CH)		Limit	Result
GFSK	8DPSK		
79	79	>15	Pass


### Test Plots (GFSK)

Number of Channels (2.4 GHz - 2.441 GHz)




### Test Plots (GFSK)

Number of Channels (2.441 GHz - 2.4835 GHz)




### Test Plots (8DPSK)

Number of Channels (2.4 GHz - 2.441 GHz)



### Test Plots (8DPSK)

Number of Channels (2.441 GHz - 2.4835 GHz)






## 8.5 TIME OF OCCUPANCY (DWELL TIME)

### LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400 MHz ~ 2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

### Test Configuration



### TEST PROCEDURE

**This test is performed with hopping off.**

EUT was set to transmit the longest packet type (DH5)

1. Span = zero span
2. RBW = 1 MHz
3. VBW = 1 MHz
4. Sweep = as necessary to capture the entire dwell time per channel

The marker-delta function was used to determine the dwell time.

### TEST RESULTS

See the table.

**DH 5**(The longest packet type for GFSK)

CH Mid :  $2.9 * (1600/6)/79 * 31.6 = 309.33$  (ms)


**3-DH 5**(The longest packet type for 8DPSK)

CH Mid :  $2.9 * (1600/6)/79 * 31.6 = 309.33$  (ms)


Channel	Pulse Time (ms)		Total of Dwell (ms)		Period Time (s)	Limit (ms)	Result
	GFSK	8DPSK	GFSK	8DPSK			
Low	2.89	2.90	308.27	309.33	31.6	400	PASS
Mid	2.90	2.90	309.33	309.33	31.6		PASS
High	2.89	2.90	308.27	309.33	31.6		PASS

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT			<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1109FR08-1	Date of Issue: December 14, 2011	EUT Type: GSM/WCDMA Phone with Bluetooth		FCC ID : JYCP6020


Test Plots (GFSK)  
Dwell Time (Low-CH)




Test Plots (GFSK)  
Dwell Time (Mid-CH)




Test Plots (GFSK)  
Dwell Time (High-CH)




Test Plots (8DPSK)  
Dwell Time (Low-CH)



Test Plots (8DPSK)  
Dwell Time (Mid-CH)



Test Plots (8DPSK)  
Dwell Time (High-CH)




## 8.6 SPURIOUS EMISSIONS

### 8.6.1 CONDUCTED SPURIOUS MEASUREMENT

#### LIMIT : §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### Test Configuration



#### TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Detector Mode is set to a peak detector Mode.

Measurements are made over the 30 MHz to 26 GHz range with the transmitter set to the lowest, middle, and highest channels.


**This test is performed with hopping off.**

#### TEST RESULTS


No non-compliance noted

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1109FR08-1	Date of Issue: December 14, 2011	EUT Type: GSM/WCDMA Phone with Bluetooth	FCC ID : JYCP6020


Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)  
Spurious Emission (Low-CH)




Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)  
Spurious Emission (Mid-CH)




Test Plots (GFSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)  
Spurious Emission (High-CH)




Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)  
Spurious Emission (Low-CH)



Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)  
Spurious Emission (Mid-CH)




Test Plots (8DPSK) - 30 MHz - 1 GHz (RBW:100 kHz, VBW: 300 kHz)  
Spurious Emission (High-CH)







Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)  
Spurious Emission (Low-CH)




Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)  
Spurious Emission (Mid-CH)




Test Plots (GFSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)  
Spurious Emission (High-CH)




Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)  
Spurious Emission (Low-CH)



Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)  
Spurious Emission (Mid-CH)



Test Plots (8DPSK) - 1 GHz - 26 GHz (RBW:1 MHz, VBW: 1 MHz)  
Spurious Emission (High-CH)



## 8.6.2 RADIATED SPURIOUS EMISSIONS


### LIMIT : §15.247(d), §15.205, §15.209

1. 20dBc in any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

## Test Configuration


### Below 30 MHz



### 30 MHz - 1 GHz



## Above 1 GHz



## TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

## TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB $\mu$ V	dB /m	dB	(H/V)	dB $\mu$ V/m	dB $\mu$ V/m	dB
No Critical peaks found							

### Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
4. Limit line = specific Limits (dB $\mu$ V) + Distance extrapolation factor
5. **This test is performed with hopping off.**

## TEST RESULTS

### Below 1 GHz

**Operation Mode:** EDR Mode (Channel : 2402)

Frequency MHz	Reading dBuV	Ant. Factor dB/m	Cable Loss dB	ANT POL (H/V)	Total dBuV/m	Limit dBuV/m	Margin dB
42.3	12.96	13.2	0.6	V	26.7	40.0	13.3
151.2	11.84	13.0	1.2	V	26.1	43.5	17.4
483.2	15.65	17.4	2.4	H	35.5	46.0	10.5
501.4	14.06	17.8	2.5	H	34.4	46.0	11.6
516.3	14.45	18.1	2.5	H	35.1	46.0	10.9
554.2	17.11	18.9	2.7	H	38.7	46.0	7.3

### Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done Normal Mode and EDR Mode test. Worst case of EUT is EDR Mode.
4. **This test is performed with hopping off.**



## Above 1 GHz

### Operation Mode: CH Low(GFSK)

Frequency [MHz]	Reading dBuV	*A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4804	54.17	-3.82	V	50.35	74	23.65	PK
4804	40.73	-3.82	V	36.91	54	17.09	AV
4804	54.41	-3.82	H	50.59	74	23.41	PK
4804	40.88	-3.82	H	37.06	54	16.94	AV

※ A.F: ANTENNA FACTOR

C.L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

### Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.
5. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normal Mode.
6. This test is performed with hopping off.

**Operation Mode: CH Mid(GFSK)**

Frequency [MHz]	Reading dBuV	※A.F+CL-AMP GAIN. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4882	52.79	-3.68	V	49.11	74	24.89	PK
4882	38.99	-3.68	V	35.31	54	18.69	AV
4882	53.14	-3.68	H	49.46	74	24.54	PK
4882	39.08	-3.68	H	35.40	54	18.60	AV

※ A·F: ANTENNA FACTOR

C·L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000 MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.
5. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normal Mode.
6. This test is performed with hopping off.

**Operation Mode: CH High(GFSK)**

Frequency [MHz]	Reading dBuV	*A.F+CL-AMP GAIN [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4960	52.30	-3.57	V	48.73	74	25.27	PK
4960	38.43	-3.57	V	34.86	54	19.14	AV
4960	52.13	-3.57	H	48.56	74	25.44	PK
4960	38.38	-3.57	H	34.81	54	19.19	AV

※ A.F: ANTENNA FACTOR

C.L: CABLE LOSS

AMP GAIN: AMPLIFIER GAIN

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 10 Hz.
5. We have done Normal Mode and EDR Mode test. Worst case of EUT is Normal Mode.
6. This test is performed with hopping off.

### 8.6.3 RADIATED RESTRICTED BAND EDGE MEASUREMENTS

#### Test Requirements and limit, §15.247(d), §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode	8DPSK(EDR)
Operating Frequency	2402 MHz, 2480 MHz
Channel No	CH 0, CH 78

Frequency [MHz]	*Fund. Reading dBuV	※ A.F.+CL [dB]	Ant. Pol. [H/V]	*Fundamental [dBuV/m]	Delta Value [dBuV/m]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2390.0	70.54	33.25	H	103.79	55.83	47.96	74	26.04	PK
2390.0	55.14	33.25	H	88.39	55.83	32.56	54	21.44	AV
2390.0	53.38	33.25	V	86.63	49.04	37.59	74	36.41	PK
2390.0	50.82	33.25	V	84.07	49.04	35.03	54	18.97	AV
2483.5	67.72	33.73	H	101.45	51.82	49.63	74	24.37	PK
2483.5	52.19	33.73	H	85.92	51.82	34.10	54	19.90	AV
2483.5	63.86	33.73	V	97.59	47.94	49.65	74	24.35	PK
2483.5	49.97	33.73	V	83.70	47.94	35.76	54	18.24	AV

※ A.F: ANTENNA FACTOR

C.L: CABLE LOSS

#### Notes:

- Spectrum setting:
  - Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
  - AV Setting 1 GHz – 26 GHz, RBW=1 MHz, VBW= 10 Hz.
- Radiated Restricted Band Edge measures by marker-delta method according to FCC guideline.
- We have done Normal Mode and EDR Mode test. Worst case of EUT is EDR Mode.
- This test is performed with hopping off.

## 8.7 POWERLINE CONDUCTED EMISSIONS

### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.
5. This test is performed with hopping on.

## ■ RESULT PLOTS

### Conducted Emissions (Line 1)


HCT

EMC

EUT: P6020  
 Manufacturer: PANTECH  
 Operating Condition: BT MODE  
 Test Site: SHIELD ROOM  
 Operator: JS LEE  
 Test Specification: FCC PART15 CLASS B  
 Comment: N

#### SCAN TABLE: "FCC PART 15 B(N)"

Short Description:		FCC PART 15 CLASS B				
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



#### MEASUREMENT RESULT: "PHONE\_fin QP"

8/23/2011 9:51PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150010	46.80	10.3	66	19.2	---	---
0.346010	41.50	10.3	59	17.5	---	---
0.494010	33.20	10.3	56	22.9	---	---
0.520000	36.40	10.3	56	19.6	---	---
0.604000	30.90	10.3	56	25.1	---	---
0.656000	26.60	10.3	56	29.4	---	---
5.000000	23.60	10.7	56	32.4	---	---
6.692000	26.40	10.9	60	33.6	---	---
10.068000	22.70	11.0	60	37.3	---	---

MEASUREMENT RESULT: "PHONE\_fin AV"

8/23/2011 9:51PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.334010	31.80	10.3	49	17.6	---	---
0.342010	33.30	10.3	49	15.8	---	---
0.494010	24.70	10.3	46	21.4	---	---
0.520000	27.90	10.3	46	18.1	---	---
1.048000	25.00	10.4	46	21.0	---	---
1.224000	23.40	10.4	46	22.6	---	---
5.000000	15.70	10.7	46	30.3	---	---
7.808000	19.20	11.0	50	30.8	---	---
9.184000	16.90	11.0	50	33.1	---	---

## Conducted Emissions (Line 2)


HCT

EMC

EUT: P6020  
 Manufacturer: PANTECH  
 Operating Condition: BT MODE  
 Test Site: SHIELD ROOM  
 Operator: JS LEE  
 Test Specification: FCC PART15 CLASS B  
 Comment: H

### SCAN TABLE: "FCC PART 15 B(H)"

Short Description:			FCC PART 15 CLASS B			
Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	500.0 kHz	1.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



### MEASUREMENT RESULT: "PHONE\_fin QP"

8/23/2011 9:46PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150010	50.30	10.1	66	15.7	---	---
0.331010	39.60	10.1	59	19.8	---	---
0.341010	42.50	10.1	59	16.7	---	---
0.520000	38.60	10.1	56	17.4	---	---
0.728000	34.70	10.1	56	21.3	---	---
0.948000	35.00	10.1	56	21.0	---	---
7.400000	29.40	10.8	60	30.6	---	---
7.620000	29.50	10.8	60	30.5	---	---
8.568000	28.90	10.9	60	31.1	---	---



**MEASUREMENT RESULT: "PHONE\_fin AV"**

8/23/2011 9:46PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.333010	32.50	10.1	49	16.9	---	---
0.344010	34.90	10.1	49	14.2	---	---
0.492010	28.80	10.1	46	17.3	---	---
0.520000	31.30	10.1	46	14.7	---	---
1.188000	25.70	10.2	46	20.3	---	---
2.448000	22.50	10.2	46	23.5	---	---
5.000000	16.60	10.5	46	29.4	---	---
7.584000	20.60	10.8	50	29.4	---	---
9.116000	18.90	10.9	50	31.1	---	---

## 9. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ESH2-Z5/ LISN	Annual	02/01/2012	861741/013
Schwarzbeck	VULB 9168/ TRILOG Antenna	Biennial	02/09/2013	200
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	ESH3-Z2/ PULSE LIMITER	Annual	10/25/2011	375.8810.352
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	Annual	09/29/2011	10094
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	09/23/2011	296
Rohde & Schwarz	FSP / Spectrum Analyzer	Annual	03/23/2012	839117/011
Agilent	E4440A / Spectrum Analyzer	Annual	05/02/2012	US45303008
Agilent	E4416A /Power Meter	Annual	01/04/2012	GB41291412
Agilent	E9327A /POWER SENSOR	Annual	05/02/2012	MY4442009
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	Annual	05/02/2012	1
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	Annual	05/02/2012	1
Hewlett Packard	11636B/Power Divider	Annual	12/29/2011	11377
Hewlett Packard	11667B / Power Splitter	Annual	11/08/2011	10126
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	01/04/2012	3110117
ITECH	IT6720 / DC POWER SUPPLY	Annual	12/01/2011	010002156287001199
TESCOM	TC-3000C / BLUETOOTH TESTER	Annual	04/01/2012	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	Annual	05/02/2012	100422
EMCO	6502.LOOP ANTENNA	Biennial	01/13/2012	9009-2536