



Pantech Co Ltd  
 Pantech Building, I-2, DMC  
 Sangam-dong, Mapo-gu,  
 Seoul, KOREA 121-792

Date: March 6, 2012  
 PCTEST TCB/CB  
 Div. of PCTEST Engineering Lab., Inc.  
 6660-B Dobbin Road  
 Columbia, MD 21045

Subject: Pantech Co., Ltd.  
 FCC ID: JYCP8010

To Whom It May Concern:

We attest the following regarding FCC ID: JYCP8010

1. Supported LTE Transmission Bands, channel BWs, and modulations:
  - a) LTE Band 2 (Channel BW 5 , 10 MHz)/QPSK & 16QAM
  - b) LTE Band 5 (Channel BW 5 , 10 MHz)/QPSK & 16QAM
  - c) LTE Band 4 (Channel BW 5 , 10 MHz)/QPSK & 16QAM
  - d) LTE Band 17 (Channel BW 5 , 10 MHz)/QPSK & 16QAM
  
2. MPR is enabled for this device, according to 3GPP TS 36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3 – 1. With the MPR permanently implemented, this device will never operate at a power higher than 23.5 dBm in QPSK and 16QAM.
  
3. We confirm the specific MPR targets and tolerances shown below:
  - a. The LTE MPR Targets for Band 2 (PCS) are:

Band	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Target MPR [dB]	Maximum MPR Allowed per 3GPP [dB]
LTE Band 2	5	QPSK	1	0	0	0
	5	QPSK	1	24	0	0
	5	QPSK	12	6	1	0-1
	5	QPSK	25	0	1	0-1
	5	16-QAM	1	0	1	0-1
	5	16-QAM	1	24	1	0-1
	5	16-QAM	12	6	2	0-2
	5	16-QAM	25	0	2	0-2
	10	QPSK	1	0	0	0
	10	QPSK	1	49	0	0
	10	QPSK	25	12	1	0-1
	10	QPSK	50	0	1	0-1
	10	16-QAM	1	0	1	0-1
	10	16-QAM	1	49	1	0-1
	10	16-QAM	25	12	2	0-2
	10	16-QAM	50	0	2	0-2

b. The LTE MPR Targets for Band 5 (Cell.) are:

Band	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Target MPR [dB]	Maximum MPR Allowed per 3GPP [dB]
LTE Band 5	5	QPSK	1	0	0	0
	5	QPSK	1	24	0	0
	5	QPSK	12	6	1	0-1
	5	QPSK	25	0	1	0-1
	5	16-QAM	1	0	1	0-1
	5	16-QAM	1	24	1	0-1
	5	16-QAM	12	6	2	0-2
	5	16-QAM	25	0	2	0-2
	10	QPSK	1	0	0	0
	10	QPSK	1	49	0	0
	10	QPSK	25	12	1	0-1
	10	QPSK	50	0	1	0-1
	10	16-QAM	1	0	1	0-1
	10	16-QAM	1	49	1	0-1
	10	16-QAM	25	12	1	0-2
	10	16-QAM	50	0	2	0-2

c. The LTE MPR Targets for Band 4 (AWS) are:

Band	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Target MPR [dB]	Maximum MPR Allowed per 3GPP [dB]
LTE Band 4	5	QPSK	1	0	0	0
	5	QPSK	1	24	0	0
	5	QPSK	12	6	1	0-1
	5	QPSK	25	0	1	0-1
	5	16-QAM	1	0	1	0-1
	5	16-QAM	1	24	1	0-1
	5	16-QAM	12	6	2	0-2
	5	16-QAM	25	0	2	0-2
	10	QPSK	1	0	0	0
	10	QPSK	1	49	0	0
	10	QPSK	25	12	1	0-1
	10	QPSK	50	0	1	0-1
	10	16-QAM	1	0	1	0-1
	10	16-QAM	1	49	1	0-1
	10	16-QAM	25	12	1	0-2
	10	16-QAM	50	0	2	0-2

d. The LTE MPR Targets for Band 17 are:

Band	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Target MPR [dB]	Maximum MPR Allowed per 3GPP [dB]
Band 17	5	QPSK	1	0	0	0
	5	QPSK	1	24	0	0
	5	QPSK	12	6	1	0-1
	5	QPSK	25	0	1	0-1
	5	16-QAM	1	0	1	0-1
	5	16-QAM	1	24	1	0-1
	5	16-QAM	12	6	2	0-2
	5	16-QAM	25	0	2	0-2
	10	QPSK	1	0	0	0
	10	QPSK	1	49	0	0
	10	QPSK	25	12	1	0-1
	10	QPSK	50	0	1	0-1
	10	16-QAM	1	0	1	0-1
	10	16-QAM	1	49	1	0-1
	10	16-QAM	25	12	1	0-2
	10	16-QAM	50	0	2	0-2

4. A-MPR was disabled for all SAR test samples for SAR testing purposes only.
5. This device does not implement power back-off schemes for SAR compliance.
6. We attest to the Simultaneous Tx listed on Operational Description to be accurate and furthermore, any other simultaneous Tx combinations not listed on the SAR report are not supported by software/hardware design.

Should you have any questions or comments concerning the above, please contact the undersigned.

Sincerely,