APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

Report No.: T120309D02-RP1

EUT Specification

EUT	USB to Bluetooth KM Switch
	☐ WLAN: 2.412GHz ~ 2.462GHz
Frequency band	WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz
(Operating)	☐ WLAN: 5.745GHz ~ 5.825GHz
	Others: Bluetooth: 2.402GHz ~ 2.480GHz
	Portable (<20cm separation)
Device category	Mobile (>20cm separation)
. ·	Others
	Occupational/Controlled exposure $(S = 5mW/cm^2)$
Exposure classification	General Population/Uncontrolled exposure
•	$S=1mW/cm^2$
	Single antenna
	Multiple antennas
Antenna diversity	Tx diversity
·	Rx diversity
	Tx/Rx diversity
Max. output power	3.9 dBm (2.45 mW)
Antenna gain (Max)	2.5 dBi (Numeric gain: 1.77)
	MPE Evaluation
Evaluation applied	SAR Evaluation
	N/A*
Remark:	
The maximum output power is <u>3.9 dBm (2.45 mW) at 2480MHz</u> (with <u>1.77 numeric antenna</u>	
gain.)	

TEST RESULTS

No non-compliance noted.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: $60/f_{(GHz)}=60/2.441=24.58$ mW)

MPE EVALUATION

Not applicable.