

## NXR-700-K Specifications

Please include the following information in the grant letter.

### NXR-700-K

Grant Notes	FCC Rule Parts	Frequency Range (MHZ)	Output Watts	Frequency Tolerance	Emission Designator
BC	22, 74, 90	150.0 - 174.0	5	1.5 PM	16K0F3E
BC	22, 74, 90.210	150.0 - 174.0	5	1.5 PM	11K0F3E
BC	22, 74, 90.210	150.0 - 174.0	5	1.5 PM	8K30F1E
BC	22, 74, 90.210	150.0 - 174.0	5	1.5 PM	8K30F1D
BC	22, 74, 90.210	150.0 - 174.0	5	1.5 PM	8K30F7W
BC	22, 74, 90	150.0 - 174.0	5	0.5 PM	16K0F3E
BC	22, 74, 90.210	150.0 - 174.0	5	0.5 PM	11K0F3E
BC	22, 74, 90.210	150.0 - 174.0	5	0.5 PM	8K30F1E
BC	22, 74, 90.210	150.0 - 174.0	5	0.5 PM	8K30F1D
BC	22, 74, 90.210	150.0 - 174.0	5	0.5 PM	8K30F7W
BC	22, 74, 90.210	150.0 - 174.0	5	0.5 PM	4K00F1E
BC	22, 74, 90.210	150.0 - 174.0	5	0.5 PM	4K00F1D
BC	22, 74, 90.210	150.0 - 174.0	5	0.5 PM	4K00F7W
BC	22, 74, 90.210	150.0 - 174.0	5	0.5 PM	4K00F2D

The 0.5 ppm frequency tolerance requires an OCXO UNIT (KXK-3).

BC: The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.