



Maximum Permissible Exposure (MPE) Evaluation

Applicant : Kenwood Corporation
 Equipment : UHF FM TRANSCEIVER
 Model No. : TK-8302H-2
 FCC ID : K44407703
 IC CN and UPN : 282F-407703

MPE Calculations

According to the OET Bulletin 65 (Edition 97-01)

$$S = \frac{PG}{4\pi R^2}$$

$$R = \sqrt{\frac{PG}{4\pi S}}$$

Where:

S=Power density (in appropriate units, e.g. mW/cm²)

P=Power input to antenna (in appropriate units, e.g., mW)

G=Power gain of the antenna in the direction of interest relative to an isotropic radiator

R=Distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Tx Frequency= 406.1 to 470 (MHz) : FCC
 406.1 to 430 , 450 to 470 (MHz) : IC
 Maximum peak power= 46.53 (dBm) (=45W)
 Antenna gain= 2.15 (dBi)

S= 0.27 (mW/cm²)
 P= 27000.00 (mW) (=Maximum peak power x 120% x Dutycycle 50%)
 G= 1.64 (numeric)
 R= 114.11 (cm)

P = Value calculated according to CFR Part 90.205(s)

Calculated minimum separation distance from antenna :

114.11 (cm)