

APPLICATION FOR VERIFICATION
On Behalf of
Superior Electronics Corporation

Outdoor Access Control Keypad with Proximity Card Reader
Model No.: SK-1123-SPQ

FCC ID: K4E1123SPQ

Prepared for : Superior Electronics Corporation
Address : No. 10 Lane 31, Chongde St., Sinyi District, Taipei City
110, Taiwan

Prepared by : Accurate Technology Co., Ltd.
Address : F1, Bldg. A&D, Changyuan New Material Port, Keyuan
Rd., Science & Industry Park, Nanshan District, Shenzhen
518057, P.R. China

Tel: +86-755-26503290
Fax: +86-755-26503396

Report No. : ATE20151933
Date of Test : September 1-8, 2015
Date of Report : September 10, 2015

TABLE OF CONTENTS

Description	Page
Test Report Declaration	
1. TEST RESULTS SUMMARY	4
2. GENERAL INFORMATION	5
2.1. Description of Device (EUT)	5
2.2. Special Accessory and Auxiliary Equipment	5
2.3. Description of Test Facility	6
2.4. Measurement Uncertainty	6
3. POWER LINE CONDUCTED MEASUREMENT	7
3.1. For Power Line Conducted Emission	7
3.2. Block Diagram of Test Setup	7
3.3. The Emission Limit	8
3.4. Configuration of EUT on Measurement	8
3.5. Operating Condition of EUT	8
3.6. Test Procedure	8
3.7. Power Line Conducted Emission Measurement Results	9
4. RADIATED EMISSION MEASUREMENT	15
4.1. For Radiated Emission Measurement	15
4.2. TEST CONFIGURATION	15
4.3. Block Diagram of Test Setup	16
4.4. Radiated Emission Limit	16
4.5. EUT Configuration on Measurement	16
4.6. Operating Condition of EUT	17
4.7. Test Procedure	17
4.8. Radiated Emission Noise Measurement Result	18
5. ANTENNA REQUIREMENT	27
5.1. The Requirement	27
5.2. Antenna Construction	27

Test Report Declaration

Applicant& address : Superior Electronics Corporation
No. 10 Lane 31, Chongde St., Sinyi District, Taipei City 110,
Taiwan

Manufacturer& address : Superior Electronics Corporation
No. 10 Lane 31, Chongde St., Sinyi District, Taipei City 110,
Taiwan

Product : Outdoor Access Control Keypad with Proximity Card Reader

Model No. : SK-1123-SPQ

Trade name : N/A


Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C 15.207&15.209 FCC/ANSI C63.4-2014

The device described above is tested by Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both radiated and conducted emissions. The measurement results are contained in this test report and Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Accurate Technology Co., Ltd.

Date of Test : September 1-8, 2015
Date of Report : September 10, 2015

Prepared by : 
(Kelly Cheng, Engineer)

Approved & Authorized Signer : 
(Sean Liu, Manager)

1. TEST RESULTS SUMMARY

Test Items	Test Standard	Test Results
Power Line Conducted Emission	FCC Part 15.207	Pass
Radiated Emission	FCC Part 15.209	Pass

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

The submitted sample is a Outdoor Access Control Keypad with Proximity Card Reader.

The sample is powered by 12-24V DC/AC..

Outdoor Access Control Keypad with Proximity Card Reader		
Frequency	:	125KHz
Number of Channels	:	1
Modulation Type	:	GFSK
Type of Antenna	:	Internal Antenna
Max antenna gain	:	0dBi
Power Supply	:	12-24V DC/AC

2.2. Special Accessory and Auxiliary Equipment

N/A

2.3. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen, May 10, 2004

Listed by FCC
The Registration Number is 253065

Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-1

Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee for Laboratories
The Certificate Registration Number is L3193

Name of Firm : Accurate Technology Co., Ltd.
Site Location : F1, Bldg. A&D, Changyuan New Material Port, Keyuan Rd., Science & Industry Park, Nanshan District, Shenzhen 518057, P.R. China

2.4. Measurement Uncertainty

Conducted emission expanded uncertainty : U=2.23dB, k=2

Power disturbance expanded uncertainty : U=2.92dB, k=2

Radiated emission expanded uncertainty : U=3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty : U=4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty : U=4.06dB, k=2
(Above 1GHz)

3. POWER LINE CONDUCTED MEASUREMENT

3.1. For Power Line Conducted Emission

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCS30	100307	Jan. 11, 2015	1 Year
2.	L.I.S.N.	Schwarzbeck	NLSK8126	8126431	Jan. 11, 2015	1 Year
3.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100815	Jan. 11, 2015	1 Year
4.	50Ω Coaxial Switch	Anritsu Corp	MP59B	620028393 3	Jan. 11, 2015	1 Year


Expanded Uncertainty: $U = 2.23\text{dB}$, $k=2$

3.2. Block Diagram of Test Setup

3.2.1. Block diagram of connection between the EUT and simulators



3.2.2. Shielding Room Test Setup Diagram



(EUT: Outdoor Access Control Keypad with Proximity Card Reader)

3.3.The Emission Limit

3.3.1.Conducted Emission Measurement Limits According to Section 15.107(a)

Frequency (MHz)	Limit dB(μ V)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

* Decreases with the logarithm of the frequency.

3.4.Configuration of EUT on Measurement

The following equipment are installed on the Conducted Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

3.4.1.Outdoor Access Control Keypad with Proximity Card Reader (EUT)

Model Number : SK-1123-SPQ
 Manufacturer : Superior Electronics Corporation

3.5.Operating Condition of EUT

3.5.1.Setup the EUT and simulator as shown as Section 3.1.

3.5.2.Turn on the power of all equipment.

3.5.3.Let the EUT work in modes (TX) and measure it.

3.6.Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2009 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.7. Power Line Conducted Emission Measurement Results

PASS.

The frequency range from 150kHz to 30MHz is checked.

Test mode : TX (AC 12V)								
MEASUREMENT RESULT: "TT02_fin"								
9/5/2015 3:32AM								
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE	
0.151202	42.50	11.0	66	23.4	QP	L1	GND	
0.306497	36.10	11.6	60	24.0	QP	L1	GND	
0.613892	33.80	11.9	56	22.2	QP	L1	GND	
MEASUREMENT RESULT: "TT02_fin2"								
9/5/2015 3:32AM								
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE	
0.553370	34.70	12.0	46	11.3	AV	L1	GND	
0.798945	34.50	11.9	46	11.5	AV	L1	GND	
1.043940	33.50	11.8	46	12.5	AV	L1	GND	
MEASUREMENT RESULT: "TT01_fin"								
9/5/2015 3:28AM								
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE	
0.150000	40.20	11.0	66	25.8	QP	N	GND	
2.274000	30.10	11.6	56	25.9	QP	N	GND	
3.502500	29.10	11.5	56	26.9	QP	N	GND	
MEASUREMENT RESULT: "TT01_fin2"								
9/5/2015 3:28AM								
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE	
0.186000	39.30	11.2	54	14.9	AV	N	GND	
2.769000	29.60	11.6	46	16.4	AV	N	GND	
3.259500	29.90	11.5	46	16.1	AV	N	GND	

Test mode : TX (AC 24V)								
MEASUREMENT RESULT: "W-0912-W03_fin"								
9/5/2015 15:44								
Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE	
0.178000	56.00	10.5	65	8.6	QP	L1	GND	
3.422000	41.10	11.7	56	14.9	QP	L1	GND	
18.983000	34.90	11.9	60	25.1	QP	L1	GND	
MEASUREMENT RESULT: "W-0912-W03_fin2"								
9/5/2015 15:44								
Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE	
0.182000	38.60	10.5	54	15.8	AV	L1	GND	
3.345500	31.90	11.7	46	14.1	AV	L1	GND	
18.848000	28.00	11.9	50	22.0	AV	L1	GND	
MEASUREMENT RESULT: "W-0912-W04_fin"								
9/5/2015 15:47								
Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE	
0.174000	51.00	10.5	65	13.8	QP	N	GND	
2.823500	39.40	11.7	56	16.6	QP	N	GND	
18.879500	34.00	11.9	60	26.0	QP	N	GND	
MEASUREMENT RESULT: "W-0912-W04_fin2"								
9/5/2015 15:47								
Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE	
0.188000	37.10	10.6	54	17.0	AV	N	GND	
3.219500	31.80	11.7	46	14.2	AV	N	GND	
18.713000	27.30	11.9	50	22.7	AV	N	GND	

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Outdoor Access Control Keypad with Proximity Card Reader
 Manufacturer: Superior M/N:SK-1123-SPQ
 Operating Condition: TX
 Test Site: 1#Shielding Room
 Operator: TOM
 Test Specification: N AC 12V
 Comment: Report No.:ATE20151933
 Start of Test: 9/5/2015 / 3:24:22AM

SCAN TABLE: "V 150K-30MHz fin"

Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	0.8 %	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
Short Description: SUB STD VTERM2 1.70			Average			




ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

EUT: Outdoor Access Control Keypad with Proximity Card Reader
 Manufacturer: Superior M/N:SK-1123-SPQ
 Operating Condition: TX
 Test Site: 1#Shielding Room
 Operator: TOM
 Test Specification: L AC 12V
 Comment: Report No.:ATE20151933
 Start of Test: 9/5/2015 / 3:29:45AM

SCAN TABLE: "V 150K-30MHz fin"

Short Description:			SUB STD VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	0.8 %	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
Average						




ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: Outdoor Access Control Keypad with Proximity Card Reader
 Manufacturer: Superior M/N:SK-1123-SPQ
 Operating Condition: TX
 Test Site: 2#Shielding Room
 Operator: TOM
 Test Specification: L AC 24V
 Comment: Report No.:ATE20151933
 Start of Test: 9/5/2015 / 15:41:03

SCAN TABLE: "V 150K-30MHz fin"

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
150.0 kHz	30.0 MHz	4.0 kHz	QuasiPeak	1.0 s	9 kHz	LISN(ESH3-Z5)
			Average			




ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15B

EUT: Outdoor Access Control Keypad with Proximity Card Reader
 Manufacturer: Superior M/N:SK-1123-SPQ
 Operating Condition: ON
 Test Site: 2#Shielding Room
 Operator: TOM
 Test Specification: N AC 24V
 Comment: Report No.:ATE20151933
 Start of Test: 9/5/2015 / 15:45:31

SCAN TABLE: "V 150K-30MHz fin"

Short Description:			SUB STD VTERM2 1.70				
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer	
150.0 kHz	30.0 MHz	4.0 kHz	QuasiPeak	1.0 s	9 kHz	LISN (ESH3-Z5)	
			Average				



4. RADIATED EMISSION MEASUREMENT


4.1. For Radiated Emission Measurement

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2015	1 Year
2.	Test Receiver	Rohde & Schwarz	ESCS30	100307	Jan. 11, 2015	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2015	1 Year
4.	Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2015	1 Year
5.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2015	1 Year
6.	50 Coaxial Switch	Anritsu Corp	MP59B	6200506474	Jan. 11, 2015	1 Year
12.	Pre-Amplifier	Rohde & Schwarz	CBLU11835 40-01	3791	Jan. 11, 2015	1 Year


Expanded Uncertainty (9kHz-30MHz): U=3.08dB, k=2
 Expanded Uncertainty (30MHz-1000MHz): U=4.42dB, k=2
 Expanded Uncertainty (Above 1GHz): U=4.06dB, k=2

4.2. TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency below 30MHz




(B) Radiated Emission Test Set-Up, Frequency 30-1000MHz



4.3. Block Diagram of Test Setup

4.3.1. Block diagram of connection between the EUT and simulators



4.4. Radiated Emission Limit

Frequency (MHz)	Field Strength Limitation		Field Strength Limitation at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	2400 / F(KHz)	300m	10000 * 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 – 1.705	24000 / F(KHz)	30m	100 * 24000/F(KHz)	20log 24000/F(KHz) + 40
1.705 – 30.00	30	30m	100 * 30	20log 30 + 40
30.0 – 88.0	100	3m	100	20log 100
88.0 – 216.0	150	3m	150	20log 150
216.0 – 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

Limit: $2400/125=19.2\mu\text{V/m}@300\text{m}$

Distance Correction Factor= $40\log(\text{test distance}/\text{specific distance})$

4.5. EUT Configuration on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.5.1. Outdoor Access Control Keypad with Proximity Card Reader (EUT)

Model Number : SK-1123-SPQ
Manufacturer : Superior Electronics Corporation

4.6. Operating Condition of EUT

4.6.1. Setup the EUT and simulator as shown as Section 4.2.

4.6.2. Turn on the power of all equipment.

4.6.3. Let the EUT work in test mode and measure it.

4.7. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10:2014 on radiated emission measurement.

From 9kHz to 30MHz at distance 3m The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

From 30MHz to 1000MHz at distance 3m The measuring antenna height varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity. The measurements were performed for both vertical and horizontal antenna polarization.

The final measurement will be performed with an EMI Receiver set to Quasi Peak detector for the frequency bands 9kHz to 90kHz and 110 to 490 kHz where an average detector will be used according to Section 15.209(d)(2).

The final level, expressed in dBuV/m, is arrived at by taking the reading from the EMI receiver (Level dBuV) and adding the antenna correction factor and cable loss factor (Factor dB) to it. This result then has to be compared with the relevant FCC limit. The resolution bandwidth during the measurement is as follows:

9kHz – 150kHz: ResBW:200Hz

150kHz – 30MHz: ResBW:9kHz

The bandwidth of the EMI test receiver (R&S ESCS30) is set at 120kHz from 30MHz to 1000MHz.

4.8.Radiated Emission Noise Measurement Result

PASS.

From 9 kHz to 30MHz (DC 24V (Worse))

Frequency (MHz)	Quasi Peak (dB μ V/m)	Azimuth	Polarity (H/V)	Factors (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
0.125	72.17	148	H	-55.33	105.7	-33.53
2.03	40.56	38	H	-52.18	69.5	-28.94
15.26	37.28	201	H	-52.04	69.5	-32.22
0.125	72.16	176	V	-56.30	105.7	-33.54
3.79	42.39	351	V	-53.24	69.5	-27.11
17.54	30.28	18	V	-52.26	69.5	-39.22

From 9 kHz to 30MHz (AC 24V (Worse))

Frequency (MHz)	Quasi Peak (dB μ V/m)	Azimuth	Polarity (H/V)	Factors (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
0.125	69.16	151	H	-56.27	105.7	-36.54
2.02	39.55	49	H	-54.12	69.5	-29.95
14.25	32.29	203	H	-52.16	69.5	-37.21
0.125	70.34	189	V	-56.01	105.7	-35.36
3.68	46.75	278	V	-55.15	69.5	-22.75
17.35	33.38	159	V	-50.31	69.5	-36.12

Part 15 Section 15.31(f)(2) (9kHz-30MHz)

Limit at 3m=Limit at 300m-40*log(300(m)/3(m))

Limit at 3m=Limit at 30m-40*log(30(m)/3(m))




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Ricky2015 #742	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 12V
Test item: Radiation Test	Date: 15/09/04/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 12/51/06
EUT: Outdoor Access Control Keypad with Proximity Card Reader	Engineer Signature: Frank
Mode: TX	Distance: 3m
Model: SK-1123-SPQ	
Manufacturer: Superior	

Note: Report NO.:ATE20151933



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.2625	46.15	-17.58	28.57	40.00	-11.43	QP			
2	160.3208	53.91	-21.31	32.60	43.50	-10.90	QP			
3	242.6888	49.53	-18.23	31.30	46.00	-14.70	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A.Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Ricky2015 #743

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Outdoor Access Control Keypad with Proximity Card Reader Engineer Signature: Frank

Mode: TX

Model: SK-1123-SPQ

Manufacturer: Superior

Polarization: Vertical


Power Source: AC 12V

Date: 15/09/04/

Time: 12/52/30

Distance: 3m

Note: Report NO.:ATE20151933



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	59.1052	59.26	-22.57	36.69	40.00	-3.31	QP			
2	130.3048	61.58	-21.74	39.84	43.50	-3.66	QP			
3	160.3209	60.55	-21.31	39.24	43.50	-4.26	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Ricky 2015 #817

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Outdoor Access Control Keypad with Proximity Card Reader Engineer Signature: Frank

Mode: TX

Distance: 3m

Model: SK-1123-SPQ

Manufacturer: Superior

Polarization: Horizontal

Power Source: DC 12V

Date: 15/09/19/

Time: 10/24/11

Note: Report NO.:ATE20151933



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.2625	49.65	-17.58	32.07	40.00	-7.93	QP			
2	59.1052	53.01	-21.07	31.94	40.00	-8.06	QP			
3	160.3206	55.42	-22.82	32.60	43.50	-10.90	QP			




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Ricky 2015 #818	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 12V
Test item: Radiation Test	Date: 15/09/19/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 10/26/27
EUT: Outdoor Access Control Keypad with Proximity Card Reader	Engineer Signature: Frank
Mode: TX	Distance: 3m
Model: SK-1123-SPQ	
Manufacturer: Superior	

Note: Report NO.:ATE20151933



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.2625	53.00	-17.58	35.42	40.00	-4.58	QP			
2	59.1052	55.76	-21.07	34.69	40.00	-5.31	QP			
3	130.7632	61.08	-23.06	38.02	43.50	-5.48	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Ricky 2015 #816
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Outdoor Access Control Keypad with Proximity Card Reader
Mode: TX
Model: SK-1123-SPQ
Manufacturer: Superior

Polarization: Vertical
Power Source: DC 24V
Date: 15/09/19/
Time: 10/20/33
Engineer Signature: Frank
Distance: 3m

Note: Report NO.:ATE20151933



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.2625	53.00	-17.58	35.42	40.00	-4.58	QP			
2	59.1052	55.76	-21.07	34.69	40.00	-5.31	QP			
3	160.3206	61.56	-22.82	38.74	43.50	-4.76	QP			




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Ricky 2015 #815	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 24V
Test item: Radiation Test	Date: 15/09/19/
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 10/18/25
EUT: Outdoor Access Control Keypad with Proximity Card Reader	Engineer Signature: Frank
Mode: TX	Distance: 3m
Model: SK-1123-SPQ	
Manufacturer: Superior	

Note: Report NO.:ATE20151933



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.2625	46.15	-17.58	28.57	40.00	-11.43	QP			
2	59.1052	51.51	-21.07	30.44	40.00	-9.56	QP			
3	160.3206	57.42	-22.82	34.60	43.50	-8.90	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Report No.: ATE20151933

Page 25 of 27

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ricky 2015 #814

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Outdoor Access Control Keypad with Proximity Card Reader Engineer Signature: Frank

Mode: TX

Distance: 3m

Model: SK-1123-SPQ

Manufacturer: Superior


Polarization: Vertical

Power Source: AC 24V

Date: 15/09/19/

Time: 10/16/55

Note: Report NO.:ATE20151933



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	59.1052	57.76	-21.07	36.69	40.00	-3.31	QP			
2	130.7632	61.08	-23.06	38.02	43.50	-5.48	QP			
3	161.4515	61.81	-22.69	39.12	43.50	-4.38	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Ricky 2015 #813

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Outdoor Access Control Keypad with Proximity Card Reader Engineer Signature: Frank

Mode: TX

Distance: 3m

Model: SK-1123-SPQ

Manufacturer: Superior

Polarization: Horizontal

Power Source: AC 24V

Date: 15/09/19/

Time: 10/13/46

Note: Report NO.:ATE20151933



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	35.2625	48.65	-17.58	31.07	40.00	-8.93	QP			
2	162.5900	52.88	-22.58	30.30	43.50	-13.20	QP			
3	250.4858	48.90	-19.71	29.19	46.00	-16.81	QP			


5. ANTENNA REQUIREMENT

5.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.2.Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Antenna gain of EUT is 0dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna