







### ISO/IEC17025Accredited Lab.

Report No.: FCC 1404077
File reference No.: 2014-06-12

Applicant: Superior Electronics Corporation

Product: Wireless Video Door Phone

Model No.: DP-236-CQ, DP-236Q

Trademark: ENFORCER

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: June 12, 2014

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

### SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

5/F, Block 4, Anhua Industrial Zone., No.8 TaiRan Rd. CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (+86 755)8344 8688 Fax (+86 755)8344 2996 Email:info@timewaytech.com

Report No: 1404077 Page 2 of 52

Date: 2014-06-12



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meets with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

### **CNAS-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

### FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.:899988.

### IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration No.: IC 5205A-02.

Page 3 of 52

Report No: 1404077 Date: 2014-06-12



# **Test Report Conclusion**

Content	
General Details	4
Test Lab Details.	4
Applicant Details.	4
Description of EUT	4
Submitted Sample	4
Test Duration.	4
Test Uncertainty	5
Test By	5
List of Measurement Equipment.	6
Technical Details	7
Summary of Test Results.	7
Test Standards.	7
EUT Modification.	7
Power Line Conducted Emission Test.	8
Schematics of the Test.	8
Test Method and Test Procedure.	8
Configuration of the EUT	8
EUT Operating Condition.	9
Conducted Emission Limit.	9
Test Result.	9
Radiated Emission test.	12
Test Method and Test Procedure.	12
Configuration of the EUT	12
EUT Operation Condition.	12
Radiated Emission Limit.	13
20dB Bandwidth Measurement.	22
Maximum Peak Output Power	26
Carrier Frequency Separation.	28
Number of Hopping Channel	30
Time of Occupancy (Dwell Time).	32
Out of Band Measurement.	36
Antenna Requirement.	41
FCC Label.	42
	General Details Test Lab Details. Applicant Details. Description of EUT Submitted Sample. Test Duration. Test Duration. Test Uncertainty. Test By. List of Measurement Equipment Technical Details. Summary of Test Results. Test Standards. EUT Modification. Power Line Conducted Emission Test. Schematics of the Test. Test Method and Test Procedure. Configuration of the EUT. EUT Operating Condition. Conducted Emission Limit. Test Result Radiated Emission test. Test Method and Test Procedure. Configuration of the EUT. EUT Operating Condition. Conducted Emission Limit. Test Result Radiated Emission test. Test Method and Test Procedure. Configuration of the EUT. EUT Operation Condition. Radiated Emission Limit. Test Result Test Method and Test Procedure. Configuration of the EUT. EUT Operation Condition. Radiated Emission Limit. Test Frequency Separation. Number of Hopping Channel. Time of Occupancy (Dwell Time) Out of Band Measurement. Antenna Requirement.

15.0

Photo of Test Setup and EUT View....

Date: 2014-06-12



#### 1.0 General Details

#### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

### 1.2 Applicant Details

Applicant: Superior Electronics Corporation

Address: No.10, Lane 31, Chongde St., Sinyi District, Taipei City 110, Taiwan (R.O.C.)

Telephone: +886-2-2378-6161 Fax: +886-2-2378-6163

### 1.3 Description of EUT

Product: Wireless Video Door Phone

Manufacturer: Superior Electronics Corporation

Address: No.10, Lane 31, Chongde St., Sinyi District, Taipei City 110, Taiwan (R.O.C.)

Brand Name: ENFORCER
Model Number: DP-236-CQ
Additional Model Name DP-236Q

Additional Trade Name N/A

Type of Modulation GFSK

Frequency range 2410.875MHz, 2417.625MHz, 2421.000MHz, 2424.375MHz, 2427.750MHz,

2431.125MHz, 2434.500MHz, 2441.250MHz, 2448.000MHz, 2451.375MHz,

2454.750MHz, 2458.125MHz, 2461.500MHz, 2464.875MHz, 2471.625MHz

Number of Channel 15

Frequency Selection By software

Antenna type Integral Antenna used, the antenna gain is 3 dBi

Power Supply: Model:BX-0501000, Input: 100-240V, 50/60Hz; Output: 5V, 1.0A DC;

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1404077 Page 5 of 52

Date: 2014-06-12



1.4 Submitted Sample: 1 Sample

1.5 Test Duration:

2014-04-10 to 2014-06-12

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

•

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 52

Report No: 1404077 Date: 2014-06-12



2.0	0 Test Equipments						
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date		
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2013-08-23	2014-08-22		
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2013-08-23	2014-08-22		
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2013-08-23	2014-08-22		
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2013-08-25	2014-08-24		
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2013-08-23	2014-08-22		
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2013-08-24	2014-08-23		
System Controller	CT	SC100	-				
Printer	EPSON	РНОТО ЕХЗ	CFNH234850				
Computer	IBM	8434	1S8434KCE99BLXL O*	-	-		
Loop Antenna	EMCO	6502	00042960	2013-08-23	2014-08-22		
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2013-08-23	2014-08-22		
3m OATS			N/A	2013-08-22	2014-08-21		
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2013-08-24	2014-08-23		
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2013-08-24	2014-08-23		
Power meter	Anritsu	ML2487A	6K00003613	2013-08-24	2014-08-23		
Power sensor	Anritsu	MA2491A	32263	2013-08-24	2014-08-23		
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2013-08-21	2014-08-20		
LISN	AFJ	LS16C	10010947251	2013-08-21	2014-08-20		
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22		
9*6*6 Anechoic			N/A	2013-08-22	2014-08-21		
EMI Test Receiver	RS	ESCS30	100139	2013-08-23	2014-08-22		

Report No: 1404077 Page 7 of 52

Date: 2014-06-12



### 3.0 Technical Details

### 3.1 Summary of test results

The EUT has been tested according to the following specifications:

Requirement	CFR 47 Section	Result	Notes
Antenna Requirement	15.203, 15.247(b)(4)	PASS	Complies
Maximum Peak Out Power	15.247 (b)(1), (4)	PASS	Complies
Carrier Frequency Separation	15.247(a)(1)	PASS	Complies
20dB Channel Bandwidth	15.247 (a)(1)	PASS	Complies
Number of Hopping Channels	15.247(a)(iii), 15.247(b)(1)	PASS	Complies
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS	Complies
Spurious Emission, Band Edge, and	15.247(d),15.205(a),	PASS	Complies
Restricted bands	15.209 (a),15.109		
<b>Conducted Emissions</b>	15.207(a), 15.107	PASS	Complies
RF Exposure	15.247(i), 1.1307(b)(1)	PASS	Complies

### 3.2 Test Standards

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

### 4.0 EUT Modification

No modification by Shenzhen Timeway Technology Consulting Co., Ltd


Report No: 1404077 Page 8 of 52

Date: 2014-06-12



### 5. Power Line Conducted Emission Test

### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

#### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Test Voltage: 120V~60Hz Block diagram of Test setup



### 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

15 channels are provided to the EUT

Report No: 1404077 Page 9 of 52

Date: 2014-06-12



#### A. EUT

Device	Manufacturer	Model	FCC ID
Wireless Video	Superior Electronics Corporation	DP-236-CQ, DP-236Q	K4E236CQ
Door Phone		DF-230-CQ, DF-230Q	

#### B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

### C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
Power	RCL	RCL-05200	VOC	
Supply				

### 5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

## 5.5 Power line conducted Emission Limit according to Paragraph 15.107, 15.207

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB $\mu$ V)			
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level		
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*		
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0		
5.00 ~ 30.00	73.0	60.0	60.0	50.0		

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1404077 Page 10 of 52

Date: 2014-06-12



### A: Conducted Emission on Live Terminal (150kHz to 30MHz)

**EUT Operating Environment** 

Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

**EUT set Condition: Keeping Transmitting** 

**Equipment Level: Class B** 

**Results: PASS** 

Please refer to following diagram for individual



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.5938	37.30	11.47	48.77	56.00	-7.23	QP	
2	0.5938	-4.10	11.47	7.37	46.00	-38.63	AVG	
3	0.5494	33.80	11.42	45.22	56.00	-10.78	QP	
4	0.5494	5.80	11.42	17.22	46.00	-28.78	AVG	
5	1.1264	30.80	11.95	42.75	56.00	-13.25	QP	
6	1.1264	-1.80	11.95	10.15	46.00	-35.85	AVG	

Report No: 1404077 Page 11 of 52

Date: 2014-06-12



### B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

**EUT Operating Environment** 


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

**EUT set Condition: Keeping Transmitting** 

**Equipment Level: Class B** 

**Results: Pass** 

Please refer to following diagram for individual



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1 *	0.5803	37.50	11.46	48.96	56.00	-7.04	QP	
2	0.5803	0.00	11.46	11.46	46.00	-34.54	AVG	
3	1.1450	29.20	11.96	41.16	56.00	-14.84	QP	
4	1.1450	-4.70	11.96	7.26	46.00	-38.74	AVG	

Report No: 1404077 Page 12 of 52


Date: 2014-06-12



#### **6** Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

### **Block diagram of Test setup**



- 6.2 Configuration of The EUT

  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

Report No: 1404077 Page 13 of 52

Date: 2014-06-12



### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.109. 15.209

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT

Report No: 1404077 Page 14 of 52

Date: 2014-06-12



#### Test result

### General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal/ In Vertical (30MHz----1000MHz)

**EUT set Condition: Keeping Transmitting** 

**Results:** Pass


Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
116.280	26.91	Н	43.50
360.000	36.85	Н	46.00
192.000	28.17	Н	43.50
768.000	35.34	Н	46.00
96.000	36.35	V	43.50
360.000	35.64	V	46.00
118.200	37.42	V	43.50
878.360	37.88	V	46.00

Report No: 1404077 Page 15 of 52

Date: 2014-06-12



### Test Figure:




Date: 7.MAY.2014 18:40:23

Report No: 1404077 Page 16 of 52

Date: 2014-06-12



### Test Figure:



Date: 7.MAY.2014 18:37:26

Report No: 1404077 Page 17 of 52

Date: 2014-06-12



# **Operation Mode: Transmitting under Low Channel** (2410.875MHz)

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
2410.875	102.63(PK)	Н	Fundamental Frequency
2410.875	107.27(PK)	V	Fundamental Frequency
4821.750	53.32(PK)/36.65(AV)	Н	74(Peak)/ 54(AV)
4821.750	56.69(PK)/38.73(AV)	V	74(Peak)/ 54(AV)
7232.625		H/V	74(Peak)/ 54(AV)
9643.500		H/V	74(Peak)/ 54(AV)
12054.375		H/V	74(Peak)/ 54(AV)
14465.250		H/V	74(Peak)/ 54(AV)
16876.125		H/V	74(Peak)/ 54(AV)
19287.000		H/V	74(Peak)/ 54(AV)
21697.875		H/V	74(Peak)/ 54(AV)
24108.750		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

# $\textbf{Operation Mode: Transmitting g under Middle Channel} \quad (2441.25 \text{MHz})$

	0.0			
Frequency (MHz)	(MHz) Level@3m (dB \( \mu \) V/m) Antenna Polarity		Limit@3m (dB \mu V/m)	
2441.25	100.96(PK)	Н	Fundamental Frequency	
2441.25	105.86(PK)	V		
4882.50	52.69(PK)/35.18(AV)	Н	74(Peak)/ 54(AV)	
4882.50	56.37(PK)/41.84(AV)	V	74(Peak)/ 54(AV)	
7323.75		H/V	74(Peak)/ 54(AV)	
9765.00		H/V	74(Peak)/ 54(AV)	
12206.25		H/V	74(Peak)/ 54(AV)	
14647.50		H/V	74(Peak)/ 54(AV)	
17088.75		H/V	74(Peak)/ 54(AV)	
19530.00		H/V	74(Peak)/ 54(AV)	
21971.25		H/V	74(Peak)/ 54(AV)	
24412.50		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Report No: 1404077 Page 18 of 52

Date: 2014-06-12



## **Operation Mode: Transmitting under High Channel** (2471.625MHz)

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)	
2471.625	104.88(PK)	Н	Fundamental Frequency	
2471.625	99.16(PK)	V		
4943.250	55.09(PK)/37.32(AV)	Н	74(Peak)/ 54(AV)	
4943.250	52.72(PK)/34.80(AV)	V	74(Peak)/ 54(AV)	
7414.875		H/V	74(Peak)/ 54(AV)	
9886.500		H/V	74(Peak)/ 54(AV)	
12358.125		H/V	74(Peak)/ 54(AV)	
14829.750		H/V	74(Peak)/ 54(AV)	
17301.375		H/V	74(Peak)/ 54(AV)	
19773.000		H/V	74(Peak)/ 54(AV)	
22244.625		H/V	74(Peak)/ 54(AV)	
24716.250		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


<sup>2.</sup> Remark "---" means that the emissions level is too low to be measured

Report No: 1404077 Date: 2014-06-12




Please refer to the following test plots for details:

#### Low Channel: Horizontal



#### **Low Channel: Vertical**



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 20 of 52


Report No: 1404077 Date: 2014-06-12



### Middle Channel: Horizontal



### **Middle Channel: Vertical**




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No: 1404077 Date: 2014-06-12



### **High Channel: Horizontal**



### **High Channel: Vertical**



Note: for the radiated emissions above 18G, it is the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1404077 Page 22 of 52

Date: 2014-06-12



#### 7.0 20dB Bandwidth Measurement

### 7.1 Regulation

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

#### 7.2 Limits of 20dB Bandwidth Measurement

N/A

### 7.3 Test Procedure.

- 1. Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span =10MHz, VBW =300kHz, RBW=100kHz, Sweep = auto Detector function = peak , $Trace = max \ hold$
- 3. Measure the highest amplitude appearing on spectral display and record the level to calculate results. 6. Repeat above procedures until all frequencies measured were complete.

#### 7.4 Test Result

EUT	Wirele	Wireless Video Door Phone		DP-236-CQ		
Mode	Ko	Keep Transmitting		Keep Transmitting		120V~
Temperat	ure	re 24 deg. C,		56% RH		
Channel	Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Maximum Limit (kHz)	Pass/ Fail		
Low	2410.875	3680		Pass		
Middle	2441.250	250 3720		Pass		
High	2471.625 3700			Pass		


Report No: 1404077 Page 23 of 52

Date: 2014-06-12



### Test Figure:

#### 1. Condition: Low Channel



Date: 8.MAY.2014 17:52:51

Report No: 1404077 Page 24 of 52

Date: 2014-06-12



### 2. Condition: Middle Channel




Date: 8.MAY.2014 17:54:14

Report No: 1404077 Page 25 of 52

Date: 2014-06-12



### 3. High Channel



Date: 8.MAY.2014 17:55:27

Report No: 1404077 Page 26 of 52

Date: 2014-06-12




### 8. Maximum Peak Output Power

### 8.1 Regulation

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band:0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 8.2 Test Setup



#### 8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

Report No: 1404077 Page 27 of 52

Date: 2014-06-12



### **8.4Test Results**

EUT	Wirele	Wireless Video Door Phone		s Video Door Phone Model		DP-236-CQ
Mode	Keep Transmitting		Input Voltage	120V~		
Temperatu	re	24 deg. C,	Humidity	56% RH		
Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass/ Fail		
Low	2410.875	18.32	30	Pass		
Middle	2441.250	17.17	30	Pass		
High	2471.625	16.07	30	Pass		

Note: 1. the result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss + Attenuator

2. Worse case was recorded

Report No: 1404077 Page 28 of 52

Date: 2014-06-12



### 9. Carrier Frequency Separation

### 9.1 Regulation

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 9.2 Limits of Carrier Frequency Separation

The Carrier Frequency Separation Measurement is 25kHz or two-thirds of the 20dB bandwidth of the hopping Channel which is great.

#### 9.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span; Video (or Average) Bandwidth (VBW)  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.

Page 29 of 52

Report No: 1404077 Date: 2014-06-12




### 9.4Test Result

#### **Type of Modulation: GFSK**

EUT	Wireless Video Do	Model		DP-236-CQ	
Mode	Hopping On		Input Voltage	120V~	
Temperature	24 deg. C,		Humidity	56% RH	
Carrier Frequency Separation		Limit		Pass/ Fail	
3384kHz		≥ 25 kHz or 2/3 of 20 dB bandwidth		Pass	

### **Test Plots**



Date: 8.MAY.2014 16:25:15

Note: Worse case was recorded.

Report No: 1404077 Page 30 of 52

Date: 2014-06-12



### 10. Number of Hopping Channels

### 10.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used. According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 10.2 Limits of Number of Hopping Channels

The frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

#### 10.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW=100 kHz, VBW= 300 kHz;

Sweep = auto; Detector function = peak; Trace = max hold

3. Record the number of hopping channels.

Page 31 of 52

Date: 2014-06-12

Report No: 1404077




### 10.4Test Result

### Type of Modulation: GFSK

EUT	Wireless Video Door Phone		l	Model	DP-236-CQ	
Mode	Hopping On			Input /oltage	120V~	
Temperature	24 deg. C,		H	umidity	56% RH	
Operating Frequency		Number of hopping channels		Limit P		Pass/ Fail
2410.875-2471.625MHz		15		≥ 15		Pass

### **Test Plot**



Date: 8.MAY.2014 16:21:31

Report No: 1404077 Page 32 of 52

Date: 2014-06-12



### 11. Time of Occupancy (Dwell Time)

### 11.1 Regulation

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### 11.2 Limits of Carrier Frequency Separation

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

### 11.3 Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Set the spectrum analyzer as follows: Span = zero span, centered on a hopping channel; RBW = 100 kHz; VBW=300 kHz; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold
- 3. Measure the dwell time using the marker-delta function.
- 4. Repeat above procedures until all frequencies measured were complete.
- 5. Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

Report No: 1404077 Page 33 of 52

Date: 2014-06-12



### 11.4 Test Result


EUT		Wireless Video Door Phone	Model		DP-236-CQ
Mode		Keep Transmitting	Input Voltage		120V~
Temperature	e	24 deg. C,	Humidity		56% RH
Channel		Actual		Limit	
Middle		0.12312s		0.4s	

Actual = (0.4\*15/1) \* 57 \*0.360=123.12ms

Report No: 1404077 Page 34 of 52

Date: 2014-06-12


### Test Plots:



Date: 6.JUN.2014 12:02:27 Report No: 1404077 Page 35 of 52

Date: 2014-06-12





Date: 6.JUN.2014 12:04:21


Report No: 1404077 Page 36 of 52

Date: 2014-06-12



#### 12 Out of Band Measurement

### 12.1 Test Setup



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

#### 12.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### 12.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of Radiated emission test. Peak values with RBW=VBW=1MHz and PK detector.

For bandage test, the spectrum set as follows: RBW=100kHz,VBW=300 kHz. A conducted measurement used

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Page 37 of 52

Date: 2014-06-12


Report No: 1404077



#### 12.4 Out of Band Test Result

Product:	Wireless Video Door Phone		Test Mode:	Low Channel
Mode	Keeping Transmitting		Input Voltage	120V~
Temperature	24 deg. C		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	51.2		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)		Limit	54(dBμV/m)
2390MHz				

## **Test Figure:**



Date: 12.JUN.2014 12:43:13

Page 38 of 52


Report No: 1404077 Date: 2014-06-12



#### 12.4 Out of Band Test Result

Product:	Wireless Video Door Phone		Test Mode:	High Channel
Mode	Keeping Transmitting		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	53.8		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)	37.1	Limit	$54(dB\mu V/m)$
2483.5MHz				

## **Test Figure:**



Date: 8.MAY.2014 18:20:30


Report No: 1404077 Page 39 of 52

Date: 2014-06-12



#### 12.4 Out of Band Test Result

Product:	Wireless Video Door Phone		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	56.6		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)	40.2	Limit	54(dBµV/m)
2390MHz				



Date: 12.JUN.2014 12:35:38

Start 2.2 GHz

23 MHz/

Stop 2.43 GHz

Report No: 1404077 Page 40 of 52


Date: 2014-06-12



#### 12.4 Out of Band Test Result

Product:	Wireless Video Door Phone		Test Mode:	Hopping mode
Mode	Hopping On		Input Voltage	120V~
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK (dBμV/m)	56.4		$74(dB\mu V/m)$
Restrict Band	AV(dBμV/m)	40.2	Limit	$54(dB\mu V/m)$
2483.5MHz				

## **Test Figure:**



Date: 8.MAY.2014 16:19:49

Report No: 1404077 Page 41 of 52

Date: 2014-06-12



#### 13.0 Antenna Requirement

#### 13.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

#### 13.2 Antenna Connected constructions

Integral Antenna used. The maximum Gain of this antenna is 3.0dBi

Report No: 1404077 Page 42 of 52

Date: 2014-06-12




#### 14.0 FCC ID Label

# FCC ID: K4E236CQ

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

# Mark Location:



Report No: 1404077 Page 43 of 52

Date: 2014-06-12



#### 15.0 Photo of testing

Conducted Emission Test Setup:




Page 44 of 52

Report No: 1404077 Date: 2014-06-12



#### Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



#### Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



#### Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.



#### Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion

of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 49 of 52

Report No: 1404077 Date: 2014-06-12



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 50 of 52

Report No: 1404077 Date: 2014-06-12



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Photo for the EUT





The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Photo for the EUT





# End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co .,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.