



**Vertex Standard**

# VX-450 SERIES


## OPERATING MANUAL



**16-Key Version**



**4-Key Version**



**Non-LCD Version**

**VERTEX STANDARD CO., LTD.**

4-8-8 Nakameguro, Meguro-Ku, Tokyo 153-8644, Japan

**VERTEX STANDARD**

**US Headquarters**

10900 Walker Street, Cypress, CA 90630, U.S.A.

**YAESU UK LTD.**

Unit 12, Sun Valley Business Park, Winnall Close  
Winchester, Hampshire, SO23 0LB, U.K.

**VERTEX STANDARD HK LTD.**

Unit 5, 20/F., Seaview Centre, 139-141 Hoi Bun Road,  
Kwun Tong, Kowloon, Hong Kong

**VERTEX STANDARD (AUSTRALIA) PTY., LTD.**

Normanby Business Park, Unit 14/45 Normanby Road  
Notting Hill 3168, Victoria, Australia

---

## CONTENTS

---

<b>Warning! FCC RF Exposure Requirements</b> .....	2	<b>Operation</b> .....	10
<b>Controls &amp; Connectors (16-Key Version)</b> .....	4	Preliminary Steps .....	10
<b>Controls &amp; Connectors (4-Key Version)</b> .....	5	Operation Quick Start .....	10
<b>Controls &amp; Connectors (Non-LCD Version)</b> .....	6	<b>Advanced Operation</b> .....	14
<b>LCD Icons &amp; Indicators (16- &amp; 4-Key Versions)</b> .....	7	Programmable Key Functions .....	14
<b>Before You Begin</b> .....	8	Description of Operating Functions .....	16
Battery Pack Installation and Removal .....	8	<b>ARTS (Auto Range Transpond System)</b> .....	24
Low Battery Indication .....	8	<b>DTMF Paging System</b> .....	25
Battery Charging .....	9	<b>LOCK</b> .....	25

## CONGRATULATIONS!

You now have at your fingertips a valuable communications tool—a Vertex Standard two-way radio! Rugged, reliable and easy to use, your Vertex Standard radio will keep you in constant touch with your colleagues for years to come, with negligible maintenance down-time. Please take a few minutes to read this manual carefully. The information presented here will allow you to derive maximum performance from your radio, in case questions arise later on.

We're glad you joined the Vertex Standard team. Call on us anytime, because communications is our business. Let us help you get your message across.

**Notice!:** There are no owner-serviceable parts inside the radio. All service jobs must be referred to an authorized Vertex Standard Service Representative. Consult your Authorized Vertex Standard Dealer for installation of optional accessories.

## IMPORTANT NOTICE FOR NORTH AMERICAN USERS REGARDING 406 MHz GUARD BAND

The U.S. Coast Guard and National Oceanographic and Atmospheric Administration have requested the cooperation of the U.S. Federal Communications Commission in preserving the integrity of the protected frequency range 406.0 to 406.1 MHz, which is reserved for use by distress beacons. Do not attempt to program this apparatus, under any circumstances, for operation in the frequency range 406.0 - 406.1 MHz if the apparatus is to be used in or near North America.

**Warning - Frequency band 406 - 406.1 MHz is reserved for use ONLY as a distress beacon by the US Coast Guard and NOAA. Under no circumstance should this frequency band be part of the preprogrammed operating frequencies of this radio.**

---

## WARNING! FCC RF EXPOSURE REQUIREMENTS

---

This Radio has been tested and complies with the Federal Communications Commission (FCC) RF exposure limits for Occupational Use/Controlled exposure environment. In addition, it complies with the following Standards and Guidelines:

- FCC 96-326, Guidelines for Evaluating the Environmental Effects of Radio-Frequency Radiation.
- FCC OET Bulletin 65 Edition 97-01 (2001) Supplement C, Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields.
- ANSI/IEEE C95.1-1992, IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.
- ANSI/IEEE C95.3-1992, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave.

### WARNING:

This radio generates RF electromagnetic energy during transmit mode. This radio is designed for and classified as *Occupational Use Only*, meaning it must be used only during the course of employment by individuals aware of the hazards, and the ways to minimize such hazards. This radio is not intended for use by the General Population in an uncontrolled environment.

### CAUTION:

To ensure that your exposure to RF electromagnetic energy is within the FCC allowable limits for occupational use, always adhere to the following guidelines:

- This radio is NOT approved for use by the general population in an uncontrolled exposure environment. This radio is restricted to occupational use, work related operations only where the radio operator must have the knowledge to control his or her RF exposure conditions.**
- When transmitting, hold the radio in a vertical position with its microphone 2 inches (5 cm) away from your mouth and keep the antenna at least 2 inches (5 cm) away from your head and body.**


---

## WARNING! RF EXPOSURE REQUIREMENTS


---

- The radio must be used with a maximum operating duty cycle not exceeding 50%, in typical Push-to-Talk configurations.  
DO NOT transmit for more than 50% of total radio use time (50% duty cycle). Transmitting more than 50% of the time can cause FCC RF exposure compliance requirements to be exceeded.  
The radio is transmitting when the red LED on the top of the radio is illuminated. You can cause the radio to transmit by pressing the P-T-T button.
- SAR compliance for body-worn use was only demonstrated for the specific belt-clip Part Number (CLIP-450). Other body-worn accessories or configurations may NOT comply with the FCC RF exposure requirements and should be avoided.
- DO NOT transmit when the radio is used in Body Worn configuration with the following accessory: belt-clip.  
It must be used ONLY for (1) there is 4 cm distance from the body during transmitting, (2) monitoring purposes, using the speaker only and (3) for carrying purposes.
- Always use Vertex Standard authorized accessories.
- The information listed above provides the user with the information needed to make him or her aware of RF exposure, and what to do to assure that this radio operates with the FCC RF exposure limits of this radio.
- Electromagnetic Interference/Compatibility  
During transmissions, this radio generates RF energy that can possibly cause interference with other devices or systems. To avoid such interference, turn off the radio in areas where signs are posted to do so. Do not operate the transmitter in areas that are sensitive to electromagnetic radiation such as hospitals, health care facilities, aircraft, and blasting sites.


## CONTROLS & CONNECTORS (16-KEY VERSION)



## CONTROLS & CONNECTORS (4-KEY VERSION)




## CONTROLS & CONNECTORS (NON-LCD VERSION)





## LCD ICONS & INDICATORS (16-KEY & 4-KEY VERSIONS)




---

## BEFORE YOU BEGIN


---

### Battery Pack Installation and Removal

- ❑ To install the battery pack, align the battery pack to the radio with an offset about 1/2 inch from the top edge of battery compartment, then slide the battery pack upward until it locks in place with a “*Click.*”



- ❑ To remove the battery, turn the radio off and remove any protective cases. Slide the Battery Pack Latch on the bottom of the radio toward the front panel while sliding the battery down about 1/2 inch. Then lift the battery out from the radio while unfolding the Belt Clip.

 **Do not attempt to open any of the rechargeable Lithium-Ion packs, as they could explode if accidentally short-circuited.**

### Low Battery Indication

As the battery discharges during use, the voltage gradually becomes lower. When the battery voltage becomes too low, substitute a freshly charged battery and recharge the depleted pack. The LED indicator on the top of the radio will blink red when the battery voltage is low.

 **Caution** 

Danger of explosion if battery is replaced with an incorrect battery. Replace only with the same or equivalent type.


---

## BEFORE YOU BEGIN

---

### Battery Charging


- ❑ Insert the DC plug from the **PA-45** AC Adapter into the DC jack on the rear panel of the **CD-49** Desktop Rapid Charger, then plug the **PA-45** AC Adapter into the AC line outlet.
- ❑ Insert the battery pack into the **CD-49** Desktop Rapid Charger while aligning the slots of the battery pack with the guides in the nest of the **CD-49**; refer to the illustration at the right for details on proper positioning of the pack. If charging with the transceiver attached, turn the transceiver off, and the antenna jack should be at the left side when viewing the charger from the front.
- ❑ If the battery pack is inserted correctly, the LED indicator will glow red. A fully-discharged pack will be charged completely in approximately 1.5 hours (**FNB-V112LI**, 2.5 hours: **FNB-V113LI**).
- ❑ The LED indicator will blink red/green alternately when charging is nearing completion.
- ❑ When charging is completed, the LED indicator will change to green. Even if the charging is completed, the LED indicator will sometimes change to red for trickle charging.
- ❑ Disconnect the pack from the **CD-49** Desktop Rapid Charger, and unplug the **PA-45** AC Adapter from the AC line outlet.





## OPERATION

### Preliminary Steps

- ❑ Install a charged battery pack onto the transceiver, as described previously.
- ❑ Screw the supplied antenna onto the Antenna jack. Never attempt to operate this transceiver without an antenna connected.
- ❑ If you have a Speaker/Microphone, we recommend that it not be connected until you are familiar with the basic operation of the **VX-450**.





### Operation Quick Start

- ❑ Turn the top panel's **VOL/PWR** knob clockwise to turn the radio on.
- 
- 
- ❑ Turn the top panel's **CH** Selector knob to choose the desired operating channel. On the 16-key and 4-key versions, a channel name will appear on the LCD.
  - ❑ If you want to select the operating channel from a different Memory Channel Zone, press the Programmable key (assigned to the Memory Zone Up or Down function) to select the Memory Channel Zone you want before selecting the operating channel. A Zone name will appear on the LCD whenever the Programmable key is pressed.  
*Note:* Some models are programmed so that the operating channels are selected by the Programmable key and the Memory Channel Zone is selected by the **CH** selector knob. For further details, contact your Vertex Standard dealer.


## OPERATION

- ❑ Rotate the **VOL/PWR** knob to set the volume level. If no signal is present, press and hold in the **SIDE-1** button (under the **PTT** switch) more than 2 seconds; background noise will now be heard, and you may use this to set the **VOL/PWR** knob for the desired audio level. Press and hold the **SIDE-1** button more than 2 seconds (or press the **SIDE-1** button *twice*) to quiet the noise and resume normal (quiet) monitoring.




- ❑ To transmit, monitor the channel and make sure it is clear.


Press and hold the **PTT** switch. Speak into the microphone area of the front panel grille (above the upper left edge of the LCD) in a normal voice level. To return to the Receive mode, release the **PTT** switch.



- ❑ Press the (Orange) **TOP SEL** key to activate one of the preprogrammed functions which may have been enabled at the time of programming by the dealer. See the next section for details regarding the available features.



- ❑ If a Speaker/Microphone is available, remove the plastic cap and its two mounting screws from the right side of the transceiver, then align the connector of the Speaker/Microphone on the transceiver body; secure the connector pin using the screws supplied with the Speaker/Microphone. Hold the speaker grille up next to your ear while receiving. To transmit, press the **PTT** switch on the Speaker/Microphone, just as you would on the main transceiver's body, and speak into the microphone on a normal voice level. *Note 1): Save the original plastic cap and its mounting screws. They should be reinstalled when not using the Speaker/Microphone.*



---

## OPERATION

---

2) *When you press the PTT switch on the Speaker/Microphone, it disables the internal microphone, and vice versa.*



*Do not remove/install the Speaker/Microphone in a hazardous location.*

- ❑ If the Busy Channel Lockout feature has been programmed on a channel, the radio will not transmit when a carrier is present. Instead, the radio will generate short beep three times and indicate “\* CH Busy \*” on the display (16-key and 4-key versions). Release the **PTT** switch and wait for the channel to be clear of activity.
- ❑ If CTCSS or Digital Coded Squelch (DCS) Lockout has been programmed on a channel, the radio can transmit only when there is no carrier being received or when the carrier being received includes the correct CTCSS tone or DCS code.

### **Automatic Time-Out Timer**

If the selected channel has been programmed for automatic time-out, you must limit the length of each transmission. While transmitting, a beep will sound 10 seconds before time-out. Another beep will sound just before the deadline; the “**TX**” indicator will disappear and transmission will cease soon thereafter. To resume transmitting, you must release the **PTT** switch and wait for the “penalty timer” to expire.

---

## NOTE

---

## ADVANCED OPERATION

### Programmable Key Functions

All versions of the **VX-450** include the **TOP SEL**, **SIDE-1**, and **SIDE-2** key. The 16-key and 4-key versions include the **[A]**, **[B]**, **[C]**, and **[D]** function keys. Furthermore, the 16-key version includes the **[\*]** and **[#]** function keys.

The Programmable key functions can be customized, via programming by your Vertex Standard dealer, to meet your communications/network requirements.

Some features may require the purchase and installation of optional internal accessories. The possible Programmable key programming features are illustrated at the right, and their functions are explained on page 16. For further details, contact your Vertex Standard dealer.

For future reference, check the box next to each function that has been assigned to the Programmable key on your particular radio, and keep it handy.

FUNCTION	PROGRAMMABLE KEY								
	TOP SEL	SIDE-1	SIDE-2	[A]	[B]	[C]	[D]	[*]	[#]
None									
Monitor									
Lamp									
Lock <sup>*1</sup>									
Scan									
Dual Watch									
Low Power									
Talk Around									
TX Save Disable									
Encryption									
FM Scan									
Zone Up <sup>*1</sup>									
Zone Down <sup>*1</sup>									
Channel Up <sup>*1</sup>									
Channel Down <sup>*1</sup>									
Set <sup>*1</sup>									
Call/Reset									



## ADVANCED OPERATION

FUNCTION	PROGRAMMABLE KEY								
	TOP SEL	SIDE-1	SIDE-2	[A]	[B]	[C]	[D]	[*]	[#]
Call 1									
Call 2									
Call 3									
Call 4									
Call 5									
Code Up*1									
Code Down*1									
Code Set*1									
Speed Dial*2									
Option SW 1									
Option SW 2									
Emergency									
PRI-1*1									
Selectable Tone*1									
Direct Channel #1*1									
Direct Channel #2*1									
Direct Channel #3*1									
Direct Channel #4*1									
REC*3									
PLAY*3									
SQL									
AF Min Volume									
Status Set*1									
Status Up*1									
Status Down*1									
Status Check									
Lone Worker									
DTMF Code Set*2									
TA Scan									
Priority Disable									
Beep Off									
Whisper									
Duty									

\*1: This function can not be selected on the Non-LCD Version

\*2: This function is only selected on the 16-key Version

\*3: Requires **DVS-8** Voice Storage Unit

---

## ADVANCED OPERATION

---

### Description of Operating Functions

#### MONITOR

Press the assigned Programmable key to cancel CTCSS- and DCS-controlled squelch; the **BUSY/TX** indicator will glow green. Press and hold this button for 2 seconds to hear background noise (unmute the audio); the **BUSY/TX** indicator will blink green.

#### LAMP

Press the assigned Programmable key to illuminate the LCD for five seconds.

#### LOCK

Press the assigned Programmable key to lock the **CH** Selector knob, Programmable keys, and **PTT** switch. The precise lockout configuration is programmed by your Dealer.

#### SCAN

The Scanning feature is used to monitor multiple signals programmed into the transceiver. While scanning, the transceiver will check each channel for the presence of a signal, and will stop on a channel if a signal is present.

#### *To activate scanning:*

- Press the assigned Programmable key to activate scanning.
- The scanner will search the channels of each channel, looking for active ones; it will pause each time it finds a channel on which someone is speaking.
- Press the assigned Programmable key again to disable scanning. Operation will revert to the programmed revert channel.

*Note:* Your dealer may have programmed your radio to stay on one of the following channels if you press the **PTT** switch during scanning pause:

- Current channel (“Talk Back”)
- “Last Busy” channel
- “Priority” channel
- “Home” channel
- “Scan Start” channel

---

## ADVANCED OPERATION

---

### DUAL WATCH

The Dual Watch feature is similar to the SCAN feature, except that only two channels are monitored:

- The current operating channel; and
- The Priority channel.

#### *To activate Dual Watch:*

- Press the assigned Programmable key.
- The scanner will search the two channels; it will pause each time it finds a channel on which someone is speaking.

#### *To stop Dual Watch:*

- Press the assigned Programmable key.
- Operation will revert to the “Dual Watch Start” channel.


### LOW POWER

Press the assigned Programmable key to set the radio’s transmitter to the “Low Power” mode, thus extending battery life. Press the key again to return to “Normal” transmit power when in difficult terrain.

When the radio’s transmitter is set to “Low Power” mode, the “**LOW**” icon will be indicated on the display.

### TALK AROUND (TA)

Press the assigned Programmable key to activate the Talk Around feature when you are operating on duplex channel systems (separate receive and transmit frequencies, utilizing a “repeater” station). The Talk Around feature allows you to bypass the repeater station and talk directly to a station that is nearby. This feature has no effect when you are operating on “simplex” channels, where the receive and transmit frequencies are already the same.

When the “TA” function is activated, the “

Note that your dealer may have mode provision for “Talk Around” channels by programming “repeater” and “Talk Around” frequencies on two adjacent channels. If so, the key may be used for one of the other Pre-Programmed Functions.

---

## ADVANCED OPERATION

---

### **TX SAVE DISABLE**

Press the assigned Programmable key to disable the Transmit Battery Saver, if you are operating in a location where high power is almost always needed.

The Transmit Battery Saver helps extend battery life by reducing transmit power when a very strong signal from an apparently nearby station is being received. Under some circumstances, though, your hand-held radio may not be heard well at the other end of the communication path, and high power may be necessary at all times.

### **ENCRYPTION**

Press the assigned Programmable key to toggle the Encryption feature “On” and “Off.”

### **FM SCAN**

The FM Scan feature checks a User-assigned Priority Channel regularly as you scan other channels. Thus, if only Channels 1, 3, and 5 (of the 8 available channels) are designated for “Scanning,” the user may nonetheless assign Channel 2 as the “User-assigned” Priority Channel via the “Follow-Me” feature.

To activate FM Scan, first select the channel you want to designate as the “User-Assigned Priority Channel” and press the assigned programmable key. Then rotate the **CH** Selector knob to recall to the “Scanning Start” channel which has been programmed by your dealer to activate the scanner. When the scanner stops on an “Active” channel, the User-assigned Priority Channel will automatically be checked every few seconds; if activity is found on the User-assigned Priority Channel, the radio will switch between it and the Dealer-Assigned Priority Channel, if any.

---

## ADVANCED OPERATION

---

### ZONE UP/DOWN

Press the assigned Programmable key to select a different Zone of channels. Once the desired Zone is reached, rotate the **CH** Selector knob to select the desired channel within the selected Zone.

You may wish to have the Scanner pass through more than one Zone during the scanning process (normally, scanning is performed within the current Zone only). To include the current Zone in the scanning loop, press and hold in the assigned Programmable key for one second. To remove a Zone from Zone Scan, press and hold in the assigned programmable key again for one second.

Multi-Zone Scanning is only possible if you are using the “User Scan” list. To edit the User Scan list, press and hold the assigned Programmable key for one second to delete the current Memory Zone from the Scanning. Alternatively, press and hold the assigned Programmable key for one second to delete the Current Memory channel from the Scanning. When you delete a Zone or channel, “-SCAN Skip-” will appear on the LCD for one second after pressing the assigned Programmable key. To restore a particular channel to your scanning list, press and hold in the assigned Programmable key again for one second;

“-SCAN Stop-” will appear on the LCD for one second after pressing the assigned programmable key.

### CHANNEL UP/DOWN

Press the assigned Programmable key to select a different channel within the current Zone.

### SET

Press the assigned Programmable key to activate the “User Set” (Menu) Mode. See page 20 for details

### CALL/RESET

#### *While the DTMF Paging System*

This feature, if enabled, allows the user to change the 3-digit Page Call code, used to call other similarly-equipped stations. Press the assigned Programmable key, followed by the three digits representing the Page Call code of the station you wish to call. Three tones will be heard after the last key is pressed (the new code will now be transmitted).

The receiver squelch of the other station will be opened, and you can begin communication.

#### *While the 2-Tone/5-Tone Paging System*

This feature, if enabled, press the assigned Programmable key to send a 2-tone/5-tone sequential tone.

---

## ADVANCED OPERATION

---

### CALL 1 TO CALL 5

Press the assigned Programmable key to send a 2-tone/5-tone sequential tone group which is pre-defined.

### CODE UP/DOWN

Press the assigned Programmable key to select a 2-tone/5-tone encode code from the pre-defined encode list.

### CODE SET

Press the assigned Programmable key to change the encode digits for 5-tone operation. To change a specific digit, select the desired digit using the [A] key, then change the number using the [B]/[C] keys, and store the number using the [D] key.

### SPEED DIAL (16-KEY VERSION ONLY)

Your Dealer may have pre-programmed Auto-Dial telephone number memories into your radio.

To dial a number, press the assigned Programmable key, then press the front panel's numeric key corresponding to the Auto-Dial memory number list provided by your Dealer or Network Administrator. The DTMF tones sent during the dialing sequence will be heard in the speaker.

### OPTION SW1

Press the assigned Programmable key to toggle the optional accessory "1" "On" and "Off."

### OPTION SW2

Press the assigned Programmable key to toggle the optional accessory "2" "On" and "Off."

### EMERGENCY

The **VX-450** series include an "Emergency" feature which may be useful for alerting another party monitoring on the same frequency as your transceiver's channel.

Press the assigned Programmable key to initiate an emergency call. For further details contact your Dealer.

### PRI-1

Press the assigned Programmable key to recall the pre-defined Priority channel. When you recall the Priority channel, the "P" notation will appear on the LCD.

---

## ADVANCED OPERATION

---

### SELECTABLE TONE

Press the assigned Programmable key to select a sub-audible tone (CTCSS/DCS) from the pre-defined tone table. You can operate using the indicated sub-audible tone in the Selectable Tone mode.

### DIRECT CH#1 TO #4

Press the assigned Programmable key to recall the Dealer pre-programmed channel directly.

### REC/PLAY (VOICE STORAGE: OPTION)

This function allows your radio to record a received voice message, and to play back the recorded audio. It requires installation of the optional Voice Recording Unit.

#### *Recording;*

Press the assigned Programmable key for 1.5 seconds to enable the Voice Recording Mode. If the incoming signal is received, so as to un-mute the squelch and pass audio, then the “☑” Icon will flash and received audio will be recorded. When the voice recording is completed, the “☑” stays on.

#### *Playback;*

Press the assigned Programmable key momentarily to play back the last message.

To stop the play-back, press the **TOP SEL** key.

While playback is proceeding, you may press the [**A**] key (4-key version) or [**\***] key (16-key version) to jump to the previous message, or press the [**B**] key (4-key version) or [**#**] key (16-key version) to jump to the next message. Furthermore, press the [**D**] key to clear the all messages and stop the play-back.

### SQL

You can manually adjust the squelch level using this function:

- Press the assigned Programmable key. A tone will sound, and the current squelch level will appear on the display.
- Press the **SIDE-1/SIDE-2** button to select the desired squelch level.
- Two seconds after releasing the **SIDE-1/SIDE-2** button, the display will revert to the normal channel indication.

### AF MIN VR

Press the assigned Programmable key to reduce the audio output to the (lower) level programmed by your Dealer.

---

## ADVANCED OPERATION

---

### STATUS SET

Press the assigned Programmable key to change the 5-Tone status code. To change the status code, select the desired digit by [**A**] key, then change the number by [**B**]/[**C**] key, and store the number by [**D**] key.

### STATUS UP/DOWN

Press the assigned Programmable key to select a 5-Tone status code from the pre-defined status list.

### STATUS CHECK

Press the assigned Programmable key to check the 5-Tone receive status code. When you press this key, the LCD display will indicate the “Message” corresponding to the receive status condition per the pre-defined status list.

### LONE WORKER

Press the assigned Programmable key to toggle the Lone Worker feature “On” and “Off.”

The Lone Worker feature is designed to emit an alarm for 30 seconds when the Lone Worker Timer (programmed by your Dealer) has expired. If the user does not reset the timer by pressing the **PTT** switch, the radio switches to the Emergency mode.



### DTMF CODE SET (16-KEY VERSION ONLY)

You may send the desired telephone number manually.

To dial a number manually, press the assigned Programmable key, then press the desired numbers on the front panel’s numeric key. Now, press the **PTT** switch to send the telephone number. The DTMF tones sent during the dialing sequence will be heard in the speaker.

### TA SCAN

Press the assigned Programmable key to toggle the TA (Talk Around) scan feature “On” and “Off.”

While TA scan is proceeding, the **VX-450** will search both the transmit and receive frequencies (the “” icon will blink). When a signal is encountered on the receive frequency, the **VX-450** will pause until the signal disappears (“” icon will appear but not blink). When a signal is encountered on the transmit frequency, the **VX-450** will check for activity on the receive frequency every few seconds (interval programmed by your Dealer).



---

## ADVANCED OPERATION

---

### **PRIORITY DISABLE**

Press the assigned Programmable key to disable the Priority feature temporarily. Again press the assigned Programmable key to resume the Priority feature.

### **BEEP OFF**

Press the assigned Programmable key to disable the radio beeps temporarily. Again press the assigned Programmable key to enable the radio beeps.

### **WHISPER**

Press the assigned Programmable key to increase the microphone gain; thus you can speak in a low voice (whisper) temporarily. Again press the assigned Programmable key to resume normal microphone gain.

### **DUTY**

Press the assigned Programmable key to toggle the Duty function of the 2-tone/5-tone decoder “On” and “Off.”

When the Duty function is set to “On,” the user will always hear (depending on the sub-audio signalling) all traffic on the paging channel. The radio will sound the paging alert when it receives the programmed 2-tone/5-tone code.

When the Duty function is set to “Off,” the user will NOT hear normal radio traffic on the paging channel. The radio will sound the paging alert and unmute only when it receives the programmed 2-tone/5-tone code.

---

## ARTS™ (AUTO RANGE TRANSPOND SYSTEM)

---

This system is designed to inform you when you and another ARTS™-equipped station are within communication range.

During ARTS™ operation, when the radio receives the correct ARTS™ signal, a short beep will sound and the “**In**” (meaning “In Service”) notation will be displayed on the sub-LCD\*. If you move out of range for more than two minutes, your radio senses that no signal has been received; three short beeps will sound, and “**Out**” (“Out of Service”) will be displayed on the sub-LCD\*. If you subsequently move back into range, as soon as the other station transmits, a short beep will sound and “**In**” will be displayed again on the sub-LCD\*.

※: Except on Non-LCD version.

---

## DTMF PAGING SYSTEM

---

This system allows paging and selective calling, using DTMF tone sequences.

When your radio is paged by a station bearing a tone sequence which matches yours, your radio’s squelch will open and the alert will sound. The three-digit code of the station which paged you will be displayed on your radio’s LCD.

---

## LOCK

---

In order to prevent accidental channel change or inadvertent transmission, various aspects of the **CH** Selector knob, Programmable keys, and **PTT** switch may be locked.

The precise lockout configuration is programmed by your Dealer.

To locked out the key locking, turn the radio off. Now, press and hold the **PTT** and **SIDE-2** key while turning the radio on again.

To cancel locking, repeat this process.

Part 15.21: Changes or modifications to this device not expressly approved by Vertex Standard could void the user's authorization to operate this device.



Copyright 2010  
VERTEX STANDARD CO., LTD.  
All rights reserved.

No portion of this manual  
may be reproduced  
without the permission of  
VERTEX STANDARD CO., LTD.

Printed in Japan