

**CERTIFICATE OF COMPLIANCE**  
**SAR EVALUATION**


<p><b><u>Test Lab:</u></b></p> <p><b>CELLTECH RESEARCH INC.</b> Testing and Engineering Lab 1955 Moss Court Kelowna, B.C. Canada V1Y 9L3 Phone: 250 - 860-3130 Fax: 250 - 860-3110 Toll Free: 1-877-545-6287 e-mail: celltech@globuswireless.com web site: www.globuswireless.com</p>	<p><b><u>Applicant Information:</u></b></p> <p><b>VERTEX STANDARD CO., LTD.</b> 4-8-8 Nakameguro, Meguro-Ku, Tokyo, 153-8644 Japan Attn: Tomiro Ohmoto Export Manager</p>
---	---

<b>FCC ID:</b>	<b>K66VX-160V</b>
<b>Model(s):</b>	<b>VX-160V/180V</b>
<b>EUT Type:</b>	<b>Portable VHF PTT Radio Transceiver</b>
<b>Modulation:</b>	<b>FM</b>
<b>Tx Frequency Range:</b>	<b>146-174 MHz</b>
<b>Max. RF Output Power:</b>	<b>4.7 W (Conducted)</b>
<b>No. of Channels:</b>	<b>16</b>
<b>FCC Rule Part(s):</b>	<b>2.1093; ET Docket 96-326</b>

This wireless mobile and/or portable device has been shown to be compliant for localized Specific Absorption Rate (SAR) for controlled environment/occupational exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in ANSI/IEEE Std. C95.3-1999.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Celltech Research Inc. certifies that no party to this application has been denied FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).



**Shawn McMillen**  
**General Manager**  
**Celltech Research Inc.**



## **TABLE OF CONTENTS**

1.0	<b>INTRODUCTION.....</b>	1
2.0	<b>DESCRIPTION OF EUT.....</b>	1
3.0	<b>SAR MEASUREMENT SYSTEM .....</b>	2
4.0	<b>MEASUREMENT SUMMARY.....</b>	3-6
5.0	<b>SAR LIMITS.....</b>	7
6.0	<b>DETAILS OF SAR EVALUATION.....</b>	8
7.0	<b>EVALUATION PROCEDURES.....</b>	9
8.0	<b>SYSTEM VALIDATION.....</b>	9
9.0	<b>SIMULATED EQUIVALENT TISSUES.....</b>	10
10.0	<b>TISSUE PARAMETERS.....</b>	10
11.0	<b>SYSTEM SPECIFICATIONS.....</b>	11
12.0	<b>TEST EQUIPMENT LIST.....</b>	12
13.0	<b>MEASUREMENT UNCERTAINTIES.....</b>	13
14.0	<b>REFERENCES.....</b>	14
	<b>APPENDIX A - SAR MEASUREMENT DATA.....</b>	15
	<b>APPENDIX B - DIPOLE VALIDATION.....</b>	16
	<b>APPENDIX C - PROBE CALIBRATION.....</b>	17
	<b>APPENDIX D - TEST SETUP PHOTOGRAPHS.....</b>	18

## 1.0 INTRODUCTION

This measurement report shows compliance of the VERTEX STANDARD Model: VX-160V/180V Portable VHF PTT Radio Transceiver FCC ID: K66VX-160V with the regulations and procedures specified in FCC Part 2.1093, ET Docket 96-326 Rules (controlled exposure) for mobile and portable devices. The test procedures, as described in American National Standards Institute C95.1-1992 (1), FCC OET Bulletin 65-1997 were employed. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

## 2.0 DESCRIPTION of Equipment Under Test (EUT)

<b>Rule Part(s)</b>	FCC 2.1093; ET Docket 96.326	<b>Modulation</b>	Direct FM
<b>EUT Type</b>	Portable VHF PTT Radio Transceiver	<b>Tx Frequency Range</b>	146-174 MHz
<b>Model No.(s)</b>	VX160V/180V	<b>Max. RF Output Power</b>	4.7 W (Conducted)
<b>Serial No.</b>	Pre-production	<b>Power Supply</b>	FNB-64 Ni-Cd Battery DC 7.2V 700mAh
<b>Antenna Type(s)</b>	Whip	<b>Antenna Length(s)</b>	
		ATV-6A	102 mm
		ATV-6B	97 mm
		ATV-6C	89 mm
		ATV-6XL (146 MHz)	188 mm
		ATV-6XL (160 MHz)	165 mm
		ATV-6XL (174 MHz)	149 mm

### ***3.0 SAR MEASUREMENT SYSTEM***

Celltech Research SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, and the generic twin phantom containing brain or muscle equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE3 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



*DASY3 SAR Measurement System*


#### 4.0 MEASUREMENT SUMMARY

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the EUT are reported in Appendix A.

#### Face-Held SAR Measurements - 4.0cm Spacing

Freq (MHz)	Channel	Mode	Max. Conducted Power (W)	Antenna Type	Separation Distance (cm)	SAR (w/kg)	
146	Low	Unmod. Carrier	4.7	ATV-6A	4.0	0.237	0.1185 (50% duty cycle)
146	Low	Unmod. Carrier	4.7	ATV-6XL	4.0	0.416	0.208 (50% duty cycle)
160	Mid	Unmod. Carrier	4.3	ATV-6B	4.0	0.359	0.1795 (50% duty cycle)
160	Mid	Unmod. Carrier	4.3	ATV-6XL	4.0	0.443	0.2215 (50% duty cycle)
174	High	Unmod. Carrier	4.3	ATV-6C	4.0	0.0705	0.03525 (50% duty cycle)
174	High	Unmod. Carrier	4.3	ATV-6XL	4.0	0.117	0.0585 (50% duty cycle)
<b>Mixture Type: Brain</b> <b>Dielectric Constant: 59.9</b> <b>Conductivity: 0.48</b>			<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT</b> <b>Spatial Peak Controlled Exposure/Occupational</b> <b>BRAIN: 8.0 W/kg (averaged over 1 gram)</b>				

Notes: 1. The SAR values found were below the maximum limit of 8.0 w/kg. The highest SAR value found was 0.2215 w/kg (50% duty cycle).



Face-held SAR Test Setup

**Body-Worn SAR Measurements with Belt-Clip - 1.0cm Spacing**

Freq (MHz)	Channel	Mode	Max. Conducted Power (W)	Antenna Type	Separation Distance (cm)	SAR (w/kg)	
146	Low	Unmod. Carrier	4.7	ATV-6A	1.0	0.438	0.2190 (50% duty cycle)
146	Low	Unmod. Carrier	4.7	ATV-6XL	1.0	0.681	0.3405 (50% duty cycle)
160	Mid	Unmod. Carrier	4.3	ATV-6B	1.0	0.416	0.208 (50% duty cycle)
160	Mid	Unmod. Carrier	4.3	ATV-6XL	1.0	0.358	0.179 (50% duty cycle)
174	High	Unmod. Carrier	4.3	ATV-6C	1.0	0.190	0.095 (50% duty cycle)
174	High	Unmod. Carrier	4.3	ATV-6XL	1.0	0.577	0.2885 (50% duty cycle)
<b>Mixture Type: Muscle                      Dielectric Constant: 65.7                      Conductivity: 0.75</b>			<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT                      Spatial Peak Controlled Exposure/Occupational                      BODY: 8.0 W/kg (averaged over 1 gram)</b>				

- Notes: 1. The SAR values found were below the maximum limit of 8.0 w/kg. The highest SAR value found was 0.3405 w/kg (50% duty cycle).  
 2. The EUT was tested for body SAR using the supplied Vertex belt-clip providing a 1.0cm separation distance between the rear of the EUT and the outer surface of the planar phantom.



EUT with Belt-Clip



Body SAR Test Setup

**Body-Worn SAR Measurements with Leather Belt Case - 0.5cm Spacing**

Freq (MHz)	Channel	Mode	Max. Conducted Power (W)	Antenna Type	Separation Distance (cm)	SAR (w/kg)	
146	Low	Unmod. Carrier	4.7	ATV-6A	0.5	0.452	0.226 (50% duty cycle)
146	Low	Unmod. Carrier	4.7	ATV-6XL	0.5	0.402	0.201 (50% duty cycle)
160	Mid	Unmod. Carrier	4.3	ATV-6B	0.5	0.310	0.155 (50% duty cycle)
160	Mid	Unmod. Carrier	4.3	ATV-6XL	0.5	0.231	0.1155 (50% duty cycle)
174	High	Unmod. Carrier	4.3	ATV-6C	0.5	0.246	0.123 (50% duty cycle)
174	High	Unmod. Carrier	4.3	ATV-6XL	0.5	0.429	0.2145 (50% duty cycle)
<b>Mixture Type: Muscle                      Dielectric Constant: 65.7                      Conductivity: 0.75</b>			<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT                      Spatial Peak Controlled Exposure/Occupational                      BODY: 8.0 W/kg (averaged over 1 gram)</b>				

- Notes: 1. The SAR values found were below the maximum limit of 8.0 w/kg. The highest SAR value found was 0.3405 w/kg (50% duty cycle).  
 2. The EUT was tested for body SAR using the supplied Vertex belt case providing a 0.5cm separation distance between the rear of the EUT and the outer surface of the planar phantom.



EUT with Leather Belt Case



Body SAR Test Setup



**Body-Worn SAR Measurements with Leather Belt Holster - 4.0cm Spacing**

Freq (MHz)	Channel	Mode	Max. Conducted Power (W)	Antenna Type	Separation Distance (cm)	SAR (w/kg)	
146	Low	Unmod. Carrier	4.7	ATV-6A	4.0	0.312	0.156 (50% duty cycle)
146	Low	Unmod. Carrier	4.7	ATV-6XL	4.0	0.382	0.191 (50% duty cycle)
160	Mid	Unmod. Carrier	4.3	ATV-6B	4.0	0.435	0.2175 (50% duty cycle)
160	Mid	Unmod. Carrier	4.3	ATV-6XL	4.0	0.359	0.1795 (50% duty cycle)
174	High	Unmod. Carrier	4.3	ATV-6C	4.0	0.102	0.051 (50% duty cycle)
174	High	Unmod. Carrier	4.3	ATV-6XL	4.0	0.427	0.2135 (50% duty cycle)
<b>Mixture Type: Muscle</b> <b>Dielectric Constant: 65.7</b> <b>Conductivity: 0.75</b>			<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT</b> <b>Spatial Peak Controlled Exposure/Occupational</b> <b>BODY: 8.0 W/kg (averaged over 1 gram)</b>				

Notes: 1. The SAR values found were below the maximum limit of 8.0 w/kg. The highest SAR value found was 0.2175 w/kg (50% duty cycle).  
 2. The EUT was tested for body SAR using the supplied Vertex belt holster providing a 4.0cm separation distance between the rear of the EUT and the outer surface of the planar phantom.



EUT with Leather Body Holster



Body SAR Test Setup



**5.0 SAR SAFETY LIMITS**

EXPOSURE LIMITS	SAR (W/Kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10g)	4.0	20.0

Notes: 1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.

2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

## **6.0 DETAILS OF SAR EVALUATION**

The VERTEX STANDARD Model: VX-160V/180V Portable VHF PTT Radio Transceiver FCC ID: K66VX-160V was found to be compliant for localized Specific Absorption Rate (SAR) based on the following test provisions and conditions:

- 1) The EUT was tested in a face-held configuration with the front of the device placed parallel to and at a nominal distance of 40mm from the outer surface of the planar phantom.
- 2) The EUT was tested in a body-worn configuration with the rear of the device placed parallel to the outer surface of the planar phantom with the attached belt-clip touching the outer surface of the planar phantom, and providing a 1cm separation distance between the rear of the EUT and the outer surface of the planar phantom.
- 3) The EUT was tested in a body-worn configuration with the rear of the device placed parallel to the outer surface of the planar phantom in the Vertex leather belt case (LCC-800/TT) touching the outer surface of the planar phantom, and providing a 0.5cm separation distance between the rear of the EUT and the outer surface of the planar phantom.
- 4) The EUT was tested in a body-worn configuration installed in the Vertex leather body holster LCC-800S/TT with the rear of the EUT placed parallel to and touching the outer surface of the planar phantom, and providing a 4cm separation distance between the rear of the EUT and the outer surface of the planar phantom.
- 5) The EUT was evaluated for SAR at maximum power and the unit was operated for an appropriate period prior to the evaluation in order to minimize drift.
- 6) The device was keyed to operate continuously in the transmit mode for the duration of the test.
- 7) The location of the maximum spatial SAR distribution (Hot Spot) was determined relative to the device and its antenna. This location was then related to a phantom that possesses human like facial attributes. The hot spot location of the EUT occurred just below the mounting point of the antenna. In a normal operating position this places the hotspot just below the left eye. In the absence of nose and lips, this region of the face is fairly planar. Therefore the use of the planar section of the phantom is warranted. The distance of 40mm from the antenna to the planar region of the phantom is large enough that does not create unrealistic loading of the antenna.
- 8) The EUT was tested with a fully charged battery.

## 7.0 EVALUATION PROCEDURES

The Specific Absorption Rate (SAR) evaluation was performed in the following manner:

- a. (i) The evaluation was performed in an applicable area of the phantom depending on the type of device being tested. For devices worn about the ear during normal operation, both the left and right ear positions were evaluated at the center frequency of the band at maximum power. The side, which produced the greatest SAR, determined which side of the phantom would be used for the entire evaluation. The positioning of the head-worn device relative to the phantom was dictated by FCC OET Bulletin 65 Supp., C.  
(ii) For face-held and body-worn devices, or devices which can be operated within 20cm of the body, the planar section of the phantom was used. The type of device being evaluated dictated the distance of the EUT to the outer surface of the planar phantom.
- b. The SAR was determined by a pre-defined procedure within the DASY3 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 20mm x 20mm.
- c. A 5x5x7 matrix was performed around the greatest spatial SAR distribution found during the area scan of the applicable exposed region. SAR values were then calculated using a 3-D spline interpolation algorithm and averaged over spatial volumes of 1 and 10 grams.
- d. If the EUT had any appreciable drift over the course of the evaluation, then the EUT was re-evaluated. Any unusual anomalies over the course of the test also warranted a re-evaluation.

## 8.0 SYSTEM VALIDATION

Prior to the assessment, the system was verified in the planar region of the phantom. For devices operating below 1GHz, an 835MHz dipole or 900MHz was used, depending on the operating frequency of the EUT. For devices operating above 1GHz, an 1800MHz dipole was used. A forward power of 250mW was applied to the dipole and system was verified to a tolerance of  $\pm 5\%$ . Following the validation, the fluid remained or was changed depending on the particular part of the body being evaluated. The applicable verifications are as follows (see Appendix B for validation test plot):

Dipole Validation Kit	Target SAR 1g (w/kg)	Measured SAR 1g (w/kg)	
D835V2	2.06	2.01 (02/16/01)	2.03 (02/20/01)

### 9.0 SIMULATED TISSUES

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution. Preservation with a bactericide is added and visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

INGREDIENT	MIXTURE %		
	835MHz Brain (Validation)	150MHz Brain	150MHz Muscle
Water	40.1	45.45	50.00
Sugar	58.1	52.48	46.00
Salt	0.7	1.62	3.55
HEC	1.0	0.20	0.20
Bactericide	0.1	0.25	0.25

### 10.0 TISSUE PARAMETERS

The dielectric parameters of the fluids were verified prior to the SAR evaluation using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer. The dielectric parameters of the fluid are as follows:

Equivalent Tissue	Dielectric Constant $\epsilon_r$	Conductivity $S$ (mho/m)	$\rho$ (Kg/m <sup>3</sup> )
Brain (835MHz Validation)	44.2 ± 5%	0.80 ± 5%	1000
Brain (150MHz)	59.9 ± 5%	0.48 ± 5%	1000
Muscle (150MHz)	65.7 ± 5%	0.75 ± 5%	1000

## **11.0 ROBOT SYSTEM SPECIFICATIONS**

### **Specifications**

**POSITIONER:** Stäubli Unimation Corp. Robot Model: RX60L  
**Repeatability:** 0.02 mm  
**No. of axis:** 6

### **Data Acquisition Electronic (DAE) System**

#### **Cell Controller**

**Processor:** Pentium III  
**Clock Speed:** 450 MHz  
**Operating System:** Windows NT  
**Data Card:** DASY3 PC-Board

#### **Data Converter**

**Features:** Signal Amplifier, multiplexer, A/D converter, and control logic  
**Software:** DASY3 software  
**Connecting Lines:** Optical downlink for data and status info.  
Optical uplink for commands and clock

### **PC Interface Card**

**Function:** 24 bit (64 MHz) DSP for real time processing  
Link to DAE3  
16 bit A/D converter for surface detection system  
serial link to robot  
direct emergency stop output for robot

### **E-Field Probe**

**Model:** ET3DV6  
**Serial No.:** 1387  
**Construction:** Triangular core fiber optic detection system  
**Frequency:** 10 MHz to 6 GHz  
**Linearity:**  $\pm 0.2$  dB (30 MHz to 3 GHz)

### **Phantom**

**Phantom:** Generic Twin  
**Shell Material:** Fiberglass  
**Thickness:** 2.0  $\pm$  0.1 mm

**12.0 TEST EQUIPMENT LIST**

<b>SAR MEASUREMENT SYSTEM</b>		
<b><u>EQUIPMENT</u></b>	<b><u>S/N</u></b>	<b><u>CALIB. DATE</u></b>
<b>DASY3 System</b> -Robot -ET3DV6 E-Field Probe -DAE -835MHz Validation Dipole -900MHz Validation Dipole -1800MHz Validation Dipole -Generic Twin Phantom V3.0	599396-01 1387 383 411 054 247 N/A	N/A Sept 1999 Sept 1999 Aug 1999 Aug 1999 Aug 1999 N/A
<b>85070C Dielectric Probe Kit</b>	N/A	N/A
<b>Gigatronics 8652A Power Meter</b> -Power Sensor 80701A -Power Sensor 80701A	1835272 1833535 1833542	Oct 1999 Oct 1999 Oct 1999
<b>E4408B Spectrum Analyzer</b>	US39240170	Nov 1999
<b>8594E Spectrum Analyzer</b>	3543A02721	Mar 2000
<b>8753E Network Analyzer</b>	US38433013	Nov 1999
<b>8648D Signal Generator</b>	3847A00611	N/A
<b>5S1G4 Amplifier Research Power Amplifier</b>	26235	N/A

### 13.0 MEASUREMENT UNCERTAINTIES

Uncertainty Description	Error	Distribution	Weight	Standard Deviation	Offset
<b>Probe Uncertainty</b>					
Axial isotropy	±0.2 dB	U-Shaped	0.5	±2.4 %	
Spherical isotropy	±0.4 dB	U-Shaped	0.5	±4.8 %	
Isotropy from gradient	±0.5 dB	U-Shaped	0	±	
Spatial resolution	±0.5 %	Normal	1	±0.5 %	
Linearity error	±0.2 dB	Rectangle	1	±2.7 %	
Calibration error	±3.3 %	Normal	1	±3.3 %	
<b>SAR Evaluation Uncertainty</b>					
Data acquisition error	±1 %	Rectangle	1	±0.6 %	
ELF and RF disturbances	±0.25 %	Normal	1	±0.25 %	
Conductivity assessment	±5 %	Rectangle	1	±5.8 %	
<b>Spatial Peak SAR Evaluation Uncertainty</b>					
Extrapolated boundary effect	±3 %	Normal	1	±3 %	±5 %
Probe positioning error	±0.1 mm	Normal	1	±1 %	
Integrated and cube orientation	±3 %	Normal	1	±3 %	
Cube Shape inaccuracies	±2 %	Rectangle	1	±1.2 %	
Device positioning	±6 %	Normal	1	±6 %	
<b>Combined Uncertainties</b>				±11.7 %	±5 %

Measurement uncertainties in SAR measurements are difficult to quantify due to several variables including biological, physiological, and environmental. However, the estimated measurement uncertainties in SAR are less than 15-25 %.

According to ANSI/IEEE C95.3, the overall uncertainties are difficult to assess and will vary with the type of meter and usage situation. However, accuracy's of ± 1 to 3 dB can be expected in practice, with greater uncertainties in near-field situations and at higher frequencies (shorter wavelengths), or areas where large reflecting objects are present. Under optimum measurement conditions, SAR measurement uncertainties of at least ± 2dB can be expected.

According to CENELEC, typical worst-case uncertainty of field measurements is ± 5 dB. For well-defined modulation characteristics the uncertainty can be reduced to ± 3 dB.



#### **14.0 REFERENCES**

- (1) ANSI, *ANSI/IEEE C95.1: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 Ghz*, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992;
- (2) Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, FCC, Washington, D.C. 20554, 1997;
- (3) Thomas Schmid, Oliver Egger, and Neils Kuster, “Automated E-field scanning system for dosimetric assessments”, *IEEE Transaction on Microwave Theory and Techniques*, Vol. 44, pp. 105 – 113, January, 1996.
- (4) Niels Kuster, Ralph Kastle, and Thomas Schmid, “Dosimetric evaluation of mobile communications equipment with know precision”, *IEICE Transactions of Communications*, vol. E80-B, no. 5, pp. 645 – 652, May 1997.

***APPENDIX A - SAR MEASUREMENT DATA***

## Vertex Standard Co., Ltd. FCC ID: K66VX-160V


Generic Twin Phantom; Flat Section; Position: (90°,90°);  
Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0;  
150MHz Brain :  $s = 0.48$  mho/m  $\epsilon_r = 59.9$   $r = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 0.237 mW/g, SAR (10g): 0.193 mW/g

Face SAR at 4.0cm Separation  
Vertex Standard Co. Ltd.  
Model: VX-180V With Antenna ATV-6A  
Unmodulated Carrier  
Low Channel [146MHz]  
Conducted Power: 4.7 Watts  
Date Tested: Feb. 16, 2001



# Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (90°,90°)

Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0

150MHz Brain :  $s = 0.48$  mho/m  $\epsilon_r = 59.9$   $r = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 0.416 mW/g, SAR (10g): 0.337 mW/g

Face SAR at 4.0cm Separation

Vertex Standard Co. Ltd.


Model: VX-180V With Antenna ATV-6XL

Unmodulated Carrier

Low Channel [146MHz]

Conducted Power: 4.7 Watts

Date Tested: Feb. 16, 2001




# Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (90°,90°);  
Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0;  
150MHz Brain :  $s = 0.48$  mho/m  $\epsilon_r = 59.9$   $r = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7

SAR (1g): 0.359 mW/g, SAR (10g): 0.291 mW/g

Face SAR at 4.0cm Separation  
Vertex Standard Co. Ltd.  
Model: VX-180V With Antenna ATV-6B  
Unmodulated Carrier  
Mid Channel [160MHz]  
Conducted Power: 4.3 Watts  
Date Tested: Feb. 16, 2001



# Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (90°,90°)

Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0

150MHz Brain :  $s = 0.48$  mho/m  $\epsilon_r = 59.9$   $r = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 0.443 mW/g, SAR (10g): 0.359 mW/g

Face SAR at 4.0cm Separation

Vertex Standard Co. Ltd.


Model: VX-180V With Antenna ATV-6XL

Unmodulated Carrier

Mid Channel [160MHz]

Conducted Power: 4.3 Watts

Date Tested: Feb. 16, 2001



## Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (90°,90°);  
Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0;  
150MHz Brain :  $s = 0.48$  mho/m  $\epsilon_r = 59.9$   $r = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 0.0705 mW/g, SAR (10g): 0.0577 mW/g

Face SAR at 4.0cm Separation

Vertex Standard Co. Ltd.


Model: VX-180V With Antenna ATV-6C

Unmodulated Carrier

High Channel [174MHz]

Conducted Power: 4.3 Watts

Date Tested: Feb. 16, 2001





# Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (90°,90°)

Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0

150MHz Brain :  $s = 0.48$  mho/m  $\epsilon_r = 59.9$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 0.117 mW/g, SAR (10g): 0.0962 mW/g

Face SAR at 4.0cm Separation

Vertex Standard Co. Ltd.


Model: VX-180V With Antenna ATV-6XL

Unmodulated Carrier

High Channel [174MHz]

Conducted Power: 4.3 Watts

Date Tested: Feb. 16, 2001




# Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0;  
150MHz Muscle:  $\sigma = 0.75$  mho/m  $\epsilon_r = 65.7$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7

SAR (1g): 0.438 mW/g, SAR (10g): 0.287 mW/g

Body SAR at 1.0cm Separation  
Vertex Standard Co. Ltd.  
Model: VX-180V With Antenna ATV 6A  
Unmodulated Carrier  
Low Channel [146MHz]  
Conducted Power: 4.7 Watts  
Date Tested: Feb.16, 2001



## Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (270°,270°)

Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0

150MHz Muscle:  $\sigma = 0.75$  mho/m  $\epsilon_r = 65.7$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7

SAR (1g): 0.681 mW/g, SAR (10g): 0.450 mW/g

Body SAR With Belt Clip at 1.0cm Separation

Vertex Standard Co. Ltd.


Model: VX-180V With Antenna ATV-6XL

Unmodulated Carrier

Low Channel [146MHz]

Conducted Power: 4.7 Watts

Date Tested: Feb. 16, 2001



# Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0;  
150MHz Muscle:  $\sigma = 0.75$  mho/m  $\epsilon_r = 65.7$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7

SAR (1g): 0.416 mW/g, SAR (10g): 0.278 mW/g

Body SAR With Belt Clip at 1.0cm Separation

Vertex Standard Co. LTD


Model: VX-180V With Antenna ATV-6B

Unmodulated Carrier

Mid Channel [160MHz]

Conducted Power: 4.3 Watts


Date Tested: Feb.16, 2001



# Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0  
150MHz Muscle:  $s = 0.75$  mho/m  $\epsilon_r = 65.7$   $r = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7  
SAR (1g): 0.358 mW/g, SAR (10g): 0.243 mW/g

Body SAR With Belt Clip at 1.0cm Separation  
Vertex Standard Co. Ltd.  
Model: VX-180V With Antenna ATV-6XL  
Unmodulated Carrier  
Mid Channel [160MHz]  
Conducted Power: 4.3 Watts  
Date Tested: Feb. 16, 2001



## Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (270°,270°);  
Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0;  
150MHz Muscle:  $s = 0.75$  mho/m  $\epsilon_r = 65.7$   $r = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7

SAR (1g): 0.190 mW/g, SAR (10g): 0.128 mW/g

Body SAR With Belt Clip at 1.0cm Separation

Vertex Standard Co. Ltd.


Model: VX-180V With Antenna ATV-6C

Unmodulated Carrier

High Channel [174MHz]

Conducted Power: 4.3 Watts

Date Tested: Feb.16, 2001



# Vertex Standard Co., Ltd. FCC ID: K66VX-160V

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(7.04,7.04,7.04); Crest factor: 1.0  
150MHz Muscle:  $s = 0.75$  mho/m  $\epsilon_r = 65.7$   $r = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7

SAR (1g): 0.577 mW/g, SAR (10g): 0.397 mW/g

Body SAR With Belt Clip at 1.0cm Separation

Vertex Standard Co. Ltd.

Model: VX-180V With Antenna ATV-6XL

Unmodulated Carrier

High Channel [174MHz]

Conducted Power: 4.3 Watts

Date Tested: Feb. 16, 2001

