

LIST OF GENERAL INFORMATION REQUIRED FOR TYPE ACCEPTANCE

IN ACCORDANCE WITH FCC RULES AND REGULATIONS,  
VOLUME II, PART 2 AND TO

90

Sub-part

2.983(a): NAME AND ADDRESS OF APPLICANT:

Yaesu Musen Co., Ltd.  
20-2, Shimomaruko 1-chome, Ota-ku  
Tokyo Japan 146

VENDOR:

Yaesu U.S.A.  
17210 Edwards Rd.  
Cerritos, CA 90703

2.983(b): FCC ID: K66VX-3000U-3

MODEL NO: VX-3000U-3

2.983(c): QUANTITY PRODUCTION PLANNED.

2.983(d): TECHNICAL DESCRIPTION: SEE ATTACHED EXHIBITS

(1): TYPE OF EMISSION: 16KOF3E, 11KOF3E

(2): FREQUENCY RANGE, MHz: 400 to 460

(3): POWER RATING, Watts: 5, 40  
SWITCHABLE  ADJUSTABLE  N/A

(4): MAXIMUM POWER RATING, Watts: 300

2.983(d)

(5): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE, INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual  
COLLECTOR VOLTAGE, Vdc = per manual  
SUPPLY VOLTAGE, Vdc = 13.8

(6): FUNCTION OF ACTIVE CIRCUIT DEVICES:

PLEASE SEE ATTACHED EXHIBITS

(7): CIRCUIT DIAGRAM:

PLEASE SEE ATTACHED EXHIBITS

(8): MANUAL:

PLEASE SEE ATTACHED EXHIBITS

(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(10): DESCRIPTION OF CIRCUITRY & DEVICES PROVIDED FOR DETERMINING AND STABILIZING FREQUENCY:

PLEASE SEE ATTACHED EXHIBITS

(11): DESCRIPTION OF CIRCUITS OR DEVICES EMPLOYED FOR

- (a) SUPPRESSION OF SPURIOUS RADIATION,
- (b) LIMITING MODULATION,
- (c) LIMITING POWER:

PLEASE SEE ATTACHED EXHIBITS

(12): DIGITAL MODULATION DESCRIPTION:

ATTACHED EXHIBITS  
N/A

x

2.983(e): TEST AND MEASUREMENT DATA:

FOLLOWS

2.983(f): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

2.983(g): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

Sub-part  
2.983(e):

TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.981, 2.983, 2.985, 2.987, 2.989, 2.991, 2.993, 2.995, 2.997, 2.999 and the following individual Parts:

- \_\_\_ 21 - Domestic Public Fixed Radio Services
- x \_\_\_ 22 - Public Mobile Services
- \_\_\_ 22 Subpart H - Cellular Radiotelephone Service
- \_\_\_ 22.901(d) - Alternative technologies and auxiliary services
- \_\_\_ 23 - International Fixed Public Radiocommunication services
- \_\_\_ 24 - Personal Communications Services
- x \_\_\_ 74 Subpart H - Low Power Auxiliary Stations
- \_\_\_ 80 - Stations in the Maritime Services
- \_\_\_ 80 Subpart E - General Technical Standards
- \_\_\_ 80 Subpart F - Equipment Authorization for Compulsory Ships
- \_\_\_ 80 Subpart K - Private Coast Stations and Marine Utility  
Stations
- \_\_\_ 80 Subpart S - Compulsory Radiotelephone Installations for  
Small Passenger Boats
- \_\_\_ 80 Subpart T - Radiotelephone Installation Required for  
Vessels on the Great Lakes
- \_\_\_ 80 Subpart U - Radiotelephone Installations Required by the  
Bridge-to-Bridge Act
- \_\_\_ 80 Subpart V - Emergency Position Indicating Radiobeacons  
(EPIRB'S)
- \_\_\_ 80 Subpart W - Global Maritime Distress and Safety System  
(GMDSS)
- \_\_\_ 80 Subpart X - Voluntary Radio Installations
- \_\_\_ 87 - Aviation Services
- x \_\_\_ 90 - Private Land Mobile Radio Services
- \_\_\_ 94 - Private Operational-Fixed Microwave Service
- \_\_\_ 95 Subpart A - General Mobile Radio Service (GMRS)
- \_\_\_ 95 Subpart C - Radio Control (R/C) Radio Service
- \_\_\_ 95 Subpart D - Citizens Band (CB) Radio Service
- \_\_\_ 95 Subpart E - Family Radio Service
- \_\_\_ 95 Subpart F - Interactive Video and Data Service (IVDS)
- \_\_\_ 101 - Fixed Microwave Services

STANDARD TEST CONDITIONS  
and  
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

ROOM TEMPERATURE	= 25±5°C
ROOM HUMIDITY	= 20-50%
D.C. SUPPLY VOLTAGE, Vdc	= 13.8
A.C. SUPPLY VOLTAGE, Vac	= N/A
A.C. SUPPLY FREQUENCY, Hz	= N/A

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 6. K66VX-3000U-3

NAME OF TEST: Carrier Output Power (Conducted)

SPECIFICATION: FCC: 47 CFR 2.985(a)  
IC: RSS-119, Section 6.2

GUIDE: TIA/EIA-603, Paragraph 2.2.1

TEST CONDITIONS: Standard Temperature and Humidity (S. T. & H.)

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is  $\pm 3\%$ .

MEASUREMENT RESULTS


<u>NOMINAL, MHz</u>	<u>R.F. POWER OUTPUT, WATTS</u>	
430.025	5	40
400.025	5	40
459.975	5	40

SUPERVISED BY:

  
MORTON FLOM, P. Eng.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT  
TEST 2: FREQUENCY STABILITY



(1) COAXIAL ATTENUATOR

NARDA 766-10	---
SIERRA 661A-30	<u>x</u>
BIRD 8329 (30 dB)	---
_____	---

(2) POWER METERS

HP 435A	---
HP 436A	<u>x</u>
HP 8901A POWER MODE	<u>x</u>
_____	---


(3) FREQUENCY COUNTER

HP 5383A	---
HP 5334B	<u>x</u>
HP 8901A FREQUENCY MODE	<u>x</u>
_____	---



TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)  
 TEST B. OUT-OF-BAND SPURIOUS



- |   |  |
|---|--|
| <p>(1) <u>AUDIO OSCILLATOR/GENERATOR</u><br/>                 HP 204D<br/>                 HP 8903A<br/>                 HP 3312A</p>                     | <p>_____<br/>                 _____<br/> <u>  x  </u><br/> <u>  x  </u></p>  |
| <p>(2) <u>COAXIAL ATTENUATOR</u><br/>                 NARDA 766-10<br/>                 SIERRA 661A-30<br/>                 BIRD 8329 (30 dB)</p>         | <p>_____<br/>                 _____<br/> <u>  x  </u><br/> <u>  x  </u></p>  |
| <p>(3) <u>FILTERS; NOTCH, HP, LP, BP</u><br/>                 CIRQTEL FHT<br/>                 EAGLE TNF-1<br/>                 PHELPS DODGE PD-495-8</p> | <p>_____<br/>                 _____<br/> <u>  x  </u><br/>                 _____</p>                                     |
| <p>(4) <u>SPECTRUM ANALYZER</u><br/>                 HP 8566B<br/>                 HP 8563E</p>   | <p>_____ <u>  x  </u><br/>                 _____<br/>                 _____</p>  |
| <p>(5) <u>SCOPE</u><br/>                 HP 1741A<br/>                 HP 181T<br/>                 TEK 935<br/>                 HP 54502A</p>            | <p>_____<br/>                 _____<br/>                 _____<br/>                 _____<br/>                 _____</p> |



PAGE NO.  
G83N004

10.1.

K66VX-3000U-3

TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED)  
POWER: LOW

---

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	LEVEL, $\mu$ W
430.025	859.750	-32.3	-69.2	1
430.025	1290.330	-31.6	-68.5	1
430.025	1720.553	-31.6	-68.5	1
430.025	2150.478	-31.9	-68.8	1
430.025	2580.117	-31.3	-68.2	1
430.025	3010.447	-32.9	-69.8	1
430.025	3440.062	-32.9	-69.8	1
430.025	3870.588	-33.4	-70.3	0
430.025	4300.198	-34.1	-71.0	0
430.025	4729.793	-33.4	-70.3	0
430.025	5160.785	-33.3	-70.2	0
430.025	5590.387	-34.1	-71.0	0
430.025	6019.887	-33.3	-70.2	0
430.025	6450.603	-33.4	-70.3	0

PAGE NO.

10.2.

K66VX-3000U-3

G83N001

TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED)

POWER: HIGH

---

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	LEVEL, $\mu$ W
430.025	860.068	-28.5	-74.5	1
430.025	1289.678	-28.9	-74.9	1
430.025	1719.718	-30.0	-76.0	1
430.025	2150.598	-29.4	-75.4	1
430.025	2579.823	-29.5	-75.5	1
430.025	3010.233	-29.0	-75.0	1
430.025	3440.328	-30.5	-76.5	1
430.025	3870.202	-30.2	-76.2	1
430.025	4299.827	-31.0	-77.0	1
430.025	4729.923	-30.2	-76.2	1
430.025	5160.468	-30.9	-76.9	1
430.025	5590.412	-30.9	-76.9	1
430.025	6019.985	-29.9	-75.9	1
430.025	6450.218	-30.2	-76.2	1

PAGE NO.

11.1.

K66VX-3000U-3

NAME OF TEST:

Field Strength of Spurious Radiation

SPECIFICATION:

FCC: 47 CFR 2.993(a)

IC: N/A

GUIDE:

TIA/EIA-603, Section 2.2.12

TEST CONDITIONS:

S. T. & H.

TEST EQUIPMENT:

AS PER ATTACHED PAGE

MEASUREMENT PROCEDURE

1. A description of the measurement facilities was filed with the FCC and was found to be in compliance with the requirements of Section 15.38, by letter from the FCC dated March 3, 1997, FILE 31040/SIT. All pertinent changes will be reported to the Commission by up-date prior to March 2000.
2. At first, in order to locate all spurious frequencies and approximate amplitudes, and to determine proper equipment functioning, the test sample was set up at a distance of three meters from the test instrument. Valid spurious signals were determined by switching the power on and off.
3. In the field, the test sample was placed on a wooden turntable above ground at three (or thirty) meters away from the search antenna. The test sample was connected to an R.F. Wattmeter and a 50 ohm dummy load, and adjusted to its rated output.  
  
In order to obtain the maximum response at each spurious frequency, the turntable was rotated. Also, the Search Antennas were raised and lowered vertically, and all cables were oriented. Excess power lead was coiled near the power supply.
4. A signal generator, connected with a non-radiating cable to a vertically polarized half-wave antenna (for each frequency involved) was substituted for the transmitter. The Search Antenna was raised and lowered to obtain maximum indicated.
5. The signal generator output was adjusted until a signal level indication equal to that from the transmitter was obtained.
6. Steps 4 and 5 were repeated, using a horizontally polarized half-wave antenna. The higher of the two observations was noted.

PAGE NO.

11.2.

K66VX-3000U-3

NAME OF TEST:

Field Strength of Spurious Radiation,

SPECIFICATION:

FCC: 47 CFR 2.993(a)

IC: N/A

MEASUREMENT PROCEDURE (CONT.)

7. Power into the half-wave antenna was calculated from the characteristic impedance of the line, and the voltage output from the signal generator.

8. The level of each spurious radiation with reference to the transmitter power in dB, was calculated from:

$$\text{SPURIOUS LEVEL, dB} = 10 \text{ LOG} \left( \frac{\text{Calculated Spurious Power}}{\text{Tx Power (Wattmeter)}} \right) \quad \text{[from para. 7].}$$


9. The worst case for all channels is shown.

10. Measurement summary:

FREQUENCY OF CARRIER, MHz	= 430.025, 400.025, 459.975
SPECTRUM SEARCHED, GHz	= 0 to 10 x F <sub>C</sub>
ALL OTHER EMISSIONS	= ≥ 20 dB BELOW LIMIT
LIMIT, dBc	= -59 (40 Watts) -50 (5 Watts)

11. Measurement results:

ATTACHED FOR WORST CASE

RADIATED TEST SETUP

## NOTES:

- (a) Search Antenna - Rotatable on boom.
- (b) Non-metallic boom.
- (c) Non-metallic mast.
- (d) Adjustable horizontally.
- (e) Equipment Under Test.
- (f) Turntable.
- (g) Boom adjustable in height.
- (h) External control cables routed horizontally at least one wavelength.
- (i) Rotatable.
- (j) Cables routed through hollow turntable center.
- (k) 30 cm or less.
- (l) External power source.
- (m) 10 cm diameter coil of excess cable.
- (n) 25 cm (V), 1 m-7 m (V, H).
- (o) 25 cm from bottom end of 'V', 1 m normally.
- (p) Calibrated Cable at least 10 m in length.
- (q) Amplifier (optional).
- (r) Spectrum Analyzer.

TRANSMITTER SPURIOUS EMISSIONS (RADIATED FIELD STRENGTH)

ALL OTHER EMISSIONS =  $\geq$  20 dB BELOW LIMIT

EMISSION, MHz/HARMONIC	SPURIOUS LEVEL BELOW	
	Lo	Hi
2nd to 10th	<-65	<-70

SUPERVISED BY:

*M. F. Flom*  
MORTON FLOM, P. Eng.


PAGE NO. 14. K66VX-3000U-3  
NAME OF TEST: Emission Masks (Occupied Bandwidth) /  
SPECIFICATION: FCC: 47 CFR 2.989(c)(1)  
IC: RSS-119, Section 6.4  
GUIDE: TIA/EIA-603, Paragraph 2.2.11  
TEST CONDITIONS: S. T. & H.  
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for  $\pm 2.5$  kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE 15.1  
SPECTRUM ANALYZER PRESENTATION  
YAESU, VX-3000U-3  
1998-MAR-23, 16:28, MON


POWER: LOW  
MODULATION: NONE





PAGE 15.2.  
SPECTRUM ANALYZER PRESENTATION  
YAESU, VX-3000U-3  
1998-MAR-23, 16:33, MON


POWER: LOW  
MODULATION: VOICE: 2500 Hz SINE WAVE  
MASK: D, VHF/UHF 12.5kHz BW






PAGE 15.4.  
SPECTRUM ANALYZER PRESENTATION  
YAESU, VX-3000U-3  
1998-MAR-23, 16:31, MON

POWER: HIGH  
MODULATION: VOICE: 2500 Hz SINE WAVE  
MASK: D, VHF/UHF 12.5kHz BW



POWER: LOW  
MODULATION: NONE




SPECTRUM ANALYZER PRESENTATION

YAESU, VX-3000U-3


1998-MAR-23, 16:21, MON

POWER: LOW  
MODULATION: VOICE: 2500 Hz SINE WAVE  
MASK: B, VHF/UHF 25kHz, w/LPF



PAGE 15.7.  
SPECTRUM ANALYZER PRESENTATION  
YAESU, VX-3000U-3  
1998-MAR-23, 16:14, MON

POWER: HIGH  
MODULATION: NONE




SPECTRUM ANALYZER PRESENTATION

YAESU, VX-3000U-3

1998-MAR-23, 16:20, MON

POWER: HIGH  
MODULATION: VOICE: 2500 Hz SINE WAVE  
MASK: B, VHF/UHF 25kHz, w/LPF



PAGE NO.

16.

K66VX-3000U-3

NAME OF TEST:

Transient Frequency Behavior

SPECIFICATION:

FCC: 47 CFR 90.214  
IC: RSS-119, Section 6.5

GUIDE:

TIA/EIA-603, Paragraph 2.2.19

TEST CONDITIONS:

S. T. & H.

TEST EQUIPMENT:

As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.

2. The transmitter was turned on.

3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.

4. The transmitter was turned off.

5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.

6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a *guide*, and to either 10 ms/div (UHF) or 5 ms/div (VHF).

7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.

8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:


<u>step f</u> , dBm	= -13.0
<u>step h</u> , dBm	= -34.2
<u>step l</u> , dBm	= 15.3

SUPERVISED BY:

  
MORTON FLOM, P. Eng.




TRANSIENT FREQUENCY BEHAVIOR



- (1) ATTENUATOR  
 (NOTE: Removed after 1st step)  
 30 dB   x
- (2) ATTENUATOR  
 30 dB         
 20 dB   x    
 10 dB         
 KAY VARIABLE
- (3) COMBINER  
 4 x 25 Ω COMBINER   x
- (4) CRYSTAL DETECTOR  
 HP 8470B   x
- (5) RF SIGNAL GENERATOR  
 HP 8656A         
 HP 8920A   x
- (6) MODULATION ANALYZER  
 HP 8901A   x
- (7) SCOPE  
 HP 54502A   x

PAGE 18.1.  
 OSCILLOSCOPE PRESENTATION  
 YAESU, VX-3000U-3  
 1998-MAR-24, 09:46, TUE

MODULATION: Ref Gen=12.5 kHz Deviation  
 REMARK: CARRIER ON TIME




ALL RIGHTS RESERVED  
 YAESU ASSOCIATES, INC.  
 1998-MAR-24 09:46:14



PAGE 18.3.  
 OSCILLOSCOPE PRESENTATION  
 YAESU, VX-3000U-3  
 1998-MAR-24, 09:49, TUE

MODULATION: Ref Gen=25 kHz Deviation  
 REMARK: CARRIER ON TIME




PAGE 18.4.

OSCILLOSCOPE PRESENTATION

YAESU, VX-3000U-3

1998-MAR-24, 09:44, TUE

MODULATION: Ref Gen=25 kHz Deviation  
REMARK: CARRIER OFF TIME



ALL RIGHTS RESERVED. © 1998 BY K. T. ASSOCIATES, INC.

PAGE NO.

19.

K66VX-3000U-3

NAME OF TEST:

Audio Low Pass Filter (Voice Input) :

SPECIFICATION:

FCC: 47 CFR 2.987(a)  
IC: RSS-119, Section 6.6

GUIDE:

TIA/EIA-603, Paragraph 2.2.15

TEST CONDITIONS:

S. T. & H.

TEST EQUIPMENT:


As per attached page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

- TEST A. MODULATION CAPABILITY/DISTORTION
- TEST B. AUDIO FREQUENCY RESPONSE
- TEST C. HUM AND NOISE LEVEL
- TEST D. RESPONSE OF LOW PASS FILTER
- TEST E. MODULATION LIMITING



(1) AUDIO OSCILLATOR/GENERATOR

HP 204D	_____
HP 8903A	_____
HP 3312A	<u>  x  </u>
_____	<u>  x  </u>

(2) COAXIAL ATTENUATOR

NARDA 766-10	_____
SIERRA 661A-30	<u>  x  </u>
BIRD 8329 (30 dB)	_____
_____	_____

(3) MODULATION ANALYZER

HP 8901A	<u>  x  </u>
_____	_____


(4) AUDIO ANALYZER

HP 8903A	<u>  x  </u>
_____	_____

(5) SCOPE

HP 1741A	_____
HP 181T	_____
TEK 935	_____
_____	_____

FREQUENCY RESPONSE OF AUDIO LOW PASS FILTER  
YAESU, VX-3000U-3  
23 MAR 1998, 15:25



PEAK AUDIO FREQUENCY, Hz: 2820

*Morton P. Eng*

SUPERVISED BY:

MORTON FLOM, P. Eng.



PAGE NO.

22.

K66VX-3000U-3

NAME OF TEST:

Audio Frequency Response

SPECIFICATION:

FCC: 47 CFR 2.987(a)  
IC: N/A

GUIDE:

TIA/EIA-603, Section 2.2.6

TEST CONDITIONS:

S. T. & H.


TEST EQUIPMENT:

As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER AUDIO FREQUENCY RESPONSE  
 YAESU, VX-3000U-3  
 23 MAR 1998, 15:22



COPYRIGHT (C) 1996 BY M. FLOM ASSOCIATES, INC. ALL RIGHTS RESERVED.

PEAK AUDIO FREQUENCY, Hz: 2820

TABLE VALUES:

FREQUENCY, Hz	LEVEL, dB	FREQUENCY, Hz	LEVEL, dB	FREQUENCY, Hz	LEVEL, dB
---------------	-----------	---------------	-----------	---------------	-----------

300	-12.9	30000	-17.6		
20000	-17.7	50000	-17.6		

*Morton P. Eng*

SUPERVISED BY:

MORTON FLOM, P. Eng.

PAGE NO.

24.

K66VX-3000U-3

NAME OF TEST:

Modulation Limiting

SPECIFICATION:

IC: RSS-119, Section 6.6  
FCC: 47 CFR 2.987(b)

GUIDE:

TIA/EIA-603, Paragraph 2.2.3

TEST CONDITIONS:


S. T. & H.

TEST EQUIPMENT:

As per attached page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation ( $\pm 1.5$  kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.
5. MEASUREMENT RESULTS: ATTACHED




REFERENCE DEVIATION, kHz = 1.25  
 REFERENCE MODULATION, Hz = 1000  
 PEAKS = POSITIVE  
 AUDIO AMPLITUDE, mV = 9.1

*Morton Flom P. Eng.*

SUPERVISED BY:

MORTON FLOM, P. Eng.




REFERENCE DEVIATION, kHz = 1.25  
 REFERENCE MODULATION, Hz = 1000  
 PEAKS = NEGATIVE  
 AUDIO AMPLITUDE, mV = 9.1

*Morton Flom P. Eng.*

SUPERVISED BY:

MORTON FLOM, P. Eng.

MODULATION LIMITING  
YAESU, VX-3000U-3  
1998-MAR-23, 15:29




COPYRIGHT © 1998 BY W. FLOM ASSOCIATES, INC. ALL RIGHTS RESERVED.

REFERENCE DEVIATION, kHz = 2.5  
REFERENCE MODULATION, Hz = 1000  
PEAKS = POSITIVE  
AUDIO AMPLITUDE, mV = 9.64

*M. F. Eng.*

SUPERVISED BY:

MORTON FLOM, P. Eng.



REFERENCE DEVIATION, kHz = 2.5  
 REFERENCE MODULATION, Hz = 1000  
 PEAKS = NEGATIVE  
 AUDIO AMPLITUDE, mV = 9.64

*Morton Flom P. Eng.*

SUPERVISED BY:

MORTON FLOM, P. Eng.

PAGE NO. 26. K66VX-3000U-3  
NAME OF TEST: Frequency Stability (Temperature Variation)  
SPECIFICATION: FCC: 47 CFR 2.995(a)(1)  
IC: RSS-119, Section 7.0  
GUIDE: TIA/EIA-602, Section 2.2.2  
TEST CONDITIONS: As indicated  
TEST EQUIPMENT: As per attached page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to  $-30^{\circ}\text{C}$  and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED



TRANSMITTER TEST SET-UP

- TEST A. OPERATIONAL STABILITY
- TEST B. CARRIER FREQUENCY STABILITY
- TEST C. OPERATIONAL PERFORMANCE STABILITY
- TEST D. HUMIDITY
- TEST E. VIBRATION
- TEST F. ENVIRONMENTAL TEMPERATURE
- TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
- TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION



(1) TEMPERATURE, HUMIDITY, VIBRATION

TENNEY TEMPERATURE CHAMBER	<u>  x  </u>
WEBER HUMIDITY CHAMBER	<u>      </u>
L.A.B. RVH 18-100	<u>      </u>

(2) COAXIAL ATTENUATOR

NARDA 766-10	<u>      </u>
SIERRA 661A-30	<u>  x  </u>
BIRD 8329 (30 dB)	<u>  x  </u>

(3) R.F. POWER

HP 435A POWER METER	<u>      </u>
HP 436A POWER METER	<u>  x  </u>
HP 8901A POWER MODE	<u>  x  </u>

(4) FREQUENCY COUNTER

HP 5383A	<u>      </u>
HP 5334B	<u>  x  </u>
HP 8901A	<u>  x  </u>

PAGE 28.

Model Name : VX-3000U  
 FCC ID : K66VX-3000U-3  
 Serial Number : 8E004003

Emission Type : 16K0F3E  
 Channel Spacing : 25 [kHz]  
 Band Type : A


Carrier Power Output Rating (PARAGRAPH 2.2.1)

Carrier Frequency [MHz]	RF Power	
	HIGH [W]	LOW [W]
400.025	40.50	5.40
430.025	40.60	5.00
459.975	40.40	5.00

Carrier Frequency Stability - Voltage Variation (PARAGRAPH 2.2.2)

STV [%]	Voltage [V]	Change in Frequency		
		[MHz]	[Hz]	[ppm]
100.00	13.80	430.0247	-300.0	-0.7
85.00	11.73	430.0247	-300.0	-0.7
115.00	15.87	430.02472	-280.0	-0.65

Carrier Frequency Stability - Temperature Variation (PARAGRAPH 2.2.2)



PAGE NO.

29.

K66VX-3000U-3

NAME OF TEST:

Frequency Stability (Voltage Variation)

SPECIFICATION:

FCC: 47 CFR 2.995 (b)(1)  
IC: RSS-119, Section 7.0

GUIDE:

TIA/EIA-602, Section 2.2.2

TEST CONDITIONS:

As indicated

TEST EQUIPMENT:

As per attached page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at  $25 \pm 5^\circ\text{C}$  and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

MEASUREMENT RESULTS

LIMIT, ppm  
LIMIT, Hz

= 5  
= 2150

<u>STV, %</u>	<u>Vdc</u>	<u>CHANGE IN FREQUENCY, Hz</u>	
85	11.7	430025000	0
100	13.8	430025000	0
115	15.9	430024990	-10
BATTERY END POINT:	11.0	430025000	0

SUPERVISED BY:

  
MORTON FLOM, P. Eng.

PAGE NO.

30.

K66VX-3000U-3

NAME OF TEST:

Necessary Bandwidth and Emission Bandwidth

PARAGRAPH:

47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz = 3  
MAXIMUM DEVIATION (D), kHz = 5  
CONSTANT FACTOR (K) = 1  
NECESSARY BANDWIDTH ( $B_N$ ), kHz =  $(2 \times M) + (2 \times D \times K)$   
= 16.0

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz = 3  
MAXIMUM DEVIATION (D), kHz = 2.5  
CONSTANT FACTOR (K) = 1  
NECESSARY BANDWIDTH ( $B_N$ ), kHz =  $(2 \times M) + (2 \times D \times K)$   
= 16.0

SUPERVISED BY:

  
MORTON FLOM, P. Eng.

TESTIMONIAL  
AND  
STATEMENT OF CERTIFICATION

K66VX-3000U-3

THIS IS TO CERTIFY:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:

  
MORTON FLOM, P. Eng.

## STATEMENT OF QUALIFICATIONS

### EDUCATION:

1. B. ENG. in ENGINEERING PHYSICS, 1949, McGill University, Montreal, Canada.
2. Post Graduate Studies, McGill University & Sir George Williams University, Montreal.

### PROFESSIONAL AFFILIATIONS:

1. ARIZONA SOCIETY OF PROFESSIONAL ENGINEERS (NSPE), #026 031 821.
2. ORDER OF ENGINEERS (QUEBEC) 1949. #4534.
3. ASSOCIATION OF PROFESSIONAL ENGINEERS, GEOPHYSICISTS & GEOLOGISTS OF ALBERTA #5916.
4. REGISTERED ENGINEERING CONSULTANT - GOVERNMENT OF CANADA, DEPARTMENT OF COMMUNICATIONS. Radio Equipment Approvals.
5. IEEE, Lifetime Member No. 0417204 (member since 1947).

### EXPERIENCE:

1. Research/Development/Senior Project Engineer, R.C.A. LIMITED (4 years).
2. Owner/Chief Engineer of Electronics. Design/Manufacturing & Cable TV Companies (10 years).
3. CONSULTING ENGINEER (over 25 years).

  
MORTON FLOM, P. Eng.

## TEST INSTRUMENTATION LIST

All equipment calibrated within last 90 days

### ADAPTER

HP X281 (Coaxial waveguide); HP S281; HP 85659 (Quasi peak)

### AMPLIFIER

Pre-amp. HP 10885A (2-1300 MHz); HP 8447D, HP 8447E, HP 8449A

### ANTENNA See end

### ATTENUATOR

kay 432D; Power, Sierra 661A-30; Narda 76610; Narda 4779-3, -6, -10 dB

### AUDIO OSCILLATOR

HP 204D; AIEC DTC-1; Motorola S-1333B; HP 3312A; HP 8903A

### BATTERY

Sears Diehard, Stock #4341

### CAMERA

Oscilloscope, Tektronix CSA; Polaroid Impulse AF; Kodak DC-50

### CAPACITOR

Feed-Thru, 10 uF, Solar 6512-106R; Solar 7525-1

### CLOSE FIELD PROBE

HP 11940A, 11941A, HP 11945A

### COMPUTER

HP 332; HP Vectra 486/25VL; Various PC Compatibles

### CONVERTOR, Down

HP 117 10B

### COUPLER

Narda 1080, Waveguide; HP 5750E (Cross guide); waveline 274/40; Solar 7415-3; Solar 7835-891 & -896

### CURRENT PROBE

Solar 6741-1

### DETECTOR

HP 8470B

### DIGITAL MULTIMETER

HP 3476A w/H.F. Probe; Fluke 8030A-01; HP 3478A

### DISTORTION ANALYZER

HP 334A; HP 8903A

### ELECTRONIC COUNTER

HP 5383A; HP 5334B

### FILTER

Cirqtel FHT/7-50-57/50-1A/1B (HP); Jerrold TLB-1; THB-1, Piezo 5064; Eagle TNF-I Series, Krohn-Hite 3202; Phelps-Dodge #PD-495-8; Newton #PD6000 Line Protector; 370-890 MHz (Lab Design); 900 MHz (Lab Design); Solar High-Pass w/n 882029

### FREQ. DEV. METER

HP 8901A

### FREQ. DOUBLER

HP 11721A

### FREQUENCY METER

HP 537A; HP 536A

### GENERATOR

Solar 6550-1 (power sweep); HP 8540B, GAW 1012, HP 8556A (signal); Solar P282-1 (spike)

### HUMIDITY CHAMBER

Ember Co FW30; Bowser 0

### LIMITER, R.F.

HP 11867A; HP 11693A; HP 10509A

### LISN

Singer 91221-1; Ailtech 94641-1 (50uH)

### LOAD, POWER

Telewave TLW-25; Bird 8329

### MILLIAMETER

HP 428B

### MIXER

HP 10514A; Mini-Circuits TAK-1H

### OPEN FIELD SITE

As filed with FCC & IC and kept up-dated.

### TURNABLES:

Up to 2000# capacity

### GROUND SCREEN:

Complies with docket 80-284

### ANTENNA MAST:

Complies as above

### OSCILLOSCOPE

HP 1741A; HP 181T; Tektronix T935; HP 54502A

### PHANTOM

M.F.A. Labs Left and Right human head

### PLOTTER

HP 7470; HP7475A

### POWER METER

AF GR 1840A; HP 435A with 8481A & 8482H Power Sensors; HP 436A; HP 8901A

### POWER SUPPLY

HP 6286A; Heathkit 1P 2711; 1P 5220; Honda EM400 (portable gas gen.); HP 6012

### PRINTER

Brother HL-8; Brother HL-10V; HP DeskJet 640C

### R. F. PRESELECTOR

HP 85685A

### RADIATION METER

Narda 8717 w/8010 Amp, 8021B and 8760 probes

### RESISTOR, PRECISION

Solar 7144-1.0, 7144-10.0; Solar 8525-1

### SCALE

Weigh-Tronix 3632T-50

### SCANNER

HP 9190A Scanjet

### SCREEN ROOM

Lindgren 22-2/2-0

### SIGNAL LEVEL METER

Jerrold 7048

### SIGNAL SAMPLER

R. F. Bird 4273-030, 4275-030

### SINAD/VOLTMETER

Helper Sinadder

### SPECTRUM ANALYZER

HP 8558B, 8557; HP 8563E; HP 853A; HP 8566B/8568B

### TEMPERATURE CHAMBER

Tenney, Jr

### TEMPERATURE PROBE

Fluke 80T-150C

### TERMINATION

Narda 320B Waveguide. Waveline #281

### TEST SET

SemiAutomatic: HP 8953A; HP 8954A Interface; Computer / Controller; P.S. Programmer; HP 59501A; RF Communications: HP 8920A

### TRANSFORMERS

Audio Isolation: Solar 6220-1A; Impedance: HP 11694A; Isolation: Solar 7032-1; Matching: Solar 7033-1

### TRANSMISSION & NOISE MEASURING SET

HP 3555B

### VIBRATION CHAMBER

Unholtz-Dickie T 500; Unholtz-Dickie T 4000

### VOLTMETER

HP 410C; HP 3478A

### WATTMETER

Bird 43, Sierra 174A-2

### ANTENNAS

30 - 50 MHz  
Emco 7603 M-Field; Emco 7604 M-Field

20 - 200 MHz  
Aprel Biconical Model AAB20200

20 - 300 MHz  
Emco Biconical H-Field

25 - 1000 MHz  
Singer DM-105A; EMCO 3121C

200 - 1000 MHz  
Aprel Log Periodic, Model AALP 2001

10 kHz - 30 MHz  
Emco 3107B, E-Field; Emco 3101B/1, Rod E-Field

10 kHz - 32 MHz  
Singer 94593-1 (Loop)

150 kHz - 32 MHz  
Singer 92197-1 (41")

150 kHz - 32 MHz  
Singer 93049-1 (9')

1 - 10 GHz  
Singer 90794-A Discone

1 - 18 GHz  
Horn: Aprel Model AAH-118

18 - 40 GHz  
Emco 3116, Horn

40 - 60 GHz  
Horn: HP 11970U, HP 11971U, HP 11975A (Lo Drive Amplifier)

50 - 75 GHz  
Mixer, HP 11970V, HP 11971V

75 - 110 GHz  
Mixer, HP 11970W