

**MFA** **M. Flom Associates, Inc. - Global Compliance Center**  
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176  
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

---

Date: December 21, 2001

Federal Communications Commission  
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Vertex Standard Co., Ltd.  
Equipment: VX-3200U  
FCC ID: K66VX-3200U  
FCC Rules: 90, 90.210, 95.29


Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,



Morton Flom, P. Eng.

enclosure(s)  
cc: Applicant  
MF/cvr

LIST OF EXHIBITS  
 (FCC **CERTIFICATION** (TRANSMITTERS) - REVISED 9/28/98)

APPLICANT: Vertex Standard Co., Ltd.

FCC ID: K66VX-3200U

BY APPLICANT:

- |   |   |
|---|---|
| 1. LETTER OF AUTHORIZATION                    | x |
| 2. IDENTIFICATION DRAWINGS, 2.1033(c)(11)     |   |
| <u>  x  </u> LABEL                            |   |
| <u>  x  </u> LOCATION OF LABEL                |   |
| <u>  x  </u> COMPLIANCE STATEMENT             |   |
| <u>  x  </u> LOCATION OF COMPLIANCE STATEMENT |   |
| 3. PHOTOGRAPHS, 2.1033(c)(12)                 | x |
| 4. DOCUMENTATION: 2.1033(c)                   |   |
| (3) USER MANUAL                               | x |
| (9) TUNE UP INFO                              | x |
| (10) SCHEMATIC DIAGRAM                        | x |
| (10) CIRCUIT DESCRIPTION                      | x |
| BLOCK DIAGRAM                                 | x |
| PARTS LIST                                    | x |
| ACTIVE DEVICES                                | x |
| 5. PART 90.203(e) & (g) ATTESTATION           | x |
| 6. MPE Report                                 | x |

BY M.F.A. INC.

- A. TESTIMONIAL & STATEMENT OF CERTIFICATION
- B. STATEMENT OF QUALIFICATIONS

**MFA** **M. Flom Associates, Inc. - Global Compliance Center**  
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176  
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

---

T R A N S M I T T E R     C E R T I F I C A T I O N

of

FCC ID: K66VX-3200U  
MODEL: VX-3200U

to

FEDERAL COMMUNICATIONS COMMISSION

Rule Part(s) 90, 90.210, 95.29

DATE OF REPORT: December 21, 2001

ON THE BEHALF OF THE APPLICANT:

Vertex Standard Co., Ltd.

AT THE REQUEST OF:

P.O. UPS 12/12/01

Vertex Standard USA Inc.  
17210 Edwards Rd.  
Cerritos, CA 90703

Attention of:

Mikio Maruya, Executive Vice President  
(800) 255-9237; FAX: (800) 477-9237  
(562) 404-2700, x280; FAX: -1210  
m.maruya@vxstdusa.com

SUPERVISED BY:



Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.


Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Conducted)	7
2.1046(a)	ERP Carrier Power (Radiated)	9
2.1051	Unwanted Emissions (Transmitter Conducted)	10
2.1053(a)	Field Strength of Spurious Radiation	14
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	18
90.214	Transient Frequency Behavior	25
2.1047(a)	Audio Low Pass Filter (Voice Input)	31
2.1047(a)	Audio Frequency Response	34
2.1047(b)	Modulation Limiting	36
2.1055(a)(1)	Frequency Stability (Temperature Variation)	39
2.1055(b)(1)	Frequency Stability (Voltage Variation)	42
2.202(g)	Necessary Bandwidth and Emission Bandwidth	43

PAGE NO. 1 of 43.

*Required information per ISO/IEC Guide 25-1990, paragraph 13.2:*

- a) TEST REPORT
- b) Laboratory: M. Flom Associates, Inc.  
 (FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107  
 (Canada: IC 2044) Chandler, AZ 85225
- c) Report Number: d01c0052
- d) Client: Vertex Standard USA Inc.  
 17210 Edwards Rd.  
 Cerritos, CA 90703
- e) Identification: VX-3200U  
 FCC ID: K66VX-3200U  
 EUT Description: UHF FM Mobile Transceiver
- f) EUT Condition: Not required unless specified in individual tests.
- g) Report Date: December 21, 2001  
 EUT Received: December 12, 2001
- h, j, k): As indicated in individual tests.
- i) Sampling method: No sampling procedure used.
- l) Uncertainty: In accordance with MFA internal quality manual.
- m) Supervised by:   
 Morton Flom, P. Eng.
- n) Results: The results presented in this report relate only to the item tested.
- o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO. 2 of 43.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATION

IN ACCORDANCE WITH FCC RULES AND REGULATIONS,  
VOLUME II, PART 2 AND TO

90, 90.210, 95.29

Sub-part 2.1033

(c)(1): NAME AND ADDRESS OF APPLICANT:

Vertex Standard Co., Ltd.  
4-8-8 Nakameguro, Meguro-Ku  
Tokyo 153-8644 Japan

MANUFACTURER:

Applicant

(c)(2): FCC ID: K66VX-3200U

MODEL NO: VX-3200U

(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 16K0F3E, 11K0F3E

(c)(5): FREQUENCY RANGE, MHz: 450 to 490


(c)(6): POWER RATING, Watts: 10 to 45  
     Switchable   x   Variable      N/A

FCC GRANT NOTE: BF - The output power is continuously variable from the value listed in this entry to 20%-25% of the value listed.

(c)(7): MAXIMUM POWER RATING, Watts: 500

DUT RESULTS: Passes   x   Fails

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Association (A2LA) as shown in the scope below.



**THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION**

**ACCREDITED LABORATORY**

A2LA has accredited


**M. FLOM ASSOCIATES, INC.**  
Chandler, AZ

for technical competence in the field of

**Electrical (EMC) Testing**


The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 - 1999 "General Requirements for the Competence of Testing and Calibration Laboratories" and any additional program requirements in the identified field of testing. Testing and calibration laboratories that comply with this International Standard also operate in accordance with ISO 9001 or ISO 9002.

Presented this 2<sup>nd</sup> day of March, 2001.



President  
For the Accreditation Council  
Certificate Number 1008.01  
Valid to December 31, 2002

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



**American Association for Laboratory Accreditation**

SCOPE OF ACCREDITATION TO ISO/IEC 17025:1999


M. FLOM ASSOCIATES, INC.  
Electronic Testing Laboratory  
3356 North San Marcos Place, Suite 107  
Chandler, AZ 85225  
Morton Flom Phone: 480 926 3100

**ELECTRICAL (EMC)**

Valid to: December 31, 2002 Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

Tests	Standard(s)
RF Emissions	FCC Part 15 (Subparts B and C) using ANSI C63.4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1; CNS 13438
Harmonic Currents	EN 61000-3-2
Fluctuation and Flicker	EN 61000-3-3
RF Immunity	EN: 50082-1, 50082-2 (both excluding "Power Frequency Magnetic Field Immunity" and "Voltage Dips, Short Interruptions, and Line Voltage Variations"); AS/NZS 4251.1
Radiated Susceptibility	EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3
EFT	EN 61000-4-4; IEC 1000-4-4; IEC 801-4
Surge	EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5
47 CFR (FCC)	2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97



5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8373 • Phone: 301-644 3248 • Fax: 301-662 2974

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.



PAGE NO. 4 of 43.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE, INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual  
 COLLECTOR VOLTAGE, Vdc = per manual  
 SUPPLY VOLTAGE, Vdc = 13.8

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

     ATTACHED EXHIBITS  
  x   N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

5 of 43.

Sub-part  
2.1033(c)(14):TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- 21 - Domestic Public Fixed Radio Services
- 22 - Public Mobile Services
- 22 Subpart H - Cellular Radiotelephone Service
- 22.901(d) - Alternative technologies and auxiliary services
- 23 - International Fixed Public Radiocommunication services
- 24 - Personal Communications Services
- 74 Subpart H - Low Power Auxiliary Stations
- 80 - Stations in the Maritime Services
- 80 Subpart E - General Technical Standards
- 80 Subpart F - Equipment Authorization for Compulsory Ships
- 80 Subpart K - Private Coast Stations and Marine Utility Stations
- 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- 80 Subpart X - Voluntary Radio Installations
- 87 - Aviation Services
- 90 - Private Land Mobile Radio Services
- 94 - Private Operational-Fixed Microwave Service
- 95 Subpart A - General Mobile Radio Service (GMRS)
- 95 Subpart C - Radio Control (R/C) Radio Service
- 95 Subpart D - Citizens Band (CB) Radio Service
- 95 Subpart E - Family Radio Service
- 95 Subpart F - Interactive Video and Data Service (IVDS)
- 97 - Amateur Radio Service
- 101 - Fixed Microwave Services

PAGE NO.

6 of 43.

STANDARD TEST CONDITIONS  
and  
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000 Draft, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 7 of 43.  
NAME OF TEST: Carrier Output Power (Conducted)  
SPECIFICATION: 47 CFR 2.1046(a)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1  
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is  $\pm 3\%$ .

MEASUREMENT RESULTS  
(Worst case)

FREQUENCY OF CARRIER, MHz = 470.1, 449.9, 490.1


<u>POWER SETTING</u>	<u>R. F. POWER, WATTS</u>
Low	10
High	45

PERFORMED BY:

  
Doug Noble, B.A.S. E.E.T.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT  
 TEST 2: FREQUENCY STABILITY



Asset	Description (as applicable)	s/n
(1)	<u>COAXIAL ATTENUATOR</u>	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(2)	<u>POWER METERS</u>	
i00014	HP 435A	1733A05836
i00039	HP 436A	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(3)	<u>FREQUENCY COUNTER</u>	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A FREQUENCY MODE	2105A01087

PAGE NO. 9 of 43.


NAME OF TEST: ERP Carrier Power (Radiated)

SPECIFICATION: TIA/EIA 603A (Substitution Method)

2.2.17.1 Definition: The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

2.2.17.2 Method of Measurement:

a) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



b) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.

c) Repeat step b) for seven additional readings at 45° interval positions of the turntable.

d) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.

e) Calculate the average radiated output power from the readings in step c) and d) by the following:

$$\text{average radiated power} = 10 \log_{10} \Sigma 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

	RESULTS			Path Loss, db
	449.90 MHz LVL, dbm	470.1 MHz LVL, dbm	490.1 MHz LVL, dbm	
0°	47.3	47.1	46.8	0.3
45°	45.0	44.9	45.0	0.3
90°	46.1	45.8	45.7	0.3
135°	43.9	43.8	42.9	0.3
180°	46.4	46.2	46.4	0.3
225°	46.7	46.6	46.5	0.3
270°	45.5	45.6	45.3	0.3
315°	43.9	45.1	45.0	0.3
Av. Radiated Power:	449.90 MHz 45.9 dbm	470.1 MHz 45.94 dbm	490.1 MHz 45.75 dbm	

PAGE NO. 10 of 43.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
  - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
  - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE


FREQUENCY OF CARRIER, MHz	=	470.1, 449.9, 490.1
SPECTRUM SEARCHED, GHz	=	0 to 10 x F <sub>c</sub>
MAXIMUM RESPONSE, Hz	=	2510
ALL OTHER EMISSIONS	=	≥ 20 dB BELOW LIMIT

PERFORMED BY:

  
Doug Noble, B.A.S. E.E.T.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)  
 TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104



PAGE NO. 12 of 43.


NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

Low Power

LIMIT(S), dBc

GBCE002: 2001-DEC-14, 13:28, FRI

TUNED MHz	EMISSION MHz	LEVEL dBm	LEVEL dBc	LEVEL uW	MARGIN dB
449.900	899.802000	-39.9	-79.9	0	-19.9
470.100	939.874000	-42.3	-82.3	0	-22.3
490.100	980.131000	-42.1	-82.1	0	-22.1
449.900	1349.724000	-42.7	-82.7	0	-22.7
470.100	1409.845000	-43.1	-83.1	0	-23.1
490.100	1470.543000	-42.8	-82.8	0	-22.8
449.900	1799.610000	-41.5	-81.5	0	-21.5
470.100	1880.694000	-40.5	-80.5	0	-20.5
490.100	1960.565000	-41.7	-81.7	0	-21.7
449.900	2249.811000	-40.3	-80.3	0	-20.3
470.100	2350.955000	-41.6	-81.6	0	-21.6
490.100	2450.984000	-41.3	-81.3	0	-21.3
449.900	2699.234000	-43.5	-83.5	0	-23.5
470.100	2820.996000	-43.5	-83.5	0	-23.5
490.100	2941.047000	-43.5	-83.5	0	-23.5
449.900	3149.214000	-44.3	-84.3	0	-24.3
470.100	3290.488000	-42.9	-82.9	0	-22.9
490.100	3430.524000	-44.0	-84.0	0	-24.0
449.900	3598.995000	-43.4	-83.4	0	-23.4
470.100	3760.987000	-44.2	-84.2	0	-24.2
490.100	3920.345000	-43.5	-83.5	0	-23.5
449.900	4048.899000	-43.6	-83.6	0	-23.6
470.100	4230.408000	-43.9	-83.9	0	-23.9
490.100	4410.956000	-43.6	-83.6	0	-23.6
449.900	4498.672000	-44.1	-84.1	0	-24.1
470.100	4700.938000	-43.9	-83.9	0	-23.9
490.100	4900.667000	-43.9	-83.9	0	-23.9
449.900	4948.893000	-44.0	-84.0	0	-24.0
470.100	5171.112000	-44.1	-84.1	0	-24.1
490.100	5390.822000	-43.6	-83.6	0	-23.6
449.900	5398.478000	-43.5	-83.5	0	-23.5
470.100	5641.443000	-44.3	-84.3	0	-24.3
449.900	5849.072000	-37.8	-77.8	0	-17.8
490.100	5880.714000	-37.9	-77.9	0	-17.9
470.100	6111.517000	-37.7	-77.7	0	-17.7
449.900	6298.534000	-37.4	-77.4	0	-17.4
490.100	6370.966000	-37.9	-77.9	0	-17.9
470.100	6581.293000	-38.2	-78.2	0	-18.2
449.900	6748.542000	-38.1	-78.1	0	-18.1
490.100	6861.354000	-38.6	-78.6	0	-18.6
470.100	7051.232000	-36.4	-76.4	0	-16.4
490.100	7351.449000	-37.8	-77.8	0	-17.8



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

PAGE NO. 13 of 43.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

High Power  
LIMIT(S), dBc

GBCE001: 2001-DEC-14, 13:23, FRI

TUNED MHz	EMISSION MHz	LEVEL dBm	LEVEL dBc	LEVEL uW	MARGIN dB
449.900	899.841000	-33.6	-80.1	0	-13.6
470.100	940.507000	-33.1	-79.6	0	-13.1
490.100	980.395000	-32.7	-79.2	1	-12.7
449.900	1349.350000	-32.8	-79.3	1	-12.8
470.100	1410.089000	-33.3	-79.8	0	-13.3
490.100	1470.011000	-32.4	-78.9	1	-12.4
449.900	1799.279000	-31.5	-78.0	1	-11.5
470.100	1880.244000	-32.4	-78.9	1	-12.4
490.100	1960.899000	-29.8	-76.3	1	-9.8
449.900	2249.435000	-31.9	-78.4	1	-11.9
470.100	2350.769000	-30.0	-76.5	1	-10.0
490.100	2450.367000	-30.9	-77.4	1	-10.9
449.900	2699.071000	-32.4	-78.9	1	-12.4
470.100	2820.969000	-33.0	-79.5	1	-13.0
490.100	2940.129000	-34.5	-81.0	0	-14.5
449.900	3149.145000	-35.2	-81.7	0	-15.2
470.100	3291.028000	-33.3	-79.8	0	-13.3
490.100	3430.731000	-34.4	-80.9	0	-14.4
449.900	3599.300000	-34.2	-80.7	0	-14.2
470.100	3761.027000	-33.7	-80.2	0	-13.7
490.100	3920.719000	-34.4	-80.9	0	-14.4
449.900	4049.595000	-33.7	-80.2	0	-13.7
470.100	4230.461000	-34.2	-80.7	0	-14.2
490.100	4410.463000	-33.9	-80.4	0	-13.9
449.900	4499.321000	-34.3	-80.8	0	-14.3
470.100	4700.995000	-33.9	-80.4	0	-13.9
490.100	4901.436000	-33.1	-79.6	0	-13.1
449.900	4949.077000	-33.3	-79.8	0	-13.3
470.100	5171.279000	-34.2	-80.7	0	-14.2
490.100	5391.106000	-33.2	-79.7	0	-13.2
449.900	5399.070000	-32.8	-79.3	1	-12.8
470.100	5640.947000	-33.0	-79.5	1	-13.0
449.900	5848.298000	-28.3	-74.8	1	-8.3
490.100	5881.006000	-28.0	-74.5	2	-8.0
470.100	6111.786000	-28.0	-74.5	2	-8.0
449.900	6298.310000	-27.0	-73.5	2	-7.0
490.100	6371.507000	-28.1	-74.6	2	-8.1
470.100	6581.615000	-28.3	-74.8	1	-8.3
449.900	6748.827000	-27.5	-74.0	2	-7.5
490.100	6860.953000	-27.7	-74.2	2	-7.7
470.100	7051.014000	-28.1	-74.6	2	-8.1
490.100	7351.398000	-27.2	-73.7	2	-7.2



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.


PAGE NO. 14 of 43.  
NAME OF TEST: Field Strength of Spurious Radiation  
SPECIFICATION: 47 CFR 2.1053(a)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 1.2.12

MEASUREMENT PROCEDURE

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

1.2.12.2 Method of Measurement


- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
- 1) Resolution Bandwidth  $\leq 3$  kHz.
  - 2) Video Bandwidth  $\geq 10$  kHz
  - 3) Sweep Speed  $\leq 2000$  Hz/second
  - 4) Detector Mode = Positive Peak
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



PAGE NO. 15 of 43.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to  $\pm$  the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

PAGE NO. 16 of 43.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =  
 $10 \log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step l)}$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset Description (as applicable)	s/n	Cycle	Last Cal
<u>TRANSDUCER</u>			
i00088 EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-01
i00065 EMCO 3301-B Active Monopole	2635	12 mo.	Sep-01
i00089 Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-01
i00103 EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-01
<u>AMPLIFIER</u>			
i00028 HP 8449A	2749A00121	12 mo.	Mar-01
<u>SPECTRUM ANALYZER</u>			
i00029 HP 8563E	3213A00104	12 mo.	Aug-01
i00033 HP 85462A	3625A00357	12 mo.	May-01
i00048 HP 8566B	2511AD1467	6 mo.	Nov-01
<u>MICROPHONE, ANTENNA PORT, AND CABELING</u>			
Microphone	Yes/No _____	Cable Length _____	Meters _____
Antenna Port Terminated	Yes/No _____	Load _____	Antenna Gain _____
All Ports Terminated by	Load _____	Peripheral _____	

PAGE NO. 17 of 43.

NAME OF TEST: Field Strength of Spurious Radiation

LIMIT'S), dBc:  $-(50+10 \times \text{LOG}(P)) = -67$  ( 45 Watts )  
 $-(50+10 \times \text{LOG}(P)) = -60$  ( 10 Watts )

High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	ERP, dBm	ERP, dBc
449.9000	1349.7000	-34.5	-81.0
470.1000	1410.3000	-33.2	-79.7
470.1000	1880.4000	-37.7	-84.2
470.1000	2350.5000	-38.0	-84.5
490.1000	2450.5000	-30.6	-77.1
470.1000	2820.6000	-39.4	-85.9
490.1000	2940.6000	-33.7	-80.2
449.9000	3149.3000	-33.9	-80.4
490.1000	3430.7000	-36.3	-82.8
449.9000	3599.2000	-23.9	-70.4
470.1000	3760.8000	-23.8	-70.3
490.1000	3920.8000	-24.0	-70.5

APPLICANT SUPPLIED DATA

PAGE NO. 18 of 43.  
NAME OF TEST: Emission Masks (Occupied Bandwidth)  
SPECIFICATION: 47 CFR 2.1049(c)(1)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11  
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for  $\pm 2.5/\pm 1.25$  kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 19 of 43.


NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECTRUM ANALYZER PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-14, 13:10, FRI

POWER: LOW  
MODULATION: NONE



PERFORMED BY:

  
Doug Noble, B.A.S. E.E.T.




PAGE NO. 20 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)


SPECTRUM ANALYZER PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-14, 13:19, FRI

POWER: LOW  
MODULATION: VOICE: 2500 Hz SINE WAVE  
MASK: D, VHF/UHF 12.5kHz BW



C:\XCOM\FACES\VTZ\4800\FCT COPYRIGHT (C) 2001 BY R. FLOTT ASSOCIATES, INC. ALL RIGHTS RESERVED

PERFORMED BY:


  
Doug Noble, B.A.S. E.E.T.

PAGE NO. 21 of 43.


NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECTRUM ANALYZER PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-14, 13:13, FRI

POWER: LOW  
MODULATION: VOICE: 2500 Hz SINE WAVE  
MASK: B, VHF/UHF 25kHz, w/LPF



PERFORMED BY:


  
Doug Noble, B.A.S. E.E.T.

PAGE NO. 22 of 43.


NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECTRUM ANALYZER PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-14, 13:07, FRI

POWER: HIGH  
MODULATION: NONE



PERFORMED BY:


  
Doug Noble, B.A.S. E.E.T.

PAGE NO. 23 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECTRUM ANALYZER PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-14, 13:18, FRI

POWER: HIGH  
MODULATION: VOICE: 2500 Hz SINE WAVE  
MASK: D, VHF/UHF 12.5kHz BW



PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 24 of 43.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECTRUM ANALYZER PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-14, 13:15, FRI

POWER: HIGH  
MODULATION: VOICE: 2500 Hz SINE WAVE  
MASK: B, VHF/UHF 25kHz, w/LPF



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.


PAGE NO. 25 of 43.  
NAME OF TEST: Transient Frequency Behavior  
SPECIFICATION: 47 CFR 90.214  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19  
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.
2. The transmitter was turned on.
3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.
4. The transmitter was turned off.
5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.
6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.
8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:


<u>step f</u> , dBm	=	-9.1
<u>step h</u> , dBm	=	-35.2
<u>step l</u> , dBm	=	15.2



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

TRANSIENT FREQUENCY BEHAVIOR




Asset	Description (as applicable)	s/n
(1)	<u>ATTENUATOR</u> (Removed after 1st step)	
	i00112 Philco 30 dB	989
(2)	<u>ATTENUATOR</u>	
	i00112 Philco 30 dB	989
	i00172 Bird 30 dB	989
	i00122 Narda 10 dB	7802
	i00123 Narda 10 dB	7802A
	i00110 Kay Variable	145-387
(3)	<u>COMBINER</u>	
	i00154 4 x 25 Ω COMBINER	154
(4)	<u>CRYSTAL DETECTOR</u>	
	i00159 HP 8470B	1822A10054
(5)	<u>RF SIGNAL GENERATOR</u>	
	i00018 HP 8656A	2228A03472
	i00031 HP 8656A	2402A06180
	i00067 HP 8920A	3345U01242
(6)	<u>MODULATION ANALYZER</u>	
	i00020 HP 8901A	2105A01087
(7)	<u>SCOPE</u>	
	i00030 HP 54502A	2927A00209

PAGE NO. 27 of 43.

NAME OF TEST: Transient Frequency Behavior

OSCILLOSCOPE PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-17, 10:23, MON

POWER: HIGH  
MODULATION: Ref Gen=12.5 kHz Deviation  
REMARK: CARRIER ON TIME



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.




PAGE NO. 28 of 43.

NAME OF TEST: Transient Frequency Behavior

OSCILLOSCOPE PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-17, 10:24, MON

POWER: HIGH  
MODULATION: Ref Gen=12.5 kHz Deviation  
REMARK: CARRIER OFF TIME



PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 29 of 43.

NAME OF TEST: Transient Frequency Behavior

OSCILLOSCOPE PRESENTATION  
VERTEXSTANDARD, VX-3200U  
2001-DEC-17, 10:19, MON

POWER: HIGH  
MODULATION: Ref Gen=25 kHz Deviation  
REMARK: CARRIER ON TIME



PERFORMED BY:


Doug Noble, B.A.S. E.E.T.

PAGE NO. 30 of 43.

NAME OF TEST: Transient Frequency Behavior

OSCILLOSCOPE PRESENTATION  
 VERTEXSTANDARD, VX-3200U  
 2001-DEC-17, 10:21, MON

POWER: HIGH  
 MODULATION: Ref Gen=25 kHz Deviation  
 REMARK: CARRIER OFF TIME



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.


PAGE NO. 31 of 43.  
NAME OF TEST: Audio Low Pass Filter (Voice Input)  
SPECIFICATION: 47 CFR 2.1047(a)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15  
TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP

- TEST A. MODULATION CAPABILITY/DISTORTION
- TEST B. AUDIO FREQUENCY RESPONSE
- TEST C. HUM AND NOISE LEVEL
- TEST D. RESPONSE OF LOW PASS FILTER
- TEST E. MODULATION LIMITING




Asset Description (as applicable)	s/n
(1) <u>Audio Oscillator</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00118 HP 33120A	US36002064
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 NARDA 766-10	7802
i00123 NARDA 766-10	7802A
i00113 SIERRA 661A-3D	1059
i00069 BIRD 8329 (30 dB)	10066
(3) <u>MODULATION ANALYZER</u>	
i00020 HP 8901A	2105A01087
(4) <u>AUDIO ANALYZER</u>	
i00017 HP 8903A	2216A01753


PAGE NO. 33 of 43.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

STATE: g011c0140 14 Dec, 2001, 09:58



PERFORMED BY:

  
Doug Noble, B.A.S. E.E.T.

PAGE NO. 34 of 43.  
NAME OF TEST: Audio Frequency Response  
SPECIFICATION: 47 CFR 2.1047(a)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6  
TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 35 of 43.

NAME OF TEST: Audio Frequency Response

STATE: g01c0139 14 Dec 2001, 09:51



Frequency of Maximum Audio Response, Hz = 2510

Additional points:

FREQUENCY, Hz	LEVEL, dB
3000	-35.9
5000	-35.7

PERFORMED BY:

Doug Noble, B.A.S. E.E.T.



PAGE NO. 36 of 43.  
NAME OF TEST: Modulation Limiting  
SPECIFICATION: 47 CFR 2.1047(b)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3  
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation ( $\pm 1.5$  kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


37 of 43.

NAME OF TEST:


Modulation Limiting

STATE: g01c0143: 2001-Dec-14, 10:21


Positive  
Peaks:



Negative  
Peaks:



PERFORMED BY:


  
Doug Noble, B.A.S. E.E.T.

PAGE NO. 38 of 43.


NAME OF TEST: Modulation Limiting

STATE: g01c0144: 2001-Dec-14, 10:30

Positive Peaks:



Negative Peaks:



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.


PAGE NO. 39 of 43.  
NAME OF TEST: Frequency Stability (Temperature Variation)  
SPECIFICATION: 47 CFR 2.1055(a)(1)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2  
TEST CONDITIONS: As Indicated  
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

TRANSMITTER TEST SET-UP


- TEST A. OPERATIONAL STABILITY
- TEST B. CARRIER FREQUENCY STABILITY
- TEST C. OPERATIONAL PERFORMANCE STABILITY
- TEST D. HUMIDITY
- TEST E. VIBRATION
- TEST F. ENVIRONMENTAL TEMPERATURE
- TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
- TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION



Asset Description (as applicable)	s/n
<u>(1) TEMPERATURE, HUMIDITY, VIBRATION</u>	
i00027 Tenney Temp. Chamber	9083-765-234
i00 Weber Humidity Chamber	
i00 L.A.B. RVH 18-100	
<u>(2) COAXIAL ATTENUATOR</u>	
i00122 NARDA 766-10	7802
i00123 NARDA 766-10	7802A
i00113 SIERRA 661A-3D	1059
i00069 BIRD 8329 (30 dB)	10066
<u>(3) R.F. POWER</u>	
i00014 HP 435A POWER METER	1733A05839
i00039 HP 436A POWER METER	2709A26776
i00020 HP 8901A POWER MODE	2105A01087
<u>(4) FREQUENCY COUNTER</u>	
i00042 HP 5383A	1628A00959
i00019 HP 5334B	2704A00347
i00020 HP 8901A	2105A01087

PAGE NO. 41 of 43.

NAME OF TEST: Frequency Stability (Temperature Variation)



APPLICANT SUPPLIED DATA

PAGE NO. 42 of 43.  
NAME OF TEST: Frequency Stability (Voltage Variation)  
SPECIFICATION: 47 CFR 2.1055(d)(1)  
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2  
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at 25±5°C and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)

LIMIT, ppm = 2.5  
 LIMIT, Hz = 1175

<u>% of STV</u>	<u>Voltage</u>	<u>Frequency, MHz</u>	<u>Change, Hz</u>	<u>Change, ppm</u>
85	11.73	470.100126	126	0.27
100	13.80	470.100126	126	0.27
115	15.87	470.100126	126	0.27

APPLICANT SUPPLIED DATA

PAGE NO. 43 of 43.  
NAME OF TEST: Necessary Bandwidth and Emission Bandwidth  
SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E


NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz = 3  
 MAXIMUM DEVIATION (D), kHz = 5  
 CONSTANT FACTOR (K) = 1  
 NECESSARY BANDWIDTH (B<sub>N</sub>), kHz = (2xM)+(2xDxK)  
 = 16.0

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz = 3  
 MAXIMUM DEVIATION (D), kHz = 2.5  
 CONSTANT FACTOR (K) = 1  
 NECESSARY BANDWIDTH (B<sub>N</sub>), kHz = (2xM)+(2xDxK)  
 = 11.0



PERFORMED BY:

Doug Noble, B.A.S. E.E.T.

END OF TEST REPORT



TESTIMONIAL  
AND  
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:



Morton Flom, P. Eng.