

## VX-3200V Circuit Description

### 1. Overview

The VX-3200V is a VHF/FM mobile transceiver designed to operate in the frequency range of 134 to 165 MHz or 148 to 174 MHz.

### 2. Circuit Configuration by Frequency

The receiver is a double-conversion superheterodyne with a first intermediate frequency (IF) of 44.25 MHz and a second IF of 450 kHz. Incoming signals from the antenna are mixed with the local signal from PLL to produce the first IF of 44.25 MHz.

This is then mixed with the 44.25 MHz second local oscillator (using the 14.6 MHz reference crystal) output to produce the 450 kHz second IF. This is detected to give the demodulated signal.

The transmit signal frequency is generated by PLL VCO, and modulated by the signal from the microphone. It is then amplified and sent to the antenna.

### 3. Receive Signal Path

Incoming RF signals from the antenna connector are delivered to the RF Unit. RF signals pass through a low-pass filter (LPF) antenna switching network consisting of coils L1001, L1003, and L1005, capacitors C1004, C1008, C1009, and C1011, and antenna switching diodes D1005, D1007, and D1031, for delivery to the receiver front end.

Signals within the frequency range of the transceiver are then passed through a varactor-tuned bandpass filter consisting of L1009 and L1014 before RF amplification by Q1011 (2SC3356).

The amplified RF is then band-pass filtered again by varactor-tuned resonators L1026, and L1027 to ensure pure in-band input to 1st mixer Q1038 (GN2011-Q).

Buffered output from the VCO Unit is amplified by Q1021 (2SC5107) and low-pass filtered by L1030 / L1031 and C1178 / C1180 / C1182, to provide a pure 1st local signal between 192.25 and 218.25 MHz to the 1st mixer.

The 44.25 MHz 1st mixer product then passes through dual monolithic crystal filters XF1001 and XF1002 ( $\pm 5.5$  kHz BW), and is amplified by Q1029 (2SC4215Y) and delivered to the input of the FM IF subsystem IC Q1028 (TA31136FN).

This IC contains the 2nd mixer, 2nd local oscillator, limiter amplifier, FM detector, noise amplifier, and squelch gates.

The 2nd LO in the IF-IC is produced from crystal X1001 (14.600 MHz) and the 1st IF is converted to 450 kHz by the 2nd mixer and stripped of unwanted components by ceramic filter CF1001 or CF1002. After passing through a limiter amplifier, the signal is demodulated by the FM detector CD1001 (CDBC450CX24).

Detected audio from Q1029 is applied to Q2016(AK2345) and audio low-pass filter. After volume adjustment by Q2014(M62364FP), the audio signal is amplified by the AF power amplifier Q1509 (TDA2003H) and passed to speaker jack.

### 4. Transmit Signal Path

Voice audio from the microphone is delivered via the Mic (Jack) Unit to the

PANEL Unit, after passing through amplifier Q2022 (NJM2902V), Mic gain-volume Q2014 (M62364FP) pre-emphasis Q2015 (NJM2902V), and limiter (IDC instantaneous deviation control), is adjusted for optimum deviation level and delivered to the next stage.

Voice input from the microphone CTCSS, and DCS audio are modulated by the VCO, and the reference frequency oscillator of the synthesizer.

Synthesizer output, after passing through diode switch D1022 (1SS321), is amplified by driver Q1025 (2SC5415E) / Q1026 (2SC5107-O) and power module Q1039 (RA60H1317M) to obtain full RF output. The RF energy then passes through antenna switch D1005 / D1007 / D1031 and a low-pass filter circuit and finally to the antenna connector.

RF output power from the final amplifier is sampled by CM coupler and is rectified by D1011, D1012 (HSM88AS x 2). The resulting DC is fed through Automatic Power Controller Q1003 (NJM2902V), to transmitter RF amplifier and thus the power output.

Generation of spurious products by the transmitter is minimized by the fundamental carrier frequency being equal to the final transmitting frequency, modulated directly in the transmit VCO. Additional harmonic suppression is provided by a low-pass filter consisting of L1001, L1003, L1004, L1027, C1004, C1009, C1011, C1151, and C1152, resulting in more than 60dB of harmonic suppression prior to delivery to the RF energy to the antenna.

## 5 PLL Frequency Synthesizer

PLL frequency synthesizer consists of the VCO Q1013 (2SK508-K52:RX) and Q1015 (2SC5107-O:TX), VCO buffers Q1018 (2SC5107-O), Q1020 (2SC5107-O), Q1021 (2SC5107-O), PLL subsystem IC Q1023 (MA15A02PFV1) and 14.6 MHz reference crystal X1001.

The frequency stability is  $\pm 2.5$  ppm within temperature range of -30 to +60 °C. The output of the 14.6 MHz reference is applied to pin 1 of the PLL IC.

While receiving, VCO Q1013 oscillates between 405.75 and 445.75 MHz according to the transceiver version and the programmed receiving frequency. The VCO generates 192.25 to 218.25 MHz for providing to the first local signal. In TX, the VCO generates 148 to 174 MHz.

The output of the VCO is amplified by the Q1020 and routed to the pin 8 of the PLL IC. Also the output of the VCO is amplified by the Q1021 and routed first local /Power Module according to D1022.

The PLL IC consists of a prescaler, fractional divider, reference divider and phase comparator and charge pump. This PLL IC is fractional-N type synthesizer and performs in the 40 or 50 kHz reference signal, which is eighth of the channel step (5 or 6.25 kHz). The input signal from pin 1 and 8 of the PLL IC is divided down to the 20 kHz and compared at phase comparator. The pulsed output signal of the phase comparator is applied to the charge pump and transformed into DC signal in the loop filter. The DC signal is applied to the pin 1 of the VCO and locked to keep the VCO frequency constant.

PLL data is output from DCS\_E (pin100), CLOCK (pin2) and PLL\_E (pin98) of the microprocessor Q2013. The data are input to PLL IC when the channel is changed or when transmission is changed to reception and vice versa. A PLL lock condition is always monitored by the pin20 of the Q2013. When the PLL is unlocked, the UL goes low.

## **6. Miscellaneous Circuits**

### **6-1 DCS/LTR Demodulator**

DCS signals are demodulated on the PANEL-UNIT, It is demodulated by Q2116 (AK2345), amplifier Q2015, and comparator Q2021.

### **6-2 CTCSS encoder/decoder**

The CTCSS code is generation and encoding by CTCSS encoder/decoder IC Q2016 (AK2345).

### **6-3 MPU**

Operation is controlled by 8-bit MPU IC Q2013 (LC87F72C8A). The system clock uses a 3.6864 MHz crystal for a time base. IC Q2003 (S-80735SN) resets the MPU when the power is on, and monitors the voltage of the regulated 5V power supply line.

### **6-4 DCS Encorder**

The DCS code is generation and encoding by MPU IC Q2013 (LC87F72C8A). It is filtered by Q2021 (NJM2902V) and adjusted the level by Q2014 (M62364FP).

### **6-5 Compandor**

The Compandor is active when Pin90 of Q2013 (LC87F72C8A) is "High". When the Compandor is active, MIC Audio is compressed, and detected audio is expanded by Q2017 (LA8630M).