



M. Flom Associates, Inc. - Global Compliance Center
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

AMENDED ENVIRONMENTAL ASSESSMENT

for

MOBILES/FIXED BASE STATION

for

FCC ID: FCC ID: K66VX-4000U-3E
Model: VX-4000UF

to

FEDERAL COMMUNICATIONS COMMISSION

47 CFR 1.1310 (MPE)
Radiofrequency Radiation Exposure Limits

DATE OF REPORT: March 8, 2001

ON THE BEHALF OF THE APPLICANT:

Vertex Standard Co., Ltd.

AT THE REQUEST OF:

P.O. Email 12/20/2000

Vertex Standard USA Inc.
17210 Edwards Rd.
Cerritos, CA 90703

Attention of:

Mikio Maruya, Executive Vice President
(800) 255-9237; FAX: (800) 477-9237
(562) 404-2700, x280; FAX: -1210
mmaruya@yaesuusa.com

A handwritten signature in black ink that reads 'Morton Flom P. Eng.' The signature is written in a cursive, flowing style.

SUPERVISED BY:


Morton Flom, P. Eng.

TABLE OF CONTENTS

| <u>RULE</u> | <u>DESCRIPTION</u> | <u>PAGE</u> |
|-------------|--|-------------|
| | Test Report | 1 |
| | Identification of the Equipment Under Test | 2 |
| | Standard Test Conditions and Engineering Practices | 4 |
| 1.1310 | Environmental Assessment | 5 |

PAGE NO. 1 of 7.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

- a) TEST REPORT (SUPPLEMENTAL)
- b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225
- c) Report Number: d0130013
- d) Client: Vertex Standard USA Inc.
17210 Edwards Rd.
Cerritos, CA 90703
- e) Identification: VX-4000UF
Description: FCC ID: K66VX-4000U-3E
UHF FM Mobile Transceiver
- f) EUT Condition: Not required unless specified in individual tests.
- g) Report Date: March 8, 2001
EUT Received: July 20, 2000
- h, j, k): As indicated in individual tests.
- i) Sampling method: No sampling procedure used.
- l) Uncertainty: In accordance with MFA internal quality manual.
- m) Supervised by: 
Morton Flom, P. Eng.
- n) Results: The results presented in this report relate only to the item tested.
- o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO.

2 of 7.

IDENTIFICATION OF THE EQUIPMENT UNDER TEST (EUT)NAME AND ADDRESS OF APPLICANT:

Vertex Standard Co., Ltd.
 4-8-8 Nakameguro, Meguro-Ku
 Tokyo 153-8644 Japan

MANUFACTURER:

Applicant

FCC ID: K66VX-4000U-3EMODEL NO: VX-4000UFDESCRIPTION: UHF FM Mobile TransceiverTYPE OF EMISSION: 16K0F3E, 11K0F3EFREQUENCY RANGE, MHz: 480 to 512


POWER RATING, Watts: 5 to 40
 ___ Switchable ___ x Variable ___ N/A

MODULATION:
 ___ AMPS
 ___ TDMA
 ___ CDMA
 ___ x OTHER

ANTENNA:
 ___ HELICAL
 ___ MONOPOLE
 ___ WHIP
 ___ x OTHER

NOTE: For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Association (A2LA) as shown in the scope below.



THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION

ACCREDITED LABORATORY

A2LA has accredited

M. FLOM ASSOCIATES, INC.
Chandler, AZ

for technical competence in the field of

Electrical (EMC) Testing


The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25-1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 24th day of November, 1998.



Peter Abjorn
President
For the Accreditation Council
Certificate Number 1008.01
Valid to December 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25-1990 AND EN 45001

M. FLOM ASSOCIATES, INC.
Electronic Testing Laboratory
3356 North San Marcos Place, Suite 107
Chandler, AZ 85225
Morton Flom Phone: 480 926 3100

ELECTRICAL (EMC)

Valid to: December 31, 2000 Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

| Tests | Standard(s) |
|-------------------------|--|
| RF Emissions | FCC Part 15 (Subparts B and C) using ANSI C63 4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; FCC Part 18; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1; CNS 13438 |
| RF Immunity | EN 50082-1; EN 50082-2; AS/NZS 4251.1 |
| Radiated Susceptibility | EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3 |
| ESD | EN 61000-4-2; IEC 1000-4-2; IEC 801-2 |
| EFT | EN 61000-4-4; IEC 1000-4-4; IEC 801-4 |
| Surge | EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5 |
| 47 CFR (FCC) | 2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97 |

Revised 2/2/2000

Peter Abjorn

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8370 • Phone: 301 644 3248 • Fax: 301 662 2974

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.

PAGE NO.

4 of 7.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2000, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 5 of 7.

Name of test: Environmental Assessment

Specification: FCC: 47 CFR 1.1310

Measurement Guide: ANSI/IEEE C95.1 1992

Test Equipment: Maximum Permissible Exposure (MPE) measurement system, consisting of:
Narda 8717-1174R, Radiation meter
Narda 8761D, E-field probe (300 kHz - 3 GHz)
(Calibrated Nov-98)

Measurement Procedure:

1. The following measurements were performed with a Narda probe using ANSI/IEEE C95.1 as a guide.
2. Prior to making any measurements, the measurements system was calibrated in accordance with the manufacturer's procedures.
3. The EUT's radiating element (antenna) was placed on a 1 m tall table for ease of testing. For equipment normally operated on a metal surface, a ground plane was used.
4. The remaining equipment necessary to operate the EUT was maintained at a distance from the measurement arrangement suitable to minimize interference with the measurements.
5. The minimum safe distance was calculated from the formula Power Density = $EIRP / 4\pi R^2$ (Peak Watts/m²). The calculation is shown with the measurement data.
6. With the EUT operating at maximum power, a search was initiated for worst case emissions with the probe raised and lowered over a range of 0.2 to 2 meters in height and over a horizontal plane of 0° to 360°.
7. Average values were calculated for the whole body (0.2-2.0m), lower body (0.2-0.8m) and upper body (1.0-2.0m).

Results: Attached.

PAGE NO.

6 of 7.

TEST SETUP: Maximum Permissible Exposure (MPE)
g0130012: 2001-Mar-07 Wed 16:38:31
STATE: 0:General



PAGE NO. 7 of 7.

Name of test: R.F. Radiation Exposure

FCC Rules: 1.1307, 1.1310, 1.1311, 2.1091
 Description, EUT: See page 2 of Test Report

Test Frequency, MHz = 480.01
 Antenna Gain = 0 dBd
 Antenna Model Mobile Gain Antenna

Rated Probe: Narda 8761D Probe = 10 $\mu\text{W}/\text{cm}^2$ to 20 mW/cm^2

LIMITS: Uncontrolled Exposure
 47 CFR 1.1310 Table 1, (B)

| | |
|-------------------|---|
| 0.3-1.234 MHz: | Limit [mW/cm^2] = 100 |
| 1.34-30 MHz: | Limit [mW/cm^2] = $(180/f^2)$ |
| 30-300 MHz: | Limit [mW/cm^2] = 0.2 |
| 300-1500 MHz: | Limit [mW/cm^2] = $f/1500$ |
| 1500-100,000 MHz: | Limit [mW/cm^2] = 1.0 |

Power, Conducted, W = 40 Watts - 46 dBm
 Power + Ant. Gain, W = 40 + 0 = 40 Watts - 46 dBm
 Limit: Uncontrolled Exposure $F/1500 = 480.01/1500 = 0.32 \text{ mW}/\text{cm}^2$
 Tested Distance: 70 cm Uncontrolled Exposure, 50% Duty Cycle

| Results: | Probe Height, m | Power Density, mW/cm^2 |
|--------------------|-----------------|--|
| at tested distance | 2.0 | 0.08 |
| | 1.8 | 0.10 |
| | 1.6 | 0.12 |
| | 1.4 | 0.20 |
| | 1.2 | 0.29 |
| | 1.0 | 0.24 |
| | 0.8 | 0.10 |
| | 0.6 | 0.06 |
| | 0.4 | 0.04 |
| | 0.2 | 0.05 |

Power Density Calculations: The measured power density readings were summed and the results divided by the number of readings to calculate the average.

For whole body: Average of 0.2 to 2.0 m, $\text{mW}/\text{cm}^2 = 0.128$
 For lower body: Average of 0.2 to 0.8 m, $\text{mW}/\text{cm}^2 = 0.053$
 For upper body: Average of 1.0 to 2.0 m, $\text{mW}/\text{cm}^2 = 0.172$

NOTE: Rule 1.1310 Table 1, B; OET Bulletin 65 Supplement C
 For 480.01 MHz, Limit = $480/1500 = 0.32 \text{ mW}/\text{cm}^2$, whole body average
 Test Result = $0.128 \text{ mW}/\text{cm}^2$, whole body average
 Separation Distance = 70 cm

SUPERVISED BY:

Morton Flom, P. Eng.

Operating Efficiency & Safety (a mandatory FCC Statement)

This statement attests to the fact that the following text will be included in the Instruction Manual supplied with the radio device when delivered to the end-user.

PROFESSIONAL INSTALLATION REQUIRED: To comply with FCC RF Safety rules & avoid possible harmful exposure, this radio device must be professionally installed.

ANTENNA: As supplied by your dealer. For any proposed changes, please contact your dealer.

ANTENNA GAIN: Must not exceed 0 dB as referenced to a dipole.

CAUTION: To comply with FCC RF Exposure limits, a separation distance equal to, or more than as shown below must be maintained between the antenna of this radio device and person/s.

MINIMUM SEPARATION DISTANCE FROM ANTENNA:
70 cm at 50 % duty cycle

MAXIMUM DUTY CYCLE FACTOR: 50% transmit, 50% receiver. Do not operate the transmitter in excess of six minutes at any one time.

NOTE: Use only with the dealer supplied 0 dbd-gain antenna. Consult your dealer for use with other antennas.

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:



Morton Flom, P. Eng.