



360 Herndon Parkway  
Suite 1400  
Herndon, VA 20170  
<http://www.rheintech.com>

## 28 SAR REPORT

Please see the following page

## CERTIFICATE OF COMPLIANCE SAR EVALUATION


<p><b><u>Test Lab:</u></b></p> <p><b>CELLTECH RESEARCH INC.</b> Testing and Engineering Lab 1955 Moss Court Kelowna, B.C. Canada V1Y 9L3 Phone: 250 - 860-3130 Fax: 250 - 860-3110 Toll Free: 1-877-545-6287 e-mail: info@celltechlabs.com web site: www.celltechlabs.com</p>	<p><b><u>Applicant Information:</u></b></p> <p><b>VERTEX STANDARD CO., LTD.</b> 4-8-8 Nakameguro, Meguro-Ku, Tokyo, 153-8644 Japan Attn: Tomiro Ohmoto, Export Manager</p>
---	--

<b>FCC ID:</b>	<b>K66VX-900U-2</b>
<b>Model(s):</b>	<b>VX-900U/600U</b>
<b>EUT Type:</b>	<b>Portable UHF PTT Radio Transceiver</b>
<b>Modulation:</b>	<b>FM</b>
<b>Tx Frequency Range:</b>	<b>400 - 430 MHz</b>
<b>Conducted Power Tested:</b>	<b>5.15 Watts (Low Channel: 400.1 MHz) 5.09 Watts (Mid Channel: 415.1 MHz) 4.80 Watts (High Channel: 429.9 MHz)</b>
<b>Body-Worn Accessories:</b>	<b>1 Belt-Clip, 2 Leather Belt-Holsters</b>
<b>FCC Rule Part(s):</b>	<b>2.1093; ET Docket 96-326</b>

This wireless mobile and/or portable device has been shown to be compliant for localized Specific Absorption Rate (SAR) for controlled environment/occupational exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in ANSI/IEEE Std. C95.3-1999.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Celltech Research Inc. certifies that no party to this application has been denied FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 853(a).



**Shawn McMillen**  
**General Manager**  
**Celltech Research Inc.**



## **TABLE OF CONTENTS**

1.0	<b>INTRODUCTION.....</b>	1
2.0	<b>DESCRIPTION OF EUT.....</b>	1
3.0	<b>SAR MEASUREMENT SYSTEM .....</b>	2
4.0	<b>MEASUREMENT SUMMARY.....</b>	3-6
5.0	<b>DETAILS OF SAR EVALUATION.....</b>	7
6.0	<b>EVALUATION PROCEDURES.....</b>	8
7.0	<b>SYSTEM VALIDATION.....</b>	8
8.0	<b>SAR LIMITS.....</b>	9
9.0	<b>SIMULATED EQUIVALENT TISSUES.....</b>	10
10.0	<b>TISSUE PARAMETERS.....</b>	10
11.0	<b>SYSTEM SPECIFICATIONS.....</b>	11
12.0	<b>TEST EQUIPMENT LIST.....</b>	12
13.0	<b>MEASUREMENT UNCERTAINTIES.....</b>	13
14.0	<b>REFERENCES.....</b>	14
	<b>APPENDIX A - SAR MEASUREMENT DATA.....</b>	15
	<b>APPENDIX B - DIPOLE VALIDATION.....</b>	16
	<b>APPENDIX C - PROBE CALIBRATION.....</b>	17
	<b>APPENDIX D - PHOTOGRAPHS.....</b>	18

**1.0 INTRODUCTION**

This measurement report shows compliance of the VERTEX STANDARD CO., LTD. Model: VX-900U/600U Portable UHF PTT Radio Transceiver FCC ID: K66VX-900U-2 with the regulations and procedures specified in FCC Part 2.1093, ET Docket 96-326 Rules (controlled exposure) for mobile and portable devices. The test procedures, as described in American National Standards Institute C95.1-1992 (1), FCC OET Bulletin 65-1997 were employed. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

**2.0 DESCRIPTION of Equipment Under Test (EUT)**

<b>Rule Part(s)</b>	FCC 2.1093; ET Docket 96.326	<b>Modulation</b>	FM
<b>EUT Type</b>	Portable UHF PTT Radio Transceiver	<b>Tx Frequency Range</b>	400 - 430 MHz
<b>Model No.(s)</b>	VX900U/600U	<b>Max. Conducted Power Tested</b>	5.15 Watts
<b>FCC ID</b>	K66VX-900U-2	<b>Power Supply</b>	Lithium-Ion Battery DC 7.4V 1800mAh
<b>Antenna Type</b>	Whip	<b>Antenna Length</b>	165 mm



*Front of EUT*



*Right Side of EUT*



*Left Side of EUT*



*Rear of EUT*



*EUT with Mic*

### ***3.0 SAR MEASUREMENT SYSTEM***

Celltech Research SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, and the generic twin phantom containing brain or muscle equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE3 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.



*DASY3 SAR Measurement System*

#### 4.0 MEASUREMENT SUMMARY

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the EUT are reported in Appendix A.

#### Face-Held SAR Measurements

Freq (MHz)	Channel	Mode	Conducted Power (W)	Antenna Position	Separation Distance (cm)	SAR (w/kg)	
						100% Duty Cycle	50% Duty Cycle
400.1	Low	Unmod.	5.15	Fixed	4.0	1.63	0.815
415.1	Mid	Unmod.	5.09	Fixed	4.0	1.97	0.985
429.9	High	Unmod.	4.80	Fixed	4.0	1.52	0.76
<b>Mixture Type: Brain                      Dielectric Constant: 48.9                      Conductivity: 0.61</b>			<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT                      Spatial Peak Controlled Exposure/Occupational                      BRAIN: 8.0 W/kg (averaged over 1 gram)</b>				

- Notes:
1. The SAR values found were below the maximum limit of 8.0 w/kg.
  2. The highest SAR value found was 0.985 w/kg (50% duty cycle).
  3. The EUT was tested for face-held SAR with a 4.0cm separation distance between the front of the EUT and the outer surface of the planar phantom.



Face-held SAR Test Setup

**Body-Worn SAR Measurements - With Belt-Clip**

Freq (MHz)	Channel	Mode	Conducted Power (W)	Antenna Position	Separation Distance (cm)	SAR (w/kg)	
						100% Duty Cycle	50% Duty Cycle
400.1	Low	Unmod.	5.15	Fixed	1.4	11.6	5.8
415.1	Mid	Unmod.	5.09	Fixed	1.4	10.9	5.45
429.9	High	Unmod.	4.80	Fixed	1.4	8.57	4.285
<b>Mixture Type: Muscle                      Dielectric Constant: 57.5                      Conductivity: 0.84</b>			<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT                      Spatial Peak Controlled Exposure/Occupational                      BODY: 8.0 W/kg (averaged over 1 gram)</b>				

- Notes: 1. The SAR values found were below the maximum limit of 8.0 w/kg (at 50% duty cycle).  
 2. The highest SAR value found was 5.8 w/kg (50% duty cycle).  
 3. The EUT was tested for body SAR using the supplied belt-clip providing a 1.4cm separation distance between the back of the EUT and the outer surface of the planar phantom.



Body SAR Test Setup with Belt-Clip

**Body-Worn SAR Measurements - With Belt-Holster #1 (13266)**

Freq (MHz)	Channel	Mode	Conducted Power (W)	Antenna Position	Separation Distance (cm)	SAR (w/kg)	
						100% Duty Cycle	50% Duty Cycle
400.1	Low	Unmod.	5.15	Fixed	4.7	2.73	1.365
415.1	Mid	Unmod.	5.09	Fixed	4.7	2.83	1.415
429.9	High	Unmod.	4.80	Fixed	4.7	2.00	1.00
<b>Mixture Type: Muscle                      Dielectric Constant: 57.5                      Conductivity: 0.84</b>			<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT                      Spatial Peak Controlled Exposure/Occupational                      BODY: 8.0 W/kg (averaged over 1 gram)</b>				

- Notes:
1. The SAR values found were below the maximum limit of 8.0 w/kg.
  2. The highest SAR value found was 1.415 w/kg (50% duty cycle).
  3. The EUT was tested for body-worn SAR using the supplied belt-holster (#1) providing a 4.7cm separation distance between the back of the EUT and the outer surface of the planar phantom.



Body SAR Test Setup with Holster #1



**Body-Worn SAR Measurements - With Belt-Holster #2 (13267)**

Freq (MHz)	Channel	Mode	Conducted Power (W)	Antenna Position	Separation Distance (cm)	SAR (w/kg)	
						100% Duty Cycle	50% Duty Cycle
400.1	Low	Unmod.	5.15	Fixed	5.5	1.70	0.85
415.1	Mid	Unmod.	5.09	Fixed	5.5	2.35	1.175
429.9	High	Unmod.	4.80	Fixed	5.5	1.67	0.835
<b>Mixture Type: Muscle                      Dielectric Constant: 57.5                      Conductivity: 0.84</b>			<b>ANSI / IEEE C95.1 1992 - SAFETY LIMIT                      Spatial Peak Controlled Exposure/Occupational                      BODY: 8.0 W/kg (averaged over 1 gram)</b>				

- Notes:
1. The SAR values found were below the maximum limit of 8.0 w/kg.
  2. The highest SAR value found was 1.175 w/kg (50% duty cycle).
  3. The EUT was tested for body SAR using the supplied belt-holster (#2) providing a 5.5 cm separation distance between the back of the EUT and the outer surface of the planar phantom.



Body SAR Test Setup with Holster #2

## ***5.0 DETAILS OF SAR EVALUATION***

The VERTEX STANDARD CO., LTD. Model: VX-900U/600U Portable UHF PTT Radio Transceiver FCC ID: K66VX-900U-2 was found to be compliant for localized Specific Absorption Rate (SAR) based on the following test provisions and conditions:

- 1) The EUT was tested in a face-held configuration with the front of the device placed parallel to and at a nominal distance of 40mm from the outer surface of the planar phantom.
- 2) The EUT was tested in a body-worn configuration with the rear of the device placed parallel to the outer surface of the planar phantom with the attached belt-clip touching the outer surface of the planar phantom, and the belt-clip provided a 1.4cm separation distance between the back of the EUT and the outer surface of the planar phantom.
- 3) The EUT was tested in a body-worn configuration with the rear of the device placed in body holster #1, parallel to the outer surface of the planar phantom, with the body holster touching the outer surface of the planar phantom and providing a 4.7cm separation distance between the back of the EUT and the outer surface of the planar phantom.
- 4) The EUT was tested in a body-worn configuration with the rear of the device placed in body holster #2, parallel to the outer surface of the planar phantom, with the body holster touching the outer surface of the planar phantom and providing a 5.5cm separation distance between the back of the EUT and the outer surface of the planar phantom.
- 5) The EUT was evaluated for SAR at maximum power and the unit was operated for an appropriate period prior to the evaluation in order to minimize drift.
- 6) The device was keyed to operate continuously in the transmit mode for the duration of the test.
- 7) The location of the maximum spatial SAR distribution (Hot Spot) was determined relative to the device and its antenna. This location was then related to a phantom that possesses human like facial attributes. The hot spot location of the EUT occurred just below the mounting point of the antenna. In a normal operating position this places the hotspot just below the left eye. In the absence of nose and lips, this region of the face is fairly planar. Therefore the use of the planar section of the phantom is warranted. The distance of 40mm from the antenna to the planar region of the phantom is large enough that does not create unrealistic loading of the antenna.
- 8) The EUT was tested with a fully charged battery.

## 6.0 EVALUATION PROCEDURES

The Specific Absorption Rate (SAR) evaluation was performed in the following manner:

- a. (i) The evaluation was performed in an applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated at the center frequency of the band at maximum power. The ear position that produced the highest SAR determined which side of the phantom would be used for the entire evaluation. FCC OET Bulletin 65, Supplement C dictates the positioning of the ear-held device relative to the phantom.  
(ii) For face-held and body-worn devices, or devices which can be operated within 20cm of the body, the planar section of the phantom was used. The type of device being evaluated dictated the distance of the EUT to the outer surface of the planar phantom.
- b. The SAR was determined by a pre-defined procedure within the DASY3 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 20mm x 20mm.
- c. For frequencies below 500MHz a 4x4x7 matrix was performed around the greatest spatial SAR distribution found during the area scan of the applicable exposed region. For frequencies above 500MHz a 5x5x7 matrix was performed. SAR values were then calculated using a 3-D spline interpolation algorithm and averaged over spatial volumes of 1 and 10 grams.
- d. If the EUT had any appreciable drift over the course of the evaluation, then the EUT was re-evaluated. Any unusual anomalies over the course of the test also warranted a re-evaluation.

## 7.0 SYSTEM VALIDATION

Prior to the assessment, the system was verified in the planar region of the phantom. For devices operating below 1GHz, an 835MHz dipole or 900MHz was used, depending on the operating frequency of the EUT. For devices operating above 1GHz, an 1800MHz dipole was used. A forward power of 250mW was applied to the dipole and system was verified to a tolerance of  $\pm 3\%$ . The applicable verification is as follows (see Appendix B for validation test plot):

Dipole Validation Kit	Target SAR 1g (w/kg)	Measured SAR 1g (w/kg)
D835V2	2.06	2.04

**8.0 SAR SAFETY LIMITS**

EXPOSURE LIMITS	SAR (W/Kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10g)	4.0	20.0

- Notes: 1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

### 9.0 SIMULATED TISSUES

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution. Preservation with a bactericide is added and visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

INGREDIENT	MIXTURE %		
	835MHz Brain (Validation)	450MHz Brain	450MHz Muscle
Water	40.1	42.0	50.0
Sugar	58.1	56.0	48.2
Salt	0.7	1.7	1.6
HEC	1.0	0.1	0.1
Bactericide	0.1	0.2	0.1

### 10.0 TISSUE PARAMETERS

The dielectric parameters of the fluids were verified prior to the SAR evaluation using an 85070C Dielectric Probe Kit and an 8753E Network Analyzer. The dielectric parameters of the fluid are as follows:

Equivalent Tissue	Dielectric Constant $\epsilon_r$	Conductivity $\sigma$ (mho/m)	$\rho$ (Kg/m <sup>3</sup> )
Brain (835MHz Validation)	44.2 ± 5%	0.80 ± 10%	1000
Brain (450MHz)	48.9 ± 5%	0.61 ± 10%	1000
Muscle (450MHz)	57.5 ± 5%	0.84 ± 10%	1000

## **11.0 ROBOT SYSTEM SPECIFICATIONS**

### **Specifications**

**POSITIONER:** Staubli Unimation Corp. Robot Model: RX60L  
**Repeatability:** 0.02 mm  
**No. of axis:** 6

### **Data Acquisition Electronic (DAE) System**

#### **Cell Controller**

**Processor:** Pentium III  
**Clock Speed:** 450 MHz  
**Operating System:** Windows NT  
**Data Card:** DASY3 PC-Board

#### **Data Converter**

**Features:** Signal Amplifier, multiplexer, A/D converter, and control logic  
**Software:** DASY3 software  
**Connecting Lines:** Optical downlink for data and status info.  
Optical uplink for commands and clock

### **PC Interface Card**

**Function:** 24 bit (64 MHz) DSP for real time processing  
Link to DAE3  
16 bit A/D converter for surface detection system  
serial link to robot  
direct emergency stop output for robot

### **E-Field Probe**

**Model:** ET3DV6  
**Serial No.:** 1387  
**Construction:** Triangular core fiber optic detection system  
**Frequency:** 10 MHz to 6 GHz  
**Linearity:**  $\pm 0.2$  dB (30 MHz to 3 GHz)

### **Phantom**

**Phantom:** Generic Twin  
**Shell Material:** Fiberglass  
**Thickness:** 2.0  $\pm$  0.1 mm

**12.0 TEST EQUIPMENT LIST**

<b>SAR MEASUREMENT SYSTEM</b>		
<b><u>EQUIPMENT</u></b>	<b><u>SERIAL NO.</u></b>	<b><u>CALIB. DATE</u></b>
<b>DASY3 System</b> -Robot -ET3DV6 E-Field Probe -DAE -835MHz Validation Dipole -900MHz Validation Dipole -1800MHz Validation Dipole -Generic Twin Phantom V3.0	599396-01 1387 383 411 054 247 N/A	N/A Sept 1999 Sept 1999 Aug 1999 Aug 1999 Aug 1999 N/A
<b>85070C Dielectric Probe Kit</b>	N/A	N/A
<b>Gigatronics 8652A Power Meter</b> -Power Sensor 80701A -Power Sensor 80701A	1835272 1833535 1833542	Oct 1999 Oct 1999 Oct 1999
<b>E4408B Spectrum Analyzer</b>	US39240170	Nov 1999
<b>8594E Spectrum Analyzer</b>	3543A02721	Mar 2000
<b>8753E Network Analyzer</b>	US38433013	Nov 1999
<b>8648D Signal Generator</b>	3847A00611	N/A
<b>5S1G4 Amplifier Research Power Amplifier</b>	26235	N/A

### 13.0 MEASUREMENT UNCERTAINTIES

Uncertainty Description	Error	Distribution	Weight	Standard Deviation	Offset
<b>Probe Uncertainty</b>					
Axial isotropy	±0.2 dB	U-Shaped	0.5	±2.4 %	
Spherical isotropy	±0.4 dB	U-Shaped	0.5	±4.8 %	
Isotropy from gradient	±0.5 dB	U-Shaped	0	±	
Spatial resolution	±0.5 %	Normal	1	±0.5 %	
Linearity error	±0.2 dB	Rectangle	1	±2.7 %	
Calibration error	±3.3 %	Normal	1	±3.3 %	
<b>SAR Evaluation Uncertainty</b>					
Data acquisition error	±1 %	Rectangle	1	±0.6 %	
ELF and RF disturbances	±0.25 %	Normal	1	±0.25 %	
Conductivity assessment	±10 %	Rectangle	1	±5.8 %	
<b>Spatial Peak SAR Evaluation Uncertainty</b>					
Extrapolated boundary effect	±3 %	Normal	1	±3 %	±5 %
Probe positioning error	±0.1 mm	Normal	1	±1 %	
Integrated and cube orientation	±3 %	Normal	1	±3 %	
Cube Shape inaccuracies	±2 %	Rectangle	1	±1.2 %	
Device positioning	±6 %	Normal	1	±6 %	
<b>Combined Uncertainties</b>				±11.7 %	±5 %

Measurement uncertainties in SAR measurements are difficult to quantify due to several variables including biological, physiological, and environmental. However, the estimated measurement uncertainties in SAR are less than 15-25 %.

According to ANSI/IEEE C95.3, the overall uncertainties are difficult to assess and will vary with the type of meter and usage situation. However, accuracy's of ± 1 to 3 dB can be expected in practice, with greater uncertainties in near-field situations and at higher frequencies (shorter wavelengths), or areas where large reflecting objects are present. Under optimum measurement conditions, SAR measurement uncertainties of at least ± 2dB can be expected.

According to CENELEC, typical worst-case uncertainty of field measurements is ± 5 dB. For well-defined modulation characteristics the uncertainty can be reduced to ± 3 dB.



#### **14.0 REFERENCES**


- (1) ANSI, *ANSI/IEEE C95.1: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 Ghz*, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992;
- (2) Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, FCC, Washington, D.C. 20554, 1997;
- (3) Thomas Schmid, Oliver Egger, and Neils Kuster, “Automated E-field scanning system for dosimetric assessments”, *IEEE Transaction on Microwave Theory and Techniques*, Vol. 44, pp. 105 – 113, January, 1996.
- (4) Niels Kuster, Ralph Kastle, and Thomas Schmid, “Dosimetric evaluation of mobile communications equipment with know precision”, *IEICE Transactions of Communications*, vol. E80-B, no. 5, pp. 645 – 652, May 1997.

***APPENDIX A - SAR MEASUREMENT DATA***

## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (90°,90°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Brain:  $\sigma = 0.61$  mho/m  $\epsilon_r = 48.9$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 1.63 mW/g , SAR (10g): 1.31 mW/g


Face SAR with 4.0cm Separation  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
Low Channel [400.1 MHz]  
Conducted Power: 5.15 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (90°,90°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Brain:  $\sigma = 0.61$  mho/m  $\epsilon_r = 48.9$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 1.97 mW/g, SAR (10g): 1.58 mW/g


Face SAR with 4.0cm Separation  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
Mid Channel [415.1 MHz]  
Conducted Power: 5.09 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (90°,90°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Brain:  $\sigma = 0.61$  mho/m  $\epsilon_r = 48.9$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 1.52 mW/g, SAR (10g): 1.23 mW/g


Face SAR with 4.0cm Separation  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
High Channel [429.9 MHz]  
Conducted Power: 4.80 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 11.6 mW/g, SAR (10g): 8.45 mW/g

Body SAR with Belt-Clip (1.4cm Separation)  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
Low Channel [400.1 MHz]  
Conducted Power: 5.15 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0

450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>

Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0

Cube 4x4x7:

SAR (1g): 10.9 mW/g, SAR (10g): 8.01 mW/g

Body SAR with Belt-Clip (1.4cm Separation)

Portable UHF PTT Radio Transceiver


Vertex Standard Model: VX-900U

Unmodulated Carrier

Mid Channel [415.1 MHz]

Conducted Power: 5.09 Watts


Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 8.57 mW/g, SAR (10g): 6.25 mW/g

Body SAR with Belt-Clip (1.4cm Separation)  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
High Channel [429.9 MHz]  
Conducted Power: 4.80 Watts  
Date Tested: May 3, 2001






## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 2.73 mW/g, SAR (10g): 2.08 mW/g


Body SAR with Holster #1 (13266)  
4.7cm Separation Distance  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
Low Channel [400.1 MHz]  
Conducted Power: 5.15 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 2.83 mW/g, SAR (10g): 2.21 mW/g


Body SAR with Holster #1 (13266)  
4.7cm Separation Distance  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
Mid Channel [415.1 MHz]  
Conducted Power: 5.09 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 2.00 mW/g, SAR (10g): 1.56 mW/g


Body SAR with Holster #1 (13266)  
4.7cm Separation Distance  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
High Channel [429.9 MHz]  
Conducted Power: 4.80 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 1.70 mW/g, SAR (10g): 1.30 mW/g


Body SAR with Holster #2 (13267)  
5.5cm Separation Distance  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
Low Channel [400.1 MHz]  
Conducted Power: 5.15 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 2.35 mW/g, SAR (10g): 1.84 mW/g


Body SAR with Holster #2 (13267)  
5.5cm Separation Distance  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
Mid Channel [415.1 MHz]  
Conducted Power: 5.09 Watts  
Date Tested: May 3, 2001



## Vertex Standard Co. Ltd. FCC ID:K66VX-900U-2

Generic Twin Phantom; Flat Section; Position: (270°,270°)  
Probe: ET3DV6 - SN1387; ConvF(6.76,6.76,6.76); Crest factor: 1.0  
450MHz Muscle:  $\sigma = 0.84$  mho/m  $\epsilon_r = 57.5$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 4x4x7:  
SAR (1g): 1.67 mW/g, SAR (10g): 1.31 mW/g

Body SAR with Holster #2 (13267)  
5.5cm Separation Distance  
Portable UHF PTT Radio Transceiver  
Vertex Standard Model: VX-900U  
Unmodulated Carrier  
High Channel [429.9 MHz]  
Conducted Power: 4.80 Watts  
Date Tested: May 3, 2001




***APPENDIX B - DIPOLE VALIDATION***

## Dipole 835 MHz

Generic Twin Phantom; Flat Section; Position: (90°,90°);  
Probe: ET3DV6 - SN1387; ConvF(6.43,6.43,6.43); Crest factor: 1.0;  
Brain 835 MHz:  $\sigma = 0.80$  mho/m  $\epsilon_r = 44.2$   $\rho = 1.00$  g/cm<sup>3</sup>  
Coarse: Dx = 20.0, Dy = 20.0, Dz = 10.0  
Cube 5x5x7  
SAR (1g): 2.04 mW/g, SAR (10g): 1.34 mW/g

Validation Date: May 3, 2001





### Validation Dipole D835V2 SN:411, $d = 15\text{mm}$

Frequency: 835 MHz; Antenna Input Power: 250 [mW]


Generic Twin Phantom; Flat Section; Grid Spacing:  $D_x = 20.0$ ,  $D_y = 20.0$ ,  $D_z = 10.0$

Probe: ET3DV5 - SN1342/DAE3; ConvF(5.75,5.75,5.75); Brain 835 MHz:  $\sigma = 0.80$  mho/m  $\epsilon_r = 44.2$   $\rho = 1.00$  g/cm<sup>3</sup>

Cubes (2): Peak:  $3.07$  mW/g  $\pm 0.05$  dB, SAR (1g):  $2.06$  mW/g  $\pm 0.05$  dB, SAR (10g):  $1.38$  mW/g  $\pm 0.05$  dB, (Worst-case extrapolation)

Penetration depth: 13.6 (12.7, 14.8) [mm]

Powerdrift: -0.00 dB



***APPENDIX C - PROBE CALIBRATION***

# Probe ET3DV6

**SN:1387**

Manufactured:	September 21, 1999
Last calibration:	September 22, 1999

Calibrated for System DASY3

**DASY3 - Parameters of Probe: ET3DV6 SN:1387**

## Sensitivity in Free Space

NormX	<b>1.55</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	<b>1.65</b> $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	<b>1.64</b> $\mu\text{V}/(\text{V}/\text{m})^2$

## Diode Compression

DCP X	<b>98</b> mV
DCP Y	<b>98</b> mV
DCP Z	<b>98</b> mV

## Sensitivity in Tissue Simulating Liquid

**Brain**                      **450 MHz**                       $\epsilon_r = 48 \pm 5\%$                        $\sigma = 0.50 \pm 10\%$  mho/m

ConvF X	<b>6.76</b> extrapolated	Boundary effect:	
ConvF Y	<b>6.76</b> extrapolated	Alpha	<b>0.30</b>
ConvF Z	<b>6.76</b> extrapolated	Depth	<b>2.52</b>

**Brain**                      **900 MHz**                       $\epsilon_r = 42.5 \pm 5\%$                        $\sigma = 0.86 \pm 10\%$  mho/m

ConvF X	<b>6.34</b> $\pm 7\%$ (k=2)	Boundary effect:	
ConvF Y	<b>6.34</b> $\pm 7\%$ (k=2)	Alpha	<b>0.47</b>
ConvF Z	<b>6.34</b> $\pm 7\%$ (k=2)	Depth	<b>2.25</b>

**Brain**                      **1500 MHz**                       $\epsilon_r = 41 \pm 5\%$                        $\sigma = 1.32 \pm 10\%$  mho/m

ConvF X	<b>5.78</b> interpolated	Boundary effect:	
ConvF Y	<b>5.78</b> interpolated	Alpha	<b>0.69</b>
ConvF Z	<b>5.78</b> interpolated	Depth	<b>1.88</b>


**Brain**                      **1800 MHz**                       $\epsilon_r = 41 \pm 5\%$                        $\sigma = 1.69 \pm 10\%$  mho/m


ConvF X	<b>5.50</b> $\pm 7\%$ (k=2)	Boundary effect:	
ConvF Y	<b>5.50</b> $\pm 7\%$ (k=2)	Alpha	<b>0.81</b>
ConvF Z	<b>5.50</b> $\pm 7\%$ (k=2)	Depth	<b>1.70</b>

## Sensor Offset


Probe Tip to Sensor Center	<b>2.7</b>	mm
Optical Surface Detection	<b>1.6 <math>\pm</math> 0.2</b>	mm

### Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$






### Isotropy Error ( $\phi$ ), $\theta = 0^\circ$





## Frequency Response of E-Field

( TEM-Cell:ifi110, Waveguide R22, R26 )




## Dynamic Range f(SAR<sub>brain</sub>) ( TEM-Cell:ifi1110 )






## Conversion Factor Assessment




## Receiving Pattern ( $\phi$ ) ( in brain tissue, z = 5 mm )



***APPENDIX D - PHOTOGRAPHS***


**FACE-HELD SAR TEST SETUP PHOTOGRAPHS**  
**4.0cm Separation Distance**



**BODY-WORN SAR TEST SETUP PHOTOGRAPHS**  
**Belt-Clip with 1.4cm Separation Distance**




**BODY-WORN SAR TEST SETUP PHOTOGRAPHS**  
**Leather Belt-Holster #1 -13266**  
**(4.7cm Separation Distance)**



**BODY-WORN SAR TEST SETUP PHOTOGRAPHS**  
**Leather Belt-Holster #2 -13267**  
**(5.5cm Separation Distance)**



### EUT PHOTOGRAPHS



## BODY-WORN ACCESSORIES

### MICROPHONE





## BODY-WORN ACCESSORIES

### BELT-CLIP



**BODY-WORN ACCESSORIES**  
**LEATHER BELT HOLSTER #1 (13266)**



**BODY-WORN ACCESSORIES**  
**LEATHER BELT HOLSTER #2 (13267)**

