Issue Date: 20<sup>th</sup> April 2001 SGS Serial Number: DUR22909/EMC/ST/01/C

Issue Number: 2

# **Radiated Emissions Test Configuration**



### **Radiated Emissions Environmental Conditions**

Power Supply	3V DC using x2 'C' size batteries	
Temperature	8°C	
Relative Humidity	49%	
Barometric Pressure	1011mb	

### **Radiated Emissions Measurement Uncertainties**

Frequency	± 200kHz
Amplitude	± 4.6dB

The uncertainties stated are calculated in accordance with the requirements of UKAS with a confidence level of 95%.

# Test Equipment Used

Equipment Type	Model Number	Last Calibration Date	Calibration Interval
Active loop antenna	EMCO 6152	7/8/98	3 Years
Spectrum Analyser	HP 8563E	10/5/00	1 Year

# TEST REPORT

Page 11 of 12

Issue Date: 20<sup>th</sup> April 2001 SGS Serial Number: DUR22909/EMC/ST/01/C Issue Number: 2

## 7.5 Transmitter Radiated Emissions 30 MHz - 1 GHz - Intentional Radiator

CFR Clause	15.209
Frequency Range	30 MHz – 1 GHz

### **Operating Mode**

The EUT was operating whilst the transmitter frequency was set at 33 kHz and repeated when set to 8 kHz.

#### **Test Results**

#### Transmitter at 33 kHz

Frequency (MHz)	3m Peak Measurement (dBμV/m)	Limit at 3m (dBµV/m)
110	17.13	43.52
262	19	46.00
267.35	18.5	46.00
271.93	18.92	46.00
276.57	19.12	46.00
850*	29.42	46.00

#### Transmitter at 8 kHz

Frequency (MHz)	3m Peak Measurement (dBμV/m)	Limit (dBμV/m)
114.67	24.26	43.52
258.05	19.68	46.00
267.3	17.97	46.00
271.93	19.35	46.00
600*	26.14	46.00
850*	29.42	46.00

<sup>\*</sup> Noise floor figures of test equipment.

### Test Method

As per ANSI C63.4: 1992

Frequency Range tested = 30 MHz to 1 GHz (as per sec 15.33 (a)(4)).

Measurement Detector Details: Peak, 300Hz bandwidth at frequencies below 150 kHz, 10 kHz at frequencies above 150 kHz.

Measurements were performed at 3m.

Issue Date: 20th April 2001 SGS Serial Number: DUR22909/EMC/ST/01/C

Issue Number: 2

# **Radiated Emissions Test Configuration**



### **Radiated Emissions Environmental Conditions**

Power Supply	3V DC using 2x 'C' size batteries	
Temperature	14°C	
Relative Humidity	32%	
Barometric Pressure	989mb	

#### **Radiated Emissions Measurement Uncertainties**

Frequency	± 200kHz
Amplitude	± 4.6dB

The uncertainties stated are calculated in accordance with the requirements of UKAS with a confidence level of 95%.

### Test Equipment Used

Equipment Type	Model Number	Last Calibration Date	Calibration Interval
Biconilog antenna	EMCO 3142	22/6/99	2 Years
Spectrum Analyser	HP 8563E	10/5/00	1 Year