

APPENDIX A DLNA ATTENUATION CHARACTERISTICS – A781-500

Table 3.2.1.6-1: Transmit Port to the Antenna Port Rejection Characteristics, Type F

Frequency (MHz)			Rejection
0.0	To	1525.0	> 80 dB
1525.0	To	1559.0	>120 dB
1559.0	To	1585.0	>111 dB
1585.0	To	1605.0	> 95 dB
1605.0	To	1610.0	> 62 dB
1610.0	To	1614.0	> 40 dB
1614.0	To	1620.0	> 30 dB
1620.0	To	1624.5	> 20 dB
1624.5	To	1625.5	> 10 dB
1625.5	To	1626.5	Decreases
1626.5	To	1633.0	Insertion loss < 1.3 dB
1633.0	To	1660.5	Insertion loss < 0.8 dB
1660.5	to	1735.0	Increases
1735.0	to	1865.0	> 50 dB
1865.0	to	3250.0	> 20 dB
3250.0	To	3333.0	> 50 dB
3330.0	to	4000.0	> 40 dB
4000.0	to	12000.0	> 50 dB
12000.0	to	18000.0	> 15 dB

**Table 3.2.1.6-2: Transmit Port to the Antenna Port Rejection Characteristics Type F
Between 55°C and 70°C**

Frequency (MHz)			Rejection
1625.0	to	1625.5	< 2.5 dB

Note: 1660.5 to 1735.0 Loss =0.8
1625.5 to 1626.5 Loss = 1.3