



# Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

## Test Report

Prepared for: EMS Technologies Canada Ltd.

Model: A781-500

Description: Aeronautical Satcom Transceiver

Serial Number: N/A

FCC ID: K6KA781-MK4

To

FCC Part 1.1310

Date of Issue: May 9, 2016

On the behalf of the applicant:

EMS Technologies Canada Ltd.  
400 Maple Grove Rd  
Ottawa, Ontario K2V 1B8  
Canada

Attention of:

Steven Mills  
(613)591-6040  
[Steven.Mills2@Honeywell.com](mailto:Steven.Mills2@Honeywell.com)

Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p1610046

Alex Macon  
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing  
All results contained herein relate only to the sample tested

### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	March 22, 2016	Alex Macon	Original Document

## ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

**Non-accredited tests contained in this report:**

N/A

### **EUT Description**

**Model:** A781-500

**Description:** Aeronautical Satcom Transceiver

**Firmware:** N/A

**Software:** N/A

**Serial Number:** N/A

### Source Based Time Averaged Power Calculation

#### Average Power calculations

Average Power = Peak Power \* duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
1643.5	46238	100	46238

### Minimum Safe Distance Evaluation

This is a mobile device used in Uncontrolled Exposure environment.

**Limits Controlled Exposure**  
**47 CFR 1.1310**  
**Table 1, (A)**

0.3-3.0 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
3.0-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (900/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 1.0
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/300
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 5

**Limits Uncontrolled Exposure**  
**47 CFR 1.1310**  
**Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 1.0

### Test Data

Test Frequency, MHz	1643.5
Power, Conducted, mW (P)	46238
Antenna Gain Isotropic	17 dBi
Antenna Gain Numeric (G)	50.11
Antenna Type	patch
Limit (L)	1.0

$R = \sqrt{(PG/4\pi L)}$	
Distance (R) cm	429.5cm

END OF TEST REPORT