



**Giant Electronics Ltd.**

Application  
For  
Permissive Change Class II

Two Way Radio with GMRS, FRS, and Weather Band Receiver

**(FCC ID: K7GT9500)**

0715190  
TL/ ac  
August 17, 2007

- The evaluation data of the report will be kept for 3 years from the date of issuance.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek Testing Services Hong Kong Ltd.**

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.  
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: [www.hk.intertek-etlsemko.com](http://www.hk.intertek-etlsemko.com)

---

# INTERTEK TESTING SERVICES

---

## SUMMARY OF CONTENTS

### LIST OF EXHIBITS

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Spurious Emission
<i>EXHIBIT 4:</i>	Technical Specifications
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Photographs
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Part List
<i>EXHIBIT 9:</i>	RF Exposure Info
<i>EXHIBIT 10:</i>	Confidentiality Request

---

## INTERTEK TESTING SERVICES

---

### MEASUREMENT/TECHNICAL REPORT

**Application** : Giant Electronics Ltd.  
**Trade Name/Model No** : Motorola/ T9550  
**Date** : August 17, 2007

This report concerns (check one:) Original Grant \_\_\_\_\_ Class II Change  X

Equipment Type: FRF – Part 95 Family Radio Face Held Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes \_\_\_\_\_ No  X

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

---

Report prepared by:

Leung Wai Leung, Tommy  
Intertek Testing Services Hong Kong Ltd.  
2/F., Garment Centre,  
576 Castle Peak Road,  
Kowloon, Hong Kong.  
Phone: 852-2173-8538  
Fax: 852-2741-1693

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

<b>1.0 General Description</b> .....	2
1.1 Product Description .....	2
1.2 Purpose of Application.....	3
1.3 Test Methodology.....	3
1.4 Test Facility.....	3
<b>2.0 System Test Configuration</b> .....	5
2.1 Justification .....	5
2.2 EUT Exercising Software.....	6
2.3 Special Accessories .....	6
2.4 Measurement Uncertainty .....	6
2.5 Equipment Modification .....	6
<b>3.0 Spurious Emission (Section 95.635(b))</b> .....	8
3.1 Field Strength of Spurious Radiation.....	9
<b>4.0 Technical Specifications</b> .....	15
<b>5.0 Product Labelling</b> .....	19
<b>6.0 Equipment Photographs</b> .....	22
<b>7.0 Instruction Manual</b> .....	24
<b>8.0 Part List</b> .....	26
<b>9.0 RF Exposure Info</b> .....	28
<b>10.0 Confidentiality Request</b> .....	30

## INTERTEK TESTING SERVICES

---

### List of attached file

Exhibit type	File Description	Filename
Operation Description	Technical Description	descri.pdf
Operation Description	Purpose of Application	product change.pdf
Test Report	Spurious Emission	spurious.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	config photos.doc
Internal Photo	Internal Photo	internal photos.doc
External Photo	External Photo	external photos.doc
Test Report	Part List	partlist.pdf
RF Exposure Info	SAR Test Report	SAR report 1 of 2.pdf SAR report 2 of 2.pdf
Cover Letter	Confidentiality Request	request.pdf

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 1**

**GENERAL DESCRIPTION**

## **INTERTEK TESTING SERVICES**

---

### **1.0 General Description**

#### **1.1 Product Description**

The Equipment Under Test (EUT) is a Two Way Radio with GMRS, FRS, and Weather Band operating between 462.5500MHz and 467.7125MHz. The EUT is powered by 3.6V (1 x 3.6V "Ni-MH" type rechargeable battery) or 4.5V (3 x "AA" size 1.5V alkaline batteries). According to the user manual instructions, the EUT is turned off while in charging tray.

##### **Transmitter Portion**

- (i) Type of Emission : GMRS: 5K52F3E; FRS: 5K52F3E
- (ii) Frequency Range : GMRS 15 Channels from 462.5500MHz to 462.7250MHz  
FRS 7 Channels from 467.5625MHz to 467.7125MHz
- (iii) Maximum Power Rating : GMRS: 1.03W ERP; FRS: 0.11W ERP
- (iv) Antenna Type : Integral

The brief circuit description is saved with filename: descri.pdf

## INTERTEK TESTING SERVICES

---

### 1.2 Purpose of Application

The purpose of application is saved with filename: purpose of change.pdf.

As the RF module remained unchanged, only results of spurious emission was included in this report.

### 1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003) and ANSI/TIA-603-B-2002. All measurement were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. For each scan, the procedure of maximizing emissions in Appendices D and E were followed. All Radiated tests were performed at an antenna the EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

### 1.4 Test Facility

The open area test site used to collect the emission data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. The test facility and site measurement data have been fully placed on file with the FCC.



**INTERTEK TESTING SERVICES**

---

**EXHIBIT 2**  
**SYSTEM TEST CONFIGURATION**

## INTERTEK TESTING SERVICES

---

### 2.0 **System Test Configuration**

#### 2.1 Justification

The device was configured for testing in a typical fashion (as a customer would normally use it). The device was placed on a turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes. The device have been tested with headset and without headset when the radiated emissions are measured.

The device was powered by 3 x new "AA" size 1.5V alkaline batteries.

The frequency range from 30 MHz to 4.69 GHz was searched for spurious emissions from the device. Only those emissions reported were detected. All other emissions were at least 20 dB below the applicable limits.

## INTERTEK TESTING SERVICES

---

### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the PTT button is pushed, a signal is transmitted.

### 2.3 Special Accessories

No special accessory is needed for compliance of this device.

### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

### 2.5 Equipment Modification

Any modification installed previous to testing by Giant Electronics Ltd. will be incorporated in each production model sold/leased in the United States.


No modification were installed by Intertek Testing Services Hong Kong Ltd.

### 2.6 Support Equipment

A headset with 1.2m unshielded cable. (Supplied by Client)

*Confirmed by:*

*Leung Wai Leung, Tommy  
Manager  
Intertek Testing Services Hong Kong Ltd.  
Agent for Giant Electronics Ltd.*



\_\_\_\_\_  
Signature

\_\_\_\_\_  
August 17, 2007 Date

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 3**

**SPURIOUS EMISSION**

## INTERTEK TESTING SERVICES

---

### 3.0 **Spurious Emission (Section 95.635)**

In order to satisfy the 95.635 requirement, the spurious emission from the EUT are measured and shown in the Exhibit 6.1.

---

## INTERTEK TESTING SERVICES

---

### 3.1 Field Strength of Spurious Radiation (Section 95.635)

#### A. Test Equipment

Equipment	Brand Name	Model No.
Antenna	EMCO	A100, 3148, 3104C, 3115
Spectrum Analyzer	ADVANTEST	U3661
Test receiver	Rohde & Schwarz	ESVS30
RF Filter	Trilithic	3VF500/1000-5-50-CC
Signal Generator	IFR	2023B

#### B. Testing Procedure

Radiated emission measurements were performed according to the procedures in ANSI C63.4(2003). All measurements were performed in Open Area Test Sites located at Roof Top of Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.

## **INTERTEK TESTING SERVICES**

---

### **C. Radiated Emission Configuration Photograph**

#### Worst Case Radiated Emission

For electronic filing, the radiated emission configurations photograph is saved with filename: config photos.doc

---

## INTERTEK TESTING SERVICES

---

### C. Test Result

**Giant Electronics Ltd.  
Motorola/ T9550**

**Table 1(a)**

1) Unwanted emission from CARRIER  $\pm 6.25\text{kHz}$  to CARRIER  $\pm 31.25\text{kHz}$

(Refer to the plots which is saved with filename: spurious.pdf)

<b>Region</b>	<b>Unwanted emission</b>	
	<b>Channel 4</b>	<b>Channel 11</b>
CARRIER $\pm 6.25\text{kHz}$ to $\pm 12.5\text{kHz}$	<25dB	<25dB
CARRIER $\pm 12.5\text{kHz}$ to $\pm 31.25\text{kHz}$	<35dB	<35dB



---

---

## INTERTEK TESTING SERVICES

---

---

**Table 1(b): Channel 4**

<b>Frequency (MHz)</b>	<b>Effective Radiated Power (dBm)</b>	<b>Transmission Power (dBm)</b>	<b>Attenuation (dBc)</b>	<b>Limit (dB)</b>	<b>Margin (dB)</b>
231.319	-47.8	29.3	77.1	42.3	-34.8
693.956	-47.2	29.3	76.5	42.3	-34.2
925.274	-39.0	29.3	68.3	42.3	-26.0
1156.593	-42.5	29.3	71.8	42.3	-29.5
1387.911	-23.2	29.3	52.5	42.3	-10.2
1619.230	-35.0	29.3	64.3	42.3	-22.0
1850.548	-21.2	29.3	50.5	42.3	-8.2
2081.867	-36.0	29.3	65.3	42.3	-23.0
2313.185	-35.0	29.3	64.3	42.3	-22.0
2544.504	-29.9	29.3	59.2	42.3	-16.9
2775.822	-28.0	29.3	57.3	42.3	-15.0
3007.141	-36.6	29.3	65.9	42.3	-23.6
3238.459	-28.0	29.3	57.3	42.3	-15.0
3469.778	-41.0	29.3	70.3	42.3	-28.0
3701.096	-33.6	29.3	62.9	42.3	-20.6
3932.415	-38.8	29.3	68.1	42.3	-25.8
4163.733	-33.9	29.3	63.2	42.3	-20.9
4395.052	-37.0	29.3	66.3	42.3	-24.0
4626.370	-33.2	29.3	62.5	42.3	-20.2

- Remark: 1. Transmission power is 29.3 dBm or -0.7 dB(W).
2. According to Section 95.635(b7), the unwanted emission should be attenuated below TP by at least  $43 + 10 \log_{10} (TP)$  dB or 42.3 dB.
3. The test is performed according to ANSI/TIA-603-B-2002.

Test Engineer: Ken Sit

Date of Test: July 1-26, 2007

---

---

## INTERTEK TESTING SERVICES

---

---

**Table 1(b): Channel 11**

<b>Frequency (MHz)</b>	<b>Effective Radiated Power (dBm)</b>	<b>Transmission Power (dBm)</b>	<b>Attenuation (dBc)</b>	<b>Limit (dB)</b>	<b>Margin (dB)</b>
233.819	-24.8	22.3	47.1	35.3	-11.8
701.456	-42.8	22.3	65.1	35.3	-29.8
935.274	-32.9	22.3	55.2	35.3	-19.9
1169.093	-40.0	22.3	62.3	35.3	-27.0
1402.911	-32.6	22.3	54.9	35.3	-19.6
1636.730	-29.9	22.3	52.2	35.3	-16.9
1870.548	-35.0	22.3	57.3	35.3	-22.0
2104.367	-34.0	22.3	56.3	35.3	-21.0
2338.185	-32.2	22.3	54.5	35.3	-19.2
2572.004	-31.1	22.3	53.4	35.3	-18.1
2805.822	-27.6	22.3	49.9	35.3	-14.6
3039.641	-38.0	22.3	60.3	35.3	-25.0
3273.459	-42.0	22.3	64.3	35.3	-29.0
3507.278	-42.2	22.3	64.5	35.3	-29.2
3741.096	-43.8	22.3	66.1	35.3	-30.8
3974.915	-44.6	22.3	66.9	35.3	-31.6
4208.733	-44.0	22.3	66.3	35.3	-31.0
4442.552	-43.1	22.3	65.4	35.3	-30.1
4676.370	-42.2	22.3	64.5	35.3	-29.2

- Remark: 1. Transmission power is 22.3 dBm or -7.7 dB(W).
2. According to Section 95.635(b7), the unwanted emission should be attenuated below TP by at least  $43 + 10 \log_{10} (TP)$  dB or 35.3 dB.
3. The test is performed according to ANSI/TIA-603-B-2002.

Test Engineer: Ken Sit

Date of Test: July 1-26, 2007

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 4**

**TECHNICAL SPECIFICATIONS**

## INTERTEK TESTING SERVICES

---

### 4.0 Technical Specifications

## INTERTEK TESTING SERVICES

---

### 4.1 Block Diagram

For electronic filing, the block diagram of the transceiver is saved with filename: block.pdf

Figure 4.1 Block Diagram

## INTERTEK TESTING SERVICES

---

### 4.2 Schematic Diagram

For electronic filing, the schematic diagram of the transceiver is saved with filename: circuit.pdf

Figure 4.2 Schematic Diagram

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 5**

**PRODUCT LABELLING**

## INTERTEK TESTING SERVICES

---

### 5.0 Product Labelling



## INTERTEK TESTING SERVICES

---

### 5.1 Label Artwork & Location

#### Figure 5.1 Label Artwork & Location

An engineering drawing of the label which will be permanently affixed to the unit.  
For electronic filing, the label artwork & location are saved with filename: label.pdf

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 6**  
**PHOTOGRAPHS**

## INTERTEK TESTING SERVICES

---

### 6.0 Equipment Photographs

For electronic filing, photographs of the tested EUT are saved with filename: external photos.doc and internal photos.doc

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 7**

**INSTRUCTION MANUAL**

## INTERTEK TESTING SERVICES

---

### 7.0 Instruction Manual

This manual will be provided to the end-user with each unit sold/leased in the United States.

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 8**

**PART LIST**

## INTERTEK TESTING SERVICES

---

### 8.0 Part List

For electronic filing, a preliminary copy of the Part List is saved with filename: partlist.pdf

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 9**

**RF EXPOSURE INFO**



## INTERTEK TESTING SERVICES

---

### 9.0 RF Exposure Info

The RF Safety Information is shown on P.1 of User Manual.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 10**

**CONFIDENTIALITY REQUEST**

## INTERTEK TESTING SERVICES

---

### 10.0 Confidentiality Request

For electronic filing, a confidentiality request is saved with filename: request.pdf