



# FCC RADIO EXPOSURE TEST REPORT

FCC ID : K7S-03571  
Equipment : AX3200 Dual Band Gigabit WiFi 6 Router  
Brand Name : LINKSYS  
Model Name : E8450, E8420  
Applicant : Belkin International, Inc.  
12045 East Waterfront Dr. Playa Vista California  
United States 90094  
Standard : 47 CFR Part 2.1091

The product was received on Jun. 22, 2020, and testing was started from Jun. 30, 2020 and completed on Jul. 20, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

  
Approved by: Cliff Chang

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
<b>1 General Description .....</b>	<b>5</b>
1.1 EUT General Information .....	5
1.2 Table for Multiple Listing .....	5
1.3 Table Information for DDR and NAND Flash .....	6
1.4 Testing Location .....	6
<b>2 Maximum Permissible Exposure .....</b>	<b>7</b>
2.1 Limit of Maximum Permissible Exposure .....	7
2.2 MPE Calculation Method.....	7
2.3 Calculated Result and Limit.....	8

### Photographs of EUT v01



**History of this test report**

Report No.	Version	Description	Issued Date
FA052055	01	Initial issue of report	Aug. 13, 2020



### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: **Sam Chen**

Report Producer: **Viola Huang**



# 1 General Description

## 1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)

## 1.2 Table for Multiple Listing

Model Name	USB Port
E8450	V
E8420	X

From the above models, model: E8450 was selected as representative model for the test and its data was recorded in this report.



### 1.3 Table Information for DDR and NAND Flash

The detail information for DDR and NAND Flash is as following:

Item	DDR		NAND Flash	
	Brand Name	Model Name	Brand Name	Model Name
Main source	Winbond	W634GG6NB-12	Fidelix	FM35Q1GA-IB
Second source	KINGSTON	D2516ECMDXGJD-U	Winbond	W25N01GVZEIG

The EUT has four types, which are identical to each other in all aspects except for the following table:

EUT	DDR	NAND Flash
1	Main source	Main source
2	Main source	Second source
3	Second source	Main source
4	Second source	Second source

### 1.4 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.



## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 24 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )
2.4G;G1D	4.50	29.97	34.47	0.50	34.97	3.14051	24	0.43388	1.00000
5.2G;D1D	5.70	27.28	32.98	0.50	33.48	2.22844	24	0.30786	1.00000
5.8G;D1D	5.50	29.84	35.34	0.50	35.84	3.83707	24	0.53011	1.00000

Simultaneous Transmission Analysis Mode: WLAN 2.4GHz+WLAN 5GHz

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm <sup>2</sup> )	S Limit (mW/cm <sup>2</sup> )	Ratio (S/Limit)
2.4G;G1D	4.50	29.97	34.47	0.50	34.97	3.14051	24	0.43388	1.00000	0.43388
5.8G;D1D	5.50	29.84	35.34	0.50	35.84	3.83707	24	0.53011	1.00000	0.53011
									Sum Ratio	0.96399
									Ratio Limit	1

Note: The above antenna gain was declared by manufacturer.

————THE END————