



BELKIN INTERNATIONAL
 12045 East Waterfront Drive
 Playa Vista
 CA 90094-2536 USA
 P 310 751 5100
 F 310 751 5969
 belkin.com

Applicant: Belkin International, Inc.	
FCC ID: K7SAUF001V2	
Date: 2021-06-15	
RF Exposure Requirements (FCC KDB 680106 D01 v03r01)	
Requirements	Statements
(a) Power transfer frequency is less than 1 MHz	The resonator system shall operate at 127.8kHz
(b) Output power from each primary coil is less than 15 watts	10W
(c) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Single Coil
(d) Client device is placed directly in contact with the transmitter.	Client device is placed directly in contact with the transmitter.
(e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	It's mobile device, and had provided RF exposure report to evaluate
(f) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Please refer to RF exposure Report

Rossi Wu
 Senior Regulatory Compliance Engineer
 Belkin International, Inc.
 TEL: +1 310 633 9309*2960
 E-mail: Rossi.Wu@belkin.com