



Test Report No.: FM2101WDG0287



RF EXPOSURE TEST REPORT



Applicant	Belkin International, Inc
Address	12045 East Waterfront Drive, Playa Vista, CA 90094, USA

Manufacturer or Supplier	Belkin International, Inc.
Address	12045 East Waterfront Drive, Playa Vista, CA 90094 USA
Product	BOOST↑CHARGE™ Magnetic Wireless Power Bank
Brand Name	belkin
Model	BPD002
Additional Model & Model Difference	N/A
Date of tests	Jan. 12, 2021 ~ Feb. 20, 2021

The submitted sample of the above equipment has been tested according to the requirements of the following standard:

- 47 CFR PART 1, Subpart I, Section 1.1310
- KDB 680106 D01

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	
	Data: Mar. 05, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RF EXPOSURE TEST REPORT	1
RELEASE CONTROL RECORD.....	3
1. GENERAL INFORMATION.....	4
1.1. GENERAL DESCRIPTION OF EUT	4
2. RF EXPOSURE MEASUREMENT	5
2.1 LIMITS	5
2.2 DESCRIPTION OF SUPPORT UNITS.....	5
2.3 CONFIGURATION OF SYSTEM UNDER TEST	6
2.4 TEST SETUP FOR WPC.....	6
2.5 EQUIPMENTS USED DURING TEST.....	7
2.6 TEST POINT DESCRIPTION	7
2.7 TEST RESULTS	8
3. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	13



**BUREAU
VERITAS**

Test Report No.: FM2101WDG0287

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2101WDG0287	Original release	Mar. 05, 2021



1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

FCC ID	K7SBPD002
PRODUCT	BOOST↑CHARGE™ Magnetic Wireless Power Bank
MODEL NO.	BPD002
ADDITIONAL MODEL	N/A
POWER SUPPLY	Input USB-C: 5V=2A Output Wireless: 5V=5W Cell Capacity: 9.25Wh, 3.7V, 2500mAh
MODULATION TECHNOLOGY	FSK
OPERATING FREQUENCY RANGE	111KHz ~ 148KHz
ANTENNA TYPE	Coil Antenna
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	See notes 4

NOTES:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- Please refer to the EUT photo document (Reference No.: 2101WDG0287) for detailed product photo.
- The cable supplied is as follows:

ID	Descriptions	Qty.	Length(m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	EUT USB-C to USB-C black cable	1	1.0m	Y	0	NT-101
2	EUT USB-C to USB-C white cable	1	1.0m	Y	0	NT-100

Note: Cable 1 and cable 2 are identical except the color of appearance, cable 1 was selected for all test.



2. RF EXPOSURE MEASUREMENT

2.1 LIMITS

§ 1.1310 The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency(RF) radiation as specified in § 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

Reference KDB 680106 D01 RF Exposure Wireless Charging App v03

The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.


2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Receiver load	N/A	N/A	N/A	N/A



2.3 CONFIGURATION OF SYSTEM UNDER TEST



2.4 TEST SETUP FOR WPC



Note: Measurements should be made from all sides and the top of the primary/client pair, with the 0cm, 2 cm, 4cm, 6cm, 8cm, or 10 cm measured from the center of the probe(s) to the edge of the device.




2.5 EQUIPMENTS USED DURING TEST

Item	Test Equipment	Manufacturer	Model No.	S/No	Due date.
1	3m Semi-Anechoic Chamber	ETS-LINDGRE N	7m*4m*3m	NSEMC003	2021-03-19
2	B-field Probe	Narda	Y2006	L-0017	2021-12-23
3	E-Field probe	Narda	NBM-520	2403/01B	2021-12-23

NOTE: 1. The test was performed in RS chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2.6 TEST POINT DESCRIPTION





2.7 TEST RESULTS

Standby Mode 1: EUT USB-C port input + Standby (distance 0 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	4.87	3.53	2.03	2.45	6.32
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-609.13	-610.47	-611.97	-611.55	-607.68
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-302.13	-303.47	-304.97	-304.55	-300.68

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.851	0.642	0.247	0.345	0.761
Max H-Field(A/m)	0.678	0.511	0.197	0.275	0.606
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-0.952	-1.119	-1.433	-1.355	-1.024
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.137	-0.304	-0.618	-0.540	-0.209

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 2: EUT USB-C port input + Receiver load operating (distance 0 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	4.21	4.33	3.54	3.95	6.38
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-609.79	-609.67	-610.46	-610.05	-607.62
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-302.79	-302.67	-303.46	-303.05	-300.62

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.237	0.274	0.248	0.241	0.246
Max H-Field(A/m)	0.189	0.218	0.197	0.192	0.196
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.441	-1.412	-1.433	-1.438	-1.434
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.626	-0.597	-0.618	-0.623	-0.619

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.



Charging Mode 3: EUT USB-C port input + Receiver load operating (distance 2 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	3.52	2.66	2.34	2.57	4.69
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-610.48	-611.34	-611.66	-611.43	-609.31
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-303.48	-304.34	-304.66	-304.43	-302.31

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.24	0.266	0.234	0.231	0.233
Max H-Field(A/m)	0.191	0.212	0.186	0.184	0.186
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.439	-1.418	-1.444	-1.446	-1.444
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.624	-0.603	-0.629	-0.631	-0.629

Measurements was made from all sides and the top of the primary/client pair, with the 2 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 4: EUT USB-C port input + Receiver load operating (distance 4 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	2.45	2.64	1.99	2.68	3.01
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-611.55	-611.36	-612.01	-611.32	-610.99
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.55	-304.36	-305.01	-304.32	-303.99

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.225	0.226	0.221	0.225	0.222
Max H-Field(A/m)	0.179	0.180	0.176	0.179	0.177
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.451	-1.450	-1.454	-1.451	-1.453
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.636	-0.635	-0.639	-0.636	-0.638

Measurements was made from all sides and the top of the primary/client pair, with the 4 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.



Charging Mode 5: EUT USB-C port input + Receiver load operating (distance 6 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	2.31	2.19	1.36	1.62	2.87
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-611.69	-611.81	-612.64	-612.38	-611.13
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.69	-304.81	-305.64	-305.38	-304.13

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.221	0.224	0.218	0.222	0.226
Max H-Field(A/m)	0.176	0.178	0.174	0.177	0.180
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.454	-1.452	-1.456	-1.453	-1.450
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.639	-0.637	-0.641	-0.638	-0.635

Measurements was made from all sides and the top of the primary/client pair, with the 6 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 6: EUT USB-C port input + Receiver load operating (distance 8 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	1.36	1.69	1.31	1.21	2.06
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-612.64	-612.31	-612.69	-612.79	-611.94
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.64	-305.31	-305.69	-305.79	-304.94

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.227	0.221	0.217	0.218	0.217
Max H-Field(A/m)	0.181	0.176	0.173	0.174	0.173
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.449	-1.454	-1.457	-1.456	-1.457
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.634	-0.639	-0.642	-0.641	-0.642

Measurements was made from all sides and the top of the primary/client pair, with the 8 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.



Charging Mode 7: EUT USB-C port input + Receiver load operating (distance 10 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	1.02	1.32	0.67	1.21	1.24
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-612.98	-612.68	-613.33	-612.79	-612.76
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.98	-305.68	-306.33	-305.79	-305.76

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.217	0.218	0.217	0.218	0.219
Max H-Field(A/m)	0.173	0.174	0.173	0.174	0.174
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.457	-1.456	-1.457	-1.456	-1.456
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.642	-0.641	-0.642	-0.641	-0.641

Measurements was made from all sides and the top of the primary/client pair, with the 10 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Standby Mode 8: Standby (Battery Full) (distance 0 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	4.88	3.53	2.01	2.21	6.32
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-609.12	-610.47	-611.99	-611.79	-607.68
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-302.12	-303.47	-304.99	-304.79	-300.68

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.758	0.642	0.241	0.364	0.754
Max H-Field(A/m)	0.604	0.511	0.192	0.290	0.600
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.026	-1.119	-1.438	-1.340	-1.030
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.211	-0.304	-0.623	-0.525	-0.215

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.



Charging Mode 9: Receiver load operating (Battery Full) (distance 0 cm)

E-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-Field(V/m)	4.33	4.36	3.54	3.85	6.34
Limit(V/m)	614	614	614	614	614
Margin (V/m)	-609.67	-609.64	-610.46	-610.15	-607.66
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-302.67	-302.64	-303.46	-303.15	-300.66

H-Field Measurement					
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-Field(uT)	0.236	0.271	0.251	0.243	0.243
Max H-Field(A/m)	0.188	0.216	0.200	0.193	0.193
Limit(A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.442	-1.414	-1.430	-1.437	-1.437
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.627	-0.599	-0.615	-0.622	-0.622

Measurements was made from all sides and the top of the primary/client pair, with the 0 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.



**BUREAU
VERITAS**

Test Report No.: FM2101WDG0287

3. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (FCC MPE Test Photos, Reference No.: 2101WDG0287-1)

--- END ---