



RF EXPOSURE REPORT

REPORT NO.: SA111024D07A
MODEL NO.: F5L104, F5L107
FCC ID: K7SF5L104
RECEIVED: Oct. 24, 2011
TESTED: Oct. 26 ~ 28, 2011
ISSUED: Feb. 3, 2012

APPLICANT: BELKIN INTERNATIONAL, INC.

ADDRESS: 12045 East Waterfront Drive Playa Vista California
United States 90094

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB LOCATION: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New
Taipei City, Taiwan (R.O.C.)

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. CONCLUSION	5



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA111024D07A	Original release	Feb. 3, 2012





1. CERTIFICATION

PRODUCT: Bluetooth Keyboard
BRAND NAME: BELKIN
MODEL NO.: F5L104, F5L107
APPLICANT: BELKIN INTERNATIONAL, INC.
TESTED: Oct. 26 ~ 28, 2011
TEST ITEM: ENGINEERING SAMPLE
STANDARDS: FCC Part 2 (Section 2.1091)
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment (Model: F5L104) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Annie Chang , **DATE:** Feb 3, 2012
(Annie Chang / Senior Specialist)

APPROVED BY : Ken Liu , **DATE:** Feb. 3, 2012
(Ken Liu / Manager)

2. CONCLUSION

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

	Pout (dBm)	Pout (mW)
Conducted Power	-2.5	0.6
EIRP Power	-3.1	0.5

***Note:** The antenna is Printed antenna with -0.56dBi gain

Threshold for no SAR evaluation is 24.58mW
 Transmitter power is 0.6mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---