## belkin



**BELKIN INTERNATIONAL** 

12045 East Waterfront Drive Playa Vista, CA 90094-2536 USA P 310 751 5100 F 310 751 5969

belkin.com

Applicant: Belkin International, Inc.	
FCC ID:K7SF7U053	
RF Exposure Requirements ( FCC KDB 680106 D01 V03)	
Requirements	Statements
(a) Power transfer frequency is less that 1 MHz	The resonator system shall operate at
	111-148kHz
(b) Output power from each primary coil is	10W
less than 15 watts	
(c) The transfer system includes only single	single coil
primary and secondary coils. This includes	
charging systems that may have multiple	
primary coils and clients that are able to detect	
and allow coupling only between individual	
pairs of coils	
(d) Client device is inserted in or placed	Client device is placed directly in
directly in contact with the transmitter	contact with the transmitter
(e) Mobile exposure conditions only (portable	It's mobile device, and had provided RF
exposure conditions are not covered by this	exposure report to evaluate.
exclusion).	
(f) The aggregate H-field strengths at 15 cm	Please refer to RF Exposure Report.
surrounding the device and 20 cm above the	
top surface from all simultaneous	
transmitting coils are demonstrated to be	
less than 50% of the MPE limit.	



Rajesh Karki / Manager, Regulatory Compliance Belkin International, Inc.

Tel: 310-751-2817

E-mail: rajesh.karki@belkin.com