



BELKIN INTERNATIONAL

12045 East Waterfront Drive
Playa Vista, CA 90094-2536 USA
P 310 751 5100
F 310 751 5969
belkin.com

Applicant	Belkin International, Inc.
FCC ID: K7SF7U054	IC: 3623A-F7U054
RF Exposure Requirements (FCC KDB 680106 D01)	
Requirements	Statements
(a) Power transfer frequency is less than 1 MHz	127.8KHz
(b) Output power from each primary coil is less than 5 watts	7.5W
(c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils	Single coil
(d) Client device is inserted in or placed directly in contact with the transmitter	Client device is placed directly in contact with the transmitter
(e) The maximum coupling surface area of the transmit (charging) device is between 60 cm ² and 400 cm ² .	16.26cm ² (diameter = 45.5mm)
(f) Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit.	Please refer to RF Exposure Report.

Rajesh Karki

Rajesh Karki / Principal Regulatory Compliance Engineer

Belkin International, Inc.

Tel: 310-751-2817

E-mail: rajesh.karki@belkin.com