



## Test Report

Product Name: Wireless Keyboard

Model No.: F8E830-KBD,K105

FCC ID.: K7SF8E830-KBD

Applicant : Darfon Electronics Corp.

Address : 6, Feng-Shu Tsuen, Gueishan, Taoyuan 333,  
Taiwan, R.O.C.

Date of Receipt : Nov. 07, 2003

Date of Test : Nov. 12, 2003

Report No. : 03BL046FI

The Test Results relate only to the samples tested.


The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

# Test Report Certification

Test Date : Nov. 12, 2003

Report No. : 03BL046FI



Product Name : Wireless Keyboard

Applicant : Darfon Electronics Corp.

Address : 6, Feng-Shu Tsuen, Gueishan, Taoyuan 333, Taiwan,  
R.O.C.

Manufacturer : Darfon Electronics Corp.

Model No. : F8E830-KBD,K105

FCC ID. : K7SF8E830-KBD

Rated Voltage : DC 3V(Power by Battery)

Trade Name : Belkin, BenQ

Measurement Standard : FCC Part 15 Intentional Radiators for Subpart C  
Paragraph 15.227

Measurement Procedure : ANSI C63.4:1992

Test Result : Complied



The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented By : Grace Lin  
( Grace Lin )

Tested By : Tom Hsieh  
( Tom Hsieh )

Approved By : Gene Chang  
( Gene Chang )

## TABLE OF CONTENTS

Description	Page
<b>1. GENERAL INFORMATION.....</b>	<b>4</b>
1.1. EUT Description.....	4
1.2. Operation Description .....	5
1.3. Tested System Details.....	6
1.4. Configuration of tested System .....	6
1.5. EUT Exercise Software .....	6
1.6. Test Facility .....	7
<b>2. Conducted Emission.....</b>	<b>8</b>
2.1. Test Equipment.....	8
2.2. Test Setup .....	8
2.3. Limits .....	8
2.4. Test Procedure .....	9
2.5. Test Data of Conducted Emission .....	10
<b>3. Radiated Emission.....</b>	<b>11</b>
3.1. Test Equipment.....	11
3.2. Test Setup .....	11
3.3. Limits .....	12
3.4. Test Procedure .....	13
3.5. Test Data of Radiated Emission .....	14
<b>4. Band Edge .....</b>	<b>16</b>
4.1. Test Equipment.....	16
4.2. Test Setup .....	16
4.3. Limit .....	17
4.4. Test Procedure .....	17
4.5. Test Result of Band Edge .....	18
<b>5. Occupied Bandwidth.....</b>	<b>20</b>
5.1. Test Equipment.....	20
5.2. Test Setup .....	20
5.3. Test Result of Occupied Bandwidth .....	21
<b>6. EMI Reduction Method During Compliance Testing .....</b>	<b>22</b>

Attachment 1: EUT Test Photographs  
Attachment 2: EUT Detailed Photographs

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name : Wireless Keyboard  
Trade Name : Belkin, BenQ  
FCC ID. : K7SF8E830-KBD  
Model No. : F8E830-KBD,K105  
EUT Voltage : DC 3V(Power by Battery)  
Frequency Range : 27.095MHz~27.145MHz  
Type of Modulation : FSK  
Type of antenna : Loop Antenna  
Channel Number : 2  
Channel Control : Auto

Frequency of Each Channel:

Channel	Frequency	Channel	Frequency
Channel 1:	27.095 MHz	Channel 2:	27.145 MHz

Note:

1. The EUT is a Wireless Keyboard intends to use in household and office PC system or related application.
2. The EUT is including two model numbers, it's different is listed as below

Model No.	Trade Name
F8E830-KBD	Belkin
K105	BenQ

3. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.227.
4. The variation of model number is for different color of outlook and Hard Key. The circuit of each model is identical.

## 1.2. Operation Description

The EUT is a 27MHz Wireless Keyboard intends to use in household and office PC system.

The device adapts FSK modulation. The antenna Loop Antenna Provides diversity function to improve the transmitting function.

The super generation type receiver was used. An external excitation was used when the test of receiver was performed.

**1.3. Tested System Details**


The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	FCC ID
(1)	Notebook PC	DELL	PP01L	N/A	Non-Shielded, 1.8m

	Signal Cable Type	Signal cable Description
A.	Receiver Cable	Shielded, 1.3m

**1.4. Configuration of tested System**



**1.5. EUT Exercise Software**

- (1) Setup the EUT and simulators as shown on 1.4.
- (2) Enable RF signal and confirm EUT active.
- (3) Modulate output capacity of EUT up to specification.

**1.6. Test Facility**

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: June 22, 2001 File on  
 Federal Communications Commission  
 FCC Engineering Laboratory  
 7435 Oakland Mills Road  
 Columbia, MD 21046  
 Reference 31040/SIT1300F2



July 03, 2001 Accreditation on NVLAP  
 NVLAP Lab Code: 200533-0

Site Name: Quietek Corporation



Site Address: No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen,  
 Lin-Kou Shiang, Taipei,  
 Taiwan, R.O.C.  
 TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789  
 E-Mail : [service@quietek.com](mailto:service@quietek.com)



## 2. Conducted Emission


### 2.1. Test Equipment

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2003	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2003	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2003	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	May, 2003	
5	No.4 Shielded Room			N/A	

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

### 2.2. Test Setup



### 2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dBuV) Limit		
Frequency MHz	Limits	
	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks : In the above table, the tighter limit applies at the band edges.



## 2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4:1992 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

## 2.5. Test Data of Conducted Emission

Owing to the DC operation of EUT, this test item is not performed.

### 3. Radiated Emission


#### 3.1. Test Equipment

The following test equipment are used during the radiated emission test:

Test Site	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 1	Test Receiver	R & S	ESCS 30 / 825442/14	May, 2003
	Spectrum Analyzer	Advantest	R3261C / 71720140	May, 2003
	Pre-Amplifier	HP	8447D/3307A01812	May, 2003
	Bilog Antenna	Chase	CBL6112B / 12452	Sep., 2002
	Horn Antenna	EM	EM6917 / 103325	May, 2003
Site # 2	Test Receiver	R & S	ESCS 30 / 825442/17	May, 2003
	Spectrum Analyzer	Advantest	R3261C / 71720609	May, 2003
	Pre-Amplifier	HP	8447D/3307A01814	May, 2003
	Bilog Antenna	Chase	CBL6112B / 2455	Sep., 2003
	Horn Antenna	EM	EM6917 / 103325	May, 2003
Site # 3	X Test Receiver	R & S	ESI 26 / 838786 / 004	May, 2003
	X Spectrum Analyzer	Advantest	3162 / 100803480	May, 2003
	X Pre-Amplifier	QTK	QTK-AMP-03 / 0003	May, 2003
	X Bilog Antenna	SCHAFFNER	CBL6112B / 2697	May, 2003
	X Horn Antenna	ETS	3115 / 0005-6160	Jul., 2003
	X Pre-Amplifier	QTK	QTK-AMP-01 / 0001	Jul., 2003

- Note:
1. All equipments that need to calibrate are with calibration period of 1 year.
  2. Mark "X" test instruments are used to measure the final test results.

#### 3.2. Test Setup



**3.3. Limits**

➤ FCC Part 15 Subpart C Paragraph 15.227 Limit

<b>FCC Part 15 Subpart C Paragraph 15.227 Limits</b>		
Fundamental Frequency MHz	Field strength of fundamental	
	uV/m	dBuV/m
26.96-27.28	10000	80.0

Remarks :

1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

➤ Frequencies in restricted band are complied to limits on Paragraph 15.209.

<b>FCC Part 15 Subpart C Paragraph 15.209 Limits</b>		
Frequency MHz	uV/m @3m	dBuV/m@3m
0.009-0.490	2400/F(kHz)	128.5-93.5
0.490-1.705	24000/F(kHz)	73.5-62.5
1.705-30.0	30	69.5
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

- Remarks :
1. RF Voltage (dBuV/m) = 20 log RF Voltage (uV/m)
  2. In the Above Table, the tighter limit applies at the band edges.
  3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

### 3.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4:1992 on radiated measurement.

Radiated emissions were investigated over the frequency range from 30MHz to 1GHz using a receiver bandwidth of 120kHz. Radiated was performed at an antenna to EUT distance of 3 meters.

The frequency range from 30MHz to 10th harmonics is checked.

### 3.5. Test Data of Radiated Emission

Product : Wireless Keyboard  
 Test Item : Fundamental Radiated Emission  
 Test Site : No.1 OATS  
 Test Voltage : DC 3V(Power by Battery)  
 Test Mode : Channel 1

Freq.	Cable	Probe	PreAMP	Reading	Emission	Margin	Limit
MHz	Loss	Factor		Level	Level		
	dB	dB/m	dB	dBuV	dBuV/m	dB	dBuV/m

#### Horizontal

##### Peak Detector:

27.150	0.17	-1.02	22.58	71.61	48.18	51.82	100.00
--------	------	-------	-------	-------	-------	-------	--------

#### Vertical

##### Peak Detector:

27.150	0.17	3.98	22.58	63.83	45.40	37.67	100.00
--------	------	------	-------	-------	-------	-------	--------

Note:

1. All Readings are Peak value.
2. Emission Level = Reading Level + Probe Factor + Cable loss – PreAMP.
3. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Wireless Keyboard  
 Test Item : General Radiated Emission  
 Test Site : No.3 OATS  
 Test Voltage : DC 3V(Power by Battery)  
 Test Mode : Channel 1

Frequency	Cable	Probe	PreAMP	Reading	Emission	Margin	Limit
MHz	Loss	Factor		Level	Level	dB	dBuV/m
	dB	dB/m	dB	dBuV	dBuV/m		

**Horizontal:**

*	32.420	0.88	17.19	0.00	17.11	35.18	4.82	40.00
	204.450	1.77	8.48	0.00	23.46	33.71	9.79	43.50
	236.100	1.93	10.05	0.00	16.65	28.63	17.37	46.00
	362.230	2.58	13.60	0.00	12.43	28.61	17.39	46.00
	384.050	2.69	14.01	0.00	11.90	28.60	17.40	46.00
	398.600	2.77	14.62	0.00	10.41	27.80	18.20	46.00

**Vertical:**

	32.420	0.88	17.49	0.00	8.93	27.30	12.70	40.00
	49.400	0.97	6.90	0.00	16.04	23.91	16.09	40.00
	204.600	1.77	8.56	0.00	20.91	31.24	12.26	43.50
*	209.450	1.79	8.75	0.00	22.33	32.87	10.63	43.50
	287.120	2.19	12.07	0.00	9.56	23.83	22.17	46.00
	801.230	4.85	19.26	0.00	5.44	29.55	16.45	46.00

## Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. “ \* ”, means this data is the worst emission level.
3. Emission Level = Reading Level + Probe Factor + Cable Loss.

## 4. Band Edge

### 4.1. Test Equipment


The following test equipments are used during the band edge tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Spectrum Analyzer	Advantest	R3272 / 72421194	May, 2003
X	Test Receiver	R & S	ESCS 30 / 825442/14	May, 2003
X	Spectrum Analyzer	Advantest	R3261C / 71720140	May, 2003
X	Pre-Amplifier	HP	8447D/3307A01812	May, 2003
X	Bilog Antenna	Chase	CBL6112B / 12452	Sep., 2003
X	Horn Antenna	EM	EM6917 / 103325	May, 2003


- Note: 1. All equipments that need to calibrate are with calibration period of 1 year.  
 2. Mark "X" test instruments are used to measure the final test results.

### 4.2. Test Setup

#### RF Conducted Measurement:



#### RF Radiated Measurement:





### 4.3. Limit

Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 4.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4:1992 on radiated measurement.

The additional latch filter below 1GHz was used to measure the level of harmonics radiated emission during field strength of harmonics measurement.

The bandwidth below 30MHz setting on the field strength meter is 10 kHz, above 1GHz are 1 MHz.


### 4.5. Test Result of Band Edge

Product : Wireless Keyboard  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test Mode : Channel 1


#### RF Radiated Measurement: (Peak Detector)

Channel No.	Frequency (MHz)	Reading Level (dBuV)	Probe Factor (dB/m)	Cable Loss (dB)	PreAMP (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Result
1 (Horizontal)	27.095	53.08	-1.02	0.13	22.8	29.39	100	Pass
1 (Vertical)	27.095	45.26	3.98	0.13	22.8	26.57	100	Pass

**Figure Channel 1:** (Horizontal)



**Figure Channel 1:** (Vertical)



Note:


- The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

Product : Wireless Keyboard  
 Test Item : Band Edge  
 Test Site : No.3 OATS  
 Test Mode : Channel 2


**RF Radiated Measurement: (Peak Detector)**

Channel No.	Frequency (MHz)	Reading Level (dBUV)	Probe Factor (dB/m)	Cable Loss (dB)	PreAMP (dB)	Emission Level (dBUV/m)	Limit (dBUV/m)	Result
2 (Horizontal)	27.30	34.28	-1.02	0.17	22.57	10.86	69.5	Pass
2 (Vertical)	27.33	21.23	3.98	0.17	22.57	2.81	69.5	Pass

**Figure Channel 2:** (Horizontal)



**Figure Channel 2:** (Vertical)



Note:

- The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.

## 5. Occupied Bandwidth


### 5.1. Test Equipment

The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Spectrum Analyzer	HP	E4407B	May, 2003

Note: 1. All equipment upon which need to calibrated are with calibration period of 1 year.  
 2. Mark "X" test instruments are used to measure the final test results.

### 5.2. Test Setup




### 5.3. Test Result of Occupied Bandwidth

Product : Wireless Keyboard  
 Test Item : Occupied Bandwidth Data  
 Test Site : No.3 OATS  
 Test Mode : Channel 1

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	27.0975	8.9159	10	Pass

Figure Channel 1:



## 6. EMI Reduction Method During Compliance Testing

No modification was made during testing.

## Attachment 1: EUT Test Photographs

**Attachment 1: EUT Test Setup Photographs**

Front View of Radiated Test



Back View of Radiated Test





## Attachment 2: EUT Detailed Photographs

**Attachment 2 : EUT Detailed Photographs**

(1) EUT Photo



(2) EUT Photo




(3) EUT Photo




(4) EUT Photo




(5) EUT Photo




(6) EUT Photo




(7) EUT Photo




(8) EUT Photo



(9) EUT Photo



(10) EUT Photo



(11) EUT Photo

