



**BELKIN INTERNATIONAL**

12045 East Waterfront Drive  
Playa Vista, CA 90094-2536 USA  
P 310 751 5100  
F 310 751 5969  
belkin.com

| Applicant: Belkin International, Inc.                                                                                                                                                                                                       |                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| FCC ID: K7SF8J183V2                                                                                                                                                                                                                         |                                                                  |
| RF Exposure Requirements ( FCC KDB 680106 D01 V03)                                                                                                                                                                                          |                                                                  |
| Requirements                                                                                                                                                                                                                                | Statements                                                       |
| (a) Power transfer frequency is less than 1 MHz                                                                                                                                                                                             | The resonator system shall operate at 326.5kHz.                  |
| (b) Output power from each primary coil is less than 15 watts                                                                                                                                                                               | Less than 5W                                                     |
| (c) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils | One coil for 326.5kHz                                            |
| (d) Client device is inserted in or placed directly in contact with the transmitter                                                                                                                                                         | Client device is placed directly in contact with the transmitter |
| (e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).                                                                                                                                       | It's mobile device, and provided RF exposure report to evaluate  |
| (f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.                                         | Please refer to RF Exposure Report.                              |

*Rajesh Karki*

**Rajesh Karki / Manager,  
Regulatory Compliance  
Belkin International, Inc.  
Tel: 310-751-2817  
E-mail: rajesh.karki@belkin.com**