



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

Project No: CB10505315

## Maximum Permissible Exposure Report

Applicant's company	Belkin International, Inc.
Applicant Address	12045 East Waterfront Drive, Playa Vista, CA 90094
FCC ID	K7SF9K1105V3

Product Name	N450 DB Wireless N Router
Brand Name	belkin
Model Name	F9K1105v5
Ref. Standard(s)	47 CFR FCC Part 2 Subpart J, section 2.1091
Received Date	Feb. 24, 2016
Final Test Date	May 21, 2016
Submission Type	Class II Change

Sam Chen  
SPORTON INTERNATIONAL INC.





## Table of Contents

<b>1. GENERAL DESCRIPTION.....</b>	<b>1</b>
1.1. EUT General Information .....	1
1.2. Table for Class II Change .....	1
1.3. Testing Location.....	1
<b>2. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>2</b>
2.1. Limit of Maximum Permissible Exposure .....	2
2.2. MPE Calculation Method .....	2
2.3. Calculated Result and Limit.....	3



## History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA4N1172-25AB	Rev. 01	Initial issue of report	Jun. 21, 2016

## 1. GENERAL DESCRIPTION

### 1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
5GHz WLAN	5150-5250 5725-5850	5180-5240 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)

### 1.2. Table for Class II Change

This product is an extension of original one reported under Sporton project number: FA4N1172-25AA

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Updating test rule of 5GHz Band 4 (5725~5850MHz) to "15.407 (b)(4)(i) of New Rules (ET Docket No. 13-49; FCC 16-24)".	Maximum Permissible Exposure.

Note: Maximum Permissible Exposure of 2.4GHz Band and 5GHz Band 1 are based on original test report.

### 1.3. Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 2. MAXIMUM PERMISSIBLE EXPOSURE

### 2.1. Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2. MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

### 2.3. Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

For 5GHz Band 1:

Antenna Type : PCB Antenna

Conducted Power for IEEE 802.11n MCS0 HT40: 21.06 dBm

Distance (cm)	Test Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBm)	(mW)			
20	5230	3.06	2.0230	21.06	127.6439	0.0513	1	Complies

For 5GHz Band 4:

Antenna Type : PCB Antenna

Conducted Power for IEEE 802.11a: 20.99 dBm

Distance (cm)	Test Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	The maximum combined Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBm)	(mW)			
20	5745	3.06	2.0230	20.99	125.4613	0.0505	1	Complies

For 2.4GHz Band:

Antenna Type : PCB Antenna

Conducted Power for IEEE 802.11g: 18.62 dBm

Distance (cm)	Test Freq. (MHz)	Antenna Gain (dBi)	Antenna Gain (numeric)	Average Output Power		Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
				(dBm)	(mW)			
20	2412	3.43	2.2029	18.62	72.7780	0.0319	1	Complies

#### Conclusion:

Both of the WLAN 2.4GHz Band and WLAN 5GHz Band can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the worst-case situation is  $0.0319 / 1 + 0.0513 / 1 = 0.0832$ , which is less than "1". This confirmed that the device complies.