

# Maximum Permissible Exposure (MPE) Evaluation Report

**Report No.** : TS12030041-EME  
**Model No.** : WiFiHU2-a, WiFiHU2-a-1-NE,  
WiFiHU2-c, WiFiHU2-c-1-NE  
**Issued Date** : Mar. 23, 2012

**Applicant:** Radicom Research Inc.  
2148 Bering Dr., San Jose, CA. 95131, USA

**Test Method/ Standard:** FCC 1.1310

**Test By:** Intertek Testing Services Taiwan Ltd.  
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,  
Shiang-Shan District, Hsinchu City, Taiwan

It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).

**The test report was prepared by:** Sign on File  
Sunny Liu / Senior Officer

**These measurements were taken by:** Sign on File  
Terry Hsu / Engineer

**The test report was reviewed by:**

**Name** Jimmy Yang  
**Title** Engineer



## Table of Contents

Summary of Tests .....	3
1. Introduction .....	4
2. RF Exposure Limit .....	4
3. RF Exposure calculations .....	5
4 Description of EUT .....	6
5. Test results .....	8



**Summary of Tests**

**MPE Evaluation meet FCC OET No. 65: 1997, IEEE C95.1-2005**

Test	Reference	Results
MPE Evaluation	FCC Guidelines for Human Exposure IEEE C95.1	Complies

## 1. Introduction

The EUT operates in the 2.4 GHz ISM band. Due to the EUT (include antenna) at its normal operation distance is at least 20 cm from the human body, the EUT was defined as a Mobile Device.

The reason to do the MPE Evaluation is to avoid the RF hazard to human body. The maximum output power and gain of the antenna were used to calculate the limited Power density (S) at 20 cm distance away from the product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and Safety Code 6 are followed.

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guideline.

## 2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
(A) Limits for Occupational / Control Exposures				
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

F= Frequency in MHz

### 3. RF Exposure calculations

From §FCC 1.1310 table 1, the maximum permissible RF exposure for an uncontrolled environment is 1 mW/(cm<sup>2</sup>) (or 10 W/m<sup>2</sup>)\*

Power density (S) is calculated by the following formula:

$$S = (P * G) / 4\pi R^2$$

where, S = Power density (mW/cm<sup>2</sup>)

P = Output power to antenna (mW)

R = Distance between radiating structure and observation point (cm)

G = Gain of antenna in numeric

$\pi = 3.1416$

Example:

Assume a mobile device operates at 2412MHz and its maximum output power is 50mW, and the maximum gain of antenna is 1 (numeric) /0dBi.

then the power density (S) =  $(50 * 1) / 4 * \pi * 20^2 = 0.00995$  (mW/cm<sup>2</sup>) (or = 0.0995 W/m<sup>2</sup>)



#### 4 Description of EUT

The EUT is an USB WiFi Module, and was defined as information technology equipment.

For more detail features, please refer to User's manual as file name “Installation guide.pdf”

The customer confirmed the models listed as below were series model to model WiFiHU2-a-1-NE, WiFiHU2-c-1-NE (EUT), the difference between main model and series model are listed as below.

Model Number	Product Description
WiFiHU2-a-1-NE	Modules (with on- board antenna)+ Carrier Boards
WiFiHU2-a	Modules (with on- board antenna)
WiFiHU2-c-1-NE	Modules (with two antenna connectors)+ Carrier Boards
WiFiHU2-c	Modules (with two antenna connectors)



## 4.1 Antenna description

### (1) Antenna 1

The EUT uses a permanently connected antenna.

Antenna Gain : 0 dBi  
Antenna Type : Chip antenna  
Connector Type : N/A

### (2) Antenna 2

The antenna is affixed to the EUT using a unique connector, which allows for replacement of a broken antenna, but DOES NOT use a standard antenna jack or electrical connector.

Antenna Gain : 2 dBi  
Antenna Type : Dipole antenna  
Connector Type : IPX

**5. Test results**

**EUT : WiFiHU2-a-1-NE**

Mode	Channel Frequency (MHz)	Antenna gain (numeric)	Output power to antenna (mW)	Power density (mW/cm <sup>2</sup> )	Limit of power density (mW/cm <sup>2</sup> )
802.11b DAC 0	2412	1.00	72.61	0.014445419	1.00
	2437	1.00	59.02	0.011741677	1.00
	2462	1.00	34.99	0.006961938	1.00
802.11g DAC 0	2412	1.00	270.40	0.053793542	1.00
	2437	1.00	301.30	0.059941850	1.00
	2462	1.00	174.18	0.034652147	1.00
802.11g DAC 1	2412	1.00	281.19	0.055940990	1.00
	2437	1.00	325.84	0.064823152	1.00
	2462	1.00	289.73	0.057640819	1.00
802.11n HT20 DAC 0+1	2412	1.00	565.69	0.112540485	1.0
	2437	1.00	592.37	0.117848727	1.0
	2462	1.00	558.32	0.111074055	1.0
802.11n HT40 DAC 0+1	2422	1.00	439.61	0.087458412	1.0
	2437	1.00	472.14	0.093929408	1.0
	2452	1.00	460.32	0.091578201	1.0

**EUT : WiFiHU2-c-1-NE**

Mode	Channel Frequency (MHz)	Antenna gain (numeric)	Output power to antenna (mW)	Power density (mW/cm <sup>2</sup> )	Limit of power density (mW/cm <sup>2</sup> )
802.11b DAC 0	2412	1.58	33.42	0.010537319	1.00
	2437	1.58	38.37	0.012098461	1.00
	2462	1.58	41.40	0.013053595	1.00
802.11g DAC 0	2412	1.58	199.07	0.062766823	1.00
	2437	1.58	257.63	0.081232561	1.00
	2462	1.58	279.90	0.088253136	1.00
802.11g DAC 1	2412	1.58	308.32	0.097214298	1.00
	2437	1.58	317.69	0.100168263	1.00
	2462	1.58	245.47	0.077398072	1.00
802.11n HT20 DAC 0+1	2412	1.58	504.24	0.158987887	1.0
	2437	1.58	511.72	0.161348431	1.0
	2462	1.58	528.72	0.166707324	1.0
802.11n HT40 DAC 0+1	2422	1.58	306.58	0.096664646	1.0
	2437	1.58	528.05	0.166495121	1.0
	2452	1.58	361.26	0.113907127	1.0

The Notice in Installation Manual has been stated as below:

While installing and operating this transmitter, the radio frequency exposure limit of 1 mW/ (cm<sup>2</sup>) may be exceeded at distances close to the transmitter. Therefore, the user must maintain a minimum distance of 20 cm from the device at all time.