


ORIGINALFORMAT A3




REVISION	ECO NO.	ISSUED	APP'D	DATE
01	SME-11379	PC-AA	EAp-AS	2303
DESCRIPTION				
1208C EX CERTIFICATION LABEL DRAWING				

FLEX CONTROLLED FIELDS

NO.	FIELD	SITE	PART NO.	MARKING FORMAT	EXAMPLE FORMAT
A	MODEL	ALL	-FLEX	<MODEL>	1208XX
B	SERIAL NO.	ALL	-FLEX	<YYAABC1234567>	22BKRL0011234
C	PRODUCTION DATE	ALL	-FLEX	<MM-YYYY>	03-2022
D	QR CODE LINKED TO MY ASSETS	ALL	-FLEX	<QR-CODE>	



Description product variant	Model	Language	Part Number	Model string
Rosemount™ 1208C Level and Flow Transmitter	1208C	English	7000007-428	1208CG
Rosemount™ 1208C Level and Flow Transmitter	1208C	English	7000007-429	1208CN
Rosemount™ 1208CG Level and Flow Transmitter	1208C	Chinese	7000007-430	1208CGC
Rosemount™ 1208CN Level and Flow Transmitter	1208C	Chinese	7000007-431	1208CNC

STRING CONTROLLED FIELDS

NO.	FIELD	MODEL	PART NO.	PART. REV.	MARKING FORMAT	LANGUAGE
1.	BASE LAYER	1208A,1208C	-0001	AA	According to base layer artwork illustration	English
		1208C	-0002	AA	According to base layer artwork illustration	Chinese
2.	CONNECTION DIAGRAM	1208C	-0202	AA		All
3.	WARNING	1208C	-0301	AA	<p>SUBSTITUTION OF COMPONENTS MAY IMPAIR INTRINSIC SAFETY. TO PREVENT IGNITION OF FLAMMABLE OR COMBUSTIBLE ATMOSPHERES, DISCONNECT POWER BEFORE SERVICING. INSTALL PER CONTROL DRAWING</p> <p>LA SUBSTITUTION DE COMPOSANTS PEUT COMPROMETTRE LA SECURITE INTRINSEQUE. POUR EVITER L'ALLUMANGE DE PRODUITS INFLAMMABLES OU ATMOSPHERES COMBUSTIBLES, DEBRANCHEZ L'ALIMENTATION AVANT L'ENTRIEN ET INSTALLEZ SELON LE SCHEMA DE CONTROLE</p>	All
4.	LOGOS	1208C	-0401	AA		All
5.	LOGOS	1208C	-0502	AA		All
6.	SUPPLY	1208C	-0602	AB	HART® 4-20 mA 14-35 VDC 22.5mA	All
7.	MADE IN	1208C	-0703	AB	泰国制造	Chinese
		1208C	-0704	AB	Made in Thailand	English
8.	RADIO OUT.	1208C BT	-0903	AA	K8C1208CLB 2827A-1208CLB 1208CLB1	All
		1208C	-0904	AA	K8C1208CL 2827A-1208CL 1208CL1	All

- LABEL TO BE CUSTOMIZED ACCORDING TO FLEX CONTROLLED FIELDS
- ALL APPROVAL LOGOS IN ACC. WITH RESP. LOGOTYPE.

FM APPROVED PRODUCT.  
No revisions to this drawing without prior Factory Mutual Approval.

D7000007-910	ISSUED BY <b>PC-AA</b>	DRAWN WEEK <b>2303</b>	PRODUCT CODE <b>1208</b>	 LAYOUTVÄGEN 1, 435 33 MÖLNLYCKE, SWEDEN
	APPROVED BY <b>EAp-AS</b>	APP'D WEEK <b>2303</b>	DOC TYPE <b>6</b>	
	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN MILLIMETERS. REMOVE ALL BURRS AND SHARP EDGES.			
	- GENERAL TOLERANCES -			
	MACHINING: ISO 2768 CASTING: ISO 8062 WELDING: EN-ISO 13920	FINISH: ✓	ANGLES:	
1 ST ANGLE 	SCALE <b>1:1</b>	SIZE <b>A3</b>	Adobe Illustrator DO NOT SCALE PRINT	DRAWING NO. <b>D7000007-910</b>
THE COPYRIGHT/OWNERSHIP OF THIS DOCUMENT IS AND WILL REMAIN OURS. THE DOCUMENT MUST NOT BE USED WITHOUT AUTHORIZATION OR BROUGHT TO THE KNOWLEDGE OF A THIRD PARTY. CONTRAVENTION WILL BE PROSECUTED. ROSEMOUNT TANK RADAR AB, SWEDEN				ISSUE <b>01</b>
				SHEET <b>1/2</b>

ORIGINALFORMAT A3

REVISION	ECO NO.	ISSUED	APP'D	DATE
01	SME-11379	PC-AA	EAp-AS	2245
DESCRIPTION				
1208 CERTIFICATION DRAWING				

<p><b>EMERSON   ROSEMOUNT</b>  <b>MODEL 1208XX</b>  <b>SERIAL 22BKRL0011234</b>  DATE MFG: 03-2022  FCC ID: K8C1208CL  IC: 2827A-1208CL  HVIN: 1208CL1</p> <p>50 CE UK CA 2460 8501</p>	<p><b>Level &amp; Flow Transmitter</b>  <b>Made in Thailand</b></p> <p>SUPPLY: HART® 4-20 mA  --- 14-35 VDC 22.5mA  ENCL. TYPE: 4X/6P, IP66/68, IK07  MWP: 3 BAR</p> <p>Substitution of components may impair intrinsic safety. To prevent ignition of flammable or combustible atmospheres, disconnect power before servicing. Install per control drawing.</p> <p>LA SUBSTITUTION DE COMPOSANTS PEUT COMPROMETTRE LA SÉCURITÉ INTRINSÈQUE. POUR ÉVITER L'ALLUMAGE DE PRODUITS INFLAMMABLES OU ATMOSPHÈRES COMBUSTIBLES, DÉBRANCHEZ L'ALIMENTATION AVANT L'ENTRÉRIEN INSTALLEZ SELON LE SCHEMA DE CONTRÔLE.</p>	 <b>EMERSON</b> <b>ROSEMOUNT™</b> 1208 Level and Flow Transmitter	
---	--	---	--

EXAMPLE LABEL 1208C

<p><b>EMERSON   ROSEMOUNT</b>  <b>型号 1208XX</b>  出厂编号 22BKRL0011234  制造日期 03-2022  FCC ID: K8C1208CL  IC: 2827A-1208CL  HVIN: 1208CL1</p> <p>50 CE UK CA 2460 8501</p>	<p><b>液位 &amp; 流量变送器</b>  <b>泰国制造</b></p> <p>电源电压: HART® 4-20 mA  --- 14-35 VDC 22.5mA  ENCL. TYPE: 4X/6P, IP66/68, IK07  MWP: 3 BAR</p> <p>Substitution of components may impair intrinsic safety. To prevent ignition of flammable or combustible atmospheres, disconnect power before servicing. Install per control drawing.</p> <p>LA SUBSTITUTION DE COMPOSANTS PEUT COMPROMETTRE LA SÉCURITÉ INTRINSÈQUE. POUR ÉVITER L'ALLUMAGE DE PRODUITS INFLAMMABLES OU ATMOSPHÈRES COMBUSTIBLES, DÉBRANCHEZ L'ALIMENTATION AVANT L'ENTRÉRIEN INSTALLEZ SELON LE SCHEMA DE CONTRÔLE.</p>	 <b>EMERSON</b> <b>ROSEMOUNT™</b> 1208 Level and Flow Transmitter 液位/流量变送器	
--	--	---	--

EXAMPLE LABEL 1208CN

1. LABEL TO BE CUSTOMIZED ACCORDING TO FLEX CONTROLLED FIELDS
2. ALL APPROVAL LOGOS IN ACC. WITH RESP. LOGOTYPE.

FM APPROVED PRODUCT.  
No revisions to this drawing without prior Factory Mutual Approval.

<b>D7000007-910</b>	ISSUED BY <b>PC-AA</b>	DRAWN WEEK <b>2303</b>	PRODUCT CODE <b>1208</b>	 LAYOUTVÄGEN 1, 435 33 MÖLNLYCKE, SWEDEN <b>ROSEMOUNT 1208C EX CERT LABEL DRAWING</b>
	APPROVED BY <b>EAp-AS</b>	APP'D WEEK <b>2303</b>	DOC TYPE <b>6</b>	
	UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN MILLIMETERS. REMOVE ALL BURRS AND SHARP EDGES.			
	- GENERAL TOLERANCES -			
MACHINING: ISO 2768 CASTING: ISO 8062 WELDING: EN-ISO 13920	FINISH: ✓	ANGLES:		
1 ST ANGLE 	SCALE <b>1:1</b>	SIZE <b>A3</b>	Adobe Illustrator DO NOT SCALE PRINT	
THE COPYRIGHT/OWNERSHIP OF THIS DOCUMENT IS AND WILL REMAIN OURS. THE DOCUMENT MUST NOT BE USED WITHOUT AUTHORIZATION OR BROUGHT TO THE KNOWLEDGE OF A THIRD PARTY. CONTRAVENTION WILL BE PROSECUTED. ROSEMOUNT TANK RADAR AB, SWEDEN				
DRAWING NO. <b>D7000007-910</b>			ISSUE <b>01</b>	SHEET <b>2/2</b>