

SAR Test exemption documentation according to CFR 47 §1.1307

Report identification number: 1-3759/21-03-13 Exemption / MPE (FCC)

contains the module with the following certification numbers	
FCC ID	K8C1208CL

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Alexander Hnatovskiy
Lab Manager
Radio Labs



Marco Scigliano
Testing Manager
Radio Labs

EUT technologies:

Technologies:	Max. rated power: (AVG)	Max. gain:
Level probing radar 77-81 GHz	-32.42 dBm / 0.57µW	<0 dBi

Note:

max. measured peak EIRP taken from CTC Advanced GmbH report 1-3759/21-01-08-A (page 24)
(AVG factor -57.4 dB)
Max. peak EIRP: 21.8 dBm
AVG EIRP: -30.27 dBm, AVG ERP: -32.42 dBm

Declared minimum safety distance: 20cm

According to the manual a safety distance of 20cm shall be applied between the user (and/or bystanders) to the EUT antenna whilst active transmitting.

MPE-Based Exemption following 47 CFR 1.1307 amendment:

If the declared ERP does not exceed the specified threshold based on the calculations below, the device is exempt from routine evaluation.

Transmitter Frequency (MHz)	Threshold ERP (W)
0.3 – 1.34	1.920 R ²
1.34 – 30	3.450 R ² /f ²
30 – 300	3.83 R ²
300 – 1500	0.0128 R ²
1500 – 100 000	19.2 R²f

where

f is the frequency (MHz)

R is the separation distance (at least $\lambda/2\pi$)

Prediction: worst case

Technology	Transmitter frequency (MHz)	R _{min} (mm)	Max. decl. ERP (mW)	Treshhold ERP		Minimal Safety Distance (mm)	Verdict
				(mW)	(dBm)		
LPR	77000	0.6	0.00093	768.00	28.8	200	EXEMPTED
LPR	81000	0.6	0.00093	768.00	28.8	200	EXEMPTED

This prediction demonstrates the following:

The power density levels for FCC that are larger than the minimum safety-distances stated above, are below the maximum levels allowed by regulations.