

5402 _____	ROSEMOUNT GOTTFORS, SWEDEN RADAR LEVEL TRANSMITTER MAY BE PROTECTED BY US AND FOREIGN PATENTS AND PATENTS PENDING	IS CL I, II, III, DIV. 1, GP A,B,C,D,E,F & G CL I, ZONE 0, AEx ia IIC T4 WHEN INSTALLED PER CONTROL DWG 9150077-XXX NI CL I, DIV 2, GP A,B,C & D; SUITABLE FOR CL II, III DIV 2, GP F & G; NI MAX 42,5 V, 25mA AMBIENT TEMPERATURE LIMITS -40°C to +70°C
TAG _____		 APPROVED WARNING: SUBSTITUTION OF COMPONENTS MAY IMPAIR SUITABILITY FOR DIV 1 & WARNING: EXPLOSION HAZARD - DO NOT DISCONNECT EQUIPMENT UNLESS AREA IS KNOWN TO BE NON-HAZARDOUS ISHART
MFG _____		
S/N _____		
HART® 4-20mA SUPPLY: 10,5 - 30VDC (I.S.) FCC ID: K8C5402 ENCL. TYPE 4X, IP66, IP67		

All text except, FCC information, Model name, Rosemount logo and manufacturing country/city is example text. The label above is placed as in the “External Photos” document.

