

# ***Measurement Report***

**Product**.....: **REMOTE CONTROL RECEIVER**  
**Applicant**.....: **SKYTECH II, INC.**  
**FCC ID**.....: **K9L1410RX**  
**Trade Name** .....: **SKYTECH**  
**Model No.**.....: **1410-A (SEE APPENDIX II)**  
**Report No.**.....: **MLT0504P15008**  
**Issue Date**.....: **May 11, 2005**

**Test By**

**Max Light Technology Co.,Ltd.**

**Room 5, 8F, No.125, Section 3 Roosevelt Road,  
Taipei, Taiwan., R.O.C.**

**Tel: 886-2-2363-2447 Fax: 886-2-2363-2597**

**The test report consists of 20 pages in total. It may be duplicated  
completely  
for legal use with the allowance of the applicant. It shall not be reproduced  
except in full, without the written approval of our laboratory.**



**Table of Contents :**

***I. General***..... **4.**

***II. Conducted Emissions Requirements***..... **7.**

***III. Radiated Emissions Requirements***..... **12.**

***Appendix I (EUT Test Setup)***..... **18.**

***Appendix II (Model No.)***..... **20.**



## **CERIFICATION**

***We here by verify that :***

**The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2003. All test were conducted by *MLT(Max Light Technology Co.,Ltd) Room 5, 8F, No.125, Section 3 Roosevelt Road, Taipei, Taiwan, R.O.C* Also, we attest to the accuracy of each.**

**We further submit that the energy emitted by the sample EUT tested as described in the report is in compliance with Class B radiated and conducted emission limit of FCC Rules Part 15 Subpart B.**

**EUT : REMOTE CONTROL RECEIVER**

**Applicant : SKYTECH II, INC.  
9230 Conservation Way, Fort.  
Wayne, IN 46809, U.S.A**

**Manufacturer : FEGO Precision Industrial Co. Ltd  
947 LIN SEN RD., WU-FENG SHIANG  
TAICHUNG HSIEN R.O.C.**

**Model No : 1410-A (SEE APPENDIX II)**

**FCC ID : K9L1410RX**

**Prepared by : Country Huang Approved by : Roger Chen  
Country Huang Roger Chen**



## **I. GENERAL**

### **1.1 Introduction**

The following measurement report is submitted on behalf of SKYTECH II, INC.. In support of a Class B Device Certification in accordance with Part2 Subpart J and Part 15 Subpart A And B of the Commission's and Regulations.

The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4:2003.

#### **ANSI STANDARD C63.4-2003 SUPERREGENERATIVE RECEIVER:**

A signal generator was set to the unit under test operating frequency. An un- modulated continuous wave (CW) signal was radiated at the super-regenerative receiver operating frequency to cohere the characteristic broadband emissions from the receiver.

**EUT : REMOTE CONTROL RECEIVER**

**Applicant : SKYTECH II, INC.**  
**9230 Conservation Way, Ft. Wayne,**  
**IN 46809, U.S.A**

**Manufacturer : FEGO Precision Industrial Co. Ltd**  
**947 LIN SEN RD., WU-FENG SHIANG**  
**TAICHUNG HSIEN R.O.C.**

**Model No : 1410-A (SEE APPENDIX II)**

**FCC ID : K9L1410RX**

**Power Type : Power By AC 120V / 60Hz**


During testing the EUT was operated at Testing mode for each emission measured. This was done in order to ensure that maximum emission levels were attained.

### 1.2 Description of Support Equipment

In order to construct the minimum system which required by the ANSI C63.4:2003, following equipments were used as the support units.

The REMOTE CONTROL RECEIVER itself forms a system. No support equipment is required for its normal operation.

### 1.3 Configuration of System Under Test



During testing the EUT (Single Line REMOTE CONTROL RECEIVER)'s one red cable was connected to LED, the other Port's cable was connected to battery box . When the EUT was "ON", the LED was lighting.



## **1.4 Test Procedure**

**All measurements contained in this report were performed according to the techniques described in Measurement procedure ANSI C63.4-2001 "Measurement of unIntentional Radiators."**

## **1.5 General Test Condition**

**The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests were chosen as that which produced the highest emission levels. However, only those conditions which the EUT was considered likely to encounter in normal use were investigated.**

**The system's radiated and conducted emissions were investigated while the EUT keep answering an incoming call form PSTN simulator to simulate the actual situation that a user will typically installed. The system's physical layout and cabling was randomly arranged to ensure that maximum emission levels were attained.**



## ***II. Conducted Emissions Requirements***

### **2.1 General & Setup :**

The power line conducted emission measurements were performed in a shielded enclosure. The EUT was assembled on a wooden table which is 80 centimeters high, was placed 40 centimeters from the backwall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and EMCO Model 3825/2 Line Impedance Stabilization Networks (LISN). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPER quasi-peak detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 2.6.

### **2.2 Test Equipment List:**

- A. EMCO 3825/2 LISN (S/N:2654)**
- B. EMCO 3825/2 LISN (S/N:2658)**
- C. HP 8591EM 9KHZ-1.8GHz Spectrum Analyzer (S/N:73412A00110)**
- D. R&S ESH3 Test Receiver (S/N:892108/025)**
- E. Shielded Room (MLT-SR1)**

### 2.3 Test Configuration:



**Front View of The Test Configuration**





**Rear View of The Test Configuration**



## 2.4 Test condition:

**EUT tested in accordance with the specifications given by the manufacturer , and exercised in the most unfavorable manner.**

## 2.5 Conducted Emissions Limits:

<b>Frequency range (MHz)</b>	<b>Limits (dBuV)</b>	
	<b>Quasi-peak</b>	<b>Average</b>
<b>0.15 to 0.50</b>	<b>66 to 56</b>	<b>56 to 46</b>
<b>0.50 to 5.0</b>	<b>56</b>	<b>46</b>
<b>5.0 to 30</b>	<b>60</b>	<b>50</b>



**2.6 Measurement Data Of Conducted Emissions:**

**2.6.1 Conducted Emissions (Subpart B)**

The following table show a summary of the highest emissions of power line conducted emissions to the HOT and NATURAL conductor of the EUT power.

**Applicant** : *SKYTECH II, INC.*  
**Model No** : *1410-A (SEE APPENDIX II)*  
**EUT** : *REMOTE CONTROL RECEIVER*  
**Test Date** : *05/09/2005*

Power Line Conducted Emissions (Class B)					
Conductor	Frequency (MHz)	Quasi-Peak (dBuV)	Limits	Average (dBuV)	Limits
L1	0.16	42.96	65.36	--	55.36
	0.21	41.07	63.17	--	53.17
	0.37	31.48	58.39	--	48.39
	1.34	30.77	56	--	46
	2.22	28.16	56	--	46
	11.93	42.09	60	--	50
	19.53	36.93	60	--	50
L2	0.16	41.60	65.36	--	55.36
	0.38	29.38	56.26	--	46.26
	0.93	29.50	56	--	46
	1.48	29.93	56	--	46
	2.57	26.79	56	--	46
	11.93	43.08	60	--	50
	19.43	38.91	60	--	50

**Notes :** *1.L1: One end & Ground L1: The other end & Ground*  
*2.Height of table on which the EUT was placed : 0.8 m.*  
*3.The Quasi-Peak Value have already met the Average Value Limit showed on above limits.*  
*4.The above test results are obtained under the normal condition.*



### ***III. Radiated Emissions Requirements***

#### **3.1 General & Setup :**

Prior to open-field testing, the EUT was placed in a shielded enclosure and scanned at a close distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration which produced the highest emissions was noted so it could be reproduced later during the open-field tests. This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT. Final radiation measurements were made on a 3-meter, open-field test site. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 30 MHz to 1000 MHz using an Hewlett Packard 8591EM Spectrum Analyzer, EMCO Biconical Antenna (Model 3142) for 30-1000MHz. At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization. Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post-detector video filters were used in the test. The spectrum analyzer's 6 dB bandwidth was set to 120 KHz, and the analyzer was operated in the quasi-peak detection mode. The highest emission amplitudes relative to the appropriate limit were measured and recorded in paragraph 3.6.

#### **3.2 Test Equipment List:**

- A. HP 8591EM 9KHz-1.8GHz Spectrum Analyzer (S/N:73412A00230)**
- B. HP 8447D Pre Amplifier (S/N:2944A08954)**
- C. EMCO 3142 Biconilog Antenna (S/N:1184)**
- D. R&S ESVP Test Receiver (S/N:881121/010)**

### 3.3 Test Configuration:



**Front View of The Test Configuration**



**Rear View of The Test Configuration**



**3.4 Test condition:**

EUT tested in accordance with the specifications given by the manufacturer , and exercised in the most unfavorable manner.

**3.5 Radiated Emissions Limits:**

<b><i>Frequency range (MHz)</i></b>	<b><i>Quasi Peak (dBuV)</i></b>
<b>30 to 88</b>	<b>40</b>
<b>88 to 216</b>	<b>43.5</b>
<b>216 to 960</b>	<b>46</b>
<b><i>Frequency range (MHz)</i></b>	<b><i>Average (dBuV)</i></b>
<b>960 to 1610</b>	<b>54</b>
<b>Above 1610</b>	<b>60</b>

**3.6 Test condition:**

- A. Testing Room : Temperature 20      Humidity 55%RH**
- B. Testing Site    : Temperature 21      Humidity 64%RH**



# MAX LIGHT

## MEASUREMENT REPORT

### 3.7 Measurement Data Of Radiated Emissions:

#### 3.7.1 Open Field Radiated Emissions (HORIZONTAL)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

**Applicant** : SKYTECH II, INC.  
**Model No** : 1410-A (SEE APPENDIX II)  
**EUT** : REMOTE CONTROL RECEIVER  
**Test Mode** : Remote Mode  
**Test Date** : 05/10/2005

Radiated Emissions (HORIZONTAL)					
Frequency (MHz)	Amplitude (dBuV/m)	Ant. (m)	Table (Degree)	Limits(Class B) (dBuV/m)	Margin (dB)
131.79	34.99	2.0	70	43.5	-8.51
145.56	33.10	2.5	120	43.5	-10.40
180.12	31.60	1.4	350	46	-14.4
282.99	38.29	1.8	340	46	-7.71
305.60	35.10	1.5	220	46	-10.90
407.10	39.48	1.6	260	46	-6.52
513.50	36.99	1.0	270	46	-9.01
641.58	38.89	1.0	60	46	-7.11
776.70	33.86	1.5	120	46	-12.14
876.80	34.70	1.2	170	46	-11.30
948.90	33.82	1.8	200	46	-12.18

- Notes :
- 1.Margin= Amplitude - Limits
  - 2.Distance of Measurement : 3 Meter (30-1000MHz)
  - 3.Height of table for EUT placed: 0.8 Meter.
  - 4.ANT= Antenna height.
  - 5.Amplitude= Reading Amplitude -Amplifier gain+Cable loss +Antenna factor  
(Auto calculate in spectrum analyzer)
  - 6.The worst case test data recorded in the tables





**3.7.2 Open Field Radiated Emissions (VERTICAL)**

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following.


**Applicant** : SKYTECH II, INC.  
**Model No** : 1410-A (SEE APPENDIX II)  
**EUT** : REMOTE CONTROL RECEIVER  
**Test Mode** : Remote Mode  
**Test Date** : 05/10/2005

<b>Radiated Emissions (VERTICAL)</b>					
<b>Frequency (MHz)</b>	<b>Amplitude (dBuV/m)</b>	<b>Ant. (m)</b>	<b>Table (Degree)</b>	<b>Limits(Class B) (dBuV/m)</b>	<b>Margin (dB)</b>
30.00	29.26	1.0	100	40	-10.74
59.70	30.84	1.2	80	40	-9.16
124.50	34.56	1.2	350	43.5	-8.94
176.07	35.02	1.0	280	43.5	-8.48
198.21	37.24	2.0	200	43.5	-6.26
304.90	38.13	1.8	340	46	-7.87
409.90	38.74	1.4	100	46	-7.26
478.50	40.18	2.5	180	46	-5.82
514.20	38.53	1.6	250	46	-7.47
638.10	39.29	1.5	220	46	-6.71
769.70	35.24	1.3	300	46	-10.76

- Notes :**
- 1. Margin= Amplitude - Limits
  - 2. Distance of Measurement : 3 Meter (30-1000MHz)
  - 3. Height of table for EUT placed: 0.8 Meter.
  - 4. ANT= Antenna height.
  - 5. Amplitude= Reading Amplitude -Amplifier gain+Cable loss +Antenna factor  
(Auto calculate in spectrum analyzer)
  - 6. The worst case test data recorded in the tables


## **Appendix I- EUT Test SETUP**

### MEASUREMENT OF POWER LINE CONDUCTED RFI VOLTAGE



**Appendix I- EUT Test SETUP**

MEASUREMENT OF RADIATED EMISSION





**Appendix II- Model No. List**

Model No.
RC-SMART-II & SMART-STAR-II 1410-A & 1410T/LCD-A 1410TH-A & 3324R 3324PM & 3002R 3002PM & 3003R 3003PM

Note: The above mentioned model numbers are added for business demands, and the Outlook and electric feature are identical same.