

# MEASUREMENT REPORT


(FCC : Part 15 Subpart C / ANSI C63.4-2003)




Testing Laboratory  
1288

Product.....: Transmitter  
Trade Name.....: Skytech II, Inc.  
Model No.....: SKY-3301P2(The others see Appendix II)  
Applicant.....: Skytech II, Inc.  
Applicant Address.....: 9230 Conservation Way Fort Wayne, IN  
46809 U.S.A.

<b>Report Number</b>	MLT0904P15001
<b>Applicant</b>	Skytech II, Inc.
<b>Product</b>	Transmitter
<b>Sample Received Date</b>	2009/04/07

<b>Report Prepared By</b>	Jesse Tien
<b>Signature</b>	
<b>Date Prepared</b>	2009/04/07 ~ 2009/05/04

<b>Report Authorized By</b>	Roger Chen
<b>Signature</b>	
<b>Date Authorized</b>	2009/05/05

Test By

**Max Light Technology Co., Ltd.**  
 Room 5, 8F, No.125, Section 3 Roosevelt Road,  
 Taipei, Taiwan., R.O.C.  
 Office : Tel: 886-2-2363-2447 Fax: 886-2-2363-2597  
 Lab. : Tel: 886-2-2663-3486 Fax: 886-2-2663-3582

It may be duplicated completely for legal use with the allowance of the applicant.  
 It shall not be reproduced except in full, without the written approval of our  
 laboratory.

## **Table of Contents :**

1. General .....	5.
2. Conducted Emissions Requirements .....	7
3. Radiated Emissions Requirements .....	8.
4. Transmitter Bandwidth Measurements .....	18.
5. Transmitter Duty Cycle Measurements .....	20.
6. Verification of De-activation after 5 seconds .....	24.
Appendix I ( EUT Test Setup ) .....	27.
Appendix II ( Brand / Trade Name & Model No. Multiple Listee ) .....	28.

## CERTIFICATION


We here by verify that :


The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4-2003. All test were conducted by MLT(Max Light Technology Co.,Ltd) Room 5, 8F, No.125, Section 3 Roosevelt Road, Taipei, Taiwan, R.O.C Also, we attest to the accuracy of each.

We further submit that the energy emitted by the sample EUT tested as described in the report is in compliance with radiated emission limit of FCC Rules Part 15 Subpart C Section 15.231.

<b>Applicant Name</b>	Skytech II, Inc.
<b>Applicant Address</b>	9230 Conservation Way,Ft. Wayne,IN 46809,U.S.A.
<b>Manufacturer Name</b>	FEGO Precision Industrial Co.,Ltd
<b>Manufacturer Address</b>	947 LIN SEN RD., WU-FENG SHIANG TAICHUNG HSIEN R.O.C.

<b>Equipment</b>	Transmitter
<b>Model No</b>	SKY-3301P2(The others see Appendix II)
<b>FCC ID</b>	K9L3301P2

<b>Report Prepared By</b>	Jesse Tien
<b>Signature</b>	

<b>Report Authorized By</b>	Roger Chen
<b>Signature</b>	

# 1. GENERAL

## 1.1 Introduction

The following measurement report is submitted on behalf of Skytech II, Inc. In support of an Intentional Periodic Radiator certification in accordance with Part 2 Subpart J and Part 15 Subpart A And C of the Commission's and Regulations.

## 1.2 Customer Details

<b>Applicant Name</b>	Skytech II, Inc.
<b>Applicant Address</b>	9230 Conservation Way, Ft. Wayne, IN 46809, U.S.A.
<b>Manufacturer Name</b>	FEGO Precision Industrial Co., Ltd.
<b>Manufacturer Address</b>	947 LIN SEN RD., WU-FENG SHIANG TAICHUNG HSIEN R.O.C.

## 1.3 Technical data of EUT


<b>Equipment</b>	Transmitter
<b>Model No</b>	SKY-3301P2(The others see Appendix II)
<b>FCC ID</b>	K9L3301P2
<b>Power Type</b>	Powered by 3V Battery (1.5V AAA Size X2).

The EUT SKY-3301P2(The others see Appendix II) is remote transmitter. The operation frequency is 303.8Mhz. Press the button on remote transmitter, can set the MODE / UP / DOWN / PROG / SET function.

## 1.4 Description of Support Equipment

The EUT itself forms a system. No support equipment is required for its normal operation.

## 1.5 Configuration of System Under Test



## 1.6 Test Procedure

All measurements contained in this report were performed according to the techniques described in Measurement procedure ANSI C63.4: 2003 "Measurement of Intentional Radiators."

## 1.7 General Test Condition

The conditions under which the EUT operates were varied to determine their effect on the equipment's emission characteristics. The final configuration of the test system and the mode of operation used during these tests was chosen as that which produced the highest emission levels. However, only those conditions which the EUT was considered likely to encounter in normal use were investigated.



## 2. Conducted Emissions Requirements

The EUT operates solely by the battery. According to the rule of Section 15.207(c), the EUT is exempt from the power line conducted test.

## **3. Radiated Emissions Requirements**

### **3.1 General Configuration:**

Prior to open-field testing, the EUT was placed in a shielded enclosure and scanned at a close distance to determine its emission characteristics. The physical arrangement of the EUT was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude, directivity, and frequency. The exact system configuration which produced the highest emissions was noted so it could be reproduced later during the open-field tests. This was done to ensure that the final measurements would demonstrate the worst-case interference potential of the EUT.

### **3.2 General Configuration:**

Final radiation measurements were made on a three-meter, open-field test site. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 30 MHz to 5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

The field strength below 1 GHz was measured by EMCO Biconilog Antenna (mode 3142C) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 – 40 GHz at a distance of 3 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).



For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m)} = \text{FI(dBuV)} + \text{AF(dBm)} + \text{CL(dBuV)} - \text{Gain(dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Duty(dB)} - \text{Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(1) For fundamental frequency :

(1.1) For the manual transmission, according to 15.231(b)

<b>FUNDAMENTAL FREQUENCY (MHz), excluding restricted band frequencies of Table 2</b>	<b>FIELD STRENGTH OF FUNDAMENTAL microvolts/m at 3 metres, (watts, EIRP)(1)</b>	<b>FIELD STRENGTH OF UNWANTED EMISSIONS(1) microvolt/metre at 3 metres</b>
40.66-40.70	2250	225
70-130	1,250	125
130-174	1,250 to 3,750*	125 to 375*
174-260 (note 1)	3,750	375
260-470 (note 1)	3,750 to 12,500*	375 to 1,250*
Above 470	12,500	1250

**Note :** Use quasi-peak or averaging meter.

\*Linear interpolation with frequency F in MHz:

For 130-174 MHz: FS (microvolts/m) = (56.82 x F) - 6136

For 260-470 MHz: FS (microvolts/m) = (41.67 x F) - 7083

(1.2) For the automatic transmission, according to 15.231(e)

<b>FUNDAMENTAL FREQUENCY (MHz), excluding restricted band frequencies of Table 2</b>	<b>FIELD STRENGTH OF FUNDAMENTAL microvolts/m at 3 metres, (watts, EIRP)(1)</b>	<b>FIELD STRENGTH OF UNWANTED EMISSIONS(1) microvolt/metre at 3 metres</b>
40.66-40.70	1000	100
70-130	500	50
130-174	500 to 1,500*	50 to 150*
174-260 (note 1)	1,500	150
260-470 (note 1)	1,500 to 5,000*	150 to 500*
Above 470	5,000	500

**Note :** Use quasi-peak or averaging meter.

\* Linear interpolation with frequency F in MHz:

For 130-174 MHz: FS (microvolts/m) = (22.73 x F) – 2454.55

For 260-470 MHz: FS (microvolts/m) = (16.67 x F) – 2833.33

(2) For spurious frequency :

Spurious emission limits = fundamental emission limit /10

### 3.3 Test Equipment List:

Item	Mfr/Brand	Instruments	Serial No.	Model/Type No.	Calibrated Date	Next Cali. Date
1.	HP	Spectrum Analyzer	73412A00110	8591EM	2009/03/26	2010/03/26
2.	HP	Pre Amplifier	2944A08954	8447D	2009/03/26	2010/03/26
3.	HP	Pre Amplifier	3113A05475	8447F	2009/03/26	2010/03/26
4.	EMCO	Biconilog Antenna	00044568	3142C	2008/08/05	2009/08/05
5.	Agilent	Spectrum Analyzer	US44300422	E4446A	2009/04/22	2010/04/22
6.	HP	Pre Amplifier	3008A01463	8449B	2009/03/20	2010/03/20
7.	SCHWARZBECK	Horn Antenna	304	BBHA 9120 D	2008/08/29	2009/08/29
8.	EMCO	Biconilog Antenna	00059739	3142C	2008/08/11	2009/08/11
9.	HP	Pre Amplifier	1937A00786	8447F	2009/04/10	2010/04/10

### 3.4 Measurement Data Of Radiated Emissions:

#### 3.4.1 Open Field Radiated Emissions (Horizontal/X-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Test Mode : Transmitter

Radiated Emissions (Fundamental Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.80	66.63	1.4	130	7.79	58.84	66.97	-8.13
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
303.80	66.63	1.4	130	66.63		86.97	-20.34

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
606.60	36.84	1.2	240	7.79	29.05	54.00	-24.95
911.10	26.48	1.1	290	7.79	18.69	54.00	-35.31

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
1213.00	29.56	1	260	29.56		74.00	-44.44
1819.00	27.86	1	90	27.86		74.00	-46.14
3238.00	31.23	1	300	31.23		74.00	-42.77

**Notes :** 1.Margin= Actual Amp – Limits

2. Distance of Measurement : 3 Meter

3. Height of table for EUT placed: 0.8 Meter.

4. ANT= Antenna height.

5. Duty= Duty cycle correction factor.

6. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ;

Y denotes Vertical Stand.

### 3.4.2 Open Field Radiated Emissions (Vertical/X-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Test Mode : Transmitter

Radiated Emissions (Fundamental Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.80	72.26	1	200	7.79	64.47	66.97	-2.50
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
303.80	72.26	1	200	72.26		86.97	-14.71

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
606.60	46.37	1.3	340	7.79	38.58	54.00	-15.42
911.10	36.08	1	120	7.79	28.29	54.00	-25.71

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
1213.00	38.84	1	200	38.84		74.00	-35.16
2245.00	29.59	1	120	29.59		74.00	-44.41
3055.00	30.88	1	140	30.88		74.00	-43.12

- Notes :**
1. Margin= Actual Amp – Limits
  2. Distance of Measurement : 3 Meter
  3. Height of table for EUT placed: 0.8 Meter.
  4. ANT= Antenna height.
  5. Duty= Duty cycle correction factor.
  6. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ;  
Y denotes Vertical Stand.

### 3.4.3 Open Field Radiated Emissions (Horizontal/Y-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Test Mode : Transmitter

Radiated Emissions (Fundamental Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.80	72.75	1.8	310	7.79	64.96	66.97	-2.01
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
303.80	72.75	1.8	310	72.75		86.97	-14.22

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
606.60	50.39	1.6	220	7.79	42.60	54.00	-11.40
909.70	37.24	1	180	7.79	29.45	54.00	-24.55

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
1213.00	36.19	1	330	36.19		74.00	-37.81
2074.00	28.89	1	160	28.89		74.00	-45.11
3085.00	31.43	1	210	31.43		74.00	-42.57

- Notes :**
1. Margin= Actual Amp – Limits
  2. Distance of Measurement : 3 Meter
  3. Height of table for EUT placed: 0.8 Meter.
  4. ANT= Antenna height.
  5. Duty= Duty cycle correction factor.
  6. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ;  
Y denotes Vertical Stand.

### 3.4.4 Open Field Radiated Emissions (Vertical/Y-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Test Mode : Transmitter

Radiated Emissions (Fundamental Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.80	70.34	1.2	190	7.79	62.55	66.97	-4.42
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
303.80	70.34	1.2	190	70.34		86.97	-16.63

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
606.60	35.88	1.1	210	7.79	28.09	54.00	-25.91
911.10	32.03	1	100	7.79	24.24	54.00	-29.76

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
1213.00	38.32	1	300	38.32		74.00	-35.68
1516.00	31.07	1	120	31.07		74.00	-42.93
1819.00	27.43	1	180	27.43		74.00	-46.57
3169.00	31.50	1	240	31.50		74.00	-42.50

- Notes :**
1. Margin= Actual Amp – Limits
  2. Distance of Measurement : 3 Meter
  3. Height of table for EUT placed: 0.8 Meter.
  4. ANT= Antenna height.
  5. Duty= Duty cycle correction factor.
  6. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ;  
Y denotes Vertical Stand.

### 3.4.5 Open Field Radiated Emissions (Horizontal/Z-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Test Mode : Transmitter

Radiated Emissions (Fundamental Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.80	73.11	1.9	170	7.79	65.32	66.97	-1.65
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
303.80	73.11	1.9	170	73.11		86.97	-13.86

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
606.60	49.78	1.5	220	7.79	41.99	54.00	-12.01
909.70	37.30	1.1	280	7.79	29.51	54.00	-24.49

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
1213.00	39.55	1	320	39.55		74.00	-34.45
1654.00	26.90	1	130	26.90		74.00	-47.10
3094.00	30.91	1	190	30.91		74.00	-43.09

- Notes :**
1. Margin= Actual Amp – Limits
  2. Distance of Measurement : 3 Meter
  3. Height of table for EUT placed: 0.8 Meter.
  4. ANT= Antenna height.
  5. Duty= Duty cycle correction factor.
  6. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ;  
Y denotes Vertical Stand.



### 3.4.6 Open Field Radiated Emissions (Vertical/Z-axis)

The highest peak values of radiated emissions from the EUT at various antenna heights, antenna polarization, EUT orientation , etc. are recorded on the following

Test Mode : Transmitter

Radiated Emissions (Fundamental Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
303.80	66.32	1	260	7.79	58.53	66.97	-8.44
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
303.80	66.32	1	260	66.32		86.97	-20.65

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Duty (dB)	Actual Amp(AV) (dBuV/m)	Limit (dBuV/m)	Margin (dB)
606.60	29.85	1.3	110	7.79	22.06	54.00	-31.94
909.70	25.37	1	90	7.79	17.58	54.00	-36.42

Radiated Emissions (Unwanted Frequency)							
Frequency (MHz)	Amplitude(Pk) (dBuV/m)	Ant. (m)	Table (Degree)	Actual Amp (Pk) (dBuV/m)		Limit (dBuV/m)	Margin (dB)
1213.00	34.95	1	160	34.95		74.00	-39.05
1516.00	27.31	1	300	27.31		74.00	-46.69
2323.00	29.50	1	110	29.50		74.00	-44.50
3058.00	31.19	1	140	31.19		74.00	-42.81

- Notes :**
1. Margin= Actual Amp – Limits
  2. Distance of Measurement : 3 Meter
  3. Height of table for EUT placed: 0.8 Meter.
  4. ANT= Antenna height.
  5. Duty= Duty cycle correction factor.
  6. EUT Orthogonal Axes : X denotes Laid on Table ; Z denotes Side Stand ;  
Y denotes Vertical Stand.


## 4. Transmitter Bandwidth Measurement

### 4.1 Test Condition & Setup :

The transmitter bandwidth measurements were performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a near field probe was used at a distance about 20 cm for receiving. While testing, EUT was set to transmit continuously.

The resolution bandwidth of the spectrum analyzer was set to 10KHz. The detector function was set to peak and hold mode to clearly observe the components. The maximum permitted bandwidth at  $-20\text{dB}$  with respect to the reference level specified by the rule was 0.25 % of the center frequency of the EUT.

### 4.2 Test Instruments Configuration:




### 4.3 Test Equipment List:

Item	Mfr/Brand	Instruments	Serial No.	Model/Type No.	Calibrated Date	Next Cali. Date
1.	Agilent	Spectrum Analyzer	US39240419	E4407B	2009/02/01	2010/02/01
2.	HP	Pre Amplifier	1937A00786	8447F	2009/04/10	2010/04/10
3.	EMCO	Biconilog Antenna	00059739	3142C	2008/08/11	2009/08/11
4.	EM	Probe	107328	EM-6992	N/A	N/A

#### 4.4 Test Result:

<b>Permitted Maximum Bandwidth</b>	759.50	KHz
<b>Bandwidth Measurement</b>	60.00	KHz

#### 4.5 Test Graphs:



## 5. Transmitter Duty Cycle Measurement

### 5.1 Test Condition & Setup :

The transmitter bandwidth measurements were performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a near field probe was used at a distance about 20 cm for receiving. While testing, EUT was set to transmit continuously. Various key configurations were also investigated to find the maximum duty cycle.

The spectrum analyzer resolution bandwidth and video bandwidth were all set to 1 MHz to encompass all Significant spectral components during the test. The analyzer was operated in linear scale and zero span mode after tuning to the transmitter carrier frequency. A digital oscilloscope was connected to the aux video output of the spectrum analyzer for measuring pulse width. The pulse width was determined by the difference between the half voltage points on a pulse.


The duty cycle was determined by the following equation :

TO calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion :

$$\text{Duty Cycle(\%)} = \frac{\text{(Total On Interval in a Complete Pulse Train)}}{\text{(Length of a Complete Pulse Train)}} \times 100\%$$

$$\text{Duty Cycle Correction Factor (dB)} = 20 \times \text{Log}_{10} (\text{Duty Cycle(\%)})$$

### 5.2 Test Instruments Configuration:



### 5.3 Test Equipment List:

Item	Mfr/Brand	Instruments	Serial No.	Model/Type No.	Calibrated Date	Next Cali. Date
1.	Agilent	Spectrum Analyzer	US39240419	E4407B	2009/02/01	2010/02/01
2.	HP	Pre Amplifier	1937A00786	8447F	2009/04/10	2010/04/10
3.	EMCO	Biconilog Antenna	00059739	3142C	2008/08/11	2009/08/11
4.	EM	Probe	107328	EM-6992	N/A	N/A


### 5.4 Test Result:

Pulse Train	Number of Pulse	T(ms)	Total Time (ms)	
Long Pulse	7	1	7	msec
Short Pulse	25	0.625	15.625	msec


<b>Total ON interval in a complete pulse train</b>	22.625	msec
<b>Length of a complete pulse train</b>	55.5	msec
<b>Duty Cycle (%)</b>	40.76	%
<b>Duty Cycle Correction Factor (dB)</b>	7.79	dB

5.5 Test Graphs: See next page.


### Length of A Complete Pulse Train




### Long Pulse



### Short Pulse



### Long Pulse & Short Pulse (Number of Pulse)




## 6. Verification of De-activation after 5 seconds

### 6.1 Test Condition & Setup :

Verification of the transmitter de-activation after 5 seconds was performed in a shielded enclosure. The EUT was placed on a wooded table which is 0.8 meters height and a near field probe was used at a distance about 20 cm for receiving.

The spectrum analyzer resolution bandwidth and video bandwidth were all set to 100KHZ to encompass all Significant spectral components during the test. The analyzer was operated in linear scale and zero span mode after tuning to the transmitter carrier frequency.

### 6.2 Test Instruments Configuration:



### 6.3 Test Equipment List:


Item	Mfr/Brand	Instruments	Serial No.	Model/Type No.	Calibrated Date	Next Cali. Date
1.	Agilent	Spectrum Analyzer	US39240419	E4407B	2009/02/01	2010/02/01
2.	HP	Pre Amplifier	1937A00786	8447F	2009/04/10	2010/04/10
3.	EMCO	Biconilog Antenna	00059739	3142C	2008/08/11	2009/08/11
4.	EM	Probe	107328	EM-6992	N/A	N/A




**6.4 Test Result:**

Compliant Conditions (Section 15.231)	EUT Status			
1. The EUT was manually operated		<b>Yes</b>	<b>x</b>	<b>No</b>
Requirement: The EUT employs a switch that would automatically deactivate the transmitter no more than 5 seconds of being released.				
2. The EUT was automatically activated	<b>x</b>	<b>Yes</b>		<b>No</b>
Requirement: The EUT operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.				

### Manually Operated




### Automatically Operated



## Appendix I- EUT Test SETUP

### MEASUREMENT OF RADIATED EMISSION



## Appendix II- Brand /Trade Name & Model No. Multiple Listee

Brand /Trade Name	Model Name
Skytech II, Inc.	SKY-3301P2 SKY-3301P2BE SKY-3301P2PF