FCC ID : KA2AP1353B1 Report No.: 90407002-RP1

Page 92 of 213

8.4 MAXIMUM PERMISSIBLE EXPOSURE

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate theenvironment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range | Electric Field | Magnetic Field | Power Density | Average Time | | | | | |
|---|----------------|----------------|----------------------|--------------|--|--|--|--|--|
| (MHz) | Strength (V/m) | Strength (A/m) | $(\mathbf{mW/cm}^2)$ | | | | | | |
| (A) Limits for Occupational / Control Exposures | | | | | | | | | |
| 300-1,500 | | | F/300 | 6 | | | | | |
| 1,500-100,000 | | | 5 | 6 | | | | | |
| (B) Limits for General Population / Uncontrol Exposures | | | | | | | | | |
| 300-1,500 | | | F/1500 | 6 | | | | | |
| 1,500-100,000 | | | 1 | 30 | | | | | |

CALCULATIONS

Given

$$E = \frac{\sqrt{30 \times P \times G}}{d} \& S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and

$$d(cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW/cm^2$

FCC ID : KA2AP1353B1 Report No. : 90407002-RP1

Page 93 of 213

LIMIT

Power Density Limit, S=1.0mW/cm²

TEST RESULTS

No non-compliance noted

| Mode | Antenna Gain (dBi) | Minimum separation distance (cm) | Output Power (dBm) | Numeric antenna gain (dB) | Power Density Limit (mW/cm²) | Power Density at 20cm (mW/cm ²) |
|-------------------|--------------------------|---|--------------------------|------------------------------------|------------------------------|--|
| IEEE 802.11b | 3 | 20.0 | 25.81 | 2 | 1.00 | 0.151259 |
| IEEE 802.11g | 3 | 20.0 | 25.82 | 2 | 1.00 | 0.151607 |
| IEEE 802.11n HT20 | 3 | 20.0 | 25.84 | 2 | 1.00 | 0.152307 |
| IEEE 802.11n HT40 | 3 | 20.0 | 25.74 | 2 | 1.00 | 0.148840 |

Remark: For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.