

# RF EXPOSURE REPORT

**REPORT NO.:** SA110324E03A

**MODEL NO.:** DAP-1522

**FCC ID:** KA2AP1522B1

**APPLICANT:** D-Link Corporation

**ADDRESS:** No.289, Sinhu 3rd Rd., Neihu District,  
Taipei City 114, Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

**LAB ADDRESS:** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 6 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement. The test results in the report only apply to the tested sample.

# TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	3
1. CERTIFICATION .....	4
2. RF EXPOSURE LIMIT .....	5
3. MPE CALCULATION FORMULA .....	5
4. CLASSIFICATION .....	5
5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA110324E03A	Original release	Oct. 06, 2011

## 1. CERTIFICATION

**PRODUCT:** Xtreme N DUO Wireless Bridge/Access Point  
**BRAND NAME:** D-Link  
**MODEL NO.:** DAP-1522  
**TEST SAMPLE:** MASS-PRODUCTION  
**APPLICANT:** D-Link Corporation  
**STANDARDS:** FCC Part 2 (Section 2.1091)  
FCC OET Bulletin 65, Supplement C (01-01)  
IEEE C95.1

The above equipment (Model: DAP-1522) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Midoli Peng, **DATE:** Oct. 06, 2011  
( Midoli Peng, Specialist )

**APPROVED BY** : May Chen, **DATE:** Oct. 06, 2011  
( May Chen, Deputy Manager )

## 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

### 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

**For 15.407(5GHz):**

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5260-5320, 5500-5700	138.4	2.68	20	0.051	1.00

--- END ---