

Label

D-LINK

Model name : DAP-1655

D-Link® **DAP-1655**

Default setting: http://192.168.0.50
Username: "Admin"
Password: " " (leave the field blank)

FCC ID: KA2AP1655A1
IC: 4261A-AP1655A1
M/N: DAP-1655A1
CAN ICES-3 (B)/NMB-3(B)

H/W Ver.: A1 F/W Ver.: 1.00
Wi-Fi Name (SSID): dlink-0001
MAC ID: XXXXXX000001

Label

Barcode

Password: XXXXXXXXXXXX

CSA60950-1
UL 60950-1
IEC 60950-1
EN 60950-1

FC

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Polarity:
⊖ ⊕
Input:
12V =1A

LR93673 US

CE

Made In China

LABEL LOCATION

Brad name : D-Link

FCC Model name : DAP-1655

IC Model name : DAP-1655A1

D-Link® **DAP-1655**

Default setting: <http://192.168.0.50>
Username: "Admin"
Password: " " (leave the field blank)

FCC ID: KA2AP1655A1
IC: 4261A-AP1655A1
M/N: DAP-1655A1
CAN ICES-3 (B)/NMB-3(B)

H/W Ver.: A1 F/W Ver.: 1.00
Wi-Fi Name (SSID): dlink-0001
MAC ID: XXXXXX000001
Password: XXXXXXXXXX

CSA C0950-1
UL 60950-1
IEC 60950-1
EN 60950-1

FCC

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Polarity:
⊖ ⊕
Input:
12V =1A

Made In China

