

## FCC Test Report (Co-Located)

**Report No.:** RF190726C11A-2

**FCC ID:** KA2BA2520PA1

**Test Model:** DBA-2520P

**Received Date:** Jul. 26, 2019

**Test Date:** Dec. 24 ~ Dec. 25, 2019

**Issued Date:** Dec. 25, 2019

**Applicant:** D-Link Corporation

**Address:** 17595 Mt. Herrmann, Fountain Valley, California, United States, 92708

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, TAIWAN

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                              | <b>3</b>  |
| <b>1 Certificate of Conformity.....</b>                          | <b>4</b>  |
| <b>2 Summary of Test Results .....</b>                           | <b>5</b>  |
| 2.1 Measurement Uncertainty .....                                | 5         |
| 2.2 Modification Record .....                                    | 5         |
| <b>3 General Information.....</b>                                | <b>6</b>  |
| 3.1 General Description of EUT .....                             | 6         |
| 3.2 Description of Test Modes .....                              | 8         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail.....     | 10        |
| 3.3 Description of Support Units .....                           | 11        |
| 3.3.1 Configuration of System under Test .....                   | 11        |
| 3.4 General Description of Applied Standards .....               | 11        |
| <b>4 Test Types and Results .....</b>                            | <b>12</b> |
| 4.1 Radiated Emission and Bandedge Measurement.....              | 12        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement ..... | 12        |
| 4.1.2 Test Instruments .....                                     | 13        |
| 4.1.3 Test Procedures.....                                       | 14        |
| 4.1.4 Deviation from Test Standard .....                         | 14        |
| 4.1.5 Test Setup.....                                            | 15        |
| 4.1.6 EUT Operating Conditions.....                              | 16        |
| 4.1.7 Test Results .....                                         | 17        |
| <b>5 Pictures of Test Arrangements.....</b>                      | <b>25</b> |
| <b>Appendix – Information of the Testing Laboratories .....</b>  | <b>26</b> |

### Release Control Record

| Issue No.      | Description       | Date Issued   |
|----------------|-------------------|---------------|
| RF190726C11A-2 | Original release. | Dec. 25, 2019 |

## 1 Certificate of Conformity

**Product:** Nuclias Cloud-Managed AC1900 Wave 2 Access Point

**Brand:** D-Link Corporation

**Test Model:** DBA-2520P

**Sample Status:** Engineering sample

**Applicant:** D-Link Corporation

**Test Date:** Dec. 24 ~ Dec. 25, 2019

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
47 CFR FCC Part 15, Subpart E (Section 15.407)  
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :**



Polly Chien / Specialist

**Date:**

Dec. 25, 2019

**Approved by :**



Bruce Chen / Senior Project Engineer

**Date:**

Dec. 25, 2019

## 2 Summary of Test Results

| Applied Standard:                                                | 47 CFR FCC Part 15, Subpart C (Section 15.247)<br>47 CFR FCC Part 15, Subpart E (Section 15.407) |        |                                                                                   |
|------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------|-----------------------------------------------------------------------------------|
| FCC Clause                                                       | Test Item                                                                                        | Result | Remarks                                                                           |
| 15.205 / 15.209 /<br>15.247(d)<br>15.407(b)<br>(1/2/3/4(i/ii)/6) | Radiated Emissions                                                                               | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -0.2dB at 2483.50MHz. |

Note:

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                    | Frequency        | Expanded Uncertainty (k=2) ( $\pm$ ) |
|--------------------------------|------------------|--------------------------------------|
| Radiated Emissions up to 1 GHz | 9kHz ~ 30MHz     | 3.04 dB                              |
|                                | 30MHz ~ 200MHz   | 3.59 dB                              |
|                                | 200MHz ~ 1000MHz | 3.60 dB                              |
| Radiated Emissions above 1 GHz | 1GHz ~ 18GHz     | 2.29 dB                              |
|                                | 18GHz ~ 40GHz    | 2.29 dB                              |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product               | Nuclias Cloud-Managed AC1900 Wave 2 Access Point                                                                                                                                                                                                                                                                                                                        |
| Brand                 | D-Link Corporation                                                                                                                                                                                                                                                                                                                                                      |
| Test Model            | DBA-2520P                                                                                                                                                                                                                                                                                                                                                               |
| Status of EUT         | Engineering sample                                                                                                                                                                                                                                                                                                                                                      |
| Power Supply Rating   | 12Vdc (From adapter)<br>54Vdc (From PoE)                                                                                                                                                                                                                                                                                                                                |
| Modulation Type       | CCK, DQPSK, DBPSK for DSSS<br>256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM                                                                                                                                                                                                                                                                                                 |
| Modulation Technology | DSSS, OFDM                                                                                                                                                                                                                                                                                                                                                              |
| Transfer Rate         | 802.11b: 11/5.5/2/1Mbps<br>802.11a/g: 54/48/36/24/18/12/9/6Mbps<br>802.11n: up to 600Mbps<br>802.11ac: up to 1300Mbps                                                                                                                                                                                                                                                   |
| Operating Frequency   | 2.4GHz: 2412 ~ 2462MHz<br>5.0GHz: 5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5720MHz,<br>5745 ~ 5825MHz                                                                                                                                                                                                                                                                     |
| Number of Channel     | 2412 ~ 2462MHz:<br>11 for 802.11b, 802.11g, 802.11n (HT20)<br>7 for 802.11n (HT40)<br>5260 ~ 5320MHz:<br>4 for 802.11a, 802.11n (HT20), 802.11ac (VHT20)<br>2 for 802.11n (HT40), 802.11ac (VHT40)<br>1 for 802.11ac (VHT80)<br>5500 ~ 5720MHz:<br>12 for 802.11a, 802.11n (HT20), 802.11ac (VHT20)<br>6 for 802.11n (HT40), 802.11ac (VHT40)<br>3 for 802.11ac (VHT80) |
| Antenna Type          | Refer to Note                                                                                                                                                                                                                                                                                                                                                           |
| Antenna Connector     | Refer to Note                                                                                                                                                                                                                                                                                                                                                           |
| Accessory Device      | Adapter                                                                                                                                                                                                                                                                                                                                                                 |
| Data Cable Supplied   | NA                                                                                                                                                                                                                                                                                                                                                                      |

**Note:**

1. This report is prepared for FCC class II permissive change. The differences compared with the original report (BV CPS report no.: RF190726C11-2) are adding 5.26GHz to 5.32GHz and 5.50GHz to 5.72GHz by software.
2. The EUT incorporates a MIMO function. Physically, the EUT provides 3 completed transmitters and 3 receivers.

| Band   | Modulation Mode  | Beamforming Mode | TX Function |
|--------|------------------|------------------|-------------|
| 2.4GHz | 802.11b          | Not Support      | 3TX         |
|        | 802.11g          | Not Support      | 3TX         |
|        | 802.11n (HT20)   | Support          | 3TX         |
|        | 802.11n (HT40)   | Support          | 3TX         |
|        | 802.11n (VHT20)  | Support          | 3TX         |
|        | 802.11n (VHT40)  | Support          | 3TX         |
| 5GHz   | 802.11a          | Not Support      | 3TX         |
|        | 802.11n (HT20)   | Support          | 3TX         |
|        | 802.11n (HT40)   | Support          | 3TX         |
|        | 802.11ac (VHT20) | Support          | 3TX         |
|        | 802.11ac (VHT40) | Support          | 3TX         |
|        | 802.11ac (VHT80) | Support          | 3TX         |

\* The modulation and bandwidth are similar for 802.11n mode for 20MHz/40MHz and 802.11ac mode for 20MHz/40MHz, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

\* For 802.11n, CDD mode is the worst case for final radiated emission tests after pretesting CDD mode and beamforming mode.

3. The EUT uses following antennas.

| Type | Connector  | Ant. Gain (dBi) |          |          |          |          |          |          |
|------|------------|-----------------|----------|----------|----------|----------|----------|----------|
|      |            | 2400 MHz        | 2450 MHz | 2500 MHz | 5150 MHz | 5350 MHz | 5725 MHz | 5825 MHz |
| PIFA | I-pex(MHF) | 3               | 3        | 3        | 4        | 4        | 4        | 4        |

4. The EUT consumes power from the following Adapters and PoE.

| Adapter 1    |                                           |
|--------------|-------------------------------------------|
| Brand        | Channel Well Technology                   |
| Model        | 2ABL030F US                               |
| Input Power  | 100-240Vac, 50-60Hz, 1.0A                 |
| Output Power | 12Vdc / 2.5A                              |
| Power Cord   | 1.2m non-shielded power cord without core |

| Adapter 2    |                                           |
|--------------|-------------------------------------------|
| Brand        | Asian Power Devices Inc.                  |
| Model        | WA-30J12R                                 |
| Input Power  | 100-240Vac~, 50-60Hz, 0.9A                |
| Output Power | 12Vdc / 2.5A                              |
| Power Cord   | 1.2m non-shielded power cord without core |

| PoE (Support unit) |                            |
|--------------------|----------------------------|
| Brand              | LEADER ELECTRONICS INC.    |
| Model              | NU90-J540167-I1            |
| Input Power        | 100-240Vac~, 50-60Hz, 1.2A |
| Output Power       | 54Vdc / 1.67A              |

### 3.2 Description of Test Modes

#### For 2.4GHz

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), 802.11n (VHT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   |         |           |

7 channels are provided for 802.11n (HT40), 802.11n (VHT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 3       | 2422MHz   | 7       | 2442MHz   |
| 4       | 2427MHz   | 8       | 2447MHz   |
| 5       | 2432MHz   | 9       | 2452MHz   |
| 6       | 2437MHz   |         |           |

#### For 5260~5320MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 52      | 5260 MHz  | 60      | 5300 MHz  |
| 56      | 5280 MHz  | 64      | 5320 MHz  |

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 54      | 5270 MHz  | 62      | 5310 MHz  |

1 channel is provided for 802.11ac (VHT80):

| Channel | Frequency |
|---------|-----------|
| 58      | 5290MHz   |

For 5500~5720MHz:

12 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 100     | 5500 MHz  | 124     | 5620 MHz  |
| 104     | 5520 MHz  | 128     | 5640 MHz  |
| 108     | 5540 MHz  | 132     | 5660 MHz  |
| 112     | 5560 MHz  | 136     | 5680 MHz  |
| 116     | 5580 MHz  | 140     | 5700 MHz  |
| 120     | 5600 MHz  | 144     | 5700 MHz  |

6 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 102     | 5510 MHz  | 126     | 5630 MHz  |
| 110     | 5550 MHz  | 134     | 5670 MHz  |
| 118     | 5590 MHz  | 142     | 5710 MHz  |

3 channels are provided for 802.11ac (VHT80):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 106     | 5530 MHz  | 122     | 5610 MHz  |
| 138     | 5690 MHz  |         |           |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable to |       | Description          |
|--------------------|---------------|-------|----------------------|
|                    | RE $\geq$ 1G  | RE<1G |                      |
| A                  | √             | √     | Power from adapter 1 |
| B                  | -             | √     | Power from adapter 2 |
| C                  | -             | √     | Power from PoE       |

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**.
2. "-" means no effect.
3. Radiated emission test items chosen the worst maximum fundamental frequency emission level of 2.4G and 5G UNII-2A Radio channel.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode                     | Freq. Range (MHz) | Available Channel | Tested Channel | Modulation Technology |
|--------------------|--------------------------|-------------------|-------------------|----------------|-----------------------|
| A                  | 802.11g + 802.11n (HT20) | 2412 ~ 2462       | 1 to 11           | 6 + 52         | BPSK                  |
|                    |                          | 5260-5320         | 52 to 64          |                | OFDM                  |

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Mode                     | Freq. Range (MHz) | Available Channel | Tested Channel | Modulation Technology |
|--------------------|--------------------------|-------------------|-------------------|----------------|-----------------------|
| A, B, C            | 802.11g + 802.11n (HT20) | 2412 ~ 2462       | 1 to 11           | 6 + 52         | BPSK                  |
|                    |                          | 5260-5320         | 52 to 64          |                | OFDM                  |

#### Test Condition:

| Applicable to | Environmental Conditions | Input Power           | Tested by |
|---------------|--------------------------|-----------------------|-----------|
| RE $\geq$ 1G  | 24 deg. C, 68% RH        | 120Vac, 60Hz          | Greg Lin  |
| RE<1G         | 24 deg. C, 68% RH        | 120Vac, 60Hz<br>54Vdc | Greg Lin  |

### 3.3 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product | Brand                   | Model No.       | Serial No. | FCC ID | Remarks            |
|----|---------|-------------------------|-----------------|------------|--------|--------------------|
| A. | PoE     | LEADER ELECTRONICS INC. | NU90-J540167-I1 | NA         | NA     | Provided by client |


| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|--------------|------|------------|--------------------|--------------|---------|
| 1. | RJ45 cable   | 1    | 10         | N                  | 0            | Cat5e   |

#### 3.3.1 Configuration of System under Test

Mode A, B



Mode C



### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specification of the EUT declared by the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**FCC Part 15, Subpart E (15.407)**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

| Applicable To                                                                                    |                                     |                  | Limit                                                                                                                                   |                                                                                                                                           |
|--------------------------------------------------------------------------------------------------|-------------------------------------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| 789033 D02 General UNII Test Procedure<br>New Rules v02r01                                       |                                     |                  | Field Strength at 3m                                                                                                                    |                                                                                                                                           |
|                                                                                                  |                                     |                  | PK: 74 (dBµV/m)                                                                                                                         | AV: 54 (dBµV/m)                                                                                                                           |
| Frequency Band                                                                                   | Applicable To                       |                  | EIRP Limit                                                                                                                              | Equivalent Field Strength at 3m                                                                                                           |
| 5150~5250 MHz                                                                                    | 15.407(b)(1)                        |                  | PK: -27 (dBm/MHz)                                                                                                                       | PK: 68.2(dBµV/m)                                                                                                                          |
| 5250~5350 MHz                                                                                    | 15.407(b)(2)                        |                  |                                                                                                                                         |                                                                                                                                           |
| 5470~5725 MHz                                                                                    | 15.407(b)(3)                        |                  |                                                                                                                                         |                                                                                                                                           |
| 5725~5850 MHz                                                                                    | <input checked="" type="checkbox"/> | 15.407(b)(4)(i)  | PK: -27 (dBm/MHz) <sup>*1</sup><br>PK: 10 (dBm/MHz) <sup>*2</sup><br>PK: 15.6 (dBm/MHz) <sup>*3</sup><br>PK: 27 (dBm/MHz) <sup>*4</sup> | PK: 68.2(dBµV/m) <sup>*1</sup><br>PK: 105.2 (dBµV/m) <sup>*2</sup><br>PK: 110.8(dBµV/m) <sup>*3</sup><br>PK: 122.2 (dBµV/m) <sup>*4</sup> |
|                                                                                                  | <input type="checkbox"/>            | 15.407(b)(4)(ii) | Emission limits in section 15.247(d)                                                                                                    |                                                                                                                                           |
| <sup>*1</sup> beyond 75 MHz or more above of the band edge.                                      |                                     |                  | <sup>*2</sup> below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.                                                    |                                                                                                                                           |
| <sup>*3</sup> below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. |                                     |                  | <sup>*4</sup> from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.                    |                                                                                                                                           |

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.2 Test Instruments

| Description & Manufacturer              | Model No.                              | Serial No.                      | Date of Calibration | Due Date of Calibration |
|-----------------------------------------|----------------------------------------|---------------------------------|---------------------|-------------------------|
| Test Receiver<br>KEYSIGHT               | N9038A                                 | MY55420137                      | Apr. 15, 2019       | Apr. 14, 2020           |
| Spectrum Analyzer<br>ROHDE & SCHWARZ    | FSP40                                  | 100039                          | Jun. 12, 2019       | Jun. 11, 2020           |
| BILOG Antenna<br>SCHWARZBECK            | VULB9168                               | 9168-160                        | Nov. 07, 2019       | Nov. 06, 2020           |
| HORN Antenna<br>SCHWARZBECK             | BBHA 9120 D                            | 9120D-1169                      | Nov. 24, 2019       | Nov. 23, 2020           |
| HORN Antenna<br>SCHWARZBECK             | BBHA 9170                              | BBHA9170241                     | Nov. 24, 2019       | Nov. 23, 2020           |
| Loop Antenna<br>TESEQ                   | HLA 6121                               | 45745                           | Jul. 01, 2019       | Jun. 30, 2020           |
| Preamplifier<br>Agilent<br>(Below 1GHz) | 8447D                                  | 2944A10638                      | Jul. 11, 2019       | Jul. 10, 2020           |
| Preamplifier<br>Agilent<br>(Above 1GHz) | 8449B                                  | 3008A02367                      | Feb. 19, 2019       | Feb. 18, 2020           |
| RF signal cable<br>HUBER+SUHNER&EMCI    | SUCOFLEX 104 &<br>EMC104-SM-SM80<br>00 | CABLE-CH9-02<br>(248780+171006) | Jan. 19, 2019       | Jan. 18, 2020           |
| RF signal cable<br>HUBER+SUHNER         | SUCOFLEX 104                           | CABLE-CH9-(2507<br>95/4)        | Jul. 11, 2019       | Jul. 10, 2020           |
| RF signal cable<br>WOKEN                | 8D-FB                                  | Cable-CH9-01                    | Jul. 30, 2019       | Jul. 29, 2020           |
| Software<br>BV ADT                      | ADT_Radiated_<br>V7.6.15.9.5           | NA                              | NA                  | NA                      |
| Antenna Tower<br>EMCO                   | 2070/2080                              | 512.835.4684                    | NA                  | NA                      |
| Turn Table<br>EMCO                      | 2087-2.03                              | NA                              | NA                  | NA                      |
| Antenna Tower & Turn<br>BV ADT          | AT100                                  | AT93021705                      | NA                  | NA                      |
| Turn Table<br>BV ADT                    | TT100                                  | TT93021705                      | NA                  | NA                      |
| Turn Table Controller<br>BV ADT         | SC100                                  | SC93021705                      | NA                  | NA                      |
| Boresight Antenna Fixture               | FBA-01                                 | FBA-SIP01                       | NA                  | NA                      |
| Pre-amplifier<br>(18GHz-40GHz)<br>EMC   | EMC184045B                             | 980175                          | Sep. 05, 2019       | Sep. 04, 2020           |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Chamber 9.

#### 4.1.3 Test Procedures

##### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz. (11g: RBW = 1 MHz, VBW = 1 kHz; 5G 11n (HT20): RBW = 1 MHz, VBW = 1 kHz)
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- The EUT ran a test program (QRCT 3.0.303.0) to enable EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 Test Results

Above 1GHz Data:

802.11g + 802.11n (HT20)

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| CHANNEL         | CH 6 + CH 52 | DETECTOR FUNCTION | Peak (PK)<br>Average (AV) |
| FREQUENCY RANGE | 1GHz ~ 40GHz |                   |                           |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 123.8 PK                      |                   |                | 2.33 H                   | 88                         | 91.7                   | 32.1                           |
| 2                                                   | *2437.00       | 113.7 AV                      |                   |                | 2.33 H                   | 88                         | 81.6                   | 32.1                           |
| 3                                                   | 2483.50        | 66.5 PK                       | 74.0              | -7.5           | 2.40 H                   | 90                         | 34.4                   | 32.1                           |
| 4                                                   | <b>2483.50</b> | <b>53.8 AV</b>                | <b>54.0</b>       | <b>-0.2</b>    | <b>2.40 H</b>            | <b>90</b>                  | <b>21.7</b>            | <b>32.1</b>                    |
| 5                                                   | 4874.00        | 47.1 PK                       | 74.0              | -26.9          | 3.09 H                   | 269                        | 43.1                   | 4.0                            |
| 6                                                   | 4874.00        | 33.1 AV                       | 54.0              | -20.9          | 3.09 H                   | 269                        | 29.1                   | 4.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 121.4 PK                      |                   |                | 3.50 V                   | 333                        | 89.3                   | 32.1                           |
| 2                                                   | *2437.00       | 111.1 AV                      |                   |                | 3.50 V                   | 333                        | 79.0                   | 32.1                           |
| 3                                                   | 2483.50        | 64.9 PK                       | 74.0              | -9.1           | 3.42 V                   | 349                        | 32.8                   | 32.1                           |
| 4                                                   | 2483.50        | 51.9 AV                       | 54.0              | -2.1           | 3.42 V                   | 349                        | 19.8                   | 32.1                           |
| 5                                                   | 4874.00        | 47.1 PK                       | 74.0              | -26.9          | 2.64 V                   | 160                        | 43.1                   | 4.0                            |
| 6                                                   | 4874.00        | 32.6 AV                       | 54.0              | -21.4          | 2.64 V                   | 160                        | 28.6                   | 4.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |              |                   |                           |
|-----------------|--------------|-------------------|---------------------------|
| CHANNEL         | CH 6 + CH 52 | DETECTOR FUNCTION | Peak (PK)<br>Average (AV) |
| FREQUENCY RANGE | 1GHz ~ 40GHz |                   |                           |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 55.3 PK                       | 74.0              | -18.7          | 2.05 H                   | 344                        | 48.9                   | 6.4                            |
| 2                                                   | 5150.00        | 42.4 AV                       | 54.0              | -11.6          | 2.05 H                   | 344                        | 36.0                   | 6.4                            |
| 3                                                   | *5260.00       | 120.3 PK                      |                   |                | 1.96 H                   | 345                        | 82.9                   | 37.4                           |
| 4                                                   | *5260.00       | 109.3 AV                      |                   |                | 1.95 H                   | 345                        | 71.9                   | 37.4                           |
| 5                                                   | #10520.00      | 57.6 PK                       | 68.2              | -10.6          | 2.55 H                   | 223                        | 40.6                   | 17.0                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 55.4 PK                       | 74.0              | -18.6          | 2.88 V                   | 260                        | 49.0                   | 6.4                            |
| 2                                                   | 5150.00        | 42.5 AV                       | 54.0              | -11.5          | 2.88 V                   | 260                        | 36.1                   | 6.4                            |
| 3                                                   | *5260.00       | 115.7 PK                      |                   |                | 2.59 V                   | 256                        | 78.3                   | 37.4                           |
| 4                                                   | *5260.00       | 104.8 AV                      |                   |                | 2.59 V                   | 256                        | 67.4                   | 37.4                           |
| 5                                                   | #10520.00      | 57.5 PK                       | 68.2              | -10.7          | 1.91 V                   | 143                        | 40.5                   | 17.0                           |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Below 1GHz data


802.11g + 802.11n (HT20)

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | CH 6 + CH 52 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | A               |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 30.00       | 33.7 QP                 | 40.0           | -6.3        | 1.00 H             | 178                  | 44.9             | -11.2                    |
| 2                                                   | 244.40      | 39.7 QP                 | 46.0           | -6.3        | 1.50 H             | 43                   | 49.6             | -9.9                     |
| 3                                                   | 375.32      | 41.0 QP                 | 46.0           | -5.0        | 1.00 H             | 266                  | 47.7             | -6.7                     |
| 4                                                   | 479.02      | 39.4 QP                 | 46.0           | -6.6        | 2.00 H             | 359                  | 44.4             | -5.0                     |
| 5                                                   | 624.61      | 39.8 QP                 | 46.0           | -6.2        | 1.00 H             | 169                  | 41.5             | -1.7                     |
| 6                                                   | 979.57      | 32.9 QP                 | 54.0           | -21.1       | 1.50 H             | 234                  | 28.4             | 4.5                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | CH 6 + CH 52 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | A               |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 30.00       | 36.7 QP                 | 40.0           | -3.3        | 1.00 V             | 355                  | 47.9             | -11.2                    |
| 2                                                 | 57.16       | 34.0 QP                 | 40.0           | -6.0        | 1.50 V             | 250                  | 44.3             | -10.3                    |
| 3                                                 | 375.32      | 40.6 QP                 | 46.0           | -5.4        | 1.00 V             | 156                  | 47.3             | -6.7                     |
| 4                                                 | 480.96      | 43.3 QP                 | 46.0           | -2.7        | 1.00 V             | 44                   | 48.2             | -4.9                     |
| 5                                                 | 624.61      | 39.0 QP                 | 46.0           | -7.0        | 2.00 V             | 28                   | 40.7             | -1.7                     |
| 6                                                 | 889.45      | 39.6 QP                 | 46.0           | -6.4        | 1.00 V             | 12                   | 36.8             | 2.8                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | CH 6 + CH 52 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | B               |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 69.77       | 32.6 QP                 | 40.0           | -7.4        | 1.00 H             | 54                   | 44.2             | -11.6                    |
| 2                                                   | 265.71      | 38.6 QP                 | 46.0           | -7.4        | 1.00 H             | 354                  | 47.6             | -9.0                     |
| 3                                                   | 375.03      | 38.8 QP                 | 46.0           | -7.2        | 1.00 H             | 315                  | 45.5             | -6.7                     |
| 4                                                   | 479.96      | 36.4 QP                 | 46.0           | -9.6        | 1.50 H             | 0                    | 41.4             | -5.0                     |
| 5                                                   | 624.96      | 37.4 QP                 | 46.0           | -8.6        | 1.50 H             | 141                  | 39.1             | -1.7                     |
| 6                                                   | 733.28      | 43.1 QP                 | 46.0           | -2.9        | 1.00 H             | 6                    | 42.9             | 0.2                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | CH 6 + CH 52 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | B               |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 30.00       | 36.1 QP                 | 40.0           | -3.9        | 1.00 V             | 169                  | 47.3             | -11.2                    |
| 2                                                 | 75.59       | 34.3 QP                 | 40.0           | -5.7        | 1.00 V             | 186                  | 47.3             | -13.0                    |
| 3                                                 | 375.43      | 39.7 QP                 | 46.0           | -6.3        | 2.00 V             | 160                  | 46.4             | -6.7                     |
| 4                                                 | 480.99      | 39.5 QP                 | 46.0           | -6.5        | 1.00 V             | 313                  | 44.4             | -4.9                     |
| 5                                                 | 749.08      | 43.5 QP                 | 46.0           | -2.5        | 1.00 V             | 282                  | 42.8             | 0.7                      |
| 6                                                 | 899.27      | 42.4 QP                 | 46.0           | -3.6        | 1.00 V             | 241                  | 39.5             | 2.9                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | CH 6 + CH 52 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | C               |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 30.00       | 30.5 QP                 | 40.0           | -9.5        | 1.00 H             | 20                   | 41.9             | -11.4                    |
| 2                                                   | 97.90       | 30.8 QP                 | 43.5           | -12.7       | 1.00 H             | 293                  | 44.8             | -14.0                    |
| 3                                                   | 374.32      | 38.9 QP                 | 46.0           | -7.1        | 1.00 H             | 311                  | 45.2             | -6.3                     |
| 4                                                   | 625.61      | 40.5 QP                 | 46.0           | -5.5        | 1.00 H             | 163                  | 42.0             | -1.5                     |
| 5                                                   | 801.15      | 35.6 QP                 | 46.0           | -10.4       | 1.00 H             | 210                  | 34.2             | 1.4                      |
| 6                                                   | 903.00      | 31.1 QP                 | 46.0           | -14.9       | 1.00 H             | 18                   | 27.9             | 3.2                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.




|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | CH 6 + CH 52 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  | TEST MODE         | C               |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 30.00       | 38.7 QP                 | 40.0           | -1.3        | 1.00 V             | 222                  | 49.9             | -11.2                    |
| 2                                                 | 149.25      | 34.2 QP                 | 43.5           | -9.3        | 1.50 V             | 266                  | 43.6             | -9.4                     |
| 3                                                 | 375.43      | 35.0 QP                 | 46.0           | -11.0       | 1.00 V             | 172                  | 41.7             | -6.7                     |
| 4                                                 | 624.76      | 38.0 QP                 | 46.0           | -8.0        | 2.00 V             | 167                  | 39.7             | -1.7                     |
| 5                                                 | 783.69      | 39.1 QP                 | 46.0           | -6.9        | 1.00 V             | 314                  | 37.5             | 1.6                      |
| 6                                                 | 939.80      | 43.5 QP                 | 46.0           | -2.5        | 1.00 V             | 245                  | 39.5             | 4.0                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
4. Margin value = Emission Level – Limit value
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20dB below the permissible value to be report.



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

### Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

### Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

Web Site: [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---