

FCC Test Report (Co-Located)

Report No.: RF170801C10-2

FCC ID: KA2WL7620APA1

Test Model: DWL-7620AP

Received Date: Aug. 01, 2017

Test Date: Oct. 11 ~ Oct. 12, 2017

Issued Date: Oct. 17, 2017

Applicant: D-Link Corporation

Address: 17595 Mt. Herrmann, Fountain Valley, California, United States, 92708

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty.....	5
2.2 Modification Record.....	5
3 General Information	6
3.1 General Description of EUT.....	6
3.2 Description of Test Modes.....	8
3.2.1 Test Mode Applicability and Tested Channel Detail.....	10
3.3 Description of Support Units.....	12
3.3.1 Configuration of System under Test.....	12
3.4 General Description of Applied Standards.....	13
4 Test Types and Results	14
4.1 Radiated Emission and Bandedge Measurement.....	14
4.1.1 Limits of Radiated Emission and Bandedge Measurement.....	14
4.1.2 Test Instruments.....	15
4.1.3 Test Procedures.....	16
4.1.4 Deviation from Test Standard.....	16
4.1.5 Test Setup.....	17
4.1.6 EUT Operating Conditions.....	18
4.1.7 Test Results.....	19
4.2 Conducted Emission Measurement.....	27
4.2.1 Limits of Conducted Emission Measurement.....	27
4.2.2 Test Instruments.....	27
4.2.3 Test Procedures.....	28
4.2.4 Deviation from Test Standard.....	28
4.2.5 Test Setup.....	28
4.2.6 EUT Operating Conditions.....	28
4.2.7 Test Results.....	29
5 Pictures of Test Arrangements	41
Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)	42
Appendix – Information on the Testing Laboratories	43

Release Control Record

Issue No.	Description	Date Issued
RF170801C10-2	Original release.	Oct. 17, 2017

1 Certificate of Conformity

Product: Unified AC Tri-band PoE Access Point

Brand: D-Link Corporation

Test Model: DWL-7620AP

Sample Status: Identical Prototype


Applicant: D-Link Corporation

Test Date: Oct. 11 ~ Oct. 12, 2017

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
47 CFR FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10-2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :



Pettie Chen / Senior Specialist

Date:

Oct. 17, 2017

Approved by :



Ken Liu / Senior Manager

Date:

Oct. 17, 2017

2 Summary of Test Results

Applied Standard:	47 CFR FCC Part 15, Subpart C (Section 15.247) 47 CFR FCC Part 15, Subpart E (Section 15.407)		
FCC Clause	Test Item	Result	Remarks
15.207 15.407(b)(6)	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -11.22dB at 0.36526MHz.
15.205 / 15.209 / 15.247(d) 15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -0.5dB at 2390.00MHz.

*For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.94 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.59 dB
	200MHz ~ 1000MHz	3.60 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Unified AC Tri-band PoE Access Point
Brand	D-Link Corporation
Test Model	DWL-7620AP
Status of EUT	Identical Prototype
Power Supply Rating	12Vdc (From adapter) 53Vdc (From POE)
Modulation Type	CCK, DQPSK, DBPSK for DSSS 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11/5.5/2/1Mbps 802.11a/g: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 300Mbps 802.11ac: up to 867Mbps
Operating Frequency	2.4GHz: 2412 ~ 2462MHz 5.0GHz: 5180 ~ 5240MHz, 5745 ~ 5825MHz
Number of Channel	2412 ~ 2462MHz: 11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40) 5180 ~ 5240MHz: 4 for 802.11a, 802.11n (HT20), 802.11ac (VHT20) 2 for 802.11n (HT40), 802.11ac (VHT40) 1 for 802.11ac (VHT80) 5745 ~ 5825MHz: 5 for 802.11a, 802.11n (HT20), 802.11ac (VHT20) 2 for 802.11n (HT40), 802.11ac (VHT40) 1 for 802.11ac (VHT80)
Output Power	CDD Mode: 2412 ~ 2462MHz: 636.566mW 5180 ~ 5240MHz: 769.284mW 5745 ~ 5825MHz: 956.517mW Beamforming Mode: 2412 ~ 2462MHz: 244.277mW 5180 ~ 5240MHz: 287.160mW 5745 ~ 5825MHz: 431.817mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter
Data Cable Supplied	NA

Note:

1. The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

Band	Modulation Mode	Beamforming Mode	TX Function	Remark
2.4GHz	802.11b	Not Support	2TX	Radio 0
	802.11g	Not Support	2TX	
	802.11n (HT20)	Support	2TX	
	802.11n (HT40)	Support	2TX	
5GHz	802.11a	Not Support	2TX	Radio 1 (Band 1), Radio 2 (Band 4)
	802.11n (HT20)	Support	2TX	
	802.11n (HT40)	Support	2TX	
	802.11ac (VHT20)	Support	2TX	
	802.11ac (VHT40)	Support	2TX	
	802.11ac (VHT80)	Support	2TX	

* For 802.11n, CDD mode is the worst case for final radiated emission and power line conducted emission tests after pretesting CDD mode and beamforming mode.

2. The EUT uses following antennas.

Type	Connector	Gain (dBi)	
		2.4GHz	5GHz
PIFA	I-PEX	3.25	4.3

3. The EUT consumes power from the following Adapter and PoE.

Adapter 1	
Brand	Channel Well Technology
Model	2ABL030F US
Input Power	100-240Vac~1.0A
Output Power	12Vdc / 2.5A
Power Cord	1.2m non-shielded power cord without core

Adapter 2	
Brand	Asian Power Devices Inc.
Model	WA-30J12R
Input Power	100-240Vac~0.9A, 50-60Hz
Output Power	12Vdc / 2.5A
Power Cord	1.2m non-shielded power cord without core

PoE (Support unit only)	
Brand	D-Link
Model	DGS-1210-10P
Input Power	100-240Vac
Output Power	53Vdc

3.2 Description of Test Modes

For 2.4GHz

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

For 5180~5240MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
42	5210MHz

5745~5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency
155	5775MHz

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to			Description
	RE \geq 1G	RE $<$ 1G	PLC	
A	√	√	√	Power from adapter 1
B	-	√	√	Power from adapter 2
C	-	√	√	Power from POE

Where **RE \geq 1G**: Radiated Emission above 1GHz & Bandedge Measurement
RE $<$ 1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

Note:

- The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.
- "-" means no effect.

Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Range (MHz)	Available Channel	Tested Channel	Modulation Technology
A	802.11b + 802.11n (HT20)	2412 ~ 2462	1 to 11	1 + 48	DSSS
		5180 ~ 5240	36 to 48		OFDM
A	802.11b + 802.11a	2412 ~ 2462	1 to 11	1 + 149	DSSS
		5745 ~ 5825	149 to 165		OFDM

Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Range (MHz)	Available Channel	Tested Channel	Modulation Technology
A, B, C	802.11b + 802.11n (HT20)	2412 ~ 2462	1 to 11	1 + 48	DSSS
		5180 ~ 5240	36 to 48		OFDM
A, B, C	802.11b + 802.11a	2412 ~ 2462	1 to 11	1 + 149	DSSS
		5745 ~ 5825	149 to 165		OFDM

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Freq. Range (MHz)	Available Channel	Tested Channel	Modulation Technology
A, B, C	802.11b + 802.11n (HT20)	2412 ~ 2462	1 to 11	1 + 48	DSSS
		5180 ~ 5240	36 to 48		OFDM
A, B, C	802.11b + 802.11a	2412 ~ 2462	1 to 11	1 + 149	DSSS
		5745 ~ 5825	149 to 165		OFDM

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE \geq 1G	25 deg. C, 66% RH	120Vac, 60Hz	Chris Lin
RE $<$ 1G	25 deg. C, 70% RH	120Vac, 60Hz	Chris Lin
PLC	25 deg. C, 65% RH	120Vac, 60Hz	Chris Lin

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	Lenovo	X201i	NA	FCC DoC Approved	Provided by manufacturer
B.	Load	NA	NA	NA	NA	-
C.	POE	D-Link	PGS-1210-10P	NA	NA	Provided by manufacturer


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ45, Cat5e	1	3	N	0	-
2.	RJ45, Cat5e	2	1.8	N	0	-
3.	RJ45, Cat5e	1	1.8	N	0	-

3.3.1 Configuration of System under Test

Adapter Mode



POE Mode



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specification of the EUT declared by the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

FCC Part 15, Subpart E (15.407)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Applicable To		Limit	
789033 D02 General UNII Test Procedure New Rules v02r01		Field Strength at 3m	
		PK: 74 (dBµV/m)	AV: 54 (dBµV/m)
Frequency Band	Applicable To	EIRP Limit	Equivalent Field Strength at 3m
5150~5250 MHz	15.407(b)(1)	PK: -27 (dBm/MHz)	PK: 68.2(dBµV/m)
5250~5350 MHz	15.407(b)(2)		
5470~5725 MHz	15.407(b)(3)		
5725~5850 MHz	<input checked="" type="checkbox"/> 15.407(b)(4)(i)	PK: -27 (dBm/MHz) ^{*1} PK: 10 (dBm/MHz) ^{*2} PK: 15.6 (dBm/MHz) ^{*3} PK: 27 (dBm/MHz) ^{*4}	PK: 68.2(dBµV/m) ^{*1} PK: 105.2 (dBµV/m) ^{*2} PK: 110.8(dBµV/m) ^{*3} PK: 122.2 (dBµV/m) ^{*4}
	<input type="checkbox"/> 15.407(b)(4)(ii)	Emission limits in section 15.247(d)	
^{*1} beyond 75 MHz or more above of the band edge.		^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.	
^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.		^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.	

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver KEYSIGHT	N9038A	MY55420137	Mar. 27, 2017	Mar. 26, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	May. 11, 2017	May. 10, 2018
BILOG Antenna SCHWARZBECK	VULB9168	9168-148	Dec. 28, 2016	Dec. 27, 2017
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-1169	Dec. 27, 2016	Dec. 26, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Dec. 14, 2016	Dec. 13, 2017
Loop Antenna EMCI	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
Preamplifier Agilent	8449B	3008A01638	Feb. 22, 2017	Feb. 21, 2018
Preamplifier Agilent	8447D	2944A10638	Aug. 08, 2017	Aug. 07, 2018
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-02 (248780+MY13377)	Aug. 08, 2017	Aug. 07, 2018
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795/4)	Aug. 08, 2017	Aug. 07, 2018
RF signal cable Woken	8D-FB	Cable-CH9-01	Aug. 01, 2017	Jul. 31, 2018
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower & Turn BV ADT	AT100	AT93021705	NA	NA
Turn Table BV ADT	TT100	TT93021705	NA	NA
Turn Table Controller BV ADT	SC100	SC93021705	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 17, 2016	Oct. 16, 2017

- Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 9.
 3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Designation Number is TW0003. The number will be varied with the Lab location and scope as attached.
 5. The IC Site Registration No. is IC 7450F-9.

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Prepared a notebook to act as a communication partner and placed it outside of testing area.
- c. The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- d. The communication partner sent data to EUT by command "PING".

4.1.7 Test Results

Above 1GHz Data:

802.11b + 802.11n (HT20)

CHANNEL	CH 1 + CH 48	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 40GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.8 PK	74.0	-11.2	1.37 H	41	29.4	33.4
2	2390.00	53.5 AV	54.0	-0.5	1.37 H	41	20.1	33.4
3	*2412.00	122.7 PK			2.62 H	21	89.2	33.5
4	*2412.00	119.9 AV			2.62 H	21	86.4	33.5
5	4824.00	58.8 PK	74.0	-15.2	2.24 H	101	55.1	3.7
6	4824.00	52.5 AV	54.0	-1.5	2.24 H	101	48.8	3.7
7	*5240.00	123.2 PK			3.17 H	53	82.4	40.8
8	*5240.00	112.5 AV			3.17 H	53	71.7	40.8
9	5350.00	59.5 PK	74.0	-14.5	2.71 H	124	55.1	4.4
10	5350.00	46.6 AV	54.0	-7.4	2.71 H	124	42.2	4.4
11	#10480.00	60.0 PK	74.0	-14.0	1.97 H	326	44.9	15.1
12	#10480.00	46.4 AV	54.0	-7.6	1.97 H	326	31.3	15.1

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.1 PK	74.0	-11.9	3.22 V	28	28.7	33.4
2	2390.00	52.5 AV	54.0	-1.5	3.22 V	28	19.1	33.4
3	*2412.00	116.9 PK			3.11 V	8	83.4	33.5
4	*2412.00	113.6 AV			3.11 V	8	80.1	33.5
5	4824.00	57.5 PK	74.0	-16.5	1.97 V	123	53.8	3.7
6	4824.00	50.6 AV	54.0	-3.4	1.97 V	123	46.9	3.7
7	*5240.00	122.0 PK			3.69 V	51	81.2	40.8
8	*5240.00	111.1 AV			3.69 V	51	70.3	40.8
9	5350.00	58.0 PK	74.0	-16.0	2.81 V	206	53.6	4.4
10	5350.00	45.1 AV	54.0	-8.9	2.81 V	206	40.7	4.4
11	#10480.00	58.9 PK	74.0	-15.1	2.26 V	89	43.8	15.1
12	#10480.00	45.5 AV	54.0	-8.5	2.26 V	89	30.4	15.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11b + 802.11a

CHANNEL	CH 1 + CH 149	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 40GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.1 PK	74.0	-12.9	1.31 H	48	27.7	33.4
2	2390.00	52.7 AV	54.0	-1.3	1.31 H	48	19.3	33.4
3	*2412.00	121.1 PK			2.67 H	26	87.6	33.5
4	*2412.00	119.1 AV			2.67 H	26	85.6	33.5
5	4824.00	58.5 PK	74.0	-15.5	1.97 H	213	54.8	3.7
6	4824.00	51.3 AV	54.0	-2.7	1.97 H	213	47.6	3.7
7	#5611.20	58.0 PK	68.2	-10.2	1.87 H	335	53.2	4.8
8	*5745.00	118.4 PK			1.87 H	335	76.9	41.5
9	*5745.00	104.6 AV			1.87 H	335	63.1	41.5
10	#5995.20	58.0 PK	68.2	-10.2	1.87 H	335	53.2	4.8
11	11490.00	63.2 PK	74.0	-10.8	3.87 H	227	47.2	16.0
12	11490.00	50.1 AV	54.0	-3.9	3.87 H	227	34.1	16.0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.6 PK	74.0	-13.4	3.08 V	37	27.2	33.4
2	2390.00	52.1 AV	54.0	-1.9	3.08 V	37	18.7	33.4
3	*2412.00	116.4 PK			2.98 V	8	82.9	33.5
4	*2412.00	114.2 AV			2.98 V	8	80.7	33.5
5	4824.00	54.6 PK	74.0	-19.4	2.17 V	188	50.9	3.7
6	4824.00	46.5 AV	54.0	-7.5	2.17 V	188	42.8	3.7
7	#5624.00	58.6 PK	68.2	-9.6	1.96 V	349	53.8	4.8
8	*5745.00	123.1 PK			1.96 V	349	81.6	41.5
9	*5745.00	111.7 AV			1.96 V	349	70.2	41.5
10	#5950.40	58.0 PK	68.2	-10.2	1.96 V	349	53.2	4.8
11	11490.00	64.3 PK	74.0	-9.7	1.84 V	87	48.3	16.0
12	11490.00	51.6 AV	54.0	-2.4	1.84 V	87	35.6	16.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

Below 1GHz data

802.11b + 802.11n (HT20)

CHANNEL	CH 1 + CH 48	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	68.71	30.3 QP	40.0	-9.7	1.50 H	163	45.5	-15.2
2	167.67	37.0 QP	43.5	-6.5	2.00 H	129	50.7	-13.7
3	287.97	41.0 QP	46.0	-5.0	1.24 H	100	53.6	-12.6
4	383.05	43.7 QP	46.0	-2.3	1.00 H	130	54.8	-11.1
5	526.64	35.6 QP	46.0	-10.4	1.50 H	23	44.6	-9.0
6	936.07	31.2 QP	46.0	-14.8	2.00 H	261	33.5	-2.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	72.59	25.0 QP	40.0	-15.0	1.00 V	159	40.9	-15.9
2	161.85	33.9 QP	43.5	-9.6	1.50 V	95	47.3	-13.4
3	336.48	43.5 QP	46.0	-2.5	1.00 V	233	55.2	-11.7
4	526.64	35.6 QP	46.0	-10.4	1.50 V	23	44.6	-9.0
5	654.71	33.4 QP	46.0	-12.6	1.24 V	12	40.1	-6.7
6	899.20	30.3 QP	46.0	-15.7	1.50 V	45	33.3	-3.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	CH 1 + CH 48	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	76.47	29.4 QP	40.0	-10.6	2.00 H	264	46.4	-17.0
2	185.13	37.9 QP	43.5	-5.6	1.50 H	120	53.3	-15.4
3	324.84	43.2 QP	46.0	-2.8	1.00 H	315	55.0	-11.8
4	472.31	29.4 QP	46.0	-16.6	2.00 H	6	39.1	-9.7
5	604.26	32.6 QP	46.0	-13.4	1.50 H	351	40.0	-7.4
6	641.13	35.2 QP	46.0	-10.8	1.24 H	357	42.1	-6.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	55.13	31.3 QP	40.0	-8.7	2.00 V	112	45.0	-13.7
2	163.79	39.1 QP	43.5	-4.4	2.00 V	98	52.6	-13.5
3	286.03	41.2 QP	46.0	-4.8	1.00 V	108	53.8	-12.6
4	408.28	32.7 QP	46.0	-13.3	2.00 V	149	43.7	-11.0
5	641.13	35.2 QP	46.0	-10.8	1.24 V	357	42.1	-6.9
6	873.97	31.2 QP	46.0	-14.8	1.00 V	13	34.5	-3.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	CH 1 + CH 48	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	55.13	29.4 QP	40.0	-10.6	1.25 H	95	43.1	-13.7
2	200.66	33.1 QP	43.5	-10.4	1.50 H	249	49.2	-16.1
3	297.68	42.0 QP	46.0	-4.0	1.00 H	220	54.5	-12.5
4	384.99	38.5 QP	46.0	-7.5	2.00 H	150	49.6	-11.1
5	745.91	36.9 QP	46.0	-9.1	1.25 H	120	42.0	-5.1
6	938.01	38.9 QP	46.0	-7.1	1.25 H	7	41.1	-2.2

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	55.13	29.4 QP	40.0	-10.6	1.25 V	95	43.1	-13.7
2	200.66	33.1 QP	43.5	-10.4	1.50 V	249	49.2	-16.1
3	326.78	42.8 QP	46.0	-3.2	1.00 V	65	54.5	-11.7
4	379.17	42.5 QP	46.0	-3.5	2.00 V	150	53.7	-11.2
5	522.76	38.1 QP	46.0	-7.9	2.00 V	7	47.1	-9.0
6	918.60	35.7 QP	46.0	-10.3	1.50 V	37	38.2	-2.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

802.11b + 802.11a

CHANNEL	CH 1 + CH 149	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	74.53	23.1 QP	40.0	-16.9	1.00 H	159	39.5	-16.4
2	179.31	36.4 QP	43.5	-7.1	1.50 H	115	51.1	-14.7
3	315.14	44.4 QP	46.0	-1.6	1.00 H	314	56.5	-12.1
4	526.64	35.6 QP	46.0	-10.4	1.50 H	23	44.6	-9.0
5	654.71	33.4 QP	46.0	-12.6	1.24 H	12	40.1	-6.7
6	936.07	31.2 QP	46.0	-14.8	2.00 H	261	33.5	-2.3

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	66.77	27.1 QP	40.0	-12.9	2.00 V	173	42.2	-15.1
2	165.73	35.9 QP	43.5	-7.6	1.24 V	100	49.6	-13.7
3	332.60	45.1 QP	46.0	-0.9	1.00 V	233	56.9	-11.8
4	390.81	37.6 QP	46.0	-8.4	1.00 V	130	48.7	-11.1
5	561.57	33.7 QP	46.0	-12.3	1.50 V	164	42.3	-8.6
6	992.34	29.7 QP	54.0	-24.3	1.00 V	148	31.1	-1.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	CH 1 + CH 149	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.88	30.0 QP	40.0	-10.0	1.99 H	7	45.0	-15.0
2	192.96	40.1 QP	43.5	-3.4	1.00 H	122	56.1	-16.0
3	361.74	41.0 QP	46.0	-5.0	1.00 H	244	52.5	-11.5
4	518.88	40.2 QP	46.0	-5.8	1.49 H	174	49.3	-9.1
5	646.92	33.1 QP	46.0	-12.9	1.49 H	10	39.9	-6.8
6	901.06	30.1 QP	46.0	-15.9	1.49 H	246	33.1	-3.0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	90.14	32.7 QP	43.5	-10.8	1.99 V	110	51.7	-19.0
2	198.78	40.5 QP	43.5	-3.0	1.00 V	122	56.6	-16.1
3	284.14	43.5 QP	46.0	-2.5	1.00 V	280	56.1	-12.6
4	518.88	40.2 QP	46.0	-5.8	1.49 V	174	49.3	-9.1
5	646.92	33.1 QP	46.0	-12.9	1.49 V	10	39.9	-6.8
6	891.36	29.3 QP	46.0	-16.7	1.49 V	239	32.5	-3.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	CH 1 + CH 149	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	43.48	27.5 QP	40.0	-12.5	1.50 H	34	41.5	-14.0
2	175.43	31.9 QP	43.5	-11.6	1.50 H	280	46.2	-14.3
3	295.73	40.6 QP	46.0	-5.4	1.25 H	241	53.1	-12.5
4	511.12	38.2 QP	46.0	-7.8	1.50 H	12	47.4	-9.2
5	730.38	44.9 QP	46.0	-1.1	1.00 H	241	50.4	-5.5
6	903.08	33.7 QP	46.0	-12.3	1.50 H	267	36.6	-2.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	101.69	29.7 QP	43.5	-13.8	2.00 V	96	47.4	-17.7
2	206.48	32.3 QP	43.5	-11.2	1.25 V	235	48.5	-16.2
3	377.23	43.5 QP	46.0	-2.5	2.00 V	142	54.8	-11.3
4	511.12	38.2 QP	46.0	-7.8	1.50 V	12	47.4	-9.2
5	672.17	33.8 QP	46.0	-12.2	1.25 V	330	40.2	-6.4
6	875.91	32.9 QP	46.0	-13.1	1.00 V	238	36.2	-3.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

- Note:** 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 21, 2016	Nov. 20, 2017
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Sep. 05, 2017	Sep. 04, 2018
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 10, 2017	Mar. 09, 2018
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 15, 2017	Aug. 14, 2018
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- Note:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.

4.2.7 Test Results


802.11b + 802.11n (HT20)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 48	Test Mode	A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.45	31.66	17.84	42.11	28.29	66.00	56.00	-23.89	-27.71
2	0.17346	10.45	28.47	15.75	38.92	26.20	64.79	54.79	-25.87	-28.59
3	0.36896	10.51	32.11	25.50	42.62	36.01	58.52	48.52	-15.90	-12.51
4	2.74624	10.57	15.12	9.87	25.69	20.44	56.00	46.00	-30.31	-25.56
5	4.30216	10.66	14.16	7.11	24.82	17.77	56.00	46.00	-31.18	-28.23
6	21.68628	11.49	8.44	1.77	19.93	13.26	60.00	50.00	-40.07	-36.74

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 48	Test Mode	A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.16526	10.21	30.61	18.01	40.82	28.22	65.20
2	0.24775	10.23	23.12	12.82	33.35	23.05	61.83	51.83	-28.48	-28.78
3	0.36816	10.23	32.68	25.88	42.91	36.11	58.54	48.54	-15.63	-12.43
4	1.40120	10.28	15.07	9.55	25.35	19.83	56.00	46.00	-30.65	-26.17
5	4.68560	10.44	16.08	9.82	26.52	20.26	56.00	46.00	-29.48	-25.74
6	21.09587	11.08	9.03	1.50	20.11	12.58	60.00	50.00	-39.89	-37.42

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 48	Test Mode	B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15719	10.45	27.96	11.79	38.41	22.24	65.61
2	0.34926	10.50	32.07	25.63	42.57	36.13	58.98	48.98	-16.41	-12.85
3	0.55241	10.51	15.19	8.08	25.70	18.59	56.00	46.00	-30.30	-27.41
4	2.70323	10.57	15.65	10.66	26.22	21.23	56.00	46.00	-29.78	-24.77
5	3.97518	10.64	17.24	11.70	27.88	22.34	56.00	46.00	-28.12	-23.66
6	21.44386	11.48	8.71	1.97	20.19	13.45	60.00	50.00	-39.81	-36.55

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 48	Test Mode	B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15513	10.21	31.56	16.36	41.77	26.57	65.72
2	0.29662	10.23	23.38	16.50	33.61	26.73	60.34	50.34	-26.73	-23.61
3	0.34560	10.23	32.37	25.77	42.60	36.00	59.07	49.07	-16.47	-13.07
4	0.70395	10.25	16.38	11.76	26.63	22.01	56.00	46.00	-29.37	-23.99
5	4.05986	10.41	17.02	10.94	27.43	21.35	56.00	46.00	-28.57	-24.65
6	21.45559	11.09	8.77	1.85	19.86	12.94	60.00	50.00	-40.14	-37.06

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 48	Test Mode	C

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15391	10.45	31.04	14.81	41.49	25.26	65.79
2	0.21256	10.46	21.37	10.15	31.83	20.61	63.10	53.10	-31.27	-32.49
3	0.36913	10.51	32.22	25.57	42.73	36.08	58.52	48.52	-15.79	-12.44
4	2.15192	10.53	17.94	13.66	28.47	24.19	56.00	46.00	-27.53	-21.81
5	4.27114	10.66	14.83	7.99	25.49	18.65	56.00	46.00	-30.51	-27.35
6	22.68724	11.53	4.53	-2.77	16.06	8.76	60.00	50.00	-43.94	-41.24

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 48	Test Mode	C

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15000	10.20	33.32	20.27	43.52	30.47	66.00
2	0.17346	10.21	29.24	18.15	39.45	28.36	64.79	54.79	-25.34	-26.43
3	0.36048	10.23	31.74	25.28	41.97	35.51	58.72	48.72	-16.75	-13.21
4	4.31806	10.42	14.65	7.98	25.07	18.40	56.00	46.00	-30.93	-27.60
5	7.03160	10.54	9.56	4.05	20.10	14.59	60.00	50.00	-39.90	-35.41
6	20.69705	11.07	7.37	0.02	18.44	11.09	60.00	50.00	-41.56	-38.91

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




802.11b + 802.11a

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 149	Test Mode	A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.16967	10.45	29.71	17.47	40.16	27.92	64.98
2	0.24343	10.47	21.54	12.46	32.01	22.93	61.98	51.98	-29.97	-29.05
3	0.36913	10.51	32.77	26.47	43.28	36.98	58.52	48.52	-15.24	-11.54
4	2.30050	10.54	17.58	12.97	28.12	23.51	56.00	46.00	-27.88	-22.49
5	4.13820	10.65	16.50	10.06	27.15	20.71	56.00	46.00	-28.85	-25.29
6	21.03331	11.46	7.26	0.74	18.72	12.20	60.00	50.00	-41.28	-37.80

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 149	Test Mode	A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.17737	10.21	29.26	17.04	39.47	27.25	64.61
2	0.19305	10.22	25.53	15.44	35.75	25.66	63.90	53.90	-28.15	-28.24
3	0.36816	10.23	32.66	26.13	42.89	36.36	58.54	48.54	-15.65	-12.18
4	0.51312	10.24	19.15	14.26	29.39	24.50	56.00	46.00	-26.61	-21.50
5	4.32979	10.42	14.47	8.16	24.89	18.58	56.00	46.00	-31.11	-27.42
6	22.27278	11.12	7.11	-0.33	18.23	10.79	60.00	50.00	-41.77	-39.21

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 149	Test Mode	B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.17374	10.45	27.65	16.43	38.10	26.88	64.78
2	0.31031	10.49	26.79	19.40	37.28	29.89	59.96	49.96	-22.68	-20.07
3	0.36334	10.50	32.76	25.95	43.26	36.45	58.65	48.65	-15.39	-12.20
4	0.50972	10.51	17.03	11.60	27.54	22.11	56.00	46.00	-28.46	-23.89
5	4.68560	10.68	15.06	8.88	25.74	19.56	56.00	46.00	-30.26	-26.44
6	21.98344	11.50	7.97	1.23	19.47	12.73	60.00	50.00	-40.53	-37.27

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 149	Test Mode	B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.17374	10.21	29.49	18.84	39.70	29.05	64.78
2	0.24472	10.23	22.69	13.85	32.92	24.08	61.93	51.93	-29.01	-27.85
3	0.37304	10.23	32.42	26.26	42.65	36.49	58.43	48.43	-15.78	-11.94
4	1.15524	10.27	15.89	12.21	26.16	22.48	56.00	46.00	-29.84	-23.52
5	4.11474	10.41	16.28	10.00	26.69	20.41	56.00	46.00	-29.31	-25.59
6	21.98344	11.11	8.29	1.57	19.40	12.68	60.00	50.00	-40.60	-37.32

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 149	Test Mode	C

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.16173	10.45	29.89	14.23	40.34	24.68	65.37
2	0.36526	10.51	33.66	26.88	44.17	37.39	58.61	48.61	-14.44	-11.22
3	0.52544	10.51	17.97	10.42	28.48	20.93	56.00	46.00	-27.52	-25.07
4	2.17929	10.54	18.75	14.58	29.29	25.12	56.00	46.00	-26.71	-20.88
5	4.13429	10.65	16.53	10.07	27.18	20.72	56.00	46.00	-28.82	-25.28
6	21.42822	11.48	9.35	2.95	20.83	14.43	60.00	50.00	-39.17	-35.57

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	CH 1 + CH 149	Test Mode	C

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15760	10.21	28.62	13.69	38.83	23.90	65.59
2	0.18519	10.22	25.32	13.08	35.54	23.30	64.25	54.25	-28.71	-30.95
3	0.22820	10.23	22.12	13.18	32.35	23.41	62.51	52.51	-30.16	-29.10
4	0.37700	10.23	30.54	23.57	40.77	33.80	58.35	48.35	-17.58	-14.55
5	4.77944	10.44	15.49	9.38	25.93	19.82	56.00	46.00	-30.07	-26.18
6	21.67455	11.10	8.81	2.01	19.91	13.11	60.00	50.00	-40.09	-36.89

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)

802.11b + 802.11a



Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---