



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



# Table of Contents

Re	Release Control Record 3				
1	1 Certificate of Conformity 4				
2	Sun	nmary of Test Results	5		
	2.1 2.2	Measurement Uncertainty Modification Record	6 6		
3	Ger	neral Information	7		
	3.1 3.2 3.3 3.4	General Description of EUT Description of Test Modes	7 10 .11 13 13 13		
4	Tes	t Types and Results	14		
	4.1	Radiated Emission and Bandedge Measurement 4.1.1 Limits of Radiated Emission and Bandedge Measurement 4.1.2 Test Instruments	14 14 16		
		<ul> <li>4.1.3 Test Procedures</li></ul>	17 17 18 19		
	12	4.1.7 Test Results	20 28		
	4.2	4.2.1 Limits of Conducted Emission Measurement	28		
		4.2.2 Test Instruments	28		
		4.2.3 Test Procedures	29		
		4.2.5 Test Setup	29		
		4.2.6 EUT Operating Conditions	29		
	4.0	4.2.7 Test Results	30		
	4.3	4 3 1 Limits of Transmit Power Measurement	32 32		
		4.3.2 Test Setup	32		
		4.3.3 Test Instruments	33		
		4.3.4 Test Procedure	33		
	4.3.5       Deviation from Test Standard       33         4.3.6       EUT Operating Conditions       33         4.3.7       Test Result       34				
5	Pict	tures of Test Arrangements	40		
Ar	Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)				
Δr	Appendix – Information of the Testing Laboratories 42				
~	, pon		- <b>T</b>		



# **Release Control Record** Issue No. Description **Date Issued** May 27, 2020 RF191203C15-1 **Original Release**



1	Certificate of Conformity		
	Product:	Business Cloud Wave 2 Access Point / Nuclias Cloud-Managed AC1300 Wave 2 Outdoor Access Point	
	Brand:	D-Link	
	Test Model:	DBA-3620P	
	Sample Status:	Engineering Sample	
	Applicant:	D-Link Corporation	
	Test Date:	Apr. 28 ~ May 22, 2020	
	Standards:	47 CFR FCC Part 15, Subpart E (Section 15.407) ANSI C63.10:2013	

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

Gina Liu / Specialist , Date: May 27, 2020

Approved by :

RADE

**Date:** May 27, 2020

Dylan Chiou / Senior Project Engineer



# 2 Summary of Test Results

	47 CFR FCC Part 15, Subpart E (Section 15.407)						
FCC Clause	Test Item	Result	Remarks				
15.407(b)(6)	AC Power Conducted Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -6.1 dB at 0.55704 MHz.				
15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions & Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.4 dB at 5150.00 MHz.				
15.407(a)(1/2/ 3)	Max Average Transmit Power	Pass	Meet the requirement of limit.				
	Occupied Bandwidth Measurement	-	Reference only				
15.407(a)(1/2/ 3)	Peak Power Spectral Density	N/A	Refer to Note				
15.407(e)	6 dB Bandwidth	N/A	Refer to Note				
15.407(g)	Frequency Stability	N/A	Refer to Note				
15.203	Antenna Requirement	Pass	Antenna connector is I-PEX / R-SMA not a standard connector.				

Note:

- This report is a partial report, only test item of Conducted Emission, Radiated Emissions, 6 dB Bandwidth and Conducted power were performed for this report. Other testing data please refer to BV report no.: RF191111C21-1 (Brand: D-Link, Model: DWL-6720AP).
- For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOBE test plots were recorded in Annex A.
- 3. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.



# 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.79 dB
	9 kHz ~ 30 MHz	3.04 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Dedicted Emissions above 1 CHz	1 GHz ~ 18 GHz	2.26 dB
Radiated Emissions above 1 GHz	18 GHz ~ 40 GHz	1.94 dB

# 2.2 Modification Record

There were no modifications required for compliance.



# 3 General Information

# 3.1 General Description of EUT

Deschust	Business Cloud Wave 2 Access Point / Nuclias Cloud-Managed AC1300
Product	Wave 2 Outdoor Access Point
Brand	D-Link
Test Model	DBA-3620P
Status of EUT	Engineering Sample
Power Supply Rating	48 Vdc (POE)
Modulation Type	256QAM, 64QAM, 16QAM, QPSK, BPSK
Modulation Technology	OFDM
	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0 Mbps
Transfer Rate	802.11n: up to 400.0 Mbps
	802.11ac: up to 866.7 Mbps
Operating Frequency	5180 ~ 5240 MHz, 5745 ~ 5825 MHz
	5180 ~ 5240 MHz: 4 for 802.11a, 802.11n (HT20), 802.11ac (VHT20)
	2 for 802.11n (HT40), 802.11ac (VHT40)
Number of Channel	1 for 802.11ac (VHT80)
	5745 ~ 5825 MHz: 5 for 802.11a, 802.11n (HT20), 802.11ac (VHT20)
	2 for 802.11n (HT40), 802.11ac (VHT40)
	1 for 802.11ac (VHT80)
	CDD Mode:
	385.555 mW for 5180 ~ 5240 MHz
Output Power	365.211 mW for 5745 ~ 5825 MHz
output i owei	Beamforming Mode:
	187.317 mW for 5180 ~ 5240 MHz
	180.668 mW for 5745 ~ 5825 MHz
Antenna Type	Refer to Note as below
Antenna Connector	Refer to Note as below
Accessory Device	Refer to Note as below
Data Cable Supplied	Refer to Note as below

#### Note:

- This report's data reuse to BV CPS report no.: RF191111C21-1. The difference compared with the report (RF191111C21-1) is changing test model (DBA-3620P), the model have the same appearance, circuit, layout, and RF characteristic with DWL-6720AP, but only different in FW Version. Therefore, only Conducted Emission, Radiated Emissions of worst case, 6 dB Bandwidth and Conducted power were re-test.
- 2. The EUT equipment will be used indoor or outdoor, and the WLAN 5GHz UNII-1 band will be turned off when used outdoor.



3. The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

Modulation Mode	Beamformng Mode	Tx Function
802.11a	Not Support	2TX
802.11n (HT20)	Support	2TX
802.11n (HT40)	Support	2TX
802.11ac (VHT20)	Support	2TX
802.11ac (VHT40)	Support	2TX
802.11ac (VHT80)	Support	2TX

\* The modulation and bandwidth are similar for 802.11n mode for HT20 / HT40 and 802.11ac mode for VHT20 / VHT40, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

\* For 802.11n and 802.11ac, CDD mode is the worst case for final radiated emission and power line conducted emission tests after pretesting CDD mode and beamforming mode.

4. The antenna information is listed as below.

Antenna NO.	RF Chain NO.	Brand	Model	Antenna Gain (dBi)	Frequency range	Antenna Type	Connecter Type
				3.50	2.412~2.462GHz		
1 (Internal)	1	whayu	C056-511224-A	4.80	5.18~5.24GHz	Dipole	i-pex(MHF)
				4.70	5.745~5.825 GHz		
				3.20	2.4~2.4835GHz		
2 (Internal)	2	whayu	C056-511225-A	4.60	5.18~5.24GHz	Dipole	i-pex(MHF)
				4.40	5.745~5.825 GHz		
3.35 2.4~2.4835GHz							
3 (External)	-	whayu	C059-510399-A	4.54	5.18~5.24GHz	Dipole	R-SMA
4.19 5.745~5.825 GHz							
*During the test, the maximum gain of Internal 1 was selected as representative antenna and therefore only Internal antenna 1 and External antenna 3 were chosen for final test.							

#### 5. The EUT contains following accessory devices.

Product	Brand	Model	Description
RJ45 Cable	N/A	N/A	1.9 m shielded

#### 6. There're 2 configurations for the EUT listed as below.

Mode A: Internal Antenna

Mode B: External Antenna



7. The EUT will install at outdoor area, the highest antenna gain from the horizon above 30 degrees as below, for more detail information please refer to antenna specification and user manual.

C056-511224-A (Internal)       1.197dBi         Due to device will restricted installation position as above photo, thus consider to above 30 degrees from the highest antenna gain are chosen from antenna specification exhibits from 120 to 240 degrees for J-NII-1 band         C059-510399-A (External)       4.54dBi         Due to device will restricted installation position as above photo, thus consider to above 30 degrees for J-NII-1 band         Due to device will restricted installation position as above photo, thus consider to above 30 degrees for J-NII-1 band         Due to device will restricted installation position as above photo, thus consider to above 30 degrees for J-NII-1 band         Due to device will restricted installation position as above photo, thus consider to above 30 degrees for J-NII-1 band         Due to device will restricted installation position as above photo, thus consider to above 30 degrees for J-NII-1 band         Due to device will restricted installation position as above photo, thus consider to above 30 degrees for J-NII-1 band         Due to device will restricted installation position as above photo, thus consider to above 30 degrees for J-NII-1 band         Due to device will restricted installation position as above photo, thus consider to above 30 degrees for J-NII-1 band	Antenna Model	Antenna gain	Antenna install degree
Due to device will restricted installation position as above photo, thus consider to above 30 degrees from the horizon the highest antenna gain are chosen from antenna specification exhibits from 120 to 240 degrees for J-NII-1 band         C059-510399-A (External)       4.54dBi         Due to device will restricted installation position as above photo, thus consider to above 30 degrees from the highest antenna gain are chosen from antenna specification exhibits from 120 to 240 degrees for J-NII-1 band         Due to device will restricted installation position as above photo, thus consider to above 30 degrees from the horizon the highest antenna gain are chosen from antenna specification exhibits from 300 to 70 degrees for J-NII-1 band         Due to device EUT information is declared by manufacturer and for more detailed features description, lease refers to the manufacturer's specifications or user's manual.	C056-511224-A (Internal)	1.197dBi	
C059-510399-A (External)       4.54dBi         Due to device will restricted installation position as above photo, thus consider to above 30 degrees from the horizon the highest antenna gain are chosen from antenna specification exhibits from 300 to 70 degrees for U-NII-1 band         The above EUT information is declared by manufacturer and for more detailed features description, lease refers to the manufacturer's specifications or user's manual.	Due to device will restricte	ed installation position as above a gain are chosen from antenr	e photo, thus consider to above 30 degrees from the
C059-510399-A (External)       4.54dBi         Due to device will restricted installation position as above photo, thus consider to above 30 degrees from the horizon the highest antenna gain are chosen from antenna specification exhibits from 300 to 70 degrees for J-NII-1 band         The above EUT information is declared by manufacturer and for more detailed features description, lease refers to the manufacturer's specifications or user's manual.	J-NII-1 band	a bain are chosen nom allem	
Due to device will restricted installation position as above photo, thus consider to above 30 degrees from the horizon the highest antenna gain are chosen from antenna specification exhibits from 300 to 70 degrees for U-NII-1 band The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.	C059-510399-A (External)	4.54dBi	
U-NII-1 band The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.	Due to device will restricte	ed installation position as above	e photo, thus consider to above 30 degrees from the
The above EUT information is declared by manufacturer and for more detailed features description, lease refers to the manufacturer's specifications or user's manual.	U-NII-1 band		a specification exhibits from 500 to 70 degrees for
lease refers to the manufacturer's specifications or user's manual.	he above EUT informat	ion is declared by manufact	urer and for more detailed features description,
	lease refers to the man	utacturer's specifications or	user's manual.



# 3.2 Description of Test Modes

#### For 5180 ~ 5240 MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
40	5200	48	5240

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency (MHz)
42	5210

# For 5745 ~ 5825 MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	161	5805
153	5765	165	5825
157	5785		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795

1 channel is provided for 802.11ac (VHT80):

Channel	Frequency (MHz)
155	5775



## 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure		Applica	able To		Description	
Mode	RE≥1G	RE<1G	PLC	APCM	Description	
А		$\checkmark$	$\checkmark$	$\checkmark$	Internal Antenna	
В	$\checkmark$	$\checkmark$	$\checkmark$	-	External Antenna	
Where RE≥1G: Radiated Emission above 1 GHz RE<1G: Radiated Emission above 1 GHz			adiated Emission below 1 GHz			
P	C. Power Line	Conducted Fr	nission	APCM · An	tenna Port Conducted Measurement	

#### Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane**. 2. "-" means no effect.

#### Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	5100 5010	802.11n (HT20)	36 to 48	40	OFDM	BPSK	6.5
В	5180-5240	802.11n (HT40)	38 to 46	46	OFDM	BPSK	13.5
А, В	5745-5825	802.11ac (VHT80)	155	155	OFDM	BPSK	29.3

Following channel(s) was (were) selected for the final test as listed below.

# Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
А	5400 5040	802.11n (HT20)	36 to 48	40	OFDM	BPSK	6.5
В	5180-5240	802.11n (HT40)	38 to 46	46	OFDM	BPSK	13.5

# Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
В	5180-5240	802.11n (HT40)	38 to 46	46	OFDM	BPSK	13.5



## Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
		802.11a	36 to 48	36, 40, 48	OFDM	BPSK	6.0
	5400 5040	802.11n (HT20)	36 to 48	36, 40, 48	OFDM	BPSK	6.5
	5180-5240	802.11n (HT40)	38 to 46	38, 46	OFDM	BPSK	13.5
^		802.11ac (VHT80)	42	42	OFDM	BPSK	29.3
A		802.11a	149 to 165	149, 157, 165	OFDM	BPSK	6.0
		802.11n (HT20)	149 to 165	149, 157, 165	OFDM	BPSK	6.5
	5745-5825	802.11n (HT40)	151 to 159	151, 159	OFDM	BPSK	13.5
		802.11ac (VHT80)	155	155	OFDM	BPSK	29.3

#### **Test Condition:**

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G 25 deg. C, 65 % RH		120 Vac, 60 Hz	Greg Lin
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Greg Lin
PLC 25 deg. C, 65 % RH		120 Vac, 60 Hz	Greg Lin
APCM 25 deg. C, 65 % RH		48 Vdc	Ivan Tseng



# 3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
Α.	Notebook	DELL	E5410	1HC2XM1	N/A	Provided by Lab
В.	POE	Ubiquiti Networks. Inc.	GP-H480-050G	N/A	N/A	Provided by Client

Note:

1. All power cords of the above support units are non-shielded (1.8m).

2. Item A acted as communication partner to transfer data.

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN Cable	1	10	N	0	RJ45, Cat5e, Provided by Lab
2.	LAN Cable	1	1.9	Y	0	Accessory of the EUT

# 3.3.1 Configuration of System under Test



# 3.4 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

#### Test Standard:

# FCC Part 15, Subpart E (15.407)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

#### **References Test Guidance:**

# KDB 789033 D02 General UNII Test Procedures New Rules v02r01 KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.



# 4 Test Types and Results

## 4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.



Limits f Unwanted Emission Out of the Restricted Bands

Арј	plicab	le To	Limit	1
789033 D02 General UNII Test Procedures New			Field Strengt	h at 3 m
Ru	les v02	2r01	PK: 74 (dBµV/m)	AV: 54 (dBµV/m)
Frequency Band	Applicable To		EIRP Limit	Equivalent Field Strength at 3 m
5150~5250 MHz	15.407(b)(1) 15.407(b)(2)			
5250~5350 MHz			PK: -27 (dBm/MHz)	PK: 68.2 (dBµV/m)
5470~5725 MHz		15.407(b)(3)		
			PK:-27 (dBm/MHz) *1	PK: 68.2 (dBµV/m) *1
		15 407(b)(4)(i)	PK:10 (dBm/MHz) *2	PK:105.2 (dBµV/m) *2
5725~5850 MHz		15.407 (D)(4)(I)	PK:15.6 (dBm/MHz) *3	PK: 110.8 (dBµV/m) *3
			PK:27 (dBm/MHz) *4	PK:122.2 (dBµV/m) *4
		15.407(b)(4)(ii)	Emission limits in se	ection 15.247(d)

<sup>\*1</sup> beyond 75 MHz or more above of the band edge.

<sup>\*2</sup> below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.

<sup>\*3</sup> below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.

<sup>\*4</sup> from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

 $E = \frac{1000000\sqrt{30P}}{3} \quad \mu V/m, \text{ where P is the eirp (Watts).}$ 



#### 4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Test Receiver KEYSIGHT	N9038A	MY55420137	Apr. 16, 2020	Apr. 15, 2021
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Jun. 04, 2019	Jun. 03, 2020
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Nov. 07, 2019	Nov. 06, 2020
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-1169	Nov. 24, 2019	Nov. 23, 2020
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Nov. 24, 2019	Nov. 23, 2020
Preamplifier Agilent (Below 1GHz)	8447D	2944A10638	Jul. 11, 2019	Jul. 10, 2020
Preamplifier Agilent (Above 1GHz)	8449B	3008A01976	Aug. 20, 2019	Aug. 19, 2020
RF signal cable HUBER+SUHNER&EMCI	SUCOFLEX 104 & EMC104-SM-SM80 00	CABLE-CH9-02 (248780+171006)	Jan. 18, 2020	Jan. 17, 2021
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(25079 5/4)	Jul. 11, 2019	Jul. 10, 2020
RF signal cable Woken	8D-FB	Cable-CH9-01	Jul. 30, 2019	Jul. 29, 2020
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower &Turn BV ADT	AT100	AT93021705	NA	NA
Turn Table BV ADT	TT100	TT93021705	NA	NA
Turn Table Controller BV ADT	SC100	SC93021705	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
USB Wideband Power Sensor KEYSIGHT	U2021XA	MY55050005/MY55 190004/MY5519000 7/MY55210005	Jul. 15, 2019	Jul. 14, 2020

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 9.



# 4.1.3 Test Procedures

## For Radiated Emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

#### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

#### For Radiated Emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

#### Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard

No deviation.



#### 4.1.5 Test Setup

#### <Radiated Emission below 30 MHz>







For the actual test configuration, please refer to the attached file (Test Setup Photo).

- 4.1.6 EUT Operating Conditions
- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



# 4.1.7 Test Results

Above 1 GHz Data :

Mode A

## 802.11n (HT20)

CHANNEL	TX Channel 40	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	64.0 PK	74.0	-10.0	3.00 H	288	59.9	4.1
2	5150.00	46.1 AV	54.0	-7.9	2.00 H	288	42.0	4.1
3	*5200.00	114.5 PK			3.00 H	288	76.1	38.4
4	*5200.00	103.5 AV			3.00 H	288	65.1	38.4
5	#10400.00	57.1 PK	68.2	-11.1	1.99 H	255	40.6	16.5
		ANTENNA	POLARITY	' & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	72.1 PK	74.0	-1.9	3.22 V	49	68.0	4.1
2	5150.00	53.6 AV	54.0	-0.4	3.22 V	49	49.5	4.1
3	*5200.00	119.2 PK			3.79 V	339	80.8	38.4
4	*5200.00	109.3 AV			3.22 V	49	70.9	38.4
5	#10400.00	55.5 PK	68.2	-12.7	3.50 V	197	39.0	16.5

## **REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

Margin value = Emission Level – Limit value

4. The other emission levels were very low against the limit.

5. " \* ": Fundamental frequency.

6. " # ": The radiated frequency is out of the restricted band.



# 802.11ac (VHT80)

CHANNEL	TX Channel 155	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5650.00	58.6 PK	68.2	-9.6	3.05 H	305	54.0	4.6
2	*5775.00	99.1 PK			3.02 H	305	60.0	39.1
3	*5775.00	89.4 AV			3.02 H	305	50.3	39.1
4	#5925.00	55.3 PK	68.2	-12.9	3.06 H	308	50.0	5.3
5	11550.00	56.1 PK	74.0	-17.9	1.99 H	135	39.4	16.7
6	11550.00	42.9 AV	54.0	-11.1	1.99 H	135	26.2	16.7
		ANTENNA	<b>POLARITY</b>	& TEST DI	STANCE: V	ERTICAL A	Т 3 М	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5650.00	67.1 PK	68.2	-1.1	3.22 V	300	62.5	4.6
2	*5775.00	108.1 PK			3.22 V	320	69.0	39.1
3	*5775.00	98.4 AV			3.22 V	320	59.3	39.1
4	#5925.00	66.4 PK	68.2	-1.8	3.23 V	330	61.1	5.3
5	11550.00	56.0 PK	74.0	-18.0	2.89 V	299	39.3	16.7
6	11550.00	43.2 AV	54.0	-10.8	2.89 V	299	26.5	16.7

#### **REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level - Limit value

4. The other emission levels were very low against the limit.

5. " \* ": Fundamental frequency.

6. " # ": The radiated frequency is out of the restricted band.



# Mode B

802.11n (HT40)

CHANNEL	TX Channel 46	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)		
1	5150.00	54.5 PK	74.0	-19.5	1.50 H	222	50.4	4.1		
2	5150.00	44.1 AV	54.0	-9.9	1.50 H	222	40.0	4.1		
3	*5230.00	102.3 PK			1.49 H	222	64.1	38.2		
4	*5230.00	92.3 AV			1.49 H	222	54.1	38.2		
5	5350.00	53.2 PK	74.0	-20.8	1.58 H	222	49.3	3.9		
6	5350.00	43.1 AV	54.0	-10.9	1.58 H	222	39.2	3.9		
7	#10460.00	56.5 PK	68.2	-11.7	2.55 H	119	40.2	16.3		
		ANTENNA		& TEST DI	STANCE: V	ERTICAL A	ТЗМ			

	ANTENNA FOLARITT & TEST DISTANCE. VERTICAE AT 5 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	5150.00	69.1 PK	74.0	-4.9	1.59 V	199	65.0	4.1	
2	5150.00	52.5 AV	54.0	-1.5	1.59 V	199	48.4	4.1	
3	*5230.00	115.2 PK			1.62 V	182	77.0	38.2	
4	*5230.00	106.3 AV			1.62 V	182	68.1	38.2	
5	5350.00	61.3 PK	74.0	-12.7	1.77 V	189	57.4	3.9	
6	5350.00	47.9 AV	54.0	-6.1	1.77 V	189	44.0	3.9	
7	#10460.00	57.3 PK	68.2	-10.9	2.35 V	359	41.0	16.3	

#### **REMARKS**:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level - Limit value

- 4. The other emission levels were very low against the limit.
- 5. " \* ": Fundamental frequency.
- 6. " # ": The radiated frequency is out of the restricted band.



# 802.11ac (VHT80)

CHANNEL	TX Channel 155	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5650.00	56.6 PK	68.2	-11.6	1.69 H	266	52.0	4.6
2	*5775.00	100.3 PK			1.59 H	266	61.2	39.1
3	*5775.00	89.9 AV			1.59 H	266	50.8	39.1
4	#5925.00	57.9 PK	68.2	-10.3	1.59 H	266	52.6	5.3
5	11550.00	56.7 PK	74.0	-17.3	2.90 H	120	40.0	16.7
6	11550.00	42.9 AV	54.0	-11.1	2.90 H	120	26.2	16.7
		ANTENNA	<b>POLARITY</b>	& TEST DI	STANCE: V	ERTICAL A	Т 3 М	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5650.00	66.9 PK	68.2	-1.3	1.77 V	199	62.3	4.6
2	*5775.00	113.4 PK			1.77 V	189	74.3	39.1
3	*5775.00	103.1 AV			1.77 V	189	64.0	39.1
4	#5925.00	65.8 PK	68.2	-2.4	1.77 V	199	60.5	5.3
5	11550.00	57.3 PK	74.0	-16.7	1.54 V	320	40.6	16.7
6	11550.00	43.3 AV	54.0	-10.7	1.54 V	320	26.6	16.7

#### **REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level - Limit value

4. The other emission levels were very low against the limit.

5. " \* ": Fundamental frequency.

6. " # ": The radiated frequency is out of the restricted band.



# 9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

#### 30 MHz ~ 1 GHz Worst-Case Data:

Mode A

802.11n (HT20)

CHANNEL	TX Channel 40	DETECTOR	
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
NO.	D. FREQ. (MHz) EMISSION LEVEL (dBuV/m) CHBUV/m) MARGIN (dBuV/m) (dBuV/m) (dB) ANTENNA TA HEIGHT AN (dB) (dB) (dB) (dB)		TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)							
1	42.65	32.3 QP	40.0	-7.7	1.50 H	291	42.5	-10.2				
2	129.81	28.5 QP	43.5	-15.0	1.50 H	274	39.2	-10.7				
3	291.48	38.9 QP	46.0	-7.1	-7.1 1.01 H 264		47.1	-8.2				
4	332.25	32.2 QP	46.0	-13.8	1.01 H	129	39.4	-7.2				
5	569.83	31.3 QP	46.0	-14.7	1.50 H	227	33.8	-2.5				
6	963.45	34.6 QP	54.0	-19.4	1.01 H	12	29.8	4.8				

**REMARKS**:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

3. Margin value = Emission Level – Limit value

4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.

5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



CHANNEL	TX Channel 40	DETECTOR	
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)				
1	35.62	38.6 QP	40.0	-1.4	1.00 V	41	49.7	-11.1				
2	204.32	31.1 QP	43.5	-12.4	1.00 V	15	43.2	-12.1				
3	304.13	37.6 QP	46.0	-8.4	1.49 V	212	45.5	-7.9				
4	575.45	36.8 QP	46.0	-9.2	1.49 V	161	39.2	-2.4				
5	732.90	33.9 QP	46.0	-12.1	1.00 V	65	33.8	0.1				
6	983.13	34.0 QP	54.0	-20.0	1.49 V	32	29.0	5.0				

#### **REMARKS**:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level – Limit value

4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.

5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.





# Mode B

#### 802.11n (HT40)

CHANNEL	TX Channel 46	DETECTOR	
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M											
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)				
1	30.81	30.2 QP	40.0	-9.8	1.50 H	135	41.9	-11.7				
2	123.19	39.3 QP	43.5	-4.2	1.50 H	111	50.6	-11.3				
3	216.16	34.1 QP	46.0	-11.9	1.01 H	253	46.0	-11.9				
4	288.86	40.1 QP	46.0	-5.9	1.01 H	252	48.3	-8.2				
5	723.65	42.6 QP	46.0	-3.4	1.01 H	305	42.8	-0.2				
6	963.45	36.6 QP	54.0	-17.4	2.01 H	12	31.8	4.8				

# **REMARKS**:

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. Margin value = Emission Level Limit value
- 4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
- 5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



CHANNEL	TX Channel 46	DETECTOR	
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	ANTENNA TABLE HEIGHT ANGLE (m) (Degree) (		CORRECTION FACTOR (dB/m)				
1	52.09	36.2 QP	40.0	-3.8	1.00 V	349	46.0	-9.8				
2	126.02	37.8 QP	43.5	-5.7	1.00 V	343	48.7	-10.9				
3	250.30	39.9 QP	46.0	-6.1	1.00 V	84	49.9	-10.0				
4	292.48	40.6 QP	46.0	-5.4	1.49 V	217	48.8	-8.2				
5	715.62	42.1 QP	46.0	-3.9	1.49 V	201	42.4	-0.3				
6	970.88	35.3 QP	54.0	-18.7	1.49 V	55	30.4	4.9				

#### **REMARKS**:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)

3. Margin value = Emission Level – Limit value

4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.

5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.





# 4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement
--

Eroquopov (MHz)	Conducted Limit (dBuV)					
Frequency (MHZ)	Quasi-Peak	Average				
0.15 - 0.5	66 - 56	56 - 46				
0.50 - 5.0	56	46				
5.0 - 30.0	60	50				

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

# 4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Dec. 11, 2019	Dec. 10, 2020
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Sep. 05, 2019	Sep. 04, 2020
LISN ROHDE & SCHWARZ (EUT)	ENV216	101826	Feb. 20, 2020	Feb. 19, 2021
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 22, 2019	Aug. 21, 2020
Software ADT	BV ADT_Cond_ V7.3.7.4	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-12040.



# 4.2.3 Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit -20 dB) was not recorded.

Note: All modes of operation were investigated and the worst-case emissions are reported.

## 4.2.4 Deviation from Test Standard

No deviation.

## 4.2.5 Test Setup



from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



# 4.2.7 Test Results

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 75%RH
Tested by	Greg Lin	Test Date	2020/4/29
Test Mode	Mode B		

	Phase Of Power : Line (L)											
	Frequency	Correction	Readin	Reading Value		Emission Level		nit	Ma	rgin		
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)		
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.		
1	0.16535	9.63	43.35	33.62	52.98	43.25	65.19	55.19	-12.21	-11.94		
2	0.55704	9.66	36.43	30.24	46.09	39.90	56.00	46.00	-9.91	-6.10		
3	0.86200	9.67	33.58	26.42	43.25	36.09	56.00	46.00	-12.75	-9.91		
4	1.13800	9.69	29.34	22.14	39.03	31.83	56.00	46.00	-16.97	-14.17		
5	3.91400	9.79	26.57	20.35	36.36	30.14	56.00	46.00	-19.64	-15.86		
6	11.72200	9.88	25.34	19.87	35.22	29.75	60.00	50.00	-24.78	-20.25		

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value





Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 75%RH
Tested by	Greg Lin	Test Date	2020/4/29
Test Mode	Mode B		

	Phase Of Power : Neutral (N)											
	Frequency	Correction	Reading Value		Emission Level		Limit		Margin			
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)		
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.		
1	0.16977	9.65	42.28	30.52	51.93	40.17	64.97	54.97	-13.04	-14.80		
2	0.54600	9.68	37.62	27.43	47.30	37.11	56.00	46.00	-8.70	-8.89		
3	0.82600	9.69	33.24	27.14	42.93	36.83	56.00	46.00	-13.07	-9.17		
4	1.12600	9.71	30.12	21.56	39.83	31.27	56.00	46.00	-16.17	-14.73		
5	1.49800	9.73	26.32	20.82	36.05	30.55	56.00	46.00	-19.95	-15.45		
6	12.06600	9.94	25.33	20.13	35.27	30.07	60.00	50.00	-24.73	-19.93		

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value





# 4.3 Transmit Power Measurement

Operation Band		EUT Category	Limit
U-NII-1	$\checkmark$	Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p ≦ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
U-NII-1		Fixed point-to-point Access Point	1 Watt (30 dBm)
		Indoor Access Point	1 Watt (30 dBm)
		Mobile and Portable client device	250mW (24 dBm)
U-NII-2A			250mW (24 dBm) or 11 dBm+10 log B*
U-NII-2C			250mW (24 dBm) or 11 dBm+10 log B*
U-NII-3	ν		1 Watt (30 dBm)

# 4.3.1 Limits of Transmit Power Measurement

\*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\ge$  40 MHz for any N<sub>ANT</sub>;

Array Gain = 5 log(N<sub>ANT</sub>/N<sub>SS</sub>) dB or 3 dB, whichever is less for 20-MHz channel widths with N<sub>ANT</sub>  $\ge$  5.

For power measurements on all other devices: Array Gain =  $10 \log(N_{ANT}/N_{SS}) dB$ .

#### 4.3.2 Test Setup

#### <Power Output Measurement>





# 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

# 4.3.4 Test Procedure

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

- a. Set span to encompass the entire 26 dB EBW (or, alternatively, the entire 99 % occupied bandwidth) of the signal.
- b. Set sweep trigger to "free run".
- c. Set RBW = 1 MHz.
- d. Set VBW ≥ 3 MHz
- e. Number of points in sweep  $\geq$  2 Span / RBW.
- f. Sweep time  $\leq$  (number of points in sweep) \* T
- g. Using emission bandwidth to determine the frequency span for integration the channel bandwidth.
- h. Detector = RMS.
- i. Trace mode = max hold.
- j. Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.
- k. Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum

#### 4.3.5 Deviation from Test Standard

No deviation.

## 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



# 4.3.7 Test Result

For U-NII-1 band (Outdoor Access Point):

#### CCD Mode

802.11a

Chan. Freq. (MHz)	Freq.	Conducted F	Power (dBm)	Total	Total	Power Limit	Ant.	EIRP	EIRP	Pass /
	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	(dBi)	(dBm)	(dBm)	Fail
36	5180	12.63	13.31	39.752	15.99	30.00	4.54	20.53	21.00	Pass
40	5200	12.78	13.55	41.613	16.19	30.00	4.54	20.73	21.00	Pass
48	5240	12.61	13.48	40.523	16.08	30.00	4.54	20.62	21.00	Pass

Note:

1. Antenna gain = 4.8dBi < 6dBi, so the limit no need to be reduced.

2. Antenna gain = 4.54dBi (above 30 degrees from the horizon).

3. EIRP = conducted power + (4.54dBi) + array gain = (0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ).

## 802.11n (HT20)

Chan. Free (MH	Freq.	Conducted F	Power (dBm)	Total Power	Total	Power	Ant.	EIRP	EIRP	Pass /
	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	(dBi)	(dBm)	(dBm)	Fail
36	5180	12.88	13.03	39.5	15.97	30.00	4.54	20.51	21.00	Pass
40	5200	12.84	13.56	41.93	16.23	30.00	4.54	20.77	21.00	Pass
48	5240	12.71	13.41	40.592	16.08	30.00	4.54	20.62	21.00	Pass

Note:

1. Antenna gain = 4.8dBi < 6dBi, so the limit no need to be reduced.

2. Antenna gain = 4.54dBi (above 30 degrees from the horizon).

3. EIRP = conducted power + (4.54dBi) + array gain = (0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ).

#### 802.11n (HT40)

Chan. Fre (MF	Freq.	Conducted F	Power (dBm)	Total	Total	Power	Ant.	EIRP	EIRP	Pass /
	(MHz)	Chain 0	Chain 1	Power (mW)	(dBm)	(dBm)	(dBi)	(dBm)	(dBm)	Fail
38	5190	12.91	13.45	41.674	16.20	30.00	4.54	20.74	21.00	Pass
46	5230	12.67	13.63	41.56	16.19	30.00	4.54	20.73	21.00	Pass

Note:

1. Antenna gain = 4.8dBi < 6dBi, so the limit no need to be reduced.

2. Antenna gain = 4.54dBi (above 30 degrees from the horizon).

3. EIRP = conducted power + (4.54dBi) + array gain = (0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ).



## 802.11ac (VHT80)

Chan.	Freq. (MHz)	Conducted F	Power (dBm)	Total	Total	al Power Ant. er Limit Gain	EIRP	EIRP	Pass /	
		Chain 0	Chain 1	(mW)	(dBm)	(dBm)	(dBi)	(dBm)	(dBm)	Fail
42	5210	12.91	13.05	39.727	15.99	30.00	4.54	20.53	21.00	Pass

Note:

1. Antenna gain = 4.8dBi < 6dBi, so the limit no need to be reduced.

2. Antenna gain = 4.54dBi (above 30 degrees from the horizon).

3. EIRP = conducted power + (4.54dBi) + array gain = (0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ).

#### Beamforming Mode

802.11n (HT20)

Chan. Freq. (MHz)	Freq.	Conducted F	Power (dBm)	Total Power	Total	Power	Ant.	EIRP	EIRP	Pass /
	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	(dBi)	(dBm)	(dBm)	Fail
36	5180	9.84	10.03	19.707	12.95	28.29	7.55	20.50	21.00	Pass
40	5200	9.83	10.51	20.862	13.19	28.29	7.55	20.74	21.00	Pass
48	5240	9.71	10.34	20.168	13.05	28.29	7.55	20.60	21.00	Pass

Note:

1. Antenna gain = 7.71dBi < 6dBi, so the power limit shall be reduced to 30-(7.71-6) = 28.29dBm.

2. Antenna gain = 7.55dBi (above 30 degrees from the horizon).

3. EIRP = conducted power + (7.55dBi) + array gain = (0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ).

802.11n (HT40)

Chan.	Freq.	Conducted F	Power (dBm)	Total	Total	Power	Ant.	EIRP	EIRP	Pass /
	(MHz)	Chain 0	Chain 1	Power (mW)	(dBm)	(dBm)	(dBi)	(dBm)	(dBm)	Fail
38	5190	9.91	10.45	20.887	13.20	28.29	7.55	20.75	21.00	Pass
46	5230	9.67	10.62	20.803	13.18	28.29	7.55	20.73	21.00	Pass

Note:

1. Antenna gain = 7.71dBi < 6dBi, so the power limit shall be reduced to 30-(7.71-6) = 28.29dBm.

2. Antenna gain = 7.55dBi (above 30 degrees from the horizon).

3. EIRP = conducted power + (7.55dBi) + array gain = (0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ).

802.11ac (VHT80)

Chan.	Freq.	Conducted F	Power (dBm)	Total Power	Total	Power Limit (dBm)	Ant.	EIRP	EIRP limit	Pass /
	(MHz)	Chain 0	Chain 1	Power (mW)	(dBm)		(dBi)	(dBm)	(dBm)	Fail
42	5210	9.89	10.11	20.007	13.01	28.29	7.55	20.56	21.00	Pass

Note:

1. Antenna gain = 7.71dBi < 6dBi, so the power limit shall be reduced to 30-(7.71-6) = 28.29dBm.

2. Antenna gain = 7.55dBi (above 30 degrees from the horizon).

3. EIRP = conducted power + (7.55dBi) + array gain = (0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ).



# For U-NII-1 band (Indoor Access Point):

CCD Mode

802.11a

Chan.	Freq.	Maximum Conducted Power (dBm)		Total Bowor	Total Power Power Limit		Pass /	
Chan.	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail	
36	5180	17.05	17.03	101.165	20.05	30.00	Pass	
40	5200	20.71	21.11	246.883	23.92	30.00	Pass	
48	5240	22.78	22.92	385.555	25.86	30.00	Pass	

# 802.11n (HT20)

Chan	Freq.	Maximum Conduc	Total Power	Total Bowor	Power	Pass /		
Chan.	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail	
36	5180	16.62	16.51	90.691	19.58	30.00	Pass	
40	5200	20.73	21.23	251.043	24.00	30.00	Pass	
48	5240	22.67	22.74	372.859	25.72	30.00	Pass	

## 802.11n (HT40)

Chan.	Freq.	Maximum Conducted Power (dBm)		Total Bowor	Total Powor	Power	Pass /
	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
38	5190	13.81	13.92	48.704	16.88	30.00	Pass
46	5230	19.01	19.37	166.113	22.20	30.00	Pass

# 802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total	Total Power	Power	Pass /
		Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
42	5210	12.91	13.12	40.055	16.03	30.00	Pass



# Beamforming Mode 802.11n (HT20)

Chan.	Freq.	Maximum Conducted Power (dBm)		Total	Total	Power	Pass /
	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
36	5180	13.56	13.47	44.932	16.53	28.29	Pass
40	5200	17.71	18.21	125.242	20.98	28.29	Pass
48	5240	19.65	19.78	187.317	22.73	28.29	Pass

Note: Beamforming gain = 7.71dBi > 6dBi , so the power limit shall be reduced to 30-(7.71-6) = 28.29dBm.

# 802.11n (HT40)

Chan	Freq.	Maximum Conducted Power (dBm)		Total Powor	Total Bower	Power	Pass /
Chan.	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
38	5190	10.81	10.92	24.409	13.88	28.29	Pass
46	5230	16.01	16.33	82.856	19.18	28.29	Pass

Note: Beamforming gain = 7.71dBi > 6dBi , so the power limit shall be reduced to 30-(7.71-6) = 28.29dBm.

## 802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total	Total	Power	Pass /
		Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
42	5210	9.89	10.11	20.007	13.01	28.29	Pass

Note: Beamforming gain = 7.71dBi > 6dBi , so the power limit shall be reduced to 30-(7.71-6) = 28.29dBm.



# For U-NII-3 band:

# CCD Mode

# 802.11a

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power	Total Power	Power	Pass /
		Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
149	5745	22.64	22.21	349.995	25.44	30.00	Pass
157	5785	22.73	22.20	353.458	25.48	30.00	Pass
165	5825	22.65	22.58	365.211	25.63	30.00	Pass

## 802.11n (HT20)

Chan.	Freq.	Maximum Conducted Power (dBm)		Total Power	Total Powor	Power	Pass /
	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
149	5745	22.62	22.33	353.812	25.49	30.00	Pass
157	5785	22.68	22.21	351.694	25.46	30.00	Pass
165	5825	22.72	22.30	356.892	25.53	30.00	Pass

# 802.11n (HT40)

Chan.	Freq.	Maximum Conducted Power (dBm)		Total Power	Total Powor	Power	Pass /
	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
151	5755	22.73	22.39	360.879	25.57	30.00	Pass
159	5795	22.69	22.35	357.571	25.53	30.00	Pass

# 802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power	Total Powor	Power	Pass /
		Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
155	5775	17.51	17.05	107.063	20.30	30.00	Pass



# Beamforming Mode 802.11n (HT20)

Chan.	Freq.	Maximum Conducted Power (dBm)		Total	Total	Power	Pass /
	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
149	5745	19.59	19.31	176.301	22.46	28.44	Pass
157	5785	19.67	19.18	175.477	22.44	28.44	Pass
165	5825	19.72	19.33	179.46	22.54	28.44	Pass

Note: Beamforming gain = 7.56dBi > 6dBi , so the power limit shall be reduced to 30-(7.56-6) = 28.44dBm.

# 802.11n (HT40)

Chan	Freq.	Maximum Conducted Power (dBm)		Total	Total	Power	Pass /
Chan.	(MHz)	Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
151	5755	19.73	19.38	180.668	22.57	28.44	Pass
159	5795	19.67	19.34	178.584	22.52	28.44	Pass

Note: Beamforming gain = 7.56dBi > 6dBi , so the power limit shall be reduced to 30-(7.56-6) = 28.44dBm.

#### 802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Powor	Total Bowor	Power	Pass /
		Chain 0	Chain 1	(mW)	(dBm)	(dBm)	Fail
155	5775	14.45	14.09	53.506	17.28	28.44	Pass

Note: Beamforming gain = 7.56dBi > 6dBi , so the power limit shall be reduced to 30-(7.56-6) = 28.44dBm.



# 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).



# Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)

## Mode A

#### 802.11ac (VHT80)



# Mode B

# 802.11ac (VHT80)





# Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab Tel: 886-2-26052180 Fax: 886-2-26051924 Hsin Chu EMC/RF/Telecom Lab Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <u>service.adt@tw.bureauveritas.com</u> Web Site: <u>www.bureauveritas-adt.com</u>

The address and road map of all our labs can be found in our web site also.

--- END ----