

FCC RF EXPOSURE REPORT

FCC ID: KA2COVR1100B1

Project No. : 2012H038
Equipment : 1) AC1200 Dual Band Mesh Wi-Fi Router
2) AC1200 Dual Band Whole Home Mesh Wi-Fi Router
Brand Name : D-Link
Test Model : COVR-1100
Series Model : COVR-1102/COVR-1103
Applicant : D-Link Corporation
Address : 17595 Mt. Herrmann Fountain Valley, CA92708 USA
Manufacturer : D-Link Corporation
Address : No.289, Sinhu 3rd Rd., Neihu District, Taipei City 114, Taiwan
Date of Receipt : Dec. 25, 2020
Date of Test : Dec. 25, 2020~Jan. 20, 2021
Issued Date : Feb. 23, 2021
Report Version : R00
Test Sample : Engineering Sample No.: SH20201223122, SH20201223123
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Maker Qi

Prepared by : Maker Qi

Ryan Wang

Approved by : Ryan Wang



Certificate # 5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Feb. 23, 2021

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	3.5
2	N/A	N/A	Internal	N/A	3.5

Note:

- The antenna gain is provided by the manufacturer.
- The EUT supports CDD, any transmit signals are correlated with each other. All antennas have the same gain, Directional gain = $G_{ANT} + \text{Array Gain}$,

For power spectral density measurements, $N_{ANT} = 2$, $N_{SS} = 1$. So Directional gain = $G_{ANT} + \text{Array Gain} = G_{ANT} + 10\log(N_{ANT}/N_{SS})$ dB = $3.5 + 10\log(2/1)$ dBi = 6.51. Then, the power density limit is $8 - (6.51 - 6) = 7.49$

For power measurements, Array Gain = 0 dB ($N_{ANT} \leq 4$), so the Directional gain = 3.5.

For 5G:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	4.5
2	N/A	N/A	Internal	N/A	4.5

Note:

- The antenna gain is provided by the manufacturer.

(2) CDD:

All antennas have the same gain, Directional gain = $G_{ANT} + \text{Array Gain}$,

For power spectral density measurements, $N_{ANT} = 2$, $N_{SS} = 1$. So Directional gain = $G_{ANT} + \text{Array Gain} = G_{ANT} + 10\log(N_{ANT}/N_{SS})$ dB = $4.5 + 10\log(2/1)$ dBi = 7.51. Then, the UNII-1 power density limit is $17 - (7.51 - 6) = 15.49$. the UNII-3 power density limit is $30 - (7.51 - 6) = 28.49$

For power measurements, Array Gain = 0 dB ($N_{ANT} \leq 4$), so the Directional gain = 4.5.

For power measurements, Array Gain = 0 dB ($N_{ANT} \leq 4$), so the Directional gain = 4.5.

Beamforming:

All antennas have the same gain, Directional gain = $G_{ANT} + 10\log(N_{ANT})$ dBi,

that is Directional gain = $4.5 + 10\log(2)$ dBi = 7.51;

So output power limit is $17 - (7.51 - 6) = 15.49$, the UNII-1 power density limit is $30 - (7.51 - 6) = 28.49$. the UNII-3 power density limit is $30 - (7.51 - 6) = 28.49$.

Table for Antenna Configuration:
For 2.4G:

Operating Mode TX Mode	Ant. 1	Ant. 2	Ant. 1+2
802.11b	✓	✓	✗
802.11g	✓	✓	✗
802.11n(20 MHz)	✓	✓	✓
802.11n(40 MHz)	✓	✓	✓

For 5G:

Operating Mode TX Mode	Ant. 1	Ant. 2	Ant. 1+2
IEEE 802.11a	✓	✓	✗
IEEE 802.11n (HT20)	✓	✓	✓
IEEE 802.11n (HT40)	✓	✓	✓
IEEE 802.11ac (VHT20)	✓	✓	✓
IEEE 802.11ac (VHT40)	✓	✓	✓
IEEE 802.11ac (VHT80)	✓	✓	✓

2. TEST RESULTS

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.5	2.2387	30	1000	0.2444	1	Complies

For 5GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
7.51	5.6364	28.49	706.3176	0.4346	1	Complies

For the max simultaneous transmission MPE:

2.4G+5G

Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Total	Limit of Power Density (S) (mW/cm ²)	Test Result
2.4GHz	5GHz			
0.2444	0.4346	0.6790	1	Complies

Note: The calculated distance is 27 cm.
Output power including tune up tolerance.

End of Test Report