



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	D-Link Corporation
Applicant Address	No.289, Sinhu 3rd Rd., Neihs District, Taipei City 114, Taiwan, R.O.C.
FCC ID	KA2CS936LA1

Product Name	HD Wi-Fi Camera
Brand Name	D-Link
Model No.	DCS-936L
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Mar. 15, 2016
Final Test Date	Mar. 24, 2016
Submission Type	Original Equipment

Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB558074 D01 v03r04.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. VERIFICATION OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	6
3.6. Table for Testing Locations.....	7
3.7. Table for Supporting Units	8
3.8. Table for Parameters of Test Software Setting	9
3.9. EUT Operation during Test	9
3.10. Duty Cycle.....	9
3.11. Test Configurations	10
4. TEST RESULT	13
4.1. AC Power Line Conducted Emissions Measurement.....	13
4.2. Maximum Conducted Output Power Measurement.....	17
4.3. Power Spectral Density Measurement	19
4.4. 6dB Spectrum Bandwidth Measurement	24
4.5. Radiated Emissions Measurement	30
4.6. Emissions Measurement	46
4.7. Antenna Requirements	60
5. LIST OF MEASURING EQUIPMENTS	61
6. MEASUREMENT UNCERTAINTY.....	63
APPENDIX A. TEST PHOTOS	A1 ~ A5


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR631827	Rev. 01	Initial issue of report	Apr. 12, 2016

1. VERIFICATION OF COMPLIANCE

Product Name : HD Wi-Fi Camera
Brand Name : D-Link
Model No. : DCS-936L
Applicant : D-Link Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 15, 2016 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	13.89 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	8.73 dB
4.3	15.247(e)	Power Spectral Density	Complies	17.05 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	2.97 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.06 dB
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter or From host system
Modulation	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: see the below table
Data Modulation	IEEE 802.11b: DSSS (BPSK / QPSK / CCK) IEEE 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	IEEE 802.11b: DSSS (1/ 2/ 5.5/11) IEEE 802.11g: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n: see the below table
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth
Channel Band Width (99%)	IEEE 802.11b: 12.36 MHz IEEE 802.11g: 17.40 MHz IEEE 802.11n MCS0 (HT20): 17.88 MHz
Maximum Conducted Output Power	IEEE 802.11b: 21.27 dBm IEEE 802.11g: 21.24 dBm IEEE 802.11n MCS0 (HT20): 19.86 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Note: This device supports 20MHz only.

Items	Description
Beamforming Function	☐ With beamforming ☒ Without beamforming

Antenna and Band width

Antenna	Single (TX)
Band width Mode	20 MHz
IEEE 802.11b	V
IEEE 802.11g	V
IEEE 802.11n	V

IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	1	MCS 0-7
Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT supports HT20 and HT40. Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n		

3.2. Accessories

Power	Brand	Model	Rating
Adapter 1 (Fixed plug)	Ktec	KSAS0050500120VUD	INPUT: 100-240V~50/60Hz, 0.18A OUTPUT: 5.0V, 1.2A
Adapter 2 (Fixed plug)	AMIGO	AMS66-0501200FU	INPUT: 100-240V~50/60Hz, 0.2A/15VA OUTPUT: 5V, 1.2A
Adapter 3 (Interchangeable plug)	Ktec	KSAS0050500120D5D	INPUT: 100-240V~50/60Hz, 0.18A OUTPUT: 5.0V, 1.2A
Others			
FCC Plug*1 (For Adapter 3 use only)			


3.3. Table for Filed Antenna

Ant.	Brand	Part Number	Antenna Type	Connector	Gain (dBi)
1	ACX	AT3216-A2R4PAAT/LF	Chip Antenna	Murata	1.5

Note: The EUT has one antenna.

For IEEE 802.11b/g/n mode:

Chain 1 can be used as transmitting antenna and receiving antenna.



Chain 1 (Connect to Ant 1 for 2.4G)

3.4. Table for Carrier Frequencies

There is one bandwidth system.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
Power Spectral Density	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1
Band Edge Emissions	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11n HT20	MCS0	1/6/11	1

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. Normal Link - EUT + power by Adapter 1

Mode 2. Normal Link - EUT + power by Adapter 2

Mode 3. Normal Link - EUT + power by Adapter 3

Mode 4. Normal Link - EUT + power by host system

Mode 3 is the worst case, so it was selected to record in this test report.

For Radiated Emission Below 1GHz test:

Mode 1. Normal Link - EUT in Y axis + power by Adapter 1

Mode 2. Normal Link - EUT in Y axis + power by Adapter 2

Mode 3. Normal Link - EUT in Y axis + power by Adapter 3

Mode 4. Normal Link - EUT in Y axis + power by host system

Mode 3 has been evaluated to be the worst case among Mode 1~4, thus measurement for Mode 5 will follow this same test mode.

Mode 5. Normal Link - EUT in Z axis + power by Adapter 3

Mode 3 is the worst case, so it was selected to record in this test report.

For Radiated Emission Above 1GHz test:

It were performed at Y axis and Z axis and the worst-case was found at Y-axis, So the measurement will follow this same test configuration

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Designation No.	IC File No.
03CH01-CB	SAC	Hsin Chu	TW0006	IC 4086D
CO01-CB	Conduction	Hsin Chu	TW0006	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	DoC
AP Router	Planex	GW-AP54SGX	KA220030603014-1
SD card	GigaSton	8G CL-4	N/A

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC
Test fixture	N/A	N/A	N/A

For Test Site No: 03CH01-CB (For below 1GHz)

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC
WLAN AP	D-LINK	DIR860L	KA2IR860LA1
SD care	GigaSton	8G CL-4	DoC

For Test Site No: 03CH01-CB (For above 1GHz)

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC
Test fixture	N/A	N/A	N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	Hypertm		
Mode	Test Frequency (MHz)		
	NCB: 20MHz		
	2412 MHz	2437 MHz	2462 MHz
802.11b	30	31	31
802.11g	28	31	24
802.11n MCS0 HT20	28	31	22

3.9. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.10. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11b	1.000	1.000	100	0.00	0.01
802.11g	1.000	1.000	100	0.00	0.01
802.11n MCS0 HT20	1.000	1.000	100	0.00	0.01

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.5m


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m

Test Configuration: above 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-11 cable	No	0.2m
3	USB cable	Yes	1.7m
4	Power cable	No	1.5m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	62%
Test Engineer	Deven Huang	Phase	Line
Configuration	Normal Link	Test Mode	Mode 3



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1516	23.35	-32.56	55.91	13.31	10.02	0.02	LINE	Average
2	0.1516	37.83	-28.08	65.91	27.79	10.02	0.02	LINE	QP
3	0.3035	29.99	-20.16	50.15	20.03	9.92	0.04	LINE	Average
4	0.3035	39.17	-20.98	60.15	29.21	9.92	0.04	LINE	QP
5	0.5611	15.07	-30.93	46.00	5.10	9.93	0.04	LINE	Average
6	0.5611	22.09	-33.91	56.00	12.12	9.93	0.04	LINE	QP
7	1.5684	14.70	-31.30	46.00	4.69	9.95	0.06	LINE	Average
8	1.5684	22.57	-33.43	56.00	12.56	9.95	0.06	LINE	QP
9	4.6469	21.35	-24.65	46.00	11.26	10.01	0.08	LINE	Average
10	4.6469	30.39	-25.61	56.00	20.30	10.01	0.08	LINE	QP
11	17.3826	17.74	-32.26	50.00	7.21	10.27	0.26	LINE	Average
12	17.3826	26.95	-33.05	60.00	16.42	10.27	0.26	LINE	QP

Temperature	23°C	Humidity	62%
Test Engineer	Deven Huang	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 3



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1508	24.83	-31.13	55.96	14.79	10.02	0.02	NEUTRAL	Average
2	0.1508	37.74	-28.22	65.96	27.70	10.02	0.02	NEUTRAL	QP
3	0.3083	36.13	-13.89	50.02	26.17	9.92	0.04	NEUTRAL	Average
4	0.3083	44.02	-16.00	60.02	34.06	9.92	0.04	NEUTRAL	QP
5	0.3217	25.07	-24.59	49.66	15.11	9.92	0.04	NEUTRAL	Average
6	0.3217	41.30	-18.36	59.66	31.34	9.92	0.04	NEUTRAL	QP
7	1.5355	15.00	-31.00	46.00	4.99	9.95	0.06	NEUTRAL	Average
8	1.5355	22.80	-33.20	56.00	12.79	9.95	0.06	NEUTRAL	QP
9	4.5015	23.79	-22.21	46.00	13.71	10.00	0.08	NEUTRAL	Average
10	4.5015	33.84	-22.16	56.00	23.76	10.00	0.08	NEUTRAL	QP
11	18.0394	14.55	-35.45	50.00	4.01	10.28	0.26	NEUTRAL	Average
12	18.0394	23.83	-36.17	60.00	13.29	10.28	0.26	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

The limit for output power is 30dBm.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB558074 D01 v03r04 section 9.2.3.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	20°C	Humidity	55%
Test Engineer	Gino Huang	Test Date	Mar. 22, 2016

Mode	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
		Chain 1		
802.11b	2412 MHz	20.05	30.00	Complies
	2437 MHz	21.14	30.00	Complies
	2462 MHz	21.27	30.00	Complies
802.11g	2412 MHz	18.09	30.00	Complies
	2437 MHz	21.24	30.00	Complies
	2462 MHz	16.72	30.00	Complies
802.11n MCS0 HT20	2412 MHz	16.62	30.00	Complies
	2437 MHz	19.86	30.00	Complies
	2462 MHz	16.60	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test was performed in accordance with KDB558074 D01 v03r04 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD).
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density


Temperature	20°C	Humidity	55%
Test Engineer	Gino Huang		

Mode	Frequency	Power Density (dBm/3kHz)	Power Density Limit (dBm/3kHz)	Result
		Chain 1		
802.11b	2412 MHz	-10.59	8.00	Complies
	2437 MHz	-9.69	8.00	Complies
	2462 MHz	-9.80	8.00	Complies
802.11g	2412 MHz	-12.02	8.00	Complies
	2437 MHz	-10.77	8.00	Complies
	2462 MHz	-16.53	8.00	Complies
802.11n MCS0 HT20	2412 MHz	-12.65	8.00	Complies
	2437 MHz	-9.05	8.00	Complies
	2462 MHz	-18.23	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1




Date: 22.MAR.2016 10:33:32

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1



Date: 22.MAR.2016 10:43:39

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1



Date: 22.MAR.2016 10:50:48

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB558074 D01 v03r04 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth = > 8.1 Option 1.
3. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth


Temperature	20°C	Humidity	55%
Test Engineer	Gino Huang		

Mode	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11b	2412 MHz	10.16	12.24	500	Complies
	2437 MHz	10.08	12.36	500	Complies
	2462 MHz	10.08	12.24	500	Complies
802.11g	2412 MHz	16.64	17.28	500	Complies
	2437 MHz	16.64	17.40	500	Complies
	2462 MHz	16.64	17.16	500	Complies
802.11n MCS0 HT20	2412 MHz	17.84	17.88	500	Complies
	2437 MHz	17.84	17.88	500	Complies
	2462 MHz	17.84	17.76	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1




Date: 22.MAR.2016 11:31:44

99% Occupied Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1




Date: 22.MAR.2016 11:10:51

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz / Chain 1




Date: 22.MAR.2016 13:15:44

99% Occupied Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1




Date: 22.MAR.2016 11:06:19

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2412 MHz / Chain 1



Date: 22.MAR.2016 13:23:32

99% Occupied Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2412 MHz / Chain 1



Date: 22.MAR.2016 11:02:57

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	Normal Link
Test Date	Mar. 15, 2016	Test Mode	Mode 3

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	Normal Link
Test Mode	Mode 3		

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	359.80	35.64	46.00	-10.36	44.75	2.20	21.22	32.53	150	178 Peak	HORIZONTAL
2	389.87	36.09	46.00	-9.91	44.41	2.27	21.95	32.54	100	174 Peak	HORIZONTAL
3	450.01	37.55	46.00	-8.45	44.71	2.42	23.00	32.58	100	157 Peak	HORIZONTAL
4	510.15	35.09	46.00	-10.91	41.21	2.63	23.87	32.62	100	334 Peak	HORIZONTAL
5	570.29	33.91	46.00	-12.09	39.19	2.77	24.62	32.67	100	35 Peak	HORIZONTAL
6	809.88	35.42	46.00	-10.58	37.81	3.25	26.71	32.35	200	162 Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	57.16	32.94	40.00	-7.06	51.67	1.02	12.87	32.62	100	51 Peak	VERTICAL
2	89.17	30.95	43.50	-12.55	47.62	1.21	14.70	32.58	125	213 Peak	VERTICAL
3	149.31	32.67	43.50	-10.83	46.90	1.49	16.84	32.56	100	300 Peak	VERTICAL
4	450.01	32.01	46.00	-13.99	39.17	2.42	23.00	32.58	300	43 Peak	VERTICAL
5	570.29	32.16	46.00	-13.84	37.44	2.77	24.62	32.67	200	50 Peak	VERTICAL
6	826.37	33.88	46.00	-12.12	35.97	3.27	26.88	32.24	200	359 Peak	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11b CH 1 / Chain 1
Test Date	Mar. 18, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4823.98	51.41	74.00	-22.59	45.53	7.58	32.82	34.52	132	208 Peak	HORIZONTAL
2	4824.03	43.99	54.00	-10.01	38.11	7.58	32.82	34.52	132	208 Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	4824.03	50.35	54.00	-3.65	44.47	7.58	32.82	34.52	24	236 Average	VERTICAL
2	4824.06	54.63	74.00	-19.37	48.75	7.58	32.82	34.52	24	236 Peak	VERTICAL

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11b CH 6 / Chain 1
Test Date	Mar. 18, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.97	52.02	74.00	-21.98	46.02	7.60	32.91	34.51	71	208	Peak	HORIZONTAL
2	4874.04	44.76	54.00	-9.24	38.76	7.60	32.91	34.51	71	208	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.94	52.41	74.00	-21.59	46.41	7.60	32.91	34.51	87	241	Peak	VERTICAL
2	4874.05	46.70	54.00	-7.30	40.70	7.60	32.91	34.51	87	241	Average	VERTICAL

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11b CH 11 / Chain 1
Test Date	Mar. 18, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4923.96	54.50	74.00	-19.50	48.38	7.62	32.99	34.49	56	233	Peak	HORIZONTAL
2	4924.03	51.03	54.00	-2.97	44.91	7.62	32.99	34.49	56	233	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4924.04	53.37	74.00	-20.63	47.25	7.62	32.99	34.49	10	228	Peak	VERTICAL
2	4924.04	48.80	54.00	-5.20	42.68	7.62	32.99	34.49	10	228	Average	VERTICAL

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11g CH 1 / Chain 1
Test Date	Mar. 16, 2016		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4817.68	49.60	74.00	-24.40	46.08	7.48	32.58	36.54	249	207 Peak	HORIZONTAL
2	4824.00	36.32	54.00	-17.68	32.80	7.48	32.58	36.54	249	207 Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4825.96	37.22	54.00	-16.78	33.65	7.50	32.61	36.54	233	178 Average	VERTICAL
2	4826.28	50.88	74.00	-23.12	47.31	7.50	32.61	36.54	233	178 Peak	VERTICAL

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11g CH 6 / Chain 1
Test Date	Mar. 19, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4874.30	35.49	54.00	-18.51	29.49	7.60	32.91	34.51	75	222	Average	HORIZONTAL
2	4874.72	49.11	74.00	-24.89	43.11	7.60	32.91	34.51	75	222	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4872.32	49.41	74.00	-24.59	43.41	7.60	32.91	34.51	15	221	Peak	VERTICAL
2	4874.01	36.17	54.00	-17.83	30.17	7.60	32.91	34.51	15	221	Average	VERTICAL

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11g CH 11 / Chain 1
Test Date	Mar. 16, 2016		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4921.20	33.88	54.00	-20.12	30.03	7.63	32.75	36.53	260	235	Average	HORIZONTAL
2	4926.68	47.50	74.00	-26.50	43.60	7.65	32.78	36.53	260	235	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4915.36	47.01	74.00	-26.99	43.16	7.63	32.75	36.53	237	181	Peak
2	4918.44	34.05	54.00	-19.95	30.20	7.63	32.75	36.53	237	181	Average

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11n MCS0 HT20 CH 1 / Chain 1
Test Date	Mar. 16, 2016		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.28	48.38	74.00	-25.62	44.86	7.48	32.58	36.54	255	173	Peak	HORIZONTAL
2	4823.56	34.34	54.00	-19.66	30.82	7.48	32.58	36.54	255	173	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.96	36.16	54.00	-17.84	32.64	7.48	32.58	36.54	272	230	Average	VERTICAL
2	4825.88	49.51	74.00	-24.49	45.94	7.50	32.61	36.54	272	230	Peak	VERTICAL

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11n MCS0 HT20 CH 6 / Chain 1
Test Date	Mar. 16, 2016		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.40	36.67	54.00	-17.33	30.67	7.60	32.91	34.51	179	232	Average	HORIZONTAL
2	4873.69	51.55	74.00	-22.45	45.55	7.60	32.91	34.51	179	232	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.14	52.68	74.00	-21.32	46.68	7.60	32.91	34.51	22	223	Peak	VERTICAL
2	4873.94	38.14	54.00	-15.86	32.14	7.60	32.91	34.51	22	223	Average	VERTICAL

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11n MCS0 HT20 CH 11 / Chain 1
Test Date	Mar. 24, 2016		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4923.96	36.62	54.00	-17.38	30.50	7.62	32.99	34.49	187	203	Average	HORIZONTAL
2	4924.36	49.59	74.00	-24.41	43.47	7.62	32.99	34.49	187	203	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4923.36	48.71	74.00	-25.29	42.62	7.61	32.97	34.49	294	203	Peak	VERTICAL
2	4924.20	36.27	54.00	-17.73	30.15	7.62	32.99	34.49	294	203	Average	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB558074 D01 v03r04 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11b CH 1, 6, 11 / Chain 1
Test Date	Mar. 18, 2016		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2389.00	59.40	74.00	-14.60	27.48	3.90	28.02	0.00	172	243	Peak	HORIZONTAL
2	2389.20	49.72	54.00	-4.28	17.80	3.90	28.02	0.00	172	243	Average	HORIZONTAL
3	2413.00	108.50			76.57	3.94	27.99	0.00	172	243	Peak	HORIZONTAL
4	2413.80	104.72			72.79	3.94	27.99	0.00	172	243	Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2388.20	56.44	74.00	-17.56	24.52	3.90	28.02	0.00	216	251	Peak	VERTICAL
2	2388.40	43.92	54.00	-10.08	12.00	3.90	28.02	0.00	216	251	Average	VERTICAL
3	2435.20	104.33			72.39	3.97	27.97	0.00	216	251	Average	VERTICAL
4	2435.60	107.99			76.05	3.97	27.97	0.00	216	251	Peak	VERTICAL
5	2485.40	56.39	74.00	-17.61	24.43	4.04	27.92	0.00	216	251	Peak	VERTICAL
6	2485.80	43.85	54.00	-10.15	11.89	4.04	27.92	0.00	216	251	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	2460.20	104.26			72.31	4.00	27.95	0.00	151	236	Average	HORIZONTAL
2	2460.60	107.86			75.91	4.01	27.94	0.00	151	236	Peak	HORIZONTAL
3	2483.50	48.92	54.00	-5.08	16.96	4.04	27.92	0.00	151	236	Average	HORIZONTAL
4	2489.20	58.80	74.00	-15.20	26.84	4.05	27.91	0.00	151	236	Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11g CH 1, 6, 11 / Chain 1
Test Date	Mar. 16, 2016 ~ Mar. 19, 2016		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2389.40	69.95	74.00	-4.05	37.53	4.52	27.90	0.00	276	350 Peak	HORIZONTAL
2	2390.00	53.37	54.00	-0.63	20.95	4.52	27.90	0.00	276	350 Average	HORIZONTAL
3	2419.40	98.51			66.08	4.56	27.87	0.00	276	350 Average	HORIZONTAL
4	2419.40	107.59			75.16	4.56	27.87	0.00	276	350 Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	2389.40	63.55	74.00	-10.45	31.63	3.90	28.02	0.00	170	238 Peak	HORIZONTAL
2	2389.80	49.82	54.00	-4.18	17.90	3.90	28.02	0.00	170	238 Average	HORIZONTAL
3	2444.20	110.22			78.28	3.98	27.96	0.00	170	238 Peak	HORIZONTAL
4	2444.20	100.82			68.88	3.98	27.96	0.00	170	238 Average	HORIZONTAL
5	2483.50	46.18	54.00	-7.82	14.22	4.04	27.92	0.00	170	238 Average	HORIZONTAL
6	2484.60	59.83	74.00	-14.17	27.87	4.04	27.92	0.00	170	238 Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2454.80	96.78			64.35	4.59	27.84	0.00	276	350 Average	HORIZONTAL
2	2455.00	105.54			73.11	4.59	27.84	0.00	276	350 Peak	HORIZONTAL
3	2483.50	52.64	54.00	-1.36	20.22	4.61	27.81	0.00	276	350 Average	HORIZONTAL
4	2483.70	68.81	74.00	-5.19	36.39	4.61	27.81	0.00	276	350 Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	20°C	Humidity	58%
Test Engineer	Brian Sun & Lucke Hsieh	Configurations	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Chain 1
Test Date	Mar. 16, 2016 ~ Mar. 24, 2016		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm	
1	2389.80	73.62	74.00	-0.38	40.87	4.85	27.90	0.00	277	349 Peak	HORIZONTAL
2	2390.00	53.10	54.00	-0.90	20.35	4.85	27.90	0.00	277	349 Average	HORIZONTAL
3	2420.00	98.79			66.01	4.91	27.87	0.00	277	349 Average	HORIZONTAL
4	2420.00	108.40			75.62	4.91	27.87	0.00	277	349 Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	2389.40	66.06	74.00	-7.94	34.14	3.90	28.02	0.00	170	216 Peak	HORIZONTAL
2	2390.00	49.99	54.00	-4.01	18.07	3.90	28.02	0.00	170	216 Average	HORIZONTAL
3	2429.00	100.02			68.08	3.96	27.98	0.00	170	216 Average	HORIZONTAL
4	2429.40	110.13			78.19	3.96	27.98	0.00	170	216 Peak	HORIZONTAL
5	2483.50	45.51	54.00	-8.49	13.55	4.04	27.92	0.00	170	216 Average	HORIZONTAL
6	2484.20	62.33	74.00	-11.67	30.37	4.04	27.92	0.00	170	216 Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	2469.20	103.37			71.42	4.02	27.93	0.00	51	123 Peak	VERTICAL
2	2470.00	93.53			61.58	4.02	27.93	0.00	51	123 Average	VERTICAL
3	2483.50	73.43	74.00	-0.57	41.47	4.04	27.92	0.00	51	123 Peak	VERTICAL
4	2483.50	53.94	54.00	-0.06	21.98	4.04	27.92	0.00	51	123 Average	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11b / Reference Level




Date: 16.MAR.2016 21:43:58

Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 16.MAR.2016 21:45:41

Plot on Configuration IEEE 802.11b / CH 1 / 2483.5MHz~26500MHz (down 30dBc)




Date: 16.MAR.2016 21:48:10

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 16.MAR.2016 21:49:31

Plot on Configuration IEEE 802.11b / CH 11 / 2483.5MHz~26500MHz (down 30dBc)




Date: 16.MAR.2016 21:50:56

Plot on Configuration IEEE 802.11g / Reference Level




Date: 16.MAR.2016 21:53:12

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 16.MAR.2016 21:54:18

Plot on Configuration IEEE 802.11g / CH 1 / 2483.5MHz~26500MHz (down 30dBc)




Date: 16.MAR.2016 21:54:52

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 16.MAR.2016 21:55:52

Plot on Configuration IEEE 802.11g / CH 11 / 2483.5MHz~26500MHz (down 30dBc)




Date: 16.MAR.2016 21:56:24

Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level




Date: 16.MAR.2016 21:57:52

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 16.MAR.2016 21:59:16

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 2483.5MHz~26500MHz (down 30dBc)




Date: 16.MAR.2016 21:59:45

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 30MHz~2400MHz (down 30dBc)



Date: 16.MAR.2016 22:00:33

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 2483.5MHz~26500MHz (down 30dBc)



Date: 16.MAR.2016 22:01:07

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 22, 2015	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 08, 2015	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 23, 2015	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	May 25, 2015	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	37880	20MHz ~ 2GHz	Sep. 03, 2015	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 12, 2015*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 22, 2015	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jul. 21, 2015	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Mar. 15, 2016	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 18, 2016	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 13, 2015	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Oct. 27, 2015	Radiation (03CH01-CB)
EMI Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8.4GHz	Jan. 27, 2016	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-17	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-1	N/A	18GHz ~ 40 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-2	N/A	18GHz ~ 40 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
Test Software	Audix	E3	6.2009-I0-7	N/A	N/A	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 09, 2015	Conducted (TH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz~40GHz	Oct. 27, 2015	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz ~ 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz ~ 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-9	1 GHz ~ 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	RG402	High Cable-10	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-6	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 02, 2015	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%