

## 5.14 BAND EDGES MEASUREMENT

## 5.14.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

## 5.14.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

### NOTES:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

## 5.14.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

## 5.14.4 DEVIATION FROM TEST STANDARD

No deviation



## 5.14.5 EUT OPERATING CONDITION


Same as Item 5.9.6

## 5.14.6 TEST RESULTS


The spectrum plots are attached on the following pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).




Normal Mode





















Turbo Mode


















## 5.15 ANTENNA REQUIREMENT

## 5.15.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

## 5.15.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Chip & Dipole antenna without antenna connector. The maximum Gain of the antenna is 3.4dBi.




# **6. PHOTOGRAPHS OF THE TEST CONFIGURATION**

CONDUCTED EMISSION TEST









RADIATED EMISSION TEST a a a h h h h \* \* \* 21 2 M X X X 93111111.03 ntie 9311111.03

Report No.: RF931111L03

Report Format Version 2.0.1



# 7. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB, GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab: Tel: 886-2-26052180 Fax: 886-2-26052943

#### Hsin Chu EMC/RF Lab: Tel: 886-3-5935343 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab: Linko RF Lab. Tel: 886-3-3183232 Fax: 886-3-3185050

Tel: 886-3-3270910 Fax: 886-3-3270892

Web Site: <u>www.adt.com.tw</u>

The address and road map of all our labs can be found in our web site also