



FCC TEST REPORT

REPORT NO.: RF941107H01

MODEL NO.: DI-624, WRG-G16

RECEIVED: Nov. 04, 2005

TESTED: Nov. 10 to 18, 2005

ISSUED: Nov. 23, 2005

APPLICANT: D-LINK Corporation

ADDRESS: No.8, Li-shing 7th Rd. Science-based Industrial Park, Hsinchu, Taiwan. R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien, Taiwan, R.O.C.

This test report consists of 76 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



0536
ILAC MRA



No. 2177-01



Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS.....	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT.....	6
3.2	DESCRIPTION OF TEST MODES.....	8
3.3	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:.....	9
3.4	GENERAL DESCRIPTION OF APPLIED STANDARDS	10
3.5	DESCRIPTION OF SUPPORT UNITS.....	11
3.6	CONFIGURATION OF SYSTEM UNDER TEST	12
4	TEST TYPES AND RESULTS.....	14
4.1	CONDUCTED EMISSION MEASUREMENT	14
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	14
4.1.2	TEST INSTRUMENTS	14
4.1.3	TEST PROCEDURES.....	15
4.1.4	TEST SETUP	15
4.1.5	EUT OPERATING CONDITIONS.....	16
4.1.6	TEST RESULTS – With adapter 1.....	17
4.1.7	TEST RESULTS – With adapter 2.....	19
4.2	RADIATED EMISSION MEASUREMENT	21
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	21
4.2.2	TEST INSTRUMENTS	22
4.2.3	TEST PROCEDURES.....	23
4.2.4	TEST SETUP	24
4.2.5	EUT OPERATING CONDITIONS.....	24
4.2.6	TEST RESULTS.....	25
4.2.7	TEST RESULTS – DSSS	27
4.2.8	TEST RESULTS – OFDM	30
4.3	6dB BANDWIDTH MEASUREMENT	35
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	35
4.3.2	TEST INSTRUMENTS	35
4.3.3	TEST PROCEDURE	36
4.3.4	TEST SETUP.....	36
4.3.5	EUT OPERATING CONDITIONS.....	36
4.3.6	TEST RESULTS –DSSS	37
4.3.7	TEST RESULTS-OFDM	40
4.4	MAXIMUM PEAK OUTPUT POWER	45
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	45
4.4.2	TEST INSTRUMENTS	45
4.4.3	TEST PROCEDURES.....	46



4.4.4 TEST SETUP 46

4.4.5 EUT OPERATING CONDITIONS 46

4.4.6 TEST RESULTS – DSSS 47

4.4.7 TEST RESULTS –OFDM 48

4.5 POWER SPECTRAL DENSITY MEASUREMENT 49

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 49

4.5.2 TEST INSTRUMENTS 49

4.5.3 TEST PROCEDURE 50

4.5.4 TEST SETUP 50

4.5.5 EUT OPERATING CONDITIONS 50

4.5.6 TEST RESULTS –DSSS 51

4.5.7 TEST RESULTS –OFDM 54

4.6 BAND EDGES MEASUREMENT 59

4.6.1 LIMITS OF BAND EDGES MEASUREMENT 59

4.6.2 TEST INSTRUMENTS 59

4.6.3 TEST PROCEDURE 59

4.6.4 EUT OPERATING CONDITION 59

4.6.5 TEST RESULTS – DSSS 60

4.6.6 TEST RESULTS –OFDM 64

4.7 ANTENNA REQUIREMENT 72

4.7.1 STANDARD APPLICABLE 72

4.7.2 ANTENNA CONNECTED CONSTRUCTION 72

5 PHOTOGRAPHS OF THE TEST CONFIGURATION 73

6 INFORMATION ON THE TESTING LABORATORIES 75

APPENDIX-A A-1



1 CERTIFICATION

PRODUCT : IEEE802.11g Wireless Router
BRAND NAME : D-Link, Alpha
MODEL NO. : DI-624, WRG-G16
TESTED: Nov. 10 to 18, 2005
APPLICANT : D-LINK Corporation
TEST ITEM: ENGINEERING SAMPLE
STANDARDS : 47 CFR Part 15, Subpart C (Section 15.247),
 ANSI C63.4-2003

The above equipment (Model: DI-624) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Midoli Peng , **DATE:** Nov. 23, 2005
 (Midoli Peng)

TECHNICAL ACCEPTANCE : Hank Chung , **DATE:** Nov. 23, 2005
 Responsible for RF (Hank Chung)

APPROVED BY : May Chen , **DATE:** Nov. 23, 2005
 (May Chen, Deputy Manager)



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -14.50 dB at 0.607 MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.1 dB at 2483.50 MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	IEEE802.11g Wireless Router
MODEL NO.	DI-624, WRG-G16
POWER SUPPLY	DC 5.0V or DC7.5V from power adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps (Turbo mode: up to 108Mbps *see Note 3)
FREQUENCY RANGE	802.11b & 802.11g: 2412 ~ 2462MHz
NUMBER OF CHANNEL	802.11b & 802.11g: 11 (1 for 802.11g Turbo mode)
CHANNEL SPACING	802.11b & 802.11g: 5MHz
OUTPUT POWER	802.11b: 100.00mW 802.11g: 169.824mW
ANTENNA TYPE	Dipole antenna, antenna gain: 1.8dBi
DATA CABLE	NA
I/O PORTS	LAN port * 4; WAN port * 1
ASSOCIATED DEVICES	NA

NOTE:

- The EUT has two model names and two brand names, which are identical to each other in all aspects except for the followings:

Brand Name	Model Name
D-Link	DI-624
Alpha	WRG-G16

From the above models, model: **DI-624** was selected as representative model for the test and its data was recorded in this report.

- The EUT operates in both the 2.4GHz Bands and compatibility with 802.11b, 802.11g technology.

3. The EUT is capable of providing data rates of up to 108 Mbps in 802.11g Turbo mode depending upon reception quality.
4. The EUT was powered by the following adapters:

Adapter 1	
Brand:	D-Link
Model No.:	JTA0302B
Input power :	100~120Vac/0.5A 50~60Hz
Output power :	5.0V/2.5A, 1.8m, non-shielded
Adapter 2	
Brand:	D-Link
Model No.:	AM-0751000D41
Input power :	120Vac/60Hz; 15W
Output power :	7.5V/1000mA, 1.8m, non-shielded

5. For Radiated Test, the EUT was pre-tested under the following modes for two different axes placements:

Test Mode	Description
Mode A	level
Mode B	upright

From the above modes, the worst emission level was found in **Mode A**. Therefore only the test data of the modes were recorded in this report individually.

6. Only for Conducted Test & Radiated Test (Below 1GHz), the EUT was tested under the following test modes, and its data were recorded in this report:

Conducted Test	
Test Mode	Description
Mode 1	Adapter 1
Mode 2	Adapter 2
Radiated Test (Below 1GHz)	
Test Mode	Description
Mode 1	Adapter 1
Mode 2	Adapter 2

7. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

For 802.11b/g normal mode: Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

For 802.11g turbo mode: One channel is provided to this EUT

Channel	Frequency
6	2437 MHz



3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	X	X	X	X	NA

Where PLC: Power Line Conducted Emission RE<1G RE: Radiated Emission below 1GHz
 RE≥1G: Radiated Emission above 1GHz APCM: Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11g turbo	6	6	OFDM	BPSK	12

- The EUT was pre-tested in chamber as the following test modes:

Test Mode	Power
Mode A	With Adapter 1
Mode B	With Adapter 2

The worst was found in Mode A, the worst cases, were chosen for final test.



Bandedge Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6
802.11g turbo	6	6	OFDM	BPSK	12

Antenna Port Conducted Measurement:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11g turbo	6	6	OFDM	BPSK	12

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an IEEE802.11g Wireless Router. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C. (15.247)

ANSI C63.4 : 2003

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of 47 CFR Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


No.	Product	Brand	Model No.	Serial No.	FCC ID
1	PERSONAL COMPUTER (Only for radiation test)	DELL	4700	G2MDF1S	NA
2	MONITOR (Only for radiation test)	DELL	2001FP	CN-0C0647-46633-58R-2W4L	NA
3	PRINTER	EPSON	LQ-300+	DCGY017079	DoC
4	MODEM	ACEEX	1414	0206026775	IFAXDM1414
5	KEYBOARD	BTC	5200U	G09302046476	E5XKB5122U
6	MOUSE	BTC	M851	G00347024431	NA
7	NOTEBOOK COMPUTER (Only for conduction test)	DELL	PP05L	CN-04Y212-48643-38E-0145	NA
8	NOTEBOOK COMPUTER	DELL	PP01L	TW-0791UH-12800-0CK-3735	DoC

No.	Signal cable description
1	NA
2	1.8 m braid shielded wire, terminated with VGA connector via metallic frame, w/o core.
3	1.5 m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core.
4	1.0 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core
5	1.5 m foil shielded wire, terminal by frame, PS2 Connector, w/o Core.
6	1.5 m foil shielded wire, terminal by frame, PS2 Connector, w/o Core.
7	NA
8	NA

Note: 1. All power cords of the above support units are unshielded (1.8m).


3.6 CONFIGURATION OF SYSTEM UNDER TEST

For conduction test:



- NOTE:**
1. Support units 8 were kept in the control room during the test.
 2. Please refer to the photos of test configuration in Item 5 also.

For radiation test:



NOTE: 1. Support units 8 were kept in the control room during the test.
 2. Please refer to the photos of test configuration in Item 5 also.



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Sep. 19, 2006
Line-Impedance Stabilization Network(for EUT)	ENV-216	100071	Nov. 10, 2006
ROHDE & SCHWARZ LISN	ESH3-Z5	848773/004	Oct. 24, 2006
RF Signal Cable	RG233	COBCAB9K-30MHz	Dec. 10, 2005
Impedance-stabilization-network	ENY 41	838119/024	Jan. 09, 2006
Impedance-stabilization-network	ENY 22	837497/019	Jan. 09, 2006
Current Probe	SMZ11	18001	Jul. 13, 2006
Current Probe	SMZ11	18013	Jul. 13, 2006

- NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in ADT Shielded Room No. B.
 3. The VCCI Con B Registration No. is C-2193.

4.1.3 TEST PROCEDURES

- a. The EUT/HOST was placed 0.4 meters from the conducting wall of the shielded room with EUT/HOST being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT/HOST were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.5 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. The support unit 7 act as a Server PC system to communicate with EUT via UTP cable.
- c. Prepared other computer system (support unit 8) to act as a communication partner and placed them outside of testing area.
- d. The communication partner runs test program "ART_52_build58" to enable EUT under wireless transmission condition continuously via one UTP cable.
- e. PC sends "H" messages to modem.
- f. PC sends "H" messages to printer, and the printer prints them on paper.




4.1.6 TEST RESULTS – With adapter 1

EUT	IEEE802.11g Wireless Router	MODEL NO.	DI-624
TEST MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50% RH, 971 hPa	TESTED BY: Moris Lin	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.185	9.29	32.82	-	42.11	-	64.25	54.25	-22.14	-
2	0.248	9.21	27.49	-	36.70	-	61.84	51.84	-25.14	-
3	0.439	9.19	27.46	-	36.65	-	57.08	47.08	-20.43	-
4	2.498	9.27	29.79	-	39.06	-	56.00	46.00	-16.94	-
5	14.321	9.60	28.34	-	37.94	-	60.00	50.00	-22.06	-
6	20.809	9.77	19.86	-	29.63	-	60.00	50.00	-30.37	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






EUT	IEEE802.11g Wireless Router	MODEL NO.	DI-624
TEST MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50% RH, 971 hPa	TESTED BY: Moris Lin	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.185	9.19	28.21	-	37.40	-	64.25	54.25	-26.85	-
2	0.439	9.24	24.59	-	33.83	-	57.08	47.08	-23.25	-
3	0.814	9.20	20.72	-	29.92	-	56.00	46.00	-26.08	-
4	2.505	9.34	32.11	-	41.45	-	56.00	46.00	-14.55	-
5	13.903	9.64	26.98	-	36.62	-	60.00	50.00	-23.38	-
6	20.108	9.81	27.62	-	37.43	-	60.00	50.00	-22.57	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






4.1.7 TEST RESULTS – With adapter 2

EUT	IEEE802.11g Wireless Router	MODEL NO.	DI-624
TEST MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50% RH, 971 hPa	TESTED BY: Moris Lin	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	9.44	36.06	-	45.50	-	65.58	55.58	-20.08	-
2	0.291	9.20	29.55	-	38.75	-	60.51	50.51	-21.75	-
3	0.552	9.19	27.20	-	36.39	-	56.00	46.00	-19.61	-
4	1.117	9.24	12.80	-	22.04	-	56.00	46.00	-33.96	-
5	1.873	9.23	11.86	-	21.09	-	56.00	46.00	-34.91	-
6	16.227	9.64	22.50	-	32.14	-	60.00	50.00	-27.86	-
7	23.070	9.83	19.50	-	29.33	-	60.00	50.00	-30.67	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






EUT	IEEE802.11g Wireless Router	MODEL NO.	DI-624
TEST MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	25 deg. C, 50% RH, 971 hPa	TESTED BY: Moris Lin	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	9.19	36.70	-	45.89	-	64.98	54.98	-19.09	-
2	0.334	9.22	32.55	-	41.77	-	59.36	49.36	-17.59	-
3	0.607	9.22	32.28	-	41.50	-	56.00	46.00	-14.50	-
4	1.505	9.26	15.42	-	24.68	-	56.00	46.00	-31.32	-
5	16.168	9.68	20.35	-	30.03	-	60.00	50.00	-29.97	-
6	21.909	9.75	21.69	-	31.44	-	60.00	50.00	-28.56	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ADVANTEST Spectrum Analyzer	R3271A	85060311	July 07, 2006
HP Pre_Amplifier	8449B	3008A01922	Oct. 02, 2006
ROHDE & SCHWARZ Test Receiver	ESCS30	100287	Dec. 08, 2005
CHASE Broadband Antenna	VULB9168	138	Dec. 21, 2005
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 11, 2005
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 30, 2006
SCHWARZBECK Biconical Antenna	VHBA9123	459	Jun. 26, 2006
SCHWARZBECK Periodic Antenna	UPA6108	1148	Jun. 26, 2006
RF Switches (ARNITSU)	CS-201	1565157	NA
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Nov. 16. 2006
RF Cable(RICHTEC)	9913-30M	STCCAB-30M- 1GHz-021	Jul. 16, 2006
Software	ADT_Radiated_V 5.14	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Periodic Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.

2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 4824-3.
7. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30MHz-1GHz)	2.98 dB
Radiated emissions (1GHz ~18GHz)	2.21 dB
Radiated emissions (18GHz ~20GHz)	1.88 dB




4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. The support units (1-6) act as a Server PC system to communicate with EUT via UTP cable.
- c. Prepared other computer system (support unit 8) to act as a communication partner and placed them outside of testing area.
- d. The communication partner runs test program "ART_52_build58" to enable EUT under wireless transmission condition continuously via one UTP cable.
- e. PC sends "H" messages to modem.
- f. PC sends "H" messages to printer, and the printer prints them on paper.

4.2.6 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	TEST MODE	With Adapter1
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 65%RH, 971 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	125.01	33.10 QP	43.50	-10.40	1.54 H	24	21.20	11.90
2	200.01	32.20 QP	43.50	-11.30	1.02 H	249	21.00	11.20
3	240.00	35.00 QP	46.00	-11.00	1.42 H	306	22.10	12.90
4	250.03	36.70 QP	46.00	-9.30	1.58 H	97	23.40	13.30
5	299.90	31.70 QP	46.00	-14.30	1.14 H	52	15.40	16.30
6	375.01	40.70 QP	46.00	-5.30	1.10 H	193	23.10	17.60
7	400.00	41.20 QP	46.00	-4.80	1.58 H	98	22.80	18.40
8	500.00	44.10 QP	46.00	-1.90	1.00 H	90	23.20	20.90
9	599.97	36.70 QP	46.00	-9.30	1.52 H	10	13.20	23.50
10	625.01	39.20 QP	46.00	-6.80	1.54 H	24	15.40	23.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	125.01	32.20 QP	43.50	-11.30	1.09 V	356	20.40	11.90
2	200.00	28.30 QP	43.50	-15.20	1.53 V	62	17.10	11.20
3	240.01	28.10 QP	46.00	-17.90	1.35 V	65	15.20	12.90
4	250.00	25.70 QP	46.00	-20.30	1.02 V	56	12.40	13.30
5	300.00	31.20 QP	46.00	-14.80	1.11 V	54	14.90	16.30
6	375.00	39.60 QP	46.00	-6.40	1.54 V	248	22.10	17.60
7	400.00	41.20 QP	46.00	-4.80	1.54 V	247	22.90	18.40
8	500.01	42.00 QP	46.00	-4.00	1.86 V	326	21.10	20.90
9	625.01	38.50 QP	46.00	-7.50	1.47 V	268	14.80	23.80
10	750.02	39.40 QP	46.00	-6.60	1.54 V	52	13.00	26.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	TEST MODE	With Adapter 2
MODE	Channel 11	FREQUENCY RANGE	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120kHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 65%RH, 971 hPa	TESTED BY	Eric Lee

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	124.99	32.50 QP	43.50	-11.00	1.24 H	123	20.60	11.90
2	200.00	32.30 QP	43.50	-11.20	1.14 H	21	21.10	11.20
3	240.01	35.50 QP	46.00	-10.50	1.14 H	72	22.60	12.90
4	250.02	35.50 QP	46.00	-10.50	1.13 H	191	22.20	13.30
5	299.99	36.10 QP	46.00	-9.90	1.23 H	359	19.80	16.30
6	375.02	41.50 QP	46.00	-4.50	1.01 H	8	23.90	17.60
7	400.02	40.60 QP	46.00	-5.40	1.00 H	21	22.20	18.40
8	500.04	43.90 QP	46.00	-2.10	1.00 H	87	23.10	20.90
9	599.89	36.40 QP	46.00	-9.60	1.00 H	317	12.90	23.50
10	625.03	39.70 QP	46.00	-6.30	1.29 H	38	16.00	23.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	125.00	31.50 QP	43.50	-12.00	1.81 V	71	19.60	11.90
2	200.01	28.10 QP	43.50	-15.40	1.68 V	312	16.90	11.20
3	240.00	29.00 QP	46.00	-17.00	1.03 V	294	16.10	12.90
4	249.98	34.00 QP	46.00	-12.00	1.48 V	120	20.80	13.30
5	300.00	32.70 QP	46.00	-13.30	1.02 V	174	16.40	16.30
6	375.02	40.20 QP	46.00	-5.80	1.07 V	124	22.60	17.60
7	400.02	40.60 QP	46.00	-5.40	1.32 V	21	22.20	18.40
8	500.03	41.00 QP	46.00	-5.00	1.00 V	12	20.10	20.90
9	624.98	37.70 QP	46.00	-8.30	1.08 V	296	13.90	23.80
10	750.07	38.20 QP	46.00	-7.80	1.24 V	189	11.90	26.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



4.2.7 TEST RESULTS – DSSS 802.11b DSSS modulation

EUT	IEEE802.11g Wireless Router	MODEL	DI-624
MODE	Channel 1	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa	TESTED BY	Wen Yu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	37.60 PK	74.00	-36.40	1.10 H	231	10.30	27.40
1	1608.00	28.80 AV	54.00	-25.20	1.10 H	231	1.50	27.40
2	2390.00	41.50 PK	74.00	-32.50	1.00 H	0	7.80	33.70
2	2390.00	34.40 AV	54.00	-19.60	1.00 H	0	0.70	33.70
3	*2412.00	102.60 PK			1.41 H	128	72.80	29.80
3	*2412.00	95.40 AV			1.41 H	128	65.60	29.80
4	3216.00	43.40 PK	74.00	-30.60	1.38 H	101	11.40	32.00
4	3216.00	37.70 AV	54.00	-16.30	1.38 H	101	5.70	32.00
5	4824.00	42.20 PK	74.00	-31.80	1.01 H	17	7.10	35.10
5	4824.00	30.50 AV	54.00	-23.50	1.01 H	17	-4.60	35.10
6	7236.00	48.10 PK	74.00	-25.90	1.12 H	315	7.60	40.50
6	7236.00	36.20 AV	54.00	-17.80	1.12 H	315	-4.30	40.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	40.20 PK	74.00	-33.80	1.02 V	178	12.90	27.40
1	1608.00	34.80 AV	54.00	-19.20	1.02 V	178	7.50	27.40
2	2390.00	52.40 PK	74.00	-21.60	1.20 V	317	18.70	33.70
2	2390.00	44.30 AV	54.00	-9.70	1.20 V	317	10.60	33.70
3	*2412.00	113.50 PK			1.20 V	317	83.70	29.80
3	*2412.00	106.30 AV			1.20 V	317	76.50	29.80
4	3216.00	48.30 PK	74.00	-25.70	1.26 V	171	16.30	32.00
4	3216.00	45.20 AV	54.00	-8.80	1.26 V	171	13.20	32.00
5	4824.00	43.30 PK	74.00	-30.70	1.54 V	329	8.20	35.10
5	4824.00	32.50 AV	54.00	-21.50	1.54 V	329	-2.60	35.10
6	7236.00	47.10 PK	74.00	-26.90	1.39 V	19	6.60	40.50
6	7236.00	36.40 AV	54.00	-17.60	1.39 V	19	-4.10	40.50

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency



EUT	IEEE802.11g Wireless Router	MODEL	DI-624
MODE	Channel 6	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa	TESTED BY	Wen Yu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.30	38.00 PK	74.00	-36.00	1.11 H	241	10.60	27.40
1	1641.30	29.30 AV	54.00	-24.70	1.11 H	241	1.90	27.40
2	*2437.00	100.20 PK			1.40 H	28	70.30	29.90
2	*2437.00	92.90 AV			1.40 H	28	63.00	29.90
3	3249.30	43.90 PK	74.00	-30.10	1.27 H	110	11.80	32.10
3	3249.30	38.00 AV	54.00	-16.00	1.27 H	110	5.90	32.10
4	4874.00	42.60 PK	74.00	-31.40	1.00 H	15	7.30	35.30
4	4874.00	30.90 AV	54.00	-23.10	1.00 H	15	-4.40	35.30
5	7311.00	48.60 PK	74.00	-25.40	1.15 H	318	7.90	40.70
5	7311.00	36.60 AV	54.00	-17.40	1.15 H	318	-4.10	40.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	40.60 PK	74.00	-33.40	1.05 V	182	13.20	27.40
1	1624.00	35.20 AV	54.00	-18.80	1.05 V	182	7.80	27.40
2	*2437.00	115.90 PK			1.10 V	348	86.00	29.90
2	*2437.00	108.30 AV			1.10 V	348	78.40	29.90
3	3249.30	46.90 PK	74.00	-27.10	1.24 V	170	14.80	32.10
3	3249.30	44.20 AV	54.00	-9.80	1.24 V	170	12.10	32.10
4	4874.00	43.70 PK	74.00	-30.30	1.55 V	332	8.40	35.30
4	4874.00	32.80 AV	54.00	-21.20	1.55 V	332	-2.50	35.30
5	7311.00	47.50 PK	74.00	-26.50	1.42 V	28	6.80	40.70
5	7311.00	36.70 AV	54.00	-17.30	1.42 V	28	-4.00	40.70

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. " * " : Fundamental frequency



EUT	IEEE802.11g Wireless Router	MODEL	DI-624
MODE	Channel 11	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa	TESTED BY	Wen Yu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.30	38.20 PK	74.00	-35.80	1.13 H	238	10.80	27.40
1	1641.30	29.50 AV	54.00	-24.50	1.13 H	238	2.10	27.40
2	*2462.00	101.40 PK			1.34 H	250	71.40	30.00
2	*2462.00	94.30 AV			1.34 H	250	64.30	30.00
3	2483.50	44.00 PK	74.00	-30.00	1.34 H	250	13.90	30.10
3	2483.50	31.50 AV	54.00	-22.50	1.34 H	250	1.40	30.10
4	3282.60	44.20 PK	74.00	-29.80	1.27 H	110	12.10	32.20
4	3282.60	38.60 AV	54.00	-15.40	1.27 H	110	6.50	32.20
5	4924.00	43.00 PK	74.00	-31.00	1.00 H	10	7.40	35.50
5	4924.00	31.30 AV	54.00	-22.70	1.00 H	10	-4.30	35.50
6	7386.00	48.70 PK	74.00	-25.30	1.17 H	233	7.90	40.80
6	7386.00	36.60 AV	54.00	-17.40	1.17 H	233	-4.20	40.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.30	41.00 PK	74.00	-33.00	1.03 V	177	13.60	27.40
1	1641.30	35.50 AV	54.00	-18.50	1.03 V	177	8.10	27.40
2	*2462.00	114.80 PK			1.20 V	276	84.70	30.00
2	*2462.00	107.50 AV			1.20 V	276	77.40	30.00
3	2483.50	57.50 PK	74.00	-16.50	1.20 V	276	27.40	30.10
3	2483.50	44.60 AV	54.00	-9.40	1.20 V	276	14.50	30.10
4	3282.60	48.80 PK	74.00	-25.20	1.31 V	185	16.70	32.20
4	3282.60	46.40 AV	54.00	-7.60	1.31 V	185	14.20	32.20
5	4924.00	44.30 PK	74.00	-29.70	1.52 V	318	8.70	35.50
5	4924.00	33.40 AV	54.00	-20.60	1.52 V	318	-2.20	35.50
6	7386.00	47.90 PK	74.00	-26.10	1.47 V	37	7.10	40.80
6	7386.00	37.00 AV	54.00	-17.00	1.47 V	37	-3.80	40.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



4.2.8 TEST RESULTS – OFDM 802.11g Normal OFDM modulation

EUT	IEEE802.11g Wireless Router	MODEL	DI-624
MODE	Channel 1	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa	TESTED BY	Wen Yu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	39.80 PK	74.00	-34.20	1.00 H	235	12.50	27.40
1	1608.00	34.30 AV	54.00	-19.70	1.00 H	235	7.00	27.40
2	2390.00	52.40 PK	74.00	-21.60	1.00 H	250	18.70	33.70
2	2390.00	40.90 AV	54.00	-13.10	1.00 H	250	7.20	33.70
3	*2412.00	99.40 PK			1.00 H	250	69.60	29.80
3	*2412.00	91.10 AV			1.00 H	250	61.30	29.80
4	3216.00	44.60 PK	74.00	-29.40	1.00 H	75	12.60	32.00
4	3216.00	39.30 AV	54.00	-14.70	1.00 H	75	7.30	32.00
5	4824.00	41.30 PK	74.00	-32.70	1.11 H	23	6.20	35.10
5	4824.00	30.10 AV	54.00	-23.90	1.11 H	23	-5.00	35.10
6	7236.00	46.60 PK	74.00	-27.40	1.22 H	105	6.10	40.50
6	7236.00	36.20 AV	54.00	-17.80	1.22 H	105	-4.30	40.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	44.20 PK	74.00	-29.80	1.54 V	176	16.90	27.40
1	1608.00	41.30 AV	54.00	-12.70	1.54 V	176	14.00	27.40
2	2390.00	64.90 PK	74.00	-9.10	1.26 V	277	31.20	33.70
2	2390.00	52.60 AV	54.00	-1.40	1.26 V	277	18.90	33.70
3	*2412.00	111.90 PK			1.26 V	277	82.10	29.80
3	*2412.00	102.80 AV			1.26 V	277	73.00	29.80
4	3216.00	44.80 PK	74.00	-29.20	1.00 V	244	12.80	32.00
4	3216.00	39.70 AV	54.00	-14.30	1.00 V	244	7.70	32.00
5	4824.00	42.70 PK	74.00	-31.30	1.22 V	320	7.60	35.10
5	4824.00	31.00 AV	54.00	-23.00	1.22 V	320	-4.10	35.10
6	7236.00	51.50 PK	74.00	-22.50	1.55 V	321	11.00	40.50
6	7236.00	37.70 AV	54.00	-16.30	1.55 V	321	-2.80	40.50

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency



EUT	IEEE802.11g Wireless Router	MODEL	DI-624
MODE	Channel 6	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa	TESTED BY	Wen Yu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.60	39.20 PK	74.00	-34.80	1.09 H	232	11.80	27.40
1	1624.60	35.60 AV	54.00	-18.40	1.09 H	232	8.20	27.40
2	*2437.00	103.00 PK			1.30 H	305	73.10	29.90
2	*2437.00	93.90 AV			1.30 H	305	64.00	29.90
3	3249.30	44.70 PK	74.00	-29.30	1.02 H	87	12.60	32.10
3	3249.30	39.40 AV	54.00	-14.60	1.02 H	87	7.30	32.10
4	4874.00	41.60 PK	74.00	-32.40	1.10 H	32	6.30	35.30
4	4874.00	30.50 AV	54.00	-23.50	1.10 H	32	-4.80	35.30
5	7311.00	47.20 PK	74.00	-26.80	1.18 H	93	6.50	40.70
5	7311.00	36.20 AV	54.00	-17.80	1.18 H	93	-4.50	40.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.60	45.00 PK	74.00	-29.00	1.55 V	180	17.60	27.40
1	1624.60	42.40 AV	54.00	-11.60	1.55 V	180	15.00	27.40
2	*2437.00	114.90 PK			1.00 V	322	85.00	29.90
2	*2437.00	106.00 AV			1.00 V	322	76.10	29.90
3	3249.30	46.60 PK	74.00	-27.40	1.02 V	256	14.50	32.10
3	3249.30	40.20 AV	54.00	-13.80	1.02 V	256	8.10	32.10
4	4874.00	43.00 PK	74.00	-31.00	1.21 V	319	7.70	35.30
4	4874.00	31.30 AV	54.00	-22.70	1.21 V	319	-4.00	35.30
5	7311.00	52.10 PK	74.00	-21.90	1.45 V	310	11.40	40.70
5	7311.00	38.10 AV	54.00	-15.90	1.45 V	310	-2.60	40.70

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. " * " : Fundamental frequency



EUT	IEEE802.11g Wireless Router	MODEL	DI-624
MODE	Channel 11	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa	TESTED BY	Wen Yu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.30	39.60 PK	74.00	-34.40	1.05 H	233	12.20	27.40
1	1641.30	33.90 AV	54.00	-20.10	1.05 H	233	6.50	27.40
2	*2462.00	102.70 PK			1.38 H	319	72.70	30.00
2	*2462.00	93.60 AV			1.38 H	319	63.60	30.00
3	2483.50	55.50 PK	74.00	-18.50	1.38 H	319	25.40	30.10
3	2483.50	42.20 AV	54.00	-11.80	1.38 H	319	12.10	30.10
4	3282.60	44.20 PK	74.00	-29.80	1.35 H	109	12.10	32.20
4	3282.60	38.80 AV	54.00	-15.20	1.35 H	109	6.70	32.20
5	4924.00	41.90 PK	74.00	-32.10	1.12 H	32	6.30	35.50
5	4924.00	30.70 AV	54.00	-23.30	1.12 H	32	-4.90	35.50
6	7386.00	47.10 PK	74.00	-26.90	1.23 H	108	6.30	40.80
6	7386.00	36.80 AV	54.00	-17.20	1.23 H	108	-4.00	40.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.30	44.40 PK	74.00	-29.60	1.56 V	180	17.00	27.40
1	1641.30	41.70 AV	54.00	-12.30	1.56 V	180	14.30	27.40
2	*2462.00	112.80 PK			1.26 V	277	82.80	30.00
2	*2462.00	104.30 AV			1.26 V	277	74.30	30.00
3	2483.50	65.60 PK	74.00	-8.40	1.26 V	277	35.50	30.10
3	2483.50	52.90 AV	54.00	-1.10	1.26 V	277	22.80	30.10
4	3282.60	45.10 PK	74.00	-28.90	1.35 V	46	13.00	32.20
4	3282.60	39.40 AV	54.00	-14.60	1.35 V	46	7.30	32.20
5	4924.00	43.40 PK	74.00	-30.60	1.22 V	330	7.80	35.50
5	4924.00	31.60 AV	54.00	-22.40	1.22 V	330	-4.00	35.50
6	7386.00	53.90 PK	74.00	-20.10	1.40 V	301	13.10	40.80
6	7386.00	38.20 AV	54.00	-15.80	1.40 V	301	-2.60	40.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



802.11g Turbo OFDM modulation

EUT	IEEE802.11g Wireless Router	MODEL	DI-624
MODE	Channel 6	FREQUENCY RANGE	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION & BANDWIDTH	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa	TESTED BY	Wen Yu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.60	40.50 PK	74.00	-33.50	1.00 H	230	13.10	27.40
1	1624.60	35.00 AV	54.00	-19.00	1.00 H	230	7.60	27.40
2	2390.00	46.80 PK	74.00	-27.20	1.22 H	298	13.10	33.70
2	2390.00	36.20 AV	54.00	-17.80	1.22 H	298	2.50	33.70
3	*2437.00	97.40 PK			1.22 H	298	67.50	29.90
3	*2437.00	88.90 AV			1.22 H	298	59.00	29.90
4	2483.50	46.40 PK	74.00	-27.60	1.22 H	298	16.30	30.10
4	2483.50	34.30 AV	54.00	-19.70	1.22 H	298	4.20	30.10
5	3249.30	43.20 PK	74.00	-30.80	1.00 H	71	11.10	32.10
5	3249.30	36.70 AV	54.00	-17.30	1.00 H	71	4.60	32.10
6	4874.00	41.60 PK	74.00	-32.40	1.09 H	25	6.30	35.30
6	4874.00	30.50 AV	54.00	-23.50	1.09 H	25	-4.80	35.30
7	7311.00	47.40 PK	74.00	-26.60	1.20 H	105	6.70	40.70
7	7311.00	36.30 AV	54.00	-17.70	1.20 H	105	-4.40	40.70


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.60	43.40 PK	74.00	-30.60	1.00 V	180	16.00	27.40
1	1624.60	39.90 AV	54.00	-14.10	1.00 V	180	12.50	27.40
2	2390.00	59.00 PK	74.00	-15.00	1.30 V	287	25.30	33.70
2	2390.00	48.20 AV	54.00	-5.80	1.30 V	287	14.50	33.70
3	*2437.00	109.50 PK			1.30 V	287	79.60	29.90
3	*2437.00	100.90 AV			1.30 V	287	71.00	29.90
4	2483.50	58.50 PK	74.00	-15.50	1.30 V	287	28.40	30.10
4	2483.50	46.30 AV	54.00	-7.70	1.30 V	287	16.20	30.10
5	3249.30	45.90 PK	74.00	-28.10	1.00 V	239	13.80	32.10
5	3249.30	40.20 AV	54.00	-13.80	1.00 V	239	8.10	32.10
6	4874.00	43.10 PK	74.00	-30.90	1.22 V	311	7.80	35.30
6	4874.00	31.40 AV	54.00	-22.60	1.22 V	311	-3.90	35.30
7	7311.00	52.20 PK	74.00	-21.80	1.40 V	321	11.50	40.70
7	7311.00	38.30 AV	54.00	-15.70	1.40 V	321	-2.40	40.70

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.6 TEST RESULTS –DSSS


802.11b DSSS modulation

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin


CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.79	0.5	PASS
6	2437	12.24	0.5	PASS
11	2462	11.79	0.5	PASS



CH1




CH6





CH11





4.3.7 TEST RESULTS-OFDM


802.11g Normal OFDM modulation

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin


CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.38	0.5	PASS
6	2437	16.38	0.5	PASS
11	2462	16.47	0.5	PASS



CH1




CH6





CH11




**802.11g Turbo OFDM modulation**

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
6	2437	31.32	0.5	PASS



CH6





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005
Agilent SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2005
TEKTRONIX OSCILLOSCOPE	TDS380	B016335	Jun. 22, 2006
NARDA DETECTOR	4503A	FSCM99899	NA


NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the peak response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

4.4.4 TEST SETUP



4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5



4.4.6 TEST RESULTS – DSSS

802.11b DSSS modulation

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	97.724	19.90	30	PASS
6	2437	91.201	19.60	30	PASS
11	2462	100.00	20.00	30	PASS



4.4.7 TEST RESULTS –OFDM

802.11g Normal OFDM modulation

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	125.893	21.00	30	PASS
6	2437	169.824	22.30	30	PASS
11	2462	117.490	20.70	30	PASS

802.11g Turbo OFDM modulation

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
6	2437	138.038	21.40	30	PASS



4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005


NOTE:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITIONS

Same as 4.3.5



4.5.6 TEST RESULTS –DSSS


802.11b DSSS modulation

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-1.02	8	PASS
6	2437	-0.78	8	PASS
11	2462	-0.32	8	PASS



CH1




CH6





CH11





4.5.7 TEST RESULTS –OFDM


802.11g Normal OFDM modulation

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin


CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	0.75	8	PASS
6	2437	3.95	8	PASS
11	2462	1.39	8	PASS




CH1



CH6



CH11




**802.11g Turbo OFDM modulation**

EUT	IEEE802.11g Wireless Router		
MODEL	DI-624	ENVIRONMENTAL CONDITIONS	20 deg. C, 60%RH, 971 hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TESTED BY	Moris Lin

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
6	2437	3.01	8	PASS



CH6





4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 1MHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

NOTE:

- 1.The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set RBW spectrum analyzer to 1 MHz and set VBW spectrum analyzer to 10 Hz with suitable frequency span including 1 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 EUT OPERATING CONDITION

Same as Item 4.3.5



4.6.5 TEST RESULTS – DSSS

The spectrum plots are attached on the following page. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

NOTE (Peak):

The band edge emission plot of DSSS technique on the following first page show 57.33dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 113.5dBuV/m, so the maximum field strength in restrict band is $113.5-57.33=56.17$ dBuV/m which is under 74 dBuV/m limit.

The band edge emission plot of DSSS technique on the following first page shows 57.42dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 114.8dBuV/m, so the maximum field strength in restrict band is $114.8-57.42=57.38$ dBuV/m which is under 74 dBuV/m limit.


NOTE (Average):

The band edge emission plot of DSSS technique on the following second page shows 61.04dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 106.3dBuV/m, so the maximum field strength in restrict band is $106.3-61.04=45.26$ dBuV/m which is under 54 dBuV/m limit.


The band edge emission plot of DSSS technique on the following second page shows 62.83dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 107.5dBuV/m, so the maximum field strength in restrict band is $107.5-62.83=44.67$ dBuV/m which is under 54 dBuV/m limit.




CH1




CH11



CH1




CH11






CH1



CH11





4.6.6 TEST RESULTS –OFDM

The spectrum plots are attached on the following page. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

NOTE (Peak):

The band edge emission plot of OFDM technique on the following first page show 46.99dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 111.9dBuV/m, so the maximum field strength in restrict band is $111.9-46.99=64.91$ dBuV/m which is under 74 dBuV/m limit.

The band edge emission plot of OFDM technique on the following first page shows 47.21dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 112.8dBuV/m, so the maximum field strength in restrict band is $112.8-47.21=65.59$ dBuV/m which is under 74 dBuV/m limit.


NOTE (Average):

The band edge emission plot of OFDM technique on the following second page shows 50.19dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 102.8dBuV/m, so the maximum field strength in restrict band is $102.8-50.19=52.61$ dBuV/m which is under 54 dBuV/m limit.


The band edge emission plot of OFDM technique on the following second page shows 51.37dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 104.3dBuV/m, so the maximum field strength in restrict band is $104.3-51.37=52.93$ dBuV/m which is under 54 dBuV/m limit.



CH1




CH11






CH1




CH11






CH1



CH11






802.11g Turbo OFDM modulation


The spectrum plots are attached on the following page. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).



CH6




CH6






CH6




CH6





CH6





4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Dipole Antenna with Reverse SMA connector. The maximum Gain of the antenna is 1.8dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



RADIATED EMISSION TEST





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA, CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB, GOST-ASIA (MOU)
Russia	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232
Fax: 886-3-3185050

Email: service@adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.