



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	D-Link Corporation
Applicant Address	No.289, Sinhu 3rd., Neihu District Taipei City 114 , Taiwan , R.O.C.
FCC ID	KA2DIR455A1
Manufacturer's company	Quanta Computer Inc.
Manufacturer Address	211, Wen Hwa 2nd Road, Kuei Shan Hsiang Tao Yuan Shien, Taiwan

Product Name	HSDPA 3.5G Mobile Communication Router
Brand Name	D-Link
Model Name	DIR-455
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Aug. 17, 2009
Final Test Date	Dec. 24, 2009
Submission Type	Class II Change
Class II Change	Please refer to section 3.7



### Statement

**Test result included is only for the 802.11b/g part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Testing Laboratory  
1190

## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	4
3.4. Table for Carrier Frequencies .....	4
3.5. Table for Test Modes .....	5
3.6. Table for Testing Locations.....	6
3.7. Table for Multiple Listing & Existing Change .....	6
3.8. Table for Supporting Units .....	6
3.9. Table for Parameters of Test Software Setting .....	7
3.10. Test Configurations .....	8
<b>4. TEST RESULT .....</b>	<b>11</b>
4.1. AC Power Line Conducted Emissions Measurement.....	11
4.2. Maximum Conducted Output Power Measurement.....	15
4.3. Power Spectral Density Measurement .....	20
4.4. 6dB Spectrum Bandwidth Measurement .....	25
4.5. Radiated Emissions Measurement .....	30
4.6. Band Edge Emissions Measurement .....	48
4.7. Antenna Requirements .....	53
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>54</b>
<b>6. TEST LOCATION.....</b>	<b>56</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>57</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT.....</b>	<b>A1 ~ A29</b>
<b>APPENDIX B. TEST PHOTOS.....</b>	<b>B1 ~ B6</b>
<b>APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>C1 ~C3</b>
<b>APPENDIX D. CO-LOCATION REPORT.....</b>	<b>D1 ~ D3</b>






## 1. CERTIFICATE OF COMPLIANCE

Product Name : HSDPA 3.5G Mobile Communication Router  
Brand Name : D-Link  
Model Name : DIR-455  
Applicant : D-Link Corporation  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Aug. 17, 2009 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads "Jordan Hsiao" followed by the date "2009.12.28". The signature is written over a horizontal line.

Jordan Hsiao

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	12.72 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	6.76 dB
4.3	15.247(e)	Power Spectral Density	Complies	12.16 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.13 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.08 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

Items	Description
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 14.76 MHz ; 11g: 16.40 MHz
Conducted Output Power	11b: 23.24 dBm ; 11g: 21.63 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Note: The 3G function has been built-in in this EUT, please refer to Section 3.5 Note 1 for further information.


#### 3.2. Accessories

Power	Brand	Model	Rating
AC Adapter	D-Link	CG2412-B	Input: 100-120VAC, 50-60Hz, 0.5A Output: 12VDC, 2A

### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	M.gear	SSR-92615	PIFA Antenna	NA	2.83

Ant. 1: TX/RX



### 3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	1
Maximum Peak Conducted Output Power	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Power Spectral Density 6dB Spectrum Bandwidth	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Radiated Emissions 9kHz~1GHz	Normal Link	Auto	-	1
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	11b/BPSK	1 Mbps	1/11	1
	11g/BPSK	6 Mbps	1/11	1

Note 1:

The EUT could be applied with one 3G PCI Module; therefore Maximum Permissible Exposure (please refer to Appendix C) and Co-location (please refer to Appendix D) tests are added for simultaneously transmit between wireless LAN and 3G card function.

Interface	Brand	Model	FCC ID
3G PCI Module	Royaltek	GLE	HFS-GLE

From above 3G PCI Module, Model number: GLE was selected for testing.

Note 2:

The test modes were illustrated as below.

Test Mode 1: GSM850 Link Mode + LAN + Wireless + Phone

Test Mode 2: WCDMA Link Mode (Band V) + LAN + Wireless + Phone

Test Mode 3: LAN + Wireless + WAN

<For Conducted Emissions Test>:

Due to the Mode 1 generated the worst test result, so it was recorded in this report.

<For Radiated Emissions Test>:

Due to the Mode 1 generated the worst test result, so it was recorded in this report.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	480872	IC 4086	-
CO04-HY	Conduction	Hwa Ya	480872	IC 4086	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Multiple Listing & Existing Change

This product is an extension of original one reported under Sporton project number: FR980321

Below is the table for the change of the product with respect to the original one.

Modifications	Description	Performance Checking
Change 3G Antenna	The 3G antenna used in this device was changed from Internal fixed antenna to external Dipole antenna.	Conducted Emissions Radiated Emissions Below 1GHz

### 3.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	E2KWM3945ABG
Notebook	DELL	1200	E2K4965AGNM
Notebook	DELL	PP25L	E2K4965AGNM
CMU200	ROHDE&SCHWARZ	108087	DoC
PHONE	SANYOZ	TEL217	DoC
HUB	Laneed	LD-LSW16C/AT	DoC

### 3.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11b/g


Test Software Version	IE		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	17	18	21
IEEE 802.11g	16	17	19

The "IE" was executed the test program to control the EUT continuously receive and transmit RF signal.


### 3.10. Test Configurations

#### 3.10.1. Radiation Emissions Test Configuration


Test Configuration: 9kHz~1GHz (WiFi) / Test Mode: Mode 1



Test Configuration: Above 1GHz (WiFi)




Above 1GHz (Co-location)



### 3.10.2. AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 1



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	56%
Test Engineer	Beck Wu	Phase	Line
Configuration	Normal Link / Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15080	49.79	-16.16	65.96	49.52	0.07	0.20	QP
2	0.15080	31.26	-24.69	55.96	30.99	0.07	0.20	AVERAGE
3	0.17584	45.96	-18.72	64.68	45.70	0.06	0.20	QP
4	0.17584	30.55	-24.13	54.68	30.29	0.06	0.20	AVERAGE
5	0.21620	41.95	-21.02	62.96	41.70	0.05	0.20	QP
6	0.21620	27.16	-25.81	52.96	26.91	0.05	0.20	AVERAGE
7	0.25751	22.48	-29.03	51.51	22.24	0.04	0.20	AVERAGE
8	0.25751	37.58	-23.93	61.51	37.34	0.04	0.20	QP
9	0.49673	23.61	-22.45	46.05	23.40	0.03	0.18	AVERAGE
10	0.49673	32.90	-23.16	56.05	32.69	0.03	0.18	QP
11	11.621	34.64	-25.36	60.00	33.81	0.43	0.40	QP
12	11.621	32.91	-17.09	50.00	32.08	0.43	0.40	AVERAGE

Temperature	23°C	Humidity	56%
Test Engineer	Beck Wu	Phase	Neutral
Configuration	Normal Link / Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15000	50.09	-15.91	66.00	49.78	0.11	0.20	QP
2	0.15000	33.14	-22.86	56.00	32.83	0.11	0.20	AVERAGE
3	0.17961	46.22	-18.28	64.50	45.93	0.09	0.20	QP
4	0.17961	32.72	-21.78	54.50	32.43	0.09	0.20	AVERAGE
5	0.22201	40.74	-22.00	62.74	40.46	0.08	0.20	QP
6	0.22201	26.53	-26.21	52.74	26.25	0.08	0.20	AVERAGE
7	0.24945	38.53	-23.25	61.78	38.25	0.08	0.20	QP
8	0.24945	26.79	-24.99	51.78	26.51	0.08	0.20	AVERAGE
9	0.49411	30.62	-25.48	56.10	30.37	0.07	0.18	QP
10	0.49411	21.22	-24.88	46.10	20.97	0.07	0.18	AVERAGE
11	10.601	37.28	-12.72	50.00	36.47	0.42	0.40	AVERAGE
12	10.601	38.23	-21.77	60.00	37.42	0.42	0.40	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	RMS
Trace	Max Hold
Sweep Time	2.5ms

### 4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

<b>Temperature</b>	24°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Jacky Ho	<b>Configurations</b>	802.11b/g

##### Configuration IEEE 802.11b Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.81	30.00	Complies
6	2437 MHz	22.09	30.00	Complies
11	2462 MHz	23.24	30.00	Complies

##### Configuration IEEE 802.11g Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	20.83	30.00	Complies
6	2437 MHz	20.95	30.00	Complies
11	2462 MHz	21.63	30.00	Complies







### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

#### 4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

<b>Temperature</b>	24°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Jacky Ho	<b>Configurations</b>	802.11b/g


##### Configuration IEEE 802.11b Ant. 1

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-5.58	8.00	Complies
6	2437 MHz	-5.30	8.00	Complies
11	2462 MHz	-4.16	8.00	Complies

##### Configuration IEEE 802.11g Ant. 1


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-8.37	8.00	Complies
6	2437 MHz	-8.21	8.00	Complies
11	2462 MHz	-7.45	8.00	Complies

### Power Density Plot on Configuration IEEE 802.11b Ant. 1 / 2412 MHz




Date: 30.AUG.2009 12:16:17

### Power Density Plot on Configuration IEEE 802.11b Ant. 1 / 2437 MHz




Date: 30.AUG.2009 12:14:05

### Power Density Plot on Configuration IEEE 802.11b Ant. 1 / 2462 MHz




Date: 30.AUG.2009 12:11:41

### Power Density Plot on Configuration IEEE 802.11g Ant. 1 / 2412 MHz




Date: 30.AUG.2009 12:04:22

**Power Density Plot on Configuration IEEE 802.11g Ant. 1 / 2437 MHz**



Date: 30.AUG.2009 12:06:50

**Power Density Plot on Configuration IEEE 802.11g Ant. 1 / 2462 MHz**



Date: 30.AUG.2009 12:09:02

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	100ms

##### 4.4.3. Test Procedures

3. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
4. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
5. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout



#### 4.4.5. Test Deviation

There is no deviation with the original standard.

#### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

<b>Temperature</b>	24°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Jacky Ho	<b>Configurations</b>	802.11b/g


##### Configuration IEEE 802.11b Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.16	14.72	500	Complies
6	2437 MHz	12.20	14.68	500	Complies
11	2462 MHz	12.20	14.76	500	Complies

##### Configuration IEEE 802.11g Ant. 1


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.48	16.40	500	Complies
6	2437 MHz	16.44	16.36	500	Complies
11	2462 MHz	16.44	16.36	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. 1 / 2412 MHz




Date: 30.AUG.2009 12:14:50

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. 1 / 2437 MHz




Date: 30.AUG.2009 12:12:37

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. 1 / 2462 MHz




Date: 30.AUG.2009 12:10:13

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. 1 / 2412 MHz




Date: 30.AUG.2009 12:02:55

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. 1 / 2437 MHz



Date: 30.AUG.2009 12:05:21

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. 1 / 2462 MHz



Date: 30.AUG.2009 12:07:34

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Allen Liu		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	Normal Link / Mode 1

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	57.16	29.33	40.00	-10.67	49.00	0.80	27.77	7.30	0	100	Peak	HORIZONTAL
2	97.90	30.65	43.50	-12.85	46.51	1.16	27.61	10.59	0	100	Peak	HORIZONTAL
3	107.60	34.34	43.50	-9.16	49.12	1.20	27.56	11.58	0	100	Peak	HORIZONTAL
4	181.32	29.93	43.50	-13.57	42.58	1.60	27.19	12.94	0	100	Peak	HORIZONTAL
5	375.32	33.84	46.00	-12.16	43.62	2.25	27.43	15.40	0	100	Peak	HORIZONTAL
6 p	934.04	37.05	46.00	-8.95	39.92	3.60	27.26	20.79	0	100	Peak	HORIZONTAL

**Vertical**



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	!	32.91	35.63	40.00	-4.37	45.78	0.50	27.80	17.15	0	400 Peak	VERTICAL
2	!	55.22	34.57	40.00	-5.43	53.90	0.80	27.78	7.65	0	400 Peak	VERTICAL
3	p	69.77	36.44	40.00	-3.56	56.72	0.80	27.72	6.64	0	400 Peak	VERTICAL
4		174.53	34.37	43.50	-9.13	46.91	1.57	27.23	13.12	0	400 Peak	VERTICAL
5		375.32	32.58	46.00	-13.42	42.36	2.25	27.43	15.40	0	400 Peak	VERTICAL
6		862.26	35.33	46.00	-10.67	39.11	3.45	27.47	20.24	0	400 Peak	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)


Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	802.11b CH 1 Ant. 1

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBUV	dB/m	dB	dB		cm	deg	
1 @	4824.200	66.09	-7.91	74.00	65.89	32.46	3.00	35.26	PEAK	187	52	HORIZONTAL
2 @	4826.100	53.58	-0.42	54.00	53.38	32.46	3.00	35.26	AVERAGE	187	52	HORIZONTAL


**Vertical**



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4824.200	63.65	-10.35	74.00	63.45	32.46	3.00	35.26	PEAK	100	172	VERTICAL
2 @	4826.100	51.44	-2.56	54.00	51.24	32.46	3.00	35.26	AVERAGE	100	172	VERTICAL


Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	802.11b CH 6 Ant. 1

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4872.440	53.87	-0.13	54.00	53.44	32.56	3.01	35.15	AVERAGE	190	52	HORIZONTAL
2 @	4874.080	65.94	-8.06	74.00	65.52	32.56	3.01	35.15	PEAK	190	52	HORIZONTAL


**Vertical**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4872.320	52.75	-1.25	54.00	52.32	32.56	3.01	35.15	AVERAGE	101	170	VERTICAL
2 @	4874.160	64.55	-9.45	74.00	64.12	32.56	3.01	35.15	PEAK	101	170	VERTICAL


Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	802.11b CH 11 Ant. 1

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4922.300	53.15	-0.85	54.00	52.49	32.66	3.02	35.03	AVERAGE	193	104	HORIZONTAL
2 @	4924.000	65.44	-8.56	74.00	64.78	32.66	3.02	35.03	PEAK	193	104	HORIZONTAL


**Vertical**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4922.400	52.01	-1.99	54.00	51.36	32.66	3.02	35.03	AVERAGE	100	172	VERTICAL
2 @	4924.000	63.70	-10.30	74.00	63.04	32.66	3.02	35.03	PEAK	100	172	VERTICAL


Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	802.11g CH 1 Ant. 1

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4822.700	69.11	-4.89	74.00	68.91	32.46	3.00	35.26	PEAK	186	50	HORIZONTAL
2 @	4826.100	53.24	-0.76	54.00	53.05	32.46	3.00	35.26	AVERAGE	186	50	HORIZONTAL


**Vertical**



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4826.000	51.88	-2.12	54.00	51.68	32.46	3.00	35.26	AVERAGE	100	173	VERTICAL
2 @	4828.300	67.33	-6.67	74.00	67.13	32.46	3.00	35.26	PEAK	100	173	VERTICAL


Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	802.11g CH 6 Ant. 1

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Antenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4875.100	53.40	-0.60	54.00	52.97	32.56	3.01	35.15	AVERAGE	190	52	HORIZONTAL
2 @	4876.400	68.09	-5.91	74.00	67.66	32.56	3.01	35.15	PEAK	190	52	HORIZONTAL


**Vertical**



	Over	Limit	Read	Antenna	Cable	Preamp		Ant	Table	
1 @	Level	Limit	Level	Factor	Loss	Factor	Remark	Pos	Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1 @	4874.100	66.02	-7.98	74.00	65.60	32.56	3.01 35.15	100	203	VERTICAL
2 @	4875.000	51.25	-2.75	54.00	50.83	32.56	3.01 35.15	100	52	VERTICAL


Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	802.11g CH 11 Ant. 1

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	4923.985	59.97	-14.03	74.00	59.31	32.66	3.02	35.03	PEAK	100	300	HORIZONTAL
2 @	4924.010	44.39	-9.61	54.00	43.73	32.66	3.02	35.03	AVERAGE	100	300	HORIZONTAL

**Vertical**



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	4923.991	50.27	-3.73	54.00	49.61	32.66	3.02	35.03	AVERAGE	100	171	VERTICAL
2 @	4924.001	66.00	-8.00	74.00	65.34	32.66	3.02	35.03	PEAK	100	171	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Band Edge Emissions Measurement

### 4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1 MHz / 1MHz for Peak

### 4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

### 4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.6.5. Test Deviation

There is no deviation with the original standard.

### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	802.11b CH 1, 6, 11 Ant. 1
Test Date	Aug. 26, 2009		

## Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2387.400	62.04	-11.96	74.00	32.13	27.87	2.04	0.00	PEAK	121	260	VERTICAL
2 @	2390.000	51.06	-2.94	54.00	21.14	27.87	2.05	0.00	AVERAGE	121	260	VERTICAL
3 @	2414.400	105.10			75.21	27.84	2.05	0.00	AVERAGE	121	260	VERTICAL
4 @	2415.000	112.70			82.81	27.84	2.05	0.00	PEAK	121	260	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

## Channel 6

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2387.200	60.58	-13.42	74.00	30.67	27.87	2.04	0.00	PEAK	115	260	VERTICAL
2 @	2390.000	48.90	-5.10	54.00	18.98	27.87	2.05	0.00	AVERAGE	115	260	VERTICAL
3 @	2433.800	112.38			82.50	27.81	2.07	0.00	PEAK	115	260	VERTICAL
4 @	2434.600	104.69			74.81	27.81	2.07	0.00	AVERAGE	115	260	VERTICAL
5 @	2483.500	46.96	-7.04	54.00	17.14	27.73	2.10	0.00	AVERAGE	115	260	VERTICAL
6 @	2483.500	58.16	-15.84	74.00	28.34	27.73	2.10	0.00	PEAK	115	260	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

## Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2463.200	111.88			82.04	27.76	2.08	0.00	PEAK	100	267	HORIZONTAL
2 @	2464.400	104.27			74.44	27.76	2.08	0.00	AVERAGE	100	267	HORIZONTAL
3 @	2487.300	47.92	-6.08	54.00	18.10	27.73	2.10	0.00	AVERAGE	100	267	HORIZONTAL
4 @	2488.100	60.27	-13.73	74.00	30.47	27.70	2.10	0.00	PEAK	100	267	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	23°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	802.11g CH 1, 6, 11 Ant. 1
Test Date	Aug. 26, 2009		

**Channel 1**

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2388.400	72.46	-1.54	74.00	42.56	27.87	2.04	0.00	PEAK	100	135	HORIZONTAL
2 @	2390.000	53.92	-0.08	54.00	24.00	27.87	2.05	0.00	AVERAGE	100	135	HORIZONTAL
3 @	2407.200	101.71			71.81	27.84	2.05	0.00	AVERAGE	100	135	HORIZONTAL
4 @	2414.000	112.52			82.63	27.84	2.05	0.00	PEAK	100	135	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1	2388.600	59.91	-14.09	74.00	30.01	27.87	2.04	0.00	PEAK	100	137	HORIZONTAL
2 @	2390.000	48.79	-5.21	54.00	18.87	27.87	2.05	0.00	AVERAGE	100	137	HORIZONTAL
3 @	2431.400	112.00			82.12	27.81	2.07	0.00	PEAK	100	137	HORIZONTAL
4 @	2432.200	101.35			71.47	27.81	2.07	0.00	AVERAGE	100	137	HORIZONTAL
5	2483.700	57.39	-16.61	74.00	27.56	27.73	2.10	0.00	PEAK	100	137	HORIZONTAL
6 @	2484.500	45.75	-8.25	54.00	15.93	27.73	2.10	0.00	AVERAGE	100	137	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

**Channel 11**

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg	
1 @	2463.800	111.84			82.00	27.76	2.08	0.00	PEAK	100	268	HORIZONTAL
2 @	2465.600	100.57			70.73	27.76	2.08	0.00	AVERAGE	100	268	HORIZONTAL
3 @	2483.500	53.11	-0.89	54.00	23.29	27.73	2.10	0.00	AVERAGE	100	268	HORIZONTAL
4 @	2483.500	71.92	-2.08	74.00	42.09	27.73	2.10	0.00	PEAK	100	268	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11b Ant. 1 / 2412 MHz




Date: 30.AUG.2009 12:16:25

High Band Edge Plot on Configuration IEEE 802.11b Ant. 1 / 2462 MHz




Date: 30.AUG.2009 12:11:48

### Low Band Edge Plot on Configuration IEEE 802.11g Ant. 1 / 2412 MHz



Date: 30.AUG.2009 12:04:30

### High Band Edge Plot on Configuration IEEE 802.11g Ant. 1 / 2462 MHz



Date: 30.AUG.2009 12:09:09

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Apr. 15, 2009	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 23, 2009	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2009	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2009	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz – 30MHz	Jun. 11, 2009	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 07, 2009	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 23, 2009	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jul. 21, 2009	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Apr. 06, 2009*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100305	9 kHz - 40 GHz	Feb. 03, 2009	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 28, 2008*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 18, 2009	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 28, 2009	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.16, 2009	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 05, 2009	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 05, 2009	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSU26.5	100015	20Hz ~ 26.5GHz	Oct. 28, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 31, 2009	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100666	DC ~ 30GHz	Aug. 05, 2009	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 31, 2009	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jul. 12, 2009*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2009	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Aug. 06, 2009	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2008	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2008	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Feb. 13, 2009	Conducted (TH01-HY)



---

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 25, 2009	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Note: \*Calibration Interval of instruments listed above is two year.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**

**EMC & Wireless Communications Laboratory**

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection : Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 10, 2007

P1, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.