



FCC TEST REPORT

REPORT NO.: RF111124E01

MODEL NO.: DIR-600, GO-RT-N150

FCC ID: KA2IR600D1

RECEIVED: Nov. 24, 2011

TESTED: Dec. 05 to 09, 2011

ISSUED: Jan. 18, 2012

APPLICANT: D-Link Corporation

ADDRESS: No.289, Sinhu 3rd Rd., Neihu District,
Taipei City 114, Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 83 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





A D T

Table of Contents

RELEASE CONTROL RECORD.....	4
1. CERTIFICATION.....	5
2. SUMMARY OF TEST RESULTS.....	6
2.1 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT.....	8
3.2 DESCRIPTION OF TEST MODES.....	11
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	12
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
3.4 DESCRIPTION OF SUPPORT UNITS.....	16
3.5 CONFIGURATION OF SYSTEM UNDER TEST	17
4. TEST TYPES AND RESULTS.....	18
4.1 CONDUCTED EMISSION MEASUREMENT	18
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	18
4.1.2 TEST INSTRUMENTS	18
4.1.3 TEST PROCEDURES.....	19
4.1.4 DEVIATION FROM TEST STANDARD	19
4.1.5 TEST SETUP	20
4.1.6 EUT OPERATING CONDITIONS.....	20
4.1.7 TEST RESULTS(MODE A).....	21
4.1.8 TEST RESULTS(MODE B)	23
4.2 RADIATED EMISSION MEASUREMENT	25
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	25
4.2.2 TEST INSTRUMENTS	26
4.2.3 TEST PROCEDURES.....	28
4.2.4 DEVIATION FROM TEST STANDARD	28
4.2.5 TEST SETUP	29
4.2.6 EUT OPERATING CONDITIONS.....	29
4.2.7 TEST RESULTS.....	30
4.3 6dB BANDWIDTH MEASUREMENT	60
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	60
4.3.2 TEST INSTRUMENTS	60
4.3.3 TEST PROCEDURE	60
4.3.4 DEVIATION FROM TEST STANDARD	60
4.3.5 TEST SETUP	60
4.3.6 EUT OPERATING CONDITIONS.....	60
4.3.7 TEST RESULTS.....	61



A D T

4.4	MAXIMUM PEAK OUTPUT POWER	65
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	65
4.4.2	INSTRUMENTS	65
4.4.3	TEST PROCEDURES.....	65
4.4.4	DEVIATION FROM TEST STANDARD	65
4.4.5	TEST SETUP	65
4.4.6	EUT OPERATING CONDITIONS.....	65
4.4.7	TEST RESULTS.....	66
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	68
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	68
4.5.2	TEST INSTRUMENTS	68
4.5.3	TEST PROCEDURE	68
4.5.4	DEVIATION FROM TEST STANDARD	68
4.5.5	TEST SETUP	68
4.5.6	EUT OPERATING CONDITION	68
4.5.7	TEST RESULTS.....	69
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	73
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT	73
4.6.2	TEST INSTRUMENTS	73
4.6.3	TEST PROCEDURE	73
4.6.4	DEVIATION FROM TEST STANDARD	73
4.6.5	EUT OPERATING CONDITION	73
4.6.6	TEST RESULTS.....	73
5.	INFORMATION ON THE TESTING LABORATORIES	82
6.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	83



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF111124E01	Original release	Jan. 18, 2012



1. CERTIFICATION

PRODUCT: WIRELESS N 150 HOME ROUTER
BRAND NAME: D-Link
MODEL NO.: DIR-600, GO-RT-N150
TEST SAMPLE: MASS-PRODUCTION
APPLICANT: D-Link Corporation
TESTED: Dec. 05 to 09, 2011
STANDARDS: FCC Part 15, Subpart C (Section 15.247)
ANSI C63.4-2003
ANSI C63.10-2009

The above equipment (Model: DIR-600) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Elsie Hsu , **DATE:** Jan. 18, 2012
(Elsie Hsu, Specialist)

APPROVED BY : May Chen , **DATE:** Jan. 18, 2012
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -3.06dB at 0.408MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -0.8dB at 2390.0 MHz and 2483.50 MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Conducted Out-Band Emission Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.



A D T

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.45 dB
Radiated emissions (30MHz-1GHz)	3.81 dB
Radiated emissions (1GHz -18GHz)	2.49 dB
Radiated emissions (18GHz -40GHz)	2.70 dB



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	WIRELESS N 150 HOME ROUTER
MODEL NO.	DIR-600, GO-RT-N150
FCC ID	KA2IR600D1
POWER SUPPLY	DC 5V from power adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: up to 11Mbps 802.11g: up to 54Mbps 802.11n (20MHz, 800ns GI): up to 65Mbps 802.11n (40MHz, 800ns GI): up to 135Mbps 802.11n (20MHz, 400ns GI): up to 72.2Mbps 802.11n (40MHz, 400ns GI): up to 150Mbps
OPERATING FREQUENCY	2.412 ~ 2.462GHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz)
MAXIMUM OUTPUT POWER	802.11b: 154.9.0mW 802.11g: 263.0mW 802.11n (20MHz): 257.0mW 802.11n (40MHz): 166.0mW
ANTENNA TYPE	Please see NOTE
DATA CABLE	NA
I/O PORTS	INTERNET port x 1 LAN(Ethernet (10, 100Mbps)) port x 4
ASSOCIATED DEVICES	Adapter x 1

NOTE:

1. The EUT is a 2.4GHz WLAN device.
2. The EUT has two model names which are identical to each other in all aspects except for the following table:

Brand name	Model No.	Difference
D-Link	DIR-600	For marketing to separate difference models
	GO-RT-N150	

From the above models, model: **DIR-600** was selected as representative model for the test and their data were recorded in this report.

3. There are four antennas provided to this EUT, please refer to the following table:

Antenna	Manufacture	Model name	Antenna Type	Peak Gain (Included Cable loss) (dBi)	Connector Type
1	SHENZHEN HONGLIN COMMUNICATION TECHNOLOGY Co., LTD	G070-310023-A	Dipole	4.26	NA
2	MAG. LAYERS SCIENTIFIC-TECHNICS CO., LTD	EDA-8709-2G4C 1-A90	Dipole	1.96	NA
3	SHENZHEN HONGLIN COMMUNICATION TECHNOLOGY Co., LTD	G070-310027-A	Dipole	2.19	NA
4	MAG. LAYERS SCIENTIFIC-TECHNICS CO., LTD	EDA-1713-2G4C 1-A24	Dipole	3.95	NA

From the above antennas, **Antenna 1** was selected as representative model for the test and its data was recorded in this report.

4. The EUT must be supplied with a power adapter and following two different models could be chosen as following table:

No	Manufacture	Brand	Model No.	Spec.
1	FRECOM	D-Link	FPS005USA-050100	Input: 100-240V, 300mA, 50/60Hz Output: 5V, 1.0A DC output cable (unshielded, 1.5m)
2	AMIGO		AMS47-0501000FU	Input: 100-240V, 0.2A, 50/60Hz Output: 5V, 1.0A DC output cable (unshielded, 1.5m)

From the above adapters, the radiated emissions worse case was found in the **adapter 2**. Therefore only the test data of the adapter was recorded in this report.

5. The EUT is 1 * 1 spatial SISO (1Tx & 1Rx) without beam forming function.
6. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 7.



7. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	OB	
A	√	√	√	√	√	With adapter 2
B	√					With adapter 1

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz
RE ≥ 1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement
OB: Conducted Out-Band Emission Measurement

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	CONFIGURE MODE
802.11n (20MHz)	1 to 11	6	OFDM	BPSK	6.5	A, B

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	CONFIGURE MODE
802.11n (20MHz)	1 to 11	6	OFDM	BPSK	6.5	A

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	CONFIGURE MODE
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	A
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	A
802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5	A

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	CONFIGURE MODE
802.11b	1 to 11	1, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 11	OFDM	BPSK	6	A
802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	A
802.11n (40MHz)	3 to 9	3, 9	OFDM	BPSK	13.5	A

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	CONFIGURE MODE
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	A
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	A
802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5	A

CONDUCTED OUT-BAND EMISSION MEASUREMENT: (

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	CONFIGURE MODE
802.11b	1 to 11	1, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 11	OFDM	BPSK	6	A
802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	A
802.11n (40MHz)	1 to 7	1, 7	OFDM	BPSK	13.5	A



A D T

※ **TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE ³ 1G	22deg. C, 78%RH	120Vac, 60Hz	Frank Liu
RE<1G	25deg. C, 68%RH	120Vac, 60Hz	Nelson Teng
PLC	25deg. C, 64%RH	120Vac, 60Hz	Kyle Huang
APCM	30deg. C, 60%RH	120Vac, 60Hz	Kent Liu
OB	25deg. C, 60% RH	120Vac, 60Hz	Kent Liu



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4-2003

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC
2	NOTEBOOK COMPUTER	DELL	PP32LA	GSLB32S	FCC DoC
3	HUB	ZyXEL	ES-116P	S060H02000215	FCC DoC

No.	Signal cable description
1	UTP Cable (10m)
2	UTP Cable (10m)
3	UTP Cable (10m)

Note: The power cords of the above support units were unshielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Test date: Dec. 08 to 09, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	100287	Mar. 02, 2011	Mar. 01, 2012
Line-Impedance Stabilization Network (for EUT)	NSLK 8127	8127-523	Sep. 20, 2011	Sep. 19, 2012
Line-Impedance Stabilization Network (for Peripheral)	ENV-216	100072	June 10, 2011	June 09, 2012
RF Cable (JYEBAO)	5DFB	CONCAB-003	Aug. 05, 2011	Aug. 04, 2012
50 ohms Terminator	50	3	Nov. 02, 2011	Nov. 01, 2012
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS


1. Placed the EUT on testing table.
2. Prepared other computer system (support unit 1~2) to act as communication partner and placed them outside of testing area.
3. The communication partners ran test program “RT5350QA.exe” to enable HUB (support unit 3) under transmission/receiving condition continuously via EUT via by UTP cables.

4.1.7 TEST RESULTS(MODE A)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.396	0.08	42.19	31.64	42.27	31.72	57.93	47.93	-15.67	-16.22
2	0.470	0.08	41.65	30.76	41.73	30.84	56.51	46.51	-14.78	-15.67
3	0.658	0.09	41.00	29.36	41.09	29.45	56.00	46.00	-14.91	-16.55
4	0.935	0.10	40.33	29.21	40.43	29.31	56.00	46.00	-15.57	-16.69
5	1.496	0.15	39.27	28.42	39.42	28.57	56.00	46.00	-16.58	-17.43
6	1.852	0.19	40.12	29.06	40.31	29.25	56.00	46.00	-15.69	-16.75
7	3.141	0.26	39.68	28.82	39.94	29.08	56.00	46.00	-16.06	-16.92
8	18.242	0.94	48.14	43.35	49.08	44.29	60.00	50.00	-10.92	-5.71


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.470	0.09	36.44	23.96	36.53	24.05	56.51	46.51	-19.98	-22.46
2	0.724	0.10	34.93	22.09	35.03	22.19	56.00	46.00	-20.97	-23.81
3	0.935	0.11	35.56	23.08	35.67	23.19	56.00	46.00	-20.33	-22.81
4	1.859	0.19	35.33	24.21	35.52	24.40	56.00	46.00	-20.48	-21.60
5	3.172	0.26	34.48	23.54	34.74	23.80	56.00	46.00	-21.26	-22.20
6	18.242	0.94	44.76	40.12	45.70	41.06	60.00	50.00	-14.30	-8.94

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.




4.1.8 TEST RESULTS(MODE B)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
--------------	----------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
	1	0.408	0.08	50.20	44.54	50.28	44.62	57.68	47.68	-7.40
2	0.517	0.08	40.76	33.25	40.84	33.33	56.00	46.00	-15.16	-12.67
3	0.892	0.10	41.59	32.50	41.69	32.60	56.00	46.00	-14.31	-13.40
4	1.719	0.17	43.26	34.86	43.43	35.03	56.00	46.00	-12.57	-10.97
5	2.422	0.22	46.79	36.33	47.01	36.55	56.00	46.00	-8.99	-9.45
6	3.406	0.27	46.21	35.35	46.48	35.62	56.00	46.00	-9.52	-10.38


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.408	0.09	46.07	37.28	46.16	37.37	57.69	47.69	-11.53	-10.32
2	0.939	0.11	37.76	24.06	37.87	24.17	56.00	46.00	-18.13	-21.83
3	1.805	0.18	39.61	27.30	39.79	27.48	56.00	46.00	-16.21	-18.52
4	2.422	0.22	43.37	30.49	43.59	30.71	56.00	46.00	-12.41	-15.29
5	2.684	0.24	42.71	30.22	42.95	30.46	56.00	46.00	-13.05	-15.54
6	3.262	0.27	43.68	29.61	43.95	29.88	56.00	46.00	-12.05	-16.12

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. Section 15.205 restricted bands of operation shall compliance with the limits in Section 15.209.



A D T

4.2.2 TEST INSTRUMENTS

For below 1GHz test (test date: Dec. 08, 2011)

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250254	July 12, 2011	July 11, 2012
Agilent Pre-Selector	N9039A	MY46520311	July 12, 2011	July 11, 2012
Agilent Signal Generator	N5181A	MY49060517	July 12, 2011	July 11, 2012
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-03	Nov. 15, 2011	Nov. 14, 2012
Agilent Pre-Amplifier	8449B	3008A02578	July 04, 2011	July 03, 2012
SPACEK LABS	SLKKa-48-6	9K16	Nov. 15, 2011	Nov. 14, 2012
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-360	Apr. 14, 2011	Apr. 13, 2012
AISI Horn_Antenna	AIH.8018	0000320091110	Nov. 14, 2011	Nov. 13, 2012
SCHWARZBECK Horn_Antenna	BBHA 9170	9170-424	Oct. 07, 2011	Oct. 06, 2012
RF CABLE	NA	RF104-201 RF104-203 RF104-204	Dec. 27, 2010	Dec. 26, 2011
RF Cable	NA	CHGCAB_001	Oct. 07, 2011	Oct. 06, 2012
Software	ADT_Radiated_V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. G.



A D T

For above 1GHz test (test date: Dec. 05, 2011)

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
ROHDE & SCHWARZ Spectrum Analyzer	FSP40	100036	Dec. 08, 2010	Dec. 07, 2011
Agilent PSA Spectrum Analyzer	E4446A	MY48250113	Nov. 30 , 2011	Nov. 29 , 2012
HP Pre_Amplifier	8449B	300801923	Oct. 31, 2011	Oct. 30 2012
ROHDE & SCHWARZ Test Receiver	ESCS30	847124/029	Sep. 02, 2011	Sep. 01, 2012
SCHWARZBECK TRILOG Broadband Antenna	VULB 9168	138	Apr. 14, 2011	Apr. 13, 2012
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 17, 2010	Dec. 16, 2011
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 17, 2011	Jan. 16, 2012
RF Switches	EMH-011	1001	Sep. 24, 2011	Sep. 23, 2012
RF CABLE (Chaintek)	Sucoflex 106	RF106-102	Jan. 27, 2011	Jan. 26, 2012
RF Cable	8DFB	STCCAB-30M-1GHz	Sep. 24, 2011	Sep. 23, 2012
Software	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The horn antenna, preamplifier (model: 8449B) and Spectrum Analyzer (model: FSP40) are used only for the measurement of emission frequency above 1GHz if tested.

3. The test was performed in Open Site No. C.

4. The FCC Site Registration No. is 656396.

5. The VCCI Site Registration No. is R-1626.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room for below 1GHz test and at a 10 meter open area test site for above 1GHz test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation

4.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA : 802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Nelson Teng

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	239.96	37.8 QP	46.0	-8.2	2.00 H	331	24.81	12.96
2	360.04	35.4 QP	46.0	-10.6	2.00 H	338	18.49	16.89
3	500.02	35.0 QP	46.0	-11.0	1.50 H	331	14.73	20.31
4	543.24	35.0 QP	46.0	-11.0	2.00 H	331	13.70	21.32
5	720.05	34.9 QP	46.0	-11.1	1.00 H	37	11.26	23.60
6	840.01	38.4 QP	46.0	-7.6	1.00 H	188	11.87	26.49
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	151.62	32.5 QP	43.5	-11.0	1.00 V	1	17.86	14.68
2	239.96	33.8 QP	46.0	-12.2	1.00 V	132	20.81	12.96
3	360.04	35.0 QP	46.0	-11.0	1.50 V	100	18.13	16.89
4	500.02	35.3 QP	46.0	-10.7	1.00 V	1	14.99	20.31
5	624.96	30.6 QP	46.0	-15.4	1.00 V	180	7.94	22.68
6	840.01	28.9 QP	46.0	-17.1	1.50 V	222	2.38	26.49

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



A D T

ABOVE 1GHz WORST-CASE DATA

802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2386.00	57.1 PK	74.0	-16.9	1.25 H	330	25.79	31.31
2	2386.00	45.3 AV	54.0	-8.7	1.25 H	330	13.99	31.31
3	*2412.00	98.4 PK			1.23 H	337	67.01	31.39
4	*2412.00	95.7 AV			1.23 H	337	64.31	31.39
5	4824.00	52.6 PK	74.0	-21.4	1.25 H	147	16.43	36.17
6	4824.00	51.0 AV	54.0	-3.0	1.25 H	147	14.83	36.17
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.8 PK	74.0	-13.2	1.25 V	174	29.48	31.32
2	2390.00	53.2 AV	54.0	-0.8	1.25 V	174	21.88	31.32
3	*2412.00	110.1 PK			1.00 V	191	78.71	31.39
4	*2412.00	107.7 AV			1.00 V	191	76.31	31.39
5	4824.00	48.3 PK	74.0	-25.7	1.00 V	13	12.13	36.17
6	4824.00	44.8 AV	54.0	-9.2	1.00 V	13	8.63	36.17

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	98.9 PK			1.24 H	338	67.41	31.49
2	*2437.00	96.6 AV			1.24 H	338	65.11	31.49
3	4874.00	50.6 PK	74.0	-23.4	1.34 H	137	14.29	36.31
4	4874.00	48.7 AV	54.0	-5.3	1.34 H	137	12.39	36.31
5	7311.00	52.6 PK	74.0	-21.4	1.24 H	318	10.37	42.23
6	7311.00	46.8 AV	54.0	-7.2	1.24 H	318	4.57	42.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	111.3 PK			1.00 V	191	79.81	31.49
2	*2437.00	108.3 AV			1.00 V	191	76.81	31.49
3	4874.00	44.7 PK	74.0	-29.3	1.00 V	358	8.39	36.31
4	4874.00	40.0 AV	54.0	-14.0	1.00 V	358	3.69	36.31
5	7311.00	57.1 PK	74.0	-16.9	1.22 V	179	14.87	42.23
6	7311.00	52.8 AV	54.0	-1.2	1.22 V	179	10.57	42.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2412.00	97.0 PK			1.32 H	331	65.61	31.39
2	*2412.00	94.5 AV			1.32 H	331	63.11	31.39
3	2483.50	56.3 PK	74.0	-17.7	1.24 H	330	24.64	31.66
4	2483.50	43.8 AV	54.0	-10.2	1.24 H	330	12.14	31.66
5	4924.00	49.8 PK	74.0	-24.2	1.36 H	141	13.38	36.42
6	4924.00	46.6 AV	54.0	-7.4	1.36 H	141	10.18	36.42
7	7386.00	52.0 PK	74.0	-22.0	1.31 H	315	9.48	42.52
8	7386.00	45.7 AV	54.0	-8.3	1.31 H	315	3.18	42.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.0 PK			1.00 V	193	77.42	31.58
2	*2462.00	105.2 AV			1.00 V	193	73.62	31.58
3	2483.50	62.0 PK	74.0	-12.0	1.25 V	191	30.34	31.66
4	2483.50	53.1 AV	54.0	-0.9	1.25 V	191	21.44	31.66
5	4924.00	45.2 PK	74.0	-28.8	1.21 V	184	8.78	36.42
6	4924.00	39.0 AV	54.0	-15.0	1.21 V	184	2.58	36.42
7	7386.00	57.0 PK	74.0	-17.0	1.21 V	184	14.48	42.52
8	7386.00	53.0 AV	54.0	-1.0	1.21 V	184	10.48	42.52

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11b MODE, CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11b MODE, CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11b MODE, CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11b MODE, CH11, VERTICAL)





A D T

802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.9 PK	74.0	-12.1	1.23 H	335	30.58	31.32
2	2390.00	46.8 AV	54.0	-7.2	1.23 H	335	15.48	31.32
3	*2412.00	98.4 PK			1.23 H	337	67.01	31.39
4	*2412.00	88.0 AV			1.23 H	337	56.61	31.39
5	4824.00	41.9 PK	74.0	-32.1	1.34 H	139	5.73	36.17
6	4824.00	31.0 AV	54.0	-23.0	1.34 H	139	-5.17	36.17

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.2 PK	74.0	-6.8	1.23 V	192	35.88	31.32
2	2390.00	53.2 AV	54.0	-0.8	1.23 V	192	21.88	31.32
3	*2412.00	110.9 PK			1.19 V	230	79.51	31.39
4	*2412.00	98.4 AV			1.19 V	230	67.01	31.39
5	4824.00	42.2 PK	74.0	-31.8	1.67 V	199	6.03	36.17
6	4824.00	31.1 AV	54.0	-22.9	1.67 V	199	-5.07	36.17

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2384.00	55.8 PK	74.0	-18.2	1.25 H	336	24.50	31.30
2	2384.00	43.4 AV	54.0	-10.6	1.25 H	336	12.10	31.30
3	*2437.00	100.5 PK			1.24 H	339	69.01	31.49
4	*2437.00	90.7 AV			1.24 H	339	59.21	31.49
5	2489.00	55.9 PK	74.0	-18.1	1.23 H	331	24.22	31.68
6	2489.00	43.6 AV	54.0	-10.4	1.23 H	331	11.92	31.68
7	4874.00	42.1 PK	74.0	-31.9	1.35 H	140	5.79	36.31
8	4874.00	31.2 AV	54.0	-22.8	1.35 H	140	-5.11	36.31
9	7311.00	48.4 PK	74.0	-25.6	1.31 H	316	6.17	42.23
10	7311.00	36.4 AV	54.0	-17.6	1.31 H	316	-5.83	42.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2384.00	61.2 PK	74.0	-12.8	1.16 V	291	29.90	31.30
2	2384.00	49.6 AV	54.0	-4.4	1.16 V	291	18.30	31.30
3	*2437.00	111.6 PK			1.16 V	231	80.11	31.49
4	*2437.00	102.1 AV			1.16 V	231	70.61	31.49
5	2489.00	62.6 PK	74.0	-11.4	1.21 V	192	30.92	31.68
6	2489.00	52.9 AV	54.0	-1.1	1.21 V	192	21.22	31.68
7	4874.00	42.1 PK	74.0	-31.9	1.68 V	203	5.79	36.31
8	4874.00	31.4 AV	54.0	-22.6	1.68 V	203	-4.91	36.31
9	7311.00	61.3 PK	74.0	-12.7	1.50 V	334	19.07	42.23
10	7311.00	48.6 AV	54.0	-5.4	1.50 V	334	6.37	42.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	98.0 PK			1.22 H	330	66.42	31.58
2	*2462.00	87.6 AV			1.22 H	330	56.02	31.58
3	2483.50	60.0 PK	74.0	-14.0	1.23 H	332	28.34	31.66
4	2483.50	45.0 AV	54.0	-9.0	1.23 H	332	13.34	31.66
5	4924.00	41.6 PK	74.0	-32.4	1.33 H	139	5.18	36.42
6	4924.00	30.7 AV	54.0	-23.3	1.33 H	139	-5.72	36.42
7	7386.00	48.7 PK	74.0	-25.3	1.33 H	331	6.18	42.52
8	7386.00	36.6 AV	54.0	-17.4	1.33 H	331	-5.92	42.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.9 PK			1.43 V	182	78.32	31.58
2	*2462.00	99.1 AV			1.43 V	182	67.52	31.58
3	2483.50	73.2 PK	74.0	-0.8	1.20 V	191	41.54	31.66
4	2483.50	52.6 AV	54.0	-1.4	1.20 V	191	20.94	31.66
5	4924.00	41.9 PK	74.0	-32.1	1.66 V	197	5.48	36.42
6	4924.00	32.0 AV	54.0	-22.0	1.66 V	197	-4.42	36.42
7	7386.00	59.1 PK	74.0	-14.9	1.46 V	329	16.58	42.52
8	7386.00	45.3 AV	54.0	-8.7	1.46 V	329	2.78	42.52

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11g MODE, CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11g MODE, CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11g MODE, CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11g MODE,CH11, VERTICAL)





A D T

802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.4 PK	74.0	-12.6	1.25 H	334	30.08	31.32
2	2390.00	46.8 AV	54.0	-7.2	1.25 H	334	15.48	31.32
3	*2412.00	95.5 PK			1.24 H	337	64.11	31.39
4	*2412.00	86.3 AV			1.24 H	337	54.91	31.39
5	4824.00	41.1 PK	74.0	-32.9	1.32 H	132	4.93	36.17
6	4824.00	30.1 AV	54.0	-23.9	1.32 H	132	-6.07	36.17
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.3 PK	74.0	-5.7	1.20 V	241	36.98	31.32
2	2390.00	53.2 AV	54.0	-0.8	1.20 V	241	21.88	31.32
3	*2412.00	108.1 PK			1.22 V	225	76.71	31.39
4	*2412.00	98.4 AV			1.22 V	225	67.01	31.39
5	4824.00	41.3 PK	74.0	-32.7	1.67 V	202	5.13	36.17
6	4824.00	30.4 AV	54.0	-23.6	1.67 V	202	-5.77	36.17

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2383.00	55.7 PK	74.0	-18.3	1.25 H	331	24.40	31.30
2	2383.00	43.6 AV	54.0	-10.4	1.25 H	331	12.30	31.30
3	*2437.00	99.5 PK			1.24 H	339	68.01	31.49
4	*2437.00	90.0 AV			1.24 H	339	58.51	31.49
5	2488.00	55.9 PK	74.0	-18.1	1.23 H	336	24.22	31.68
6	2488.00	43.1 AV	54.0	-10.9	1.23 H	336	11.42	31.68
7	4874.00	41.6 PK	74.0	-32.4	1.34 H	133	5.29	36.31
8	4874.00	30.6 AV	54.0	-23.4	1.34 H	133	-5.71	36.31
9	7311.00	49.1 PK	74.0	-24.9	1.31 H	319	6.87	42.23
10	7311.00	37.2 AV	54.0	-16.8	1.31 H	319	-5.03	42.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2383.00	59.9 PK	74.0	-14.1	1.10 V	222	28.60	31.30
2	2383.00	49.6 AV	54.0	-4.4	1.10 V	222	18.30	31.30
3	*2437.00	109.6 PK			1.08 V	223	78.11	31.49
4	*2437.00	100.9 AV			1.08 V	223	69.41	31.49
5	2488.00	69.5 PK	74.0	-4.5	1.07 V	227	37.82	31.68
6	2488.00	52.7 AV	54.0	-1.3	1.07 V	227	21.02	31.68
7	4874.00	41.5 PK	74.0	-32.5	1.68 V	193	5.19	36.31
8	4874.00	30.6 AV	54.0	-23.4	1.68 V	193	-5.71	36.31
9	7311.00	62.6 PK	74.0	-11.4	1.48 V	331	20.37	42.23
10	7311.00	47.0 AV	54.0	-7.0	1.48 V	331	4.77	42.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	96.3 PK			1.22 H	333	64.72	31.58
2	*2462.00	86.5 AV			1.22 H	333	54.92	31.58
3	2483.50	58.6 PK	74.0	-15.4	1.23 H	329	26.94	31.66
4	2483.50	44.5 AV	54.0	-9.5	1.23 H	329	12.84	31.66
5	4924.00	42.2 PK	74.0	-31.8	1.35 H	134	5.78	36.42
6	4924.00	31.1 AV	54.0	-22.9	1.35 H	134	-5.32	36.42
7	7386.00	49.9 PK	74.0	-24.1	1.32 H	320	7.38	42.52
8	7386.00	37.6 AV	54.0	-16.4	1.32 H	320	-4.92	42.52
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.3 PK			1.20 V	230	78.72	31.58
2	*2462.00	100.5 AV			1.20 V	230	68.92	31.58
3	2483.50	69.5 PK	74.0	-4.5	1.16 V	194	37.84	31.66
4	2483.50	52.7 AV	54.0	-1.3	1.16 V	194	21.04	31.66
5	4924.00	41.9 PK	74.0	-32.1	1.66 V	197	5.48	36.42
6	4924.00	31.2 AV	54.0	-22.8	1.66 V	197	-5.22	36.42
7	7386.00	58.7 PK	74.0	-15.3	1.47 V	330	16.18	42.52
8	7386.00	45.9 AV	54.0	-8.1	1.47 V	330	3.38	42.52

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, VERTICAL)





A D T

802.11n (40MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.9 PK	74.0	-14.1	1.21 H	331	28.58	31.32
2	2390.00	45.8 AV	54.0	-8.2	1.21 H	331	14.48	31.32
3	*2422.00	90.3 PK			1.23 H	337	58.87	31.43
4	*2422.00	81.2 AV			1.23 H	337	49.77	31.43
5	4844.00	41.7 PK	74.0	-32.3	1.34 H	136	5.48	36.22
6	4844.00	30.5 AV	54.0	-23.5	1.34 H	136	-5.72	36.22

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.5 PK	74.0	-4.5	1.26 V	265	38.18	31.32
2	2390.00	53.2 AV	54.0	-0.8	1.26 V	265	21.88	31.32
3	*2422.00	101.6 PK			1.23 V	227	70.17	31.43
4	*2422.00	92.9 AV			1.23 V	227	61.47	31.43
5	4844.00	41.8 PK	74.0	-32.2	1.64 V	211	5.58	36.22
6	4844.00	30.9 AV	54.0	-23.1	1.64 V	211	-5.32	36.22
7	7266.00	52.4 PK	74.0	-21.6	1.48 V	331	10.27	42.13
8	7266.00	38.7 AV	54.0	-15.3	1.48 V	331	-3.43	42.13

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.6 PK	74.0	-14.4	1.23 H	339	28.28	31.32
2	2390.00	45.0 AV	54.0	-9.0	1.23 H	339	13.68	31.32
3	*2437.00	94.3 PK			1.22 H	334	62.81	31.49
4	*2437.00	84.6 AV			1.22 H	334	53.11	31.49
5	2483.50	56.1 PK	74.0	-17.9	1.25 H	340	24.44	31.66
6	2483.50	43.6 AV	54.0	-10.4	1.25 H	340	11.94	31.66
7	4874.00	41.6 PK	74.0	-32.4	1.35 H	321	5.29	36.31
8	4874.00	30.8 AV	54.0	-23.2	1.35 H	321	-5.51	36.31
9	7311.00	48.7 PK	74.0	-25.3	1.32 H	321	6.47	42.23
10	7311.00	37.0 AV	54.0	-17.0	1.32 H	321	-5.23	42.23
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.1 PK	74.0	-9.9	1.24 V	261	32.78	31.32
2	2390.00	52.0 AV	54.0	-2.0	1.24 V	261	20.68	31.32
3	*2437.00	105.4 PK			1.20 V	228	73.91	31.49
4	*2437.00	96.5 AV			1.20 V	228	65.01	31.49
5	2483.50	67.4 PK	74.0	-6.6	1.18 V	196	35.74	31.66
6	2483.50	53.1 AV	54.0	-0.9	1.18 V	196	21.44	31.66
7	4874.00	42.9 PK	74.0	-31.1	1.68 V	203	6.59	36.31
8	4874.00	31.2 AV	54.0	-22.8	1.68 V	203	-5.11	36.31
9	7311.00	53.3 PK	74.0	-20.7	1.47 V	336	11.07	42.23
10	7311.00	40.7 AV	54.0	-13.3	1.47 V	336	-1.53	42.23

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	22deg. C, 78%RH	TESTED BY	Frank Liu



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	88.7 PK			1.22 H	336	57.16	31.54
2	*2452.00	80.1 AV			1.22 H	336	48.56	31.54
3	2483.50	57.6 PK	74.0	-16.4	1.22 H	331	25.94	31.66
4	2483.50	43.9 AV	54.0	-10.1	1.22 H	331	12.24	31.66
5	4904.00	41.6 PK	74.0	-32.4	1.34 H	136	5.21	36.39
6	4904.00	30.9 AV	54.0	-23.1	1.34 H	136	-5.49	36.39
7	7356.00	48.6 PK	74.0	-25.4	1.35 H	319	6.20	42.40
8	7356.00	36.1 AV	54.0	-17.9	1.35 H	319	-6.30	42.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	103.0 PK			1.19 V	226	71.46	31.54
2	*2452.00	93.7 AV			1.19 V	226	62.16	31.54
3	2483.50	68.9 PK	74.0	-5.1	1.15 V	207	37.24	31.66
4	2483.50	53.2 AV	54.0	-0.8	1.15 V	207	21.54	31.66
5	4904.00	41.9 PK	74.0	-32.1	1.66 V	194	5.51	36.39
6	4904.00	30.1 AV	54.0	-23.9	1.66 V	194	-6.29	36.39
7	7356.00	52.1 PK	74.0	-21.9	1.45 V	332	9.70	42.40
8	7356.00	38.6 AV	54.0	-15.4	1.45 V	332	-3.80	42.40

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH3, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH3, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH9, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH9, VERTICAL)



4.3 6DB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Test date: Dec. 08, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




A D T

4.3.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	11.56	0.5	PASS
6	2437	11.29	0.5	PASS
11	2462	11.27	0.5	PASS

CH1






A D T

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.58	0.5	PASS
6	2437	16.59	0.5	PASS
11	2462	16.56	0.5	PASS

CH6






A D T

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.71	0.5	PASS
6	2437	17.72	0.5	PASS
11	2462	17.69	0.5	PASS

CH6






A D T

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	36.49	0.5	PASS
6	2437	36.50	0.5	PASS
9	2452	36.49	0.5	PASS

CH6



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Test date: Dec. 08, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Peak Power Meter	ML2495A	0824006	May 04, 2011	May 03, 2012
Power Sensor	MA2411B	0738172	May 03, 2011	May 02, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. The transmitter output was connected to the power meter through an attenuator; the bandwidth of the fundamental frequency was measured with the power meter.
2. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



A D T

4.4.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	154.9	21.9	30	PASS
6	2437	147.9	21.7	30	PASS
11	2462	114.8	20.6	30	PASS

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	245.5	23.9	30	PASS
6	2437	263.0	24.2	30	PASS
11	2462	208.9	23.2	30	PASS

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	177.8	22.5	30	PASS
6	2437	257.0	24.1	30	PASS
11	2462	208.9	23.2	30	PASS



A D T

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
3	2422	104.7	20.2	30	PASS
6	2437	166.0	22.2	30	PASS
9	2452	91.2	19.6	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Test date: Oct. 18, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6




A D T

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-11.1	8	PASS
6	2437	-11.0	8	PASS
11	2462	-13.2	8	PASS

CH6






A D T

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-12.0	8	PASS
6	2437	-10.7	8	PASS
11	2462	-12.0	8	PASS


CH6



802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
3	2422	-14.4	8	PASS
6	2437	-11.6	8	PASS
9	2452	-15.0	8	PASS

CH6





4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Test date: Dec. 08, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set RBW of spectrum analyzer to 100kHz and VBW of spectrum analyzer to 300kHz with suitable frequency span including 100MHz or 200MHz bandwidth from band edge. The band edges were measured and recorded.

The spectrum plots (RBW = 100kHz, VBW = 300kHz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation



4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).


802.11b DSSS MODULATION: CH1






A D T

CH11



A D T





A D T



A D T



802.11g OFDM MODULATION: CH1





A D T

CH11







A D T

802.11n (20MHz) OFDM MODULATION:



CH1







A D T

CH11



802.11n (40MHz) OFDM MODULATION:



CH3





A D T

CH9





5. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation and authorization certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5.phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also



A D T

6.APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---